toll-free: (866)311-3268 fax: (480)926-3598

http://www.ComplianceTesting.com info@ComplianceTesting.com

## **Test Report**

Prepared for: EMS Technologies Honeywell Satcom

Model: HSD-MK2

**Description: Aeronautical Satcom Transceiver** 

Serial Number: N/A

FCC ID: K6KHSD-MK2

To

FCC Part 1.1310

Date of Issue: July 6, 2016

On the behalf of the applicant: **EMS Technologies Honeywell Satcom** 

> 400 Maple Grove Rd Ottawa, Ontario K2V 1B8

Attention of: Steven Mills, Director

Ph: (613)591-6040

Email: Steven.Mills2@Honeywell.com

**Prepared By Compliance Testing, LLC** 1724 S. Nevada Way Mesa, AZ 85204 (480) 926-3100 phone / (480) 926-3598 fax www.compliancetesting.com

Project No: p1640029

**Alex Macon** 

**Project Test Engineer** 

This report may not be reproduced, except in full, without written permission from Compliance Testing All results contained herein relate only to the sample tested

# **Test Report Revision History**

Revision	Date	Revised By	Reason for Revision
1.0	June 22, 2016	Alex Macon	Original Document

#### ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <a href="http://www.compliancetesting.com/labscope.html">http://www.compliancetesting.com/labscope.html</a> for current scope of accreditation.

Testing Certificate Number: 2152.01



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description Model: HSD-MK2

**Description:** Aeronautical Satcom Transceiver

Firmware: N/A Software: N/A Serial Number: N/A

## **Minimum Safe Distance Evaluation**

This is a mobile device used in Uncontrolled Exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
1.34-30 MHz:	Limit $[mW/cm^2] = (180/f^2)$
30-300 MHz:	Limit $[mW/cm^2] = 0.2$
300-1500 MHz:	Limit $[mW/cm^2] = f/1500$
1500-100,000 MHz:	Limit [mW/cm <sup>2</sup> ] = 1.0

## **Test Data**

Test Frequency, MHz	1643.5
Power, Conducted, mW (P)	60000
Antenna Gain Isotropic	17 dBi
Antenna Gain Numeric (G)	50.12
Antenna Type	patch
Limit (L)	1.0

R=√(PG/4πL)	
Distance (R) cm	489.3cm

The minimum safe distance is 489.3 cm

**END OF TEST REPORT**