

Appendix L: Test Results of Field Strength of Spurious Radiation for NB-IoT operation

APPENDIX L.1: FIELD STRENGTH OF SPURIOUS RADIATION FOR BAND 2	2
Below 1 GHz	2
Above 1 GHz	6
APPENDIX L.2: FIELD STRENGTH OF SPURIOUS RADIATION FOR BAND 4	35
Below 1 GHz	35
Above 1 GHz	39
APPENDIX L.3: FIELD STRENGTH OF SPURIOUS RADIATION FOR BAND 5	69
Below 1 GHz	69
Above 1 GHz	73
APPENDIX L.4: FIELD STRENGTH OF SPURIOUS RADIATION FOR BAND 12	103
Below 1 GHz	103
Above 1 GHz	107
APPENDIX L.5: FIELD STRENGTH OF SPURIOUS RADIATION FOR BAND 13	137
Below 1 GHz	137
Above 1 GHz	141
APPENDIX L.6: FIELD STRENGTH OF SPURIOUS RADIATION FOR BAND 25	171
Below 1 GHz	171
Above 1 GHz	175
APPENDIX L.7: FIELD STRENGTH OF SPURIOUS RADIATION FOR BAND 26 LOWER BAND	205
Below 1 GHz	205
Above 1 GHz	209
APPENDIX L.8: FIELD STRENGTH OF SPURIOUS RADIATION FOR BAND 26 UPPER BAND	239
Below 1 GHz	239
Above 1 GHz	243
APPENDIX L.9: FIELD STRENGTH OF SPURIOUS RADIATION FOR BAND 66	273
Below 1 GHz	273
Above 1 GHz	277
APPENDIX L.10: FIELD STRENGTH OF SPURIOUS RADIATION FOR BAND 71	307
Below 1 GHz	307
Above 1 GHz	311
APPENDIX L.11: FIELD STRENGTH OF SPURIOUS RADIATION FOR BAND 85	341
Below 1 GHz	341
Above 1 GHz	345


Appendix L.1: Field Strength of Spurious Radiation for Band 2

Below 1 GHz
BPSK

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
50.806500	18.03	---	40.00	21.97	100.0	H	90.0	-18.6
728.885000	26.37	---	46.00	19.63	100.0	H	205.0	-7.9

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin


[illegible]

QPSK

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz QPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
41.033750	-77.61	-13.00	64.61	100.0	H	124.0	-112.3
240.611250	-83.96	-13.00	70.97	100.0	H	187.0	-110.4
848.073750	-73.43	-13.00	60.43	100.0	H	276.0	-100.3

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz QPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
41.882500	-89.68	-13.00	76.68	100.0	V	229.0	-123.2
94.141250	-72.45	-13.00	59.45	100.0	V	156.0	-99.7
430.852500	-83.21	-13.00	70.21	100.0	V	290.0	-111.0

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
100.0000	100.0000	100.0000	100.0000	100.0000	100.0000		100.0000	100.0000

Test Report

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
----	-----	-----	-----	-----	-----		-----	-----


Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---	---		---	---

15 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1852.500000	-43.06	-13.00	30.06	100.0	H	0.0	-90.6
2120.500000	-45.69	-13.00	32.69	100.0	H	130.0	-88.6
2468.000000	-37.89	-13.00	24.89	100.0	H	211.0	-87.9
3710.500000	-46.87	-13.00	33.88	100.0	H	80.0	-86.8

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-VV
Test Mode:	TX Low 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1855.500000	-43.80	-13.00	30.80	100.0	V	186.0	-90.1
2131.500000	-44.25	-13.00	31.25	100.0	V	57.0	-87.7
2463.500000	-36.96	-13.00	23.96	100.0	V	325.0	-88.1
3708.500000	-48.77	-13.00	35.77	100.0	V	351.0	-86.7

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1857.500000	-44.31	-13.00	31.31	100.0	H	258.0	-90.4
2120.500000	-45.66	-13.00	32.66	100.0	H	119.0	-88.6
2425.500000	-41.55	-13.00	28.55	100.0	H	224.0	-87.4
2462.000000	-40.31	-13.00	27.31	100.0	H	328.0	-87.9
3697.500000	-48.62	-13.00	35.62	100.0	H	157.0	-86.7

Test Report

EUT Information

EUT Name: DATA TERMINAL MODULE
Model: ME310G1-WW
Test Mode: TX Low 15kHz BPSK 1@0
Test Voltage: DC 3.8V
Remark: Temp 24 Humi:45%
Test Standard: FCC Part 24 and RSS-133 Issue 6
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1857.500000	-42.22	-13.00	29.22	100.0	V	14.0	-90.1
1943.500000	-45.02	-13.00	32.02	100.0	V	152.0	-89.6
2125.500000	-45.43	-13.00	32.43	100.0	V	112.0	-87.9
2461.000000	-44.90	-13.00	31.90	100.0	V	347.0	-88.1
3710.000000	-48.47	-13.00	35.47	100.0	V	302.0	-86.7

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-VW
Test Mode:	TX Low 15kHz QPSK 12@0
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1856.500000	-42.59	-13.00	29.59	100.0	H	43.0	-90.4
2133.000000	-43.22	-13.00	30.22	100.0	H	341.0	-88.2
2461.500000	-36.75	-13.00	23.75	100.0	H	37.0	-87.9
3700.000000	-43.33	-13.00	30.33	100.0	H	177.0	-86.7
5550.500000	-33.60	-13.00	20.60	100.0	H	59.0	-83.2

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
100.0000	100.0000	100.0000	100.0000	100.0000	100.0000		100.0000	100.0000

[illegible]

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.5000	93.5000	93.5000	93.5000	93.5000	93.5000		93.5000	93.5000


Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
100.000000	-100.000000	-100.000000	-100.000000	-100.000000	-100.000000		-100.000000	-100.000000

15 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz BPSK 1@11
Test Voltage:	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1857.500000	-43.23	-13.00	30.23	100.0	H	172.0	-90.4
1958.000000	-44.97	-13.00	31.97	100.0	H	0.0	-89.7
2125.500000	-45.40	-13.00	32.40	100.0	H	107.0	-88.4
2465.500000	-39.91	-13.00	26.91	100.0	H	96.0	-87.9
3737.500000	-47.68	-13.00	34.68	100.0	H	143.0	-86.7

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1698.500000	-41.97	-13.00	28.97	100.0	V	218.0	-92.1
1855.500000	-43.37	-13.00	30.37	100.0	V	195.0	-90.1
1957.500000	-43.26	-13.00	30.26	100.0	V	91.0	-89.6
2056.500000	-40.05	-13.00	27.05	100.0	V	114.0	-89.0
2131.500000	-42.77	-13.00	29.77	100.0	V	24.0	-87.7
2630.500000	-47.49	-13.00	34.49	100.0	V	102.0	-88.5
3755.500000	-46.20	-13.00	33.20	100.0	V	17.0	-86.9

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz QPSK 12@0
Test Voltage:	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1857.000000	-43.60	-13.00	30.60	100.0	H	342.0	-90.4
1957.500000	-44.75	-13.00	31.75	100.0	H	210.0	-89.7
2134.000000	-43.19	-13.00	30.19	100.0	H	163.0	-88.3
2468.500000	-40.07	-13.00	27.07	100.0	H	250.0	-87.9
3755.500000	-45.79	-13.00	32.79	100.0	H	127.0	-86.6

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz QPSK 12@0
Test Voltage:	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1857.500000	-42.82	-13.00	29.82	100.0	V	101.0	-90.1
1958.000000	-44.95	-13.00	31.95	100.0	V	356.0	-89.6
2134.500000	-42.48	-13.00	29.48	100.0	V	233.0	-87.7
3755.500000	-47.71	-13.00	34.71	100.0	V	329.0	-86.9

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
TestMode:	TX Mid 15kHz BPSK 1@0
TestVoltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1857.500000	-41.30	-13.00	28.30	100.0	H	245.0	-90.4
1958.000000	-44.77	-13.00	31.77	100.0	H	251.0	-89.7
2134.000000	-44.01	-13.00	31.01	100.0	H	320.0	-88.3
2468.000000	-34.65	-13.00	21.65	100.0	H	124.0	-87.9
3755.000000	-40.90	-13.00	27.90	100.0	H	316.0	-86.6

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz BPSK 1@0
Test Voltage:	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1698.500000	-42.99	-13.00	29.99	100.0	V	295.0	-92.1
1852.000000	-42.80	-13.00	29.80	100.0	V	341.0	-90.2
2056.500000	-42.63	-13.00	29.63	100.0	V	196.0	-89.0
2465.500000	-39.69	-13.00	26.69	100.0	V	4.0	-88.1
3754.500000	-46.67	-13.00	33.67	100.0	V	50.0	-86.9

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
100.000	100.000	100.000	100.000	100.000	100.000		100.000	100.000

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.5000	93.5000	93.5000	93.5000	93.5000	93.5000		93.5000	93.5000


[illegible]

15 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1767.000000	-45.31	-13.00	32.31	100.0	H	231.0	-90.5
1861.000000	-43.99	-13.00	30.99	100.0	H	46.0	-90.2
1943.500000	-40.99	-13.00	27.99	100.0	H	356.0	-89.9
2468.000000	-39.40	-13.00	26.40	100.0	H	7.0	-87.9
3864.000000	-47.50	-13.00	34.50	100.0	H	193.0	-86.5

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1848.500000	-42.92	-13.00	29.92	100.0	V	71.0	-90.2
1943.000000	-39.37	-13.00	26.37	100.0	V	0.0	-89.6
2134.000000	-43.70	-13.00	30.70	100.0	V	19.0	-87.7
2461.500000	-36.36	-13.00	23.36	100.0	V	318.0	-88.1
3847.500000	-47.32	-13.00	34.32	100.0	V	135.0	-86.7

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1857.500000	-43.76	-13.00	30.76	100.0	H	0.0	-90.4
1941.500000	-38.31	-13.00	25.31	100.0	H	260.0	-89.9
2133.500000	-43.94	-13.00	30.94	100.0	H	127.0	-88.3
2468.500000	-38.74	-13.00	25.74	100.0	H	278.0	-87.9
3783.000000	-47.84	-13.00	34.84	100.0	H	343.0	-86.6
3849.500000	-48.39	-13.00	35.39	100.0	H	58.0	-86.7

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@11
Test Voltage:	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1857.500000	-43.01	-13.00	30.01	100.0	V	352.0	-90.1
2132.000000	-43.79	-13.00	30.79	100.0	V	103.0	-87.7
2468.500000	-37.46	-13.00	24.46	100.0	V	6.0	-88.1
3821.500000	-48.89	-13.00	35.89	100.0	V	239.0	-86.9

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz QPSK 12@0
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1849.000000	-44.61	-13.00	31.61	100.0	H	207.0	-90.5
1989.500000	-44.73	-13.00	31.73	100.0	H	236.0	-89.3
2134.000000	-43.49	-13.00	30.49	100.0	H	271.0	-88.3
2468.500000	-39.63	-13.00	26.63	100.0	H	133.0	-87.9
3824.000000	-48.09	-13.00	35.09	100.0	H	239.0	-86.8

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz QPSK 12@0
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 24 and RSS-133 Issue 6
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1857.500000	-43.65	-13.00	30.65	100.0	V	357.0	-90.1
2134.000000	-43.81	-13.00	30.81	100.0	V	124.0	-87.7
2468.500000	-37.63	-13.00	24.63	100.0	V	334.0	-88.1
3831.500000	-48.52	-13.00	35.52	100.0	V	31.0	-86.9


Appendix L.2: Field Strength of Spurious Radiation for Band 4

Below 1 GHz
 BPSK

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
41.155000	-78.32	-13.00	65.32	100.0	H	221.0	-112.2
249.341250	-84.70	-13.00	71.70	100.0	H	49.0	-110.0
633.703750	-77.99	-13.00	64.99	100.0	H	176.0	-104.9

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
94.505000	-72.23	-13.00	59.23	100.0	V	308.0	-99.6
330.942500	-84.22	-13.00	71.22	100.0	V	0.0	-112.1
787.327500	-76.18	-13.00	63.18	100.0	V	151.0	-102.6

QPSK

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz BPSK 1@0
Test Voltage:	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
94.505000	-72.23	-13.00	59.23	100.0	V	308.0	-99.6
330.942500	-84.22	-13.00	71.22	100.0	V	0.0	-112.1
787.327500	-76.18	-13.00	63.18	100.0	V	151.0	-102.6

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz QPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.535000	-73.36	-13.00	60.36	100.0	V	166.0	-100.8
534.278750	-81.27	-13.00	68.27	100.0	V	175.0	-107.6
739.918750	-75.34	-13.00	62.34	100.0	V	76.0	-102.0

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.500000	93.500000	93.500000	93.500000	93.500000	93.500000		93.500000	93.500000

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.5000	93.5000	93.5000	93.5000	93.5000	93.5000		93.5000	93.5000

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 3.75kHzQPSK 1@47
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
3414.000000	-49.01	---	-13.00	36.01	100.0	V	327.0	-87.8


Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
144.375	-120.0	-120.0	-120.0	0.0	100.0	V	0.0	0.0

15 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz BPSK 1@0
Test Voltage:	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2468.500000	-44.05	-13.00	31.05	100.0	H	242.0	-87.9
3420.500000	-44.27	-13.00	31.27	100.0	H	6.0	-87.9
5130.000000	-45.40	-13.00	32.40	100.0	H	0.0	-84.8

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz BPSK 1@0
Test Voltage:	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1943.500000	-43.77	-13.00	30.77	100.0	V	79.0	-89.6
2110.500000	-46.39	-13.00	33.39	100.0	V	62.0	-88.5
2474.500000	-47.05	-13.00	34.05	100.0	V	166.0	-88.0
3420.000000	-46.73	-13.00	33.73	100.0	V	40.0	-87.7
4614.000000	-46.16	-13.00	33.16	100.0	V	95.0	-85.7

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2109.500000	-48.27	-13.00	35.27	100.0	H	233.0	-89.0
2469.000000	-43.09	-13.00	30.09	100.0	H	337.0	-87.9
3418.500000	-50.37	-13.00	37.37	100.0	H	113.0	-87.9
4353.500000	-46.44	-13.00	33.44	100.0	H	210.0	-86.4

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1056.000000	-47.33	-13.00	34.33	100.0	V	215.0	-96.6
2110.500000	-46.87	-13.00	33.87	100.0	V	0.0	-88.5
3420.000000	-48.78	-13.00	35.78	100.0	V	66.0	-87.7

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz QPSK 12@0
Test Voltage::	DC 5V From Adapter
Remark:	Temp 23 Humi:42%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2854.000000	-49.12	-13.00	36.12	100.0	H	128.0	-87.3
5166.000000	-46.33	-13.00	33.33	100.0	H	0.0	-84.6
6805.000000	-43.18	-13.00	30.18	100.0	H	82.0	-81.5

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz QPSK 12@0
Test Voltage::	DC 5V From Adapter
Remark:	Temp 23 Humi:42%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2866.500000	-49.27	-13.00	36.27	100.0	V	36.0	-86.8
5114.500000	-46.05	-13.00	33.05	100.0	V	108.0	-85.0
6925.500000	-43.28	-13.00	30.28	100.0	V	60.0	-81.2

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.500000	93.500000	93.500000	93.500000	93.500000	93.500000		93.500000	93.500000

[illegible]

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
900.000	90.000	80.000	90.000	0.000	100.000		0.000	0.000


Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.5000	-10.0000	-10.0000	-10.0000	0.0000	0.0000		0.0000	0.0000

15 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz BPSK 1@11
Test Voltage:	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2132.500000	-46.81	-13.00	33.81	100.0	H	81.0	-88.2
2469.000000	-42.60	-13.00	29.60	100.0	H	4.0	-87.9
3465.000000	-41.90	-13.00	28.90	100.0	H	301.0	-88.1
5197.500000	-43.38	-13.00	30.38	100.0	H	0.0	-84.8
6232.000000	-42.95	-13.00	29.95	100.0	H	205.0	-82.1

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1582.000000	-48.29	-13.00	35.29	100.0	V	134.0	-93.0
1883.000000	-41.56	-13.00	28.56	100.0	V	105.0	-90.2
2132.000000	-46.13	-13.00	33.13	100.0	V	53.0	-87.7
2468.500000	-43.59	-13.00	30.59	100.0	V	348.0	-88.1
3465.000000	-42.20	-13.00	29.20	100.0	V	65.0	-87.8
5197.500000	-38.30	-13.00	25.30	100.0	V	30.0	-84.8
7580.000000	-41.62	-13.00	28.62	100.0	V	155.0	-79.4

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz QPSK 12@0
Test Voltage::	DC 5V From Adapter
Remark:	Temp 23 Humi:42%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2843.000000	-49.78	-13.00	36.78	100.0	H	357.0	-87.7
5203.500000	-46.74	-13.00	33.74	100.0	H	7.0	-84.9
6812.000000	-43.75	-13.00	30.75	100.0	H	209.0	-81.4

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz QPSK 12@0
Test Voltage::	DC 5V From Adapter
Remark:	Temp 23 Humi:42%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2839.500000	-49.55	-13.00	36.55	100.0	V	12.0	-87.4
5148.000000	-47.03	-13.00	34.03	100.0	V	277.0	-84.7
6919.000000	-42.88	-13.00	29.88	100.0	V	312.0	-81.2

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
TestMode:	TX Mid 15kHz BPSK 1@0
TestVoltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1581.500000	-50.74	-13.00	37.74	100.0	H	25.0	-92.9
2468.000000	-42.62	-13.00	29.62	100.0	H	280.0	-87.9
3464.500000	-46.31	-13.00	33.31	100.0	H	316.0	-88.1
5197.000000	-31.63	-13.00	18.63	100.0	H	58.0	-84.8

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 24 Humi:45%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1581.500000	-48.20	-13.00	35.20	100.0	V	133.0	-93.0
1883.000000	-41.19	-13.00	28.19	100.0	V	121.0	-90.2
2461.000000	-43.13	-13.00	30.13	100.0	V	110.0	-88.1
3461.500000	-48.09	-13.00	35.09	100.0	V	150.0	-87.8
5197.000000	-43.38	-13.00	30.38	100.0	V	322.0	-84.8

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.500000	93.500000	93.500000	93.500000	93.500000	93.500000		93.500000	93.500000

Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.5000	93.5000	93.5000	93.5000	93.5000	93.5000		93.5000	93.5000


Frequency (MHz)	MaxPeak (dBm)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.5000	-10.0000	-10.0000	-10.0000	0.0000	0.0000		0.0000	0.0000

15 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@0
Test Voltage::	DC 5V From Adapter
Remark:	Temp 23 Humi:42%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
3600.500000	-48.45	-13.00	35.45	100.0	H	123.0	-86.8
5431.000000	-45.28	-13.00	32.28	100.0	H	221.0	-83.8
9240.000000	-48.91	-13.00	35.91	100.0	H	164.0	-84.0

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@0
Test Voltage::	DC 5V From Adapter
Remark:	Temp 23 Humi:42%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
3444.000000	-57.55	-13.00	44.55	100.0	V	329.0	-87.5
5267.500000	-52.45	-13.00	39.45	100.0	V	10.0	-85.1
6868.500000	-47.39	-13.00	34.39	100.0	V	10.0	-81.4

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@11
Test Voltage::	DC 5V From Adapter
Remark:	Temp 23 Humi:42%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
3458.500000	-50.52	-13.00	37.52	100.0	H	294.0	-88.0
5550.500000	-45.11	-13.00	32.11	100.0	H	294.0	-83.2
6924.000000	-43.71	-13.00	30.71	100.0	H	51.0	-81.0

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@11
Test Voltage::	DC 5V From Adapter
Remark:	Temp 23 Humi:42%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1930.000000	-57.18	-13.00	44.18	100.0	V	242.0	-89.5
3216.500000	-54.95	-13.00	41.95	100.0	V	185.0	-87.2
5261.000000	-51.80	-13.00	38.80	100.0	V	338.0	-85.0

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz QPSK 12@0
Test Voltage::	DC 5V From Adapter
Remark:	Temp 23 Humi:42%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
3442.500000	-49.55	-13.00	36.55	100.0	H	28.0	-87.8
5196.500000	-46.75	-13.00	33.75	100.0	H	111.0	-84.8
6863.000000	-43.67	-13.00	30.67	100.0	H	320.0	-81.3

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-VV
Test Mode:	TX High 15kHz QPSK 12@0
Test Voltage::	DC 5V From Adapter
Remark:	Temp 23 Humi:42%
Test Standard:	FCC Part 27 and RSS-139 Issue 3 and RSS-130 Issue 2
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2908.000000	-48.61	-13.00	35.61	100.0	V	271.0	-87.2
5169.500000	-46.24	-13.00	33.24	100.0	V	291.0	-84.6
6846.000000	-43.31	-13.00	30.31	100.0	V	187.0	-81.4


Appendix L.3: Field Strength of Spurious Radiation for Band 5

Below 1 GHz
BPSK

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
43.580000	-79.91	-13.00	66.91	100.0	H	259.0	-113.8
238.307500	-83.94	-13.00	70.94	100.0	H	28.0	-110.8
828.310000	-74.41	-13.00	61.41	100.0	H	349.0	-101.9

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.413750	-72.62	-13.00	59.62	100.0	V	276.0	-101.0
333.852500	-85.03	-13.00	72.03	100.0	V	159.0	-111.8
742.707500	-77.04	-13.00	64.04	100.0	V	352.0	-102.0

QPSK

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz QPSK 1@0
Test Voltage:	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
41.155000	-77.59	-13.00	64.59	100.0	H	40.0	-112.2
241.460000	-83.29	-13.00	70.29	100.0	H	31.0	-110.2
631.400000	-78.86	-13.00	65.86	100.0	H	49.0	-105.0

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX 15kHz QPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
43.337500	-89.76	-13.00	76.76	100.0	V	0.0	-124.0
95.111250	-72.83	-13.00	59.83	100.0	V	330.0	-99.6
374.350000	-83.89	-13.00	70.89	100.0	V	355.0	-110.9

Above 1 GHz
Low Channel
3.75 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 3.75kHzQPSK 1@0
Test Voltage:	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1648.000000	-55.28	---	-13.00	42.28	100.0	H	72.0	-92.4


Final_Result

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---		---	---

Test Report

EUT Information

EUT Name: DATA TERMINAL MODULE
Model: ME310G1-WW
Test Mode: TX Low 3.75kHzQPSK 1@0
Test Voltage:: DC 3.8V
Remark: Temp 22 Humi:50%
Test Standard: FCC Part 22 and RSS-132 Issue 3
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1648.500000	-55.65	---	-13.00	42.65	100.0	V	270.0	-92.4


Final_Result

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---		---	---

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 3.75kHz QPSK 1@47
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1648.000000	-54.68	---	-13.00	41.68	100.0	H	78.0	-92.4
2470.000000	-49.53	---	-13.00	36.53	100.0	H	316.0	-87.9


Final Result

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---		---	---

Test Report

EUT Information

EUT Name: DATA TERMINAL MODULE
Model: ME310G1-WW
Test Mode: TX Low 3.75kHz QPSK 1@47
Test Voltage: DC 3.8V
Remark: Temp 22 Humi:50%
Test Standard: FCC Part 22 and RSS-132 Issue 3
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2480.000000	-48.04	---	-13.00	35.04	100.0	V	356.0	-88.0

Final_Result


Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---	---	---	---

15 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-VV
Test Mode:	TX Low 15kHz BPSK 1@0
Test Voltage:	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1647.500000	-47.51	-13.00	34.51	100.0	H	314.0	-92.4
2472.000000	-31.32	-13.00	18.32	100.0	H	314.0	-87.9

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1648.000000	-54.09	-13.00	41.09	100.0	V	94.0	-92.4
2472.000000	-48.80	-13.00	35.80	100.0	V	46.0	-88.0

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1648.000000	-51.32	-13.00	38.32	100.0	H	302.0	-92.4
2472.500000	-28.38	-13.00	15.38	100.0	H	302.0	-87.9

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1648.000000	-55.86	-13.00	42.86	100.0	V	51.0	-92.4
2472.000000	-33.38	-13.00	20.38	100.0	V	183.0	-88.0

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz QPSK 12@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1648.500000	-56.31	-13.00	43.31	100.0	H	91.0	-92.4
2474.500000	-50.63	-13.00	37.63	100.0	H	77.0	-88.0

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Low 15kHz QPSK 12@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1647.000000	-56.37	-13.00	43.37	100.0	V	51.0	-92.4
2478.500000	-50.18	-13.00	37.18	100.0	V	253.0	-88.0

Mid Channel
3.75 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 3.75kHz QPSK 1@0
Test Voltage:	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1672.500000	-42.68	---	-13.00	29.68	100.0	H	73.0	-92.5
2509.000000	-44.76	---	-13.00	31.76	100.0	H	0.0	-88.3


Final_Result

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---	---	---	---

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 3.75kHz QPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1672.500000	-46.74	---	-13.00	33.74	100.0	V	312.0	-92.2
2509.000000	-44.04	---	-13.00	31.04	100.0	V	45.0	-88.2


Final Result

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---		---	---

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 3.75kHz QPSK 1@47
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1673.000000	-43.77	---	-13.00	30.77	100.0	H	86.0	-92.5
2509.500000	-45.57	---	-13.00	32.57	100.0	H	343.0	-88.3


Final Result

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---		---	---

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 3.75kHz QPSK 1@47
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1672.500000	-47.04	---	-13.00	34.04	100.0	V	309.0	-92.2
2509.500000	-43.44	---	-13.00	30.44	100.0	V	0.0	-88.2

Final Result


Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---	---	---	---

15 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz BPSK 1@0
Test Voltage:	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1673.000000	-55.03	-13.00	42.03	100.0	H	337.0	-92.5
2509.500000	-44.27	-13.00	31.27	100.0	H	52.0	-88.3

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1672.500000	-50.92	-13.00	37.92	100.0	V	184.0	-92.2
2509.500000	-37.47	-13.00	24.47	100.0	V	212.0	-88.2

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1673.000000	-54.87	-13.00	41.87	100.0	H	230.0	-92.5
2509.500000	-49.61	-13.00	36.61	100.0	H	15.0	-88.3

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1673.500000	-54.08	-13.00	41.08	100.0	V	11.0	-92.2
2509.500000	-43.05	-13.00	30.05	100.0	V	227.0	-88.2

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz QPSK 12@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1675.000000	-55.13	-13.00	42.13	100.0	H	255.0	-92.5
2509.500000	-51.74	-13.00	38.74	100.0	H	192.0	-88.3

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX Mid 15kHz QPSK 12@0
Test Voltage:	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1672.500000	-53.76	-13.00	40.76	100.0	V	36.0	-92.2
2510.000000	-43.90	-13.00	30.90	100.0	V	293.0	-88.2


Produkte
Products

High Channel
3.75 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 3.75kHz QPSK 1@0
Test Voltage:	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1697.000000	-54.72	---	-13.00	41.72	100.0	H	30.0	-92.4


Final Result

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---	---	---	---

Test Report

EUT Information

EUT Name: DATA TERMINAL MODULE
Model: ME310G1-WW
Test Mode: TX High 3.75kHz QPSK 1@0
Test Voltage:: DC 3.8V
Remark: Temp 22 Humi:50%
Test Standard: FCC Part 22 and RSS-132 Issue 3
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1694.000000	-55.36	---	-13.00	42.36	100.0	V	347.0	-92.1


Final_Result

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---	---	---	---

Test Report

EUT Information

EUT Name: DATA TERMINAL MODULE
Model: ME310G1-WW
Test Mode: TX High 3.75kHz QPSK 1@47
Test Voltage:: DC 3.8V
Remark: Temp 22 Humi:50%
Test Standard: FCC Part 22 and RSS-132 Issue 3
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1694.500000	-54.83	---	-13.00	41.83	100.0	H	272.0	-92.4


Final_Result

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---		---	---

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 3.75kHz QPSK 1@47
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:50%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	DET 2 (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1680.500000	-53.66	---	-13.00	40.66	100.0	V	311.0	-92.1

Final_Result


Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
---	---	---	---	---	---	---	---

15 kHz

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@0
Test Voltage:	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1698.000000	-55.62	-13.00	42.62	100.0	H	309.0	-92.4
2546.500000	-41.24	-13.00	28.24	100.0	H	302.0	-88.3

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@0
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1700.500000	-54.98	-13.00	41.98	100.0	V	239.0	-92.0
2546.000000	-38.24	-13.00	25.24	100.0	V	23.0	-88.4

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1698.000000	-56.22	-13.00	43.22	100.0	H	51.0	-92.4
2546.500000	-46.58	-13.00	33.58	100.0	H	44.0	-88.3

Test Report

EUT Information

EUT Name:	DATA TERMINAL MODULE
Model:	ME310G1-WW
Test Mode:	TX High 15kHz BPSK 1@11
Test Voltage::	DC 3.8V
Remark:	Temp 22 Humi:52%
Test Standard:	FCC Part 22 and RSS-132 Issue 3
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1699.500000	-54.51	-13.00	41.51	100.0	V	129.0	-92.1
2547.000000	-52.16	-13.00	39.16	100.0	V	254.0	-88.4