

ShaoXing Prolux Lighting Co., Ltd. RF TEST REPORT

Report Type: FCC Part 15C RF report

Model: PL-0170QI, PL-0170UQ

REPORT NUMBER: 190602340SHA-001

ISSUE DATE: July 12, 2019

DOCUMENT CONTROL NUMBER: TTRFFCCPART15C_V1 © 2018 Intertek



		Intertek Testing Services Shanghai
intoctok		Building No.86, 1198 Qinzhou Road (North)
UICHICH		Shanghai 200233, China
Total Quality. Assured. TEST REPORT		Telephone: 86 21 6127 8200 www.intertek.com
		Report no.: 190602340SHA-001
Applicant	:	ShaoXing Prolux Lighting Co., Ltd.
		Lu Dong Industrial Zone, Bai Guan District, Shangyu City, Zhejiang 312300, P.R. CHINA
Manufacturer	:	ShaoXing Prolux Lighting Co., Ltd.
		Lu Dong Industrial Zone, Bai Guan District, Shangyu City, Zhejiang 312300, P.R. CHINA
Factory	:	ShaoXing Prolux Lighting Co., Ltd.
		Lu Dong Industrial Zone, Bai Guan District, Shangyu City, Zhejiang 312300, P.R. CHINA
FCC ID	:	2AP2V-DESKLAMP06

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2017): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2013): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

PREPARED BY:

Frie. li

Project Engineer Eric Li

REVIEWED BY:

Reviewer Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Total Quality. Assured. TEST REPORT

Content

R	EVISION HISTORY		
Μ	IEASU	REMENT RESULT SUMMARY	5
1	G	ENERAL INFORMATION	6
	1 1		6
	1.1		6
	1.3	DESCRIPTION OF TEST FACILITY	.7
-			
2	16	EST SPECIFICATIONS	8
	2.1	STANDARDS OR SPECIFICATION	.8
	2.2	MODE OF OPERATION DURING THE TEST	.8
	2.3	TEST SOFTWARE LIST	.8
	2.4	TEST PERIPHERALS LIST	.8
	2.5	TEST ENVIRONMENT CONDITION:	.8
	2.6	INSTRUMENT LIST	.9
	2.7	MEASUREMENT UNCERTAINTY	10
3	R	ADIATED EMISSIONS	11
	3.1	Liмit1	11
	3.2	Measurement Procedure	11
	3.3	Test Configuration	12
	3.4	Test Results of Radiated Emissions	L4
4	С	ONDUCTED EMISSIONS	16
	4.1	LIMIT	16
	4.2	TEST CONFIGURATION	16
	4.3	MEASUREMENT PROCEDURE	L7
	4.4	Test Results of Conducted Emissions	18

Total Quality. Assured. TEST REPORT

Revision History

Report No. Version		Description	Issued Date
190602340SHA-001	Rev. 01	Initial issue of report	July 12, 2019



Measurement result summary

TEST ITEM	FCC REFERANCE	RESULT	
Radiated emissions	15.209	Pass	
Conducted emissions	15.207	Pass	

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

intertek Total Quality. Assured.

TEST REPORT

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Infuse LED Desk Lamp with Wireless		
Type/Model:	PL-0170QI, PL-0170UQ		
Description of EUT:	EUT is a wireless charger LED Luminaire. There are two models. Both of them use the same wireless charging module, PL-0170UQ has USB output function. We test both of them and list the results in this report.		
	PL-0170QI:		
	Adapter: RSS1006-156130-W2-B		
	Input: 100-240V~ 50/60Hz 1.4A, Output: 13.0V DC 1.2A		
	3.2W (only Lamp, except other functions), Total max.10W		
	PL-0170UQ:		
	Adapter: RSS1006-234130-W2-B		
	Input: 100-240V~ 50/60Hz 1.4A, Output: 13.0V DC 1.8A		
Rating:	3.2W (only Lamp, except other functions), USB: DC5V,2.1A lotal max.23.5W		
Category of EUT:	Class B		
EUT type:	Table top 🔲 Floor standing		
Software Version:	/		
Hardware Version:	/		
Sample received date:	July 4, 2019		
Date of test:	July 5, 2019 ~ July 10, 2019		

1.2 Technical Specification

Frequency Range:	110kHz – 205kHz



TEST REPORT

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139 FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab Registration code No.: 2042B-1 VCCI Registration Lab Registration No.: R-4243, G-845, C-4723, T-2252
	NVLAP Accreditation Lab NVLAP LAB CODE: 200849-0 A2LA Accreditation Lab Certificate Number: 3309.02

TEST REPORT

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2017) ANSI C63.10 (2013)

2.2 Mode of operation during the test

Within this test report, EUT was tested under all available operation modes and tested under its rating voltage and frequency. Other voltage and frequency are specified if used.

2.3 Test software list

Test Items	Software	Manufacturer	Version	
Conducted emission ESxS-K1		R&S	V2.1.0	
Radiated emission ES-K1		R&S	V1.71	

2.4 Test peripherals list

Item No.	Name	Brand and Model	Description	
1	Wireless load	KjB/ZS3012	100% power level	
2	Wireless load	KjB/ZS3012	50% power level	
3	Wireless load	KjB/ZS3012	0% power level	
4 USB load		RX21	Used for PL-0170UQ	

2.5 Test environment condition:

Test items	Temperature	Humidity	
Radiated emission	25°C	54% RH	
Power line conducted emission	24°C	54% RH	

Total Quality. Assured.

2.6 Instrument list

Conducted Emission						
Used	Equipment	Manufacturer	Туре	Internal no.	Due date	
•	Test Receiver	R&S	ESCS 30	EC 2107	2019-07-15	
	A.M.N.	R&S	ESH2-Z5	EC 3119	2019-12-07	
	A.M.N.	R&S	ENV 216	EC 3393	2020-07-04	
	A.M.N.	R&S	ENV4200	EC 3558	2020-06-10	
<	Shielding room	Zhongyu	-	EC 2838	2020-01-07	
Radiate	ed Emission					
Used	Equipment	Manufacturer	Туре	Internal no.	Due date	
	Test Receiver	R&S	ESIB 26	EC 3045	2019-09-12	
K	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2020-05-30	
	Pre-amplifier	R&S	AFS42-00101800- 25-S-42	EC5262	2020-06-10	
	Horn antenna	R&S	HF 906	EC 3049	2019-11-17	
	Horn antenna	ETS	3117	EC 4792-1	2020-01-09	
	Horn antenna	R&S	STLP9149	EC5881	2020-06-19	
	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2020-03-07	
	Semi-anechoic chamber	Albatross project	-	EC 3048	2019-09-15	

intertek Total Quality. Assured.

TEST REPORT

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Frequency	Expanded Uncertainty (k=2)
Conducted emission at mains norts	9kHz ~ 150kHz	3.52 dB
Conducted emission at mains ports	150kHz ~ 30MHz	3.19 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	4.90 dB
Padiated Emissions above 1 CHz	1GHz ~ 6GHz	5.02 dB
	6GHz ~ 18GHz	5.28 dB

Total Quality. Assured.

3 Radiated emissions

Test result: Pass

3.1 Limit

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88~216	150	3
216 ~ 960	200	3
Above 960	500	3

3.2 Measurement Procedure

For Radiated emission below 30MHz:

- a) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) Both X and Y axes of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz:

- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

Total Quality. Assured.

TEST REPORT

- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. All modes of operation were evaluated and the worst-case emissions were reported

3.3 Test Configuration

For Radiated emission below 30MHz:





For Radiated emission 30MHz to 1GHz:



For Radiated emission above 1GHz:



intertek Total Quality. Assured.

TEST REPORT

3.4 Test Results of Radiated Emissions

EUT was tested with empty load, half load and full load, the full load is the worst case and we listed the results in the report.

Model of PL-0170QI: Test data below 30MHz:

Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin	Detector	Remark
Х	0.15	67.00	20.20	88.60	21.60	РК	Fundamental
Х	0.75	45.40	20.10	60.20	14.80	РК	Spurious
Х	1.65	30.70	20.20	46.60	15.90	РК	Spurious
Х	2.84	30.90	20.30	59.10	28.20	РК	Spurious
Х	7.03	42.10	20.20	59.10	17.00	РК	Spurious
Y	0.15	62.90	20.20	88.80	25.90	РК	Fundamental
Y	0.75	42.50	20.10	60.20	17.70	РК	Spurious
Y	1.65	30.10	20.20	46.60	16.50	РК	Spurious
Y	3.32	32.20	20.30	59.10	26.90	РК	Spurious
Y	6.91	34.40	20.20	59.10	24.70	PK	Spurious

Test data from 30MHz to 1000MHz:

Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin	Detector
Н	35.83	25.20	15.50	40.00	14.80	PK
Н	78.60	14.20	7.80	40.00	25.80	PK
Н	156.35	24.30	11.50	43.50	19.20	РК
Н	208.84	23.40	11.00	43.50	20.10	РК
Н	556.79	26.30	20.40	46.00	19.70	РК
Н	937.80	31.90	24.10	46.00	14.10	РК
V	37.78	36.78	14.50	40.00	3.20	QP
V	55.27	24.90	7.80	40.00	15.10	РК
V	158.30	23.90	11.40	43.50	19.60	РК
V	257.43	24.80	15.10	46.00	21.20	РК
V	547.07	27.10	20.30	46.00	18.90	РК
V	933.91	31.50	24.00	46.00	14.50	РК

intertek Total Quality. Assured.

TEST REPORT

Model of PL-0170UQ:

Test data below 30MHz:

Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin	Detector	Remark
Х	0.15	76.20	20.20	89.00	12.80	РК	Fundamental
Х	0.75	45.90	20.10	60.20	14.30	РК	Spurious
Х	1.65	31.50	20.20	46.60	15.10	PK	Spurious
Х	7.09	46.20	20.20	59.10	12.90	PK	Spurious
Х	7.39	45.50	20.20	59.10	13.60	PK	Spurious
Y	0.15	68.80	20.20	89.00	20.20	PK	Fundamental
Y	0.51	47.70	20.00	66.90	19.20	РК	Spurious
Y	0.75	44.50	20.10	60.20	15.70	РК	Spurious
Y	1.59	33.00	20.20	47.20	14.20	PK	Spurious
Y	7.21	37.60	20.20	59.10	21.50	РК	Spurious

Test data from 30MHz to 1000MHz:

Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin	Detector
Н	133.03	30.50	12.80	43.50	13.00	PK
Н	234.11	32.50	12.40	46.00	13.50	PK
Н	344.91	32.60	16.30	46.00	13.40	PK
Н	418.78	40.50	18.10	46.00	5.50	PK
Н	504.31	38.90	19.70	46.00	7.10	PK
Н	896.97	36.50	23.70	46.00	9.50	РК
V	41.66	30.80	12.60	40.00	9.20	PK
V	49.44	38.47	9.00	40.00	1.50	QP
V	61.10	30.20	7.10	40.00	9.80	РК
V	156.35	31.60	11.50	43.50	11.90	PK
V	426.55	40.40	18.30	46.00	5.60	PK
V	523.75	37.40	20.00	46.00	8.60	РК

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.

2. Corrected Reading = Original Receiver Reading + Correct Factor

- 3. Margin = Limit Corrected Reading
- 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,

Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV, Limit = 40.00dBuV/m. Then Correct Factor = 30.20 + 2.00 - 32.00 = 0.20dB/m; Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m; Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

Total Quality. Assured.

4 Conducted emissions

Test result: Pass

4.1 Limit

From on of Emission (MUL-)	Conducted Emissions Limit (dBuV)					
Frequency of Emission (MHZ)	QP	AV				
0.15-0.5	66 to 56*	56 to 46 *				
0.5-5	56	46				
5-30	60	50				
* Decreases with the logarithm of the frequency.						

4.2 Test Configuration



Total Quality. Assured.

4.3 Measurement Procedure

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

Total Quality. Assured.

4.4 Test Results of Conducted Emissions

Test Curve of PL-0170QI:



	Quasi-peak			Average			
Frequency (MHz)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	
0.43	41.39	57.25	15.86	33.24	47.25	14.01	
0.72	36.31	56.00	19.69	31.85	46.00	14.15	
1.01	37.11	56.00	18.89	32.30	46.00	13.70	
1.30	36.12	56.00	19.88	31.75	46.00	14.25	
1.58	36.29	56.00	19.71	32.16	46.00	13.84	
28.34	25.18	60.00	34.82	10.25	50.00	39.75	
Note: * means the emission level 20dB below the relevant limit.							

Total Quality. Assured.





	Quasi-peak			Average			
Frequency (MHz)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	
0.43	42.01	57.28	15.27	33.95	47.28	13.33	
0.71	34.81	56.00	21.19	29.99	46.00	16.01	
1.00	36.03	56.00	19.97	31.56	46.00	14.44	
1.29	34.84	56.00	21.16	30.88	46.00	15.12	
2.15	31.69	56.00	24.31	28.06	46.00	17.94	
5.88	28.99	60.00	31.01	22.16	50.00	27.84	
Note: * means the emission level 20dB below the relevant limit.							

Total Quality. Assured.

Test Curve of PL-0170UQ:



	Quasi-peak			Average				
Frequency (MHz)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)		
0.15	46.96	65.97	19.01	29.24	55.97	26.73		
0.16	42.64	65.50	22.86	24.78	55.50	30.72		
0.19	53.16	64.21	11.05	32.71	54.21	21.50		
0.25	44.90	61.62	16.72	23.97	51.62	27.65		
0.48	39.20	56.38	17.18	21.84	46.38	24.54		
19.55	34.46	60.00	25.54	26.85	50.00	23.15		
Note: * means the e	Note: * means the emission level 20dB below the relevant limit.							

Total Quality. Assured.





	Quasi-peak			Average			
Frequency (MHz)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	
0.18	53.55	64.34	10.79	31.97	54.34	22.37	
0.26	43.39	61.52	18.13	25.04	51.52	26.48	
0.31	37.75	59.87	22.12	18.96	49.87	30.91	
0.47	38.63	56.45	17.82	21.49	46.45	24.96	
0.76	38.55	56.00	17.45	32.02	46.00	13.98	
19.01	37.69	60.00	22.31	29.51	50.00	20.49	
Note: * means the emission level 20dB below the relevant limit.							

Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

- 2. Corrected Reading = Original Receiver Reading + Correct Factor
- 3. Margin = Limit Corrected Reading
- 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.