

## FCC RF Exposure

EUT Description: Smart P&T Camera

Model No.: MI-CW054-199W SK112

Series Model: MI-CW059-199W SK114, SK200, SK201, SK203, SK204, SK205, SK206, SK207, SK208, SK209, SK210, SK211, SK212, SK213, SK214, SK215, SK216, SK217, SK218

FCC ID: 2BE8B-SK112

Equipment type: Mobile Device equipment

Test procedures according to the technical standards: KDB 447498 D01 V06 and FCC 2.1091.

### 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F = frequency in MHz

Formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where :

$P_d$  = power density in mW/cm<sup>2</sup>,

$P_{out}$  = output power to antenna in mW;

G = gain of antenna in linear scale,

$\pi$  = 3.14;

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE

limit is reached.

## 2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 3. Test Result of RF Exposure Evaluation

### WIFI

Modulation	Channel Freq. (MHz)	Conduct ed power (dBm)	Max tune-up power (mW)	Antenna Gain (dBi)	Antenna gain numeric	Evaluation result (mW/cm2 )	Power density Limits (mW/cm2)
802.11b	2412	18.61	72.61059	1.66	1.465	0.021173273	1
	2437	18.45	69.98419	1.66	1.465	0.020407415	1
	2462	18.73	74.64487	1.66	1.465	0.02176647	1
802.11g	2412	17.62	57.80960	1.66	1.465	0.016857299	1
	2437	17.72	59.15616	1.66	1.465	0.017249956	1
	2462	17.85	60.95368	1.66	1.465	0.017774115	1
802.11n	2412	16.58	45.49880	1.66	1.465	0.013267466	1
	2437	16.65	46.23810	1.66	1.465	0.013483045	1
	2462	16.90	48.97788	1.66	1.465	0.014281966	1

Wifi: Conclusion: the max result 0.02176647:  $\leq 1.0$  compliance with FCC's RF Exposure.

Conclusion: No SAR is required