

FCC Part 15C Measurement and Test Report

For

SUPERDIGITAL TECHNOLOGY CO., LIMITED

19th Floor, Block B, Nanxian Building, Longhua New District, Shenzhen

518000, P.R. China

FCC ID: 2ACDFF12

FCC Rule(s): FCC Part 15C

Product Description: Smart Phone

Tested Model: F12

Report No.: STR15038284I-4

Tested Date: 2015-03-28 to 2015-04-09

Issued Date: 2015-04-09

Tested By: Lebron Wang / Engineer

Reviewed By: Lahm Peng / EMC Manager

Approved & Authorized By: Jandy So / PSQ Manager

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
2. SUMMARY OF TEST RESULTS	7
3. RF EXPOSURE	8
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
4. ANTENNA REQUIREMENT	9
4.1 STANDARD APPLICABLE.....	9
4.2 EVALUATION INFORMATION	9
5. POWER SPECTRAL DENSITY	10
5.1 STANDARD APPLICABLE.....	10
5.2 TEST EQUIPMENT LIST AND DETAILS	10
5.3 TEST PROCEDURE.....	10
5.4 ENVIRONMENTAL CONDITIONS	10
5.5 SUMMARY OF TEST RESULTS/PLOTS	11
6. 6DB BANDWIDTH	18
6.1 STANDARD APPLICABLE.....	18
6.2 TEST EQUIPMENT LIST AND DETAILS	18
6.3 TEST PROCEDURE.....	18
6.4 ENVIRONMENTAL CONDITIONS	18
6.5 SUMMARY OF TEST RESULTS/PLOTS	19
7. RF OUTPUT POWER.....	26
7.1 STANDARD APPLICABLE.....	26
7.2 TEST EQUIPMENT LIST AND DETAILS	26
7.3 TEST PROCEDURE.....	26
7.4 ENVIRONMENTAL CONDITIONS	26
7.5 SUMMARY OF TEST RESULTS/PLOTS	27
8. FIELD STRENGTH OF SPURIOUS EMISSIONS	34
8.1 MEASUREMENT UNCERTAINTY	34
8.2 STANDARD APPLICABLE.....	34
8.3 TEST EQUIPMENT LIST AND DETAILS	34
8.4 TEST PROCEDURE.....	35
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	35
8.6 ENVIRONMENTAL CONDITIONS	36
8.7 SUMMARY OF TEST RESULTS/PLOTS	36
9. OUT OF BAND EMISSIONS.....	65
9.1 STANDARD APPLICABLE.....	65
9.2 TEST EQUIPMENT LIST AND DETAILS	65
9.3 TEST PROCEDURE.....	65
9.4 ENVIRONMENTAL CONDITIONS	66
9.5 SUMMARY OF TEST RESULTS/PLOTS	66
10. CONDUCTED EMISSIONS	75
10.1 MEASUREMENT UNCERTAINTY	75
10.2 TEST EQUIPMENT LIST AND DETAILS	75
10.3 TEST PROCEDURE.....	75
10.4 BASIC TEST SETUP BLOCK DIAGRAM.....	75
10.5 ENVIRONMENTAL CONDITIONS	76
10.6 TEST RECEIVER SETUP	76
10.7 SUMMARY OF TEST RESULTS/PLOTS	76
10.8 CONDUCTED EMISSIONS TEST DATA.....	76

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: SUPERDIGITAL TECHNOLOGY CO., LIMITED
Address of applicant: 19th Floor, Block B, Nanxian Building, Longhua New District, Shenzhen 518000, P.R. China
Manufacturer: SUPERDIGITAL TECHNOLOGY CO., LIMITED
Address of manufacturer: 19th Floor, Block B, Nanxian Building, Longhua New District, Shenzhen 518000, P.R. China

General Description of EUT	
Product Name:	Smart Phone
Brand Name:	Superinworld
Model No.:	F12
Adding Model:	/
Hardware Version:	A3-02
Software Version:	a3e_ax_tiaomao_3g_q6_b2b5_gps_teeno_v01_05022015
IMEI:	352527061645962/352527071645970
Rated Voltage:	DC 3.7V Li-ion Battery
Battery:	1400mAh
Power Adaptor:	F12
	Input 100-260V, 50/60Hz, Output DC 5.2V/800mA
Device Category:	Portable Device
<i>The EUT is GSM850/900/DCS1800/PCS1900, WCDMA Band II, Band V, smart phone. the smart phone is intended for speech and Multimedia Message Service (MMS) transmission. It is equipped with GPRS class 12 for GSM850 and GSM1900 and Bluetooth, Wi-Fi, GPS and camera functions. For more information see the following datasheet</i>	
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40)
RF Output Power:	13.42dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11/7
Channel Separation:	5MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	1.89dBi
Lowest Internal Frequency	32.768KHz

1.2 Test Standards

The following report is prepared on behalf of the SUPERDIGITAL TECHNOLOGY CO., LIMITED in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 V03r02 for digital transmission systems shall be performed also.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz
TM2	802.11g	2412MHz, 2437MHz, 2462MHz
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz
TM4	802.11n-HT40	2422MHz, 2437MHz, 2452MHz

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	1.0	Shielded	Without Core
Earphone	1.0	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has an integral antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2014-05-28	2015-05-27
Attenuator	ATTEN	ATS100-4-20	/	2014-05-28	2015-05-27

5.3 Test Procedure

According to the KDB 558074 D01 V03r02, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.4 Environmental Conditions


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.5 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b	2412	-16.81	8
	2437	-17.08	8
	2462	-17.27	8
802.11g	2412	-22.95	8
	2437	-23.17	8
	2462	-23.41	8
802.11n HT20	2412	-23.49	8
	2437	-23.55	8
	2462	-23.89	8
802.11n HT40	2422	-28.39	8
	2437	-28.55	8
	2452	-28.85	8

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT20-Middle Channel



802.11n-HT20-High Channel



6. 6dB Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2014-05-28	2015-05-27
Attenuator	ATTEN	ATS100-4-20	/	2014-05-28	2015-05-27

6.3 Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Environmental Conditions


Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

6.5 Summary of Test Results/Plots


Test Mode	Test Channel MHz	6 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz
802.11b	2412	9522	12568.1	500
	2437	9563	12485.9	500
	2462	9560	12486.6	500
802.11g	2412	16503	16373.1	500
	2437	16498	16369.4	500
	2462	16484	16374.7	500
802.11n-HT20	2412	17601	17541.9	500
	2437	17649	17535.5	500
	2462	17612	17518.9	500
802.11n-HT20	2422	36107	35861.1	500
	2437	36418	35903.4	500
	2452	36391	35839.9	500

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT20-High Channel



7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2014-05-28	2015-05-27
Attenuator	ATTEN	ATS100-4-20	/	2014-05-28	2015-05-27

7.3 Test Procedure

According to section 15.247(b)-power output of the KDB-558074 D01 V03r02, 9.2.2.2 (channel integration method) When this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- Set span to at least 1.5 times the OBW.
- Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- Set VBW $\geq 3 \times$ RBW.
- Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto.
- Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.4 Environmental Conditions


Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

7.5 Summary of Test Results/Plots


Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b _ 11Mbps	2412	13.42	21.98	1000
	2437	12.69	18.58	1000
	2462	12.27	16.87	1000
802.11g_54Mbps	2412	10.48	11.17	1000
	2437	10.04	10.09	1000
	2462	9.83	9.62	1000
802.11n HT20_MCS7	2412	10.28	10.67	1000
	2437	9.80	9.55	1000
	2462	9.51	8.93	1000
802.11n HT40_MCS7	2422	8.76	7.52	1000
	2437	8.57	7.19	1000
	2452	8.53	7.13	1000

Please refer to the following test plots:


802.11b-11Mbps-Low Channel




802.11b -11Mbps-Middle Channel




802.11b -11Mbps-High Channel




802.11g-54Mbps-Low Channel




802.11g-54Mbps-Middle Channel




802.11g-54Mbps-High Channel




802.11n-HT20-MCS7-Low Channel




802.11n-HT20-MCS7-Middle Channel




802.11n-HT20-MCS7-High Channel




802.11n-HT40-MCS7-Low Channel



802.11n-HT40-MCS7-Middle Channel



802.11n-HT40-MCS7-High Channel



8. Field Strength of Spurious Emissions

8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.10 dB.

8.2 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.3 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
EMI Test Receiver	R&S	ESVB	825471/005	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23
Horn Antenna	ETS	3116B	00088203	2014-05-24	2015-05-23
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2014-05-24	2015-05-23

8.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.6 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

8.7 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: Smart Phone
 Tested Model: F12
 Operating Condition: 802.11b Transmitting Low Channel-2412MHz
 Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	40.2757	21.64	-8.39	13.25	40.00	-26.75	105	100	peak
2	55.4147	22.15	-7.99	14.16	40.00	-25.84	160	100	peak
3	99.5281	21.88	-9.61	12.27	43.50	-31.23	180	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	49.3594	24.54	-7.45	17.09	40.00	-22.91	140	100	peak
2	141.8262	29.29	-13.12	16.17	43.50	-27.33	250	100	peak
3	909.6667	23.90	5.38	29.28	46.00	-16.72	120	100	peak

Operating Condition: 802.11b Transmitting Middle Channel-2437MHz


Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	38.3462	22.12	-8.77	13.35	40.00	-26.65	145	100	peak
2	103.4421	21.68	-9.57	12.11	43.50	-31.39	120	100	peak
3	416.1791	23.29	-2.56	20.73	46.00	-25.27	108	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	36.3814	26.86	-9.52	17.34	40.00	-22.66	120	100	peak
2	56.0007	24.57	-8.07	16.50	40.00	-23.50	113	100	peak
3	640.6110	22.98	1.70	24.68	46.00	-21.32	157	100	peak

Operating Condition: 802.11b Transmitting High Channel-2462MHz


Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	49.0145	22.54	-7.44	15.10	40.00	-24.90	120	100	peak
2	275.1570	23.41	-6.91	16.50	46.00	-29.50	250	100	peak
3	734.4913	25.08	0.45	25.53	46.00	-20.47	360	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	49.8814	25.39	-7.44	17.95	40.00	-22.05	360	100	peak
2	103.4421	21.93	-9.57	12.36	43.50	-31.14	200	100	peak
3	401.8385	22.52	-2.89	19.63	46.00	-26.37	120	100	peak

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: Smart Phone
 Tested Model: F12
 Operating Condition: 802.11g Transmitting Low Channel-2412MHz
 Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	47.8260	22.04	-7.46	14.58	40.00	-25.42	170	100	peak
2	110.5687	21.75	-9.70	12.05	43.50	-31.45	120	100	peak
3	766.0572	24.04	1.55	25.59	46.00	-20.41	320	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	33.3279	24.81	-10.48	14.33	40.00	-25.67	270	100	peak
2	108.2667	22.08	-9.59	12.49	43.50	-31.01	190	100	peak
3	345.5952	22.25	-4.38	17.87	46.00	-28.13	360	100	peak

Operating Condition: 802.11g Transmitting Middle Channel-2437MHz


Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	49.3594	22.31	-7.45	14.86	40.00	-25.14	270	100	peak
2	487.3151	23.63	-1.59	22.04	46.00	-23.96	160	100	peak
3	906.4824	22.39	5.34	27.73	46.00	-18.27	228	200	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	35.4993	36.79	-9.88	26.91	40.00	-13.09	360	100	peak
2	45.3755	34.39	-7.46	26.93	40.00	-13.07	120	100	peak
3	93.1132	33.00	-10.57	22.43	43.50	-21.07	270	100	peak

Operating Condition: 802.11g Transmitting High Channel-2462MHz


Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	49.0145	21.82	-7.44	14.38	40.00	-25.62	270	100	peak
2	543.2742	23.82	-1.36	22.46	46.00	-23.54	150	100	peak
3	919.2866	21.65	5.51	27.16	46.00	-18.84	360	100	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	36.8953	24.99	-9.26	15.73	40.00	-24.27	360	100	peak
2	51.8430	28.03	-7.63	20.40	40.00	-19.60	180	100	peak
3	601.4265	22.32	1.16	23.48	46.00	-22.52	120	100	peak

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: Smart Phone

Tested Model: F12

Operating Condition: 802.11n-HT20 Transmitting Low Channel-2412MHz


Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	41.8596	22.72	-8.08	14.64	40.00	-25.36	260	100	peak
2	234.9909	23.32	-8.06	15.26	46.00	-30.74	120	200	peak
3	711.6734	24.00	-0.38	23.62	46.00	-22.38	289	200	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	33.3279	23.81	-10.48	13.33	40.00	-26.67	130	100	peak
2	36.8953	23.67	-9.26	14.41	40.00	-25.59	120	100	peak
3	157.0074	25.31	-12.52	12.79	43.50	-30.71	360	100	peak

Operating Condition: 802.11n-HT20 Transmitting Middle Channel-2437MHz


Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	47.4918	22.20	-7.45	14.75	40.00	-25.25	274	100	peak
2	54.0711	22.56	-7.85	14.71	40.00	-25.29	130	100	peak
3	629.4772	24.71	-1.44	23.27	46.00	-22.73	120	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	33.3279	24.81	-10.48	14.33	40.00	-25.67	360	100	peak
2	36.6375	23.77	-9.39	14.38	40.00	-25.62	110	100	peak
3	148.9625	26.35	-12.98	13.37	43.50	-30.13	120	100	peak

Operating Condition: 802.11n-HT20 Transmitting High Channel-2462MHz


Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	55.8047	22.44	-8.04	14.40	40.00	-25.60	360	100	peak
2	106.0126	22.28	-9.58	12.70	43.50	-30.80	138	100	peak
3	642.8613	25.04	-1.26	23.78	46.00	-22.22	180	200	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	50.4089	26.75	-7.49	19.26	40.00	-20.74	270	100	peak
2	145.8611	25.70	-13.04	12.66	43.50	-30.84	120	100	peak
3	909.6667	22.53	5.38	27.91	46.00	-18.09	360	100	peak

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: Smart Phone

Tested Model: F12

Operating Condition: 802.11n-HT40 Transmitting Low Channel-2422MHz


Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	49.7068	23.33	-7.44	15.89	40.00	-24.11	260	100	peak
2	100.5806	22.04	-9.57	12.47	43.50	-31.03	120	200	peak
3	595.1329	25.13	-1.81	23.32	46.00	-22.68	289	200	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	36.3814	24.24	-9.52	14.72	40.00	-25.28	130	100	peak
2	51.1209	24.69	-7.56	17.13	40.00	-22.87	120	100	peak
3	506.4791	23.25	-1.17	22.08	46.00	-23.92	360	100	peak

Operating Condition: 802.11n-HT40 Transmitting Middle Channel-2437MHz


Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	46.1780	22.25	-7.46	14.79	40.00	-25.21	274	100	peak
2	55.8047	24.02	-8.04	15.98	40.00	-24.02	130	100	peak
3	434.0651	23.14	-2.32	20.82	46.00	-25.18	120	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	33.3279	25.07	-10.48	14.59	40.00	-25.41	360	100	peak
2	36.6375	24.94	-9.39	15.55	40.00	-24.45	110	100	peak
3	99.5281	22.72	-9.61	13.11	43.50	-30.39	120	100	peak

Operating Condition: 802.11n-HT40 Transmitting High Channel-2452MHz


Comment: Battery: DC3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	53.8818	22.60	-7.83	14.77	40.00	-25.23	360	100	peak
2	552.8833	22.91	-1.38	21.53	46.00	-24.47	138	100	peak
3	798.9797	23.17	2.60	25.77	46.00	-20.23	180	200	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	36.6375	23.98	-9.39	14.59	40.00	-25.41	270	100	peak
2	55.4147	23.65	-7.99	15.66	40.00	-24.34	120	100	peak
3	912.8620	21.34	5.43	26.77	46.00	-19.23	360	100	peak

*Spurious Emissions Above 1GHz**Test Mode: 802.11b*

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	59.24	0.57	59.81	74.00	-14.19	H	PK
4824.000	44.84	0.57	45.41	54.00	-8.59	H	AV
7236.000	35.01	3.69	38.70	74.00	-35.30	H	PK
7236.000	23.58	3.69	27.27	54.00	-26.73	H	AV
4824.000	50.85	0.57	51.42	74.00	-22.58	V	PK
4824.000	37.17	0.57	37.74	54.00	-16.26	V	AV
7236.000	34.80	3.69	38.49	74.00	-35.51	V	PK
7236.000	23.41	3.69	27.10	54.00	-26.90	V	AV
Middle Channel-2437MHz							
4874.000	57.35	0.66	58.01	74.00	-15.99	H	PK
4874.000	42.77	0.66	43.43	54.00	-10.57	H	AV
7311.000	37.61	3.76	41.37	74.00	-32.63	H	PK
7311.000	25.87	3.76	29.63	54.00	-24.37	H	AV
4874.000	51.19	0.66	51.85	74.00	-22.15	V	PK
4874.000	37.61	0.66	38.27	54.00	-15.73	V	AV
7311.000	38.83	3.76	42.59	74.00	-31.41	V	PK
7311.000	25.84	3.76	29.60	54.00	-24.40	V	AV
High Channel-2462MHz							
4924.000	56.32	0.74	57.06	74.00	-16.94	H	PK
4924.000	42.94	0.74	43.68	54.00	-10.32	H	AV
7386.000	37.91	3.83	41.74	74.00	-32.26	H	PK
7386.000	27.26	3.83	31.09	54.00	-22.91	H	AV
4924.000	53.07	0.74	53.81	74.00	-20.19	V	PK
4924.000	39.42	0.74	40.16	54.00	-13.84	V	AV
7386.000	38.69	3.83	42.52	74.00	-31.48	V	PK
7386.000	27.20	3.83	31.03	54.00	-22.97	V	AV

Test Mode: 802.11g

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	54.00	0.57	54.57	74.00	-19.43	H	PK
4824.000	47.78	0.57	48.35	54.00	-5.65	H	AV
7236.000	35.17	3.69	38.86	74.00	-35.14	H	PK
7236.000	23.82	3.69	27.51	54.00	-26.49	H	AV
4824.000	42.22	0.57	42.79	74.00	-31.21	V	PK
4824.000	33.11	0.57	33.68	54.00	-20.32	V	AV
7236.000	35.08	3.69	38.77	74.00	-35.23	V	PK
7236.000	23.89	3.69	27.58	54.00	-26.42	V	AV
Middle Channel-2437MHz							
4874.000	53.19	0.66	53.85	74.00	-20.15	H	PK
4874.000	46.35	0.66	47.01	54.00	-6.99	H	AV
7311.000	37.62	3.76	41.38	74.00	-32.62	H	PK
7311.000	26.04	3.76	29.80	54.00	-24.20	H	AV
4874.000	43.36	0.66	44.02	74.00	-29.98	V	PK
4874.000	32.19	0.66	32.85	54.00	-21.15	V	AV
7311.000	37.03	3.76	40.79	74.00	-33.21	V	PK
7311.000	26.65	3.76	30.41	54.00	-23.59	V	AV
High Channel-2462MHz							
4924.000	55.79	0.74	56.53	74.00	-17.47	H	PK
4924.000	33.00	0.74	33.74	54.00	-20.26	H	AV
7386.000	37.86	3.83	41.69	74.00	-32.31	H	PK
7386.000	27.21	3.83	31.04	54.00	-22.96	H	AV
4924.000	45.15	0.74	45.89	74.00	-28.11	V	PK
4924.000	33.60	0.74	34.34	54.00	-19.66	V	AV
7386.000	38.93	3.83	42.76	74.00	-31.24	V	PK
7386.000	27.12	3.83	30.95	54.00	-23.05	V	AV

Test Mode: 802.11n-HT20

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	55.85	0.57	56.42	74.00	-17.58	H	PK
4824.000	32.67	0.57	33.24	54.00	-20.76	H	AV
7236.000	34.49	3.69	38.18	74.00	-35.82	H	PK
7236.000	23.28	3.69	26.97	54.00	-27.03	H	AV
4824.000	43.03	0.57	43.60	74.00	-30.40	V	PK
4824.000	31.74	0.57	32.31	54.00	-21.69	V	AV
7236.000	34.59	3.69	38.28	74.00	-35.72	V	PK
7236.000	23.31	3.69	27.00	54.00	-27.00	V	AV
Middle Channel-2437MHz							
4874.000	53.08	0.66	53.74	74.00	-20.26	H	PK
4874.000	31.66	0.66	32.32	54.00	-21.68	H	AV
7311.000	36.80	3.76	40.56	74.00	-33.44	H	PK
7311.000	26.16	3.76	29.92	54.00	-24.08	H	AV
4874.000	44.14	0.66	44.80	74.00	-29.20	V	PK
4874.000	32.41	0.66	33.07	54.00	-20.93	V	AV
7311.000	37.59	3.76	41.35	74.00	-32.65	V	PK
7311.000	25.48	3.76	29.24	54.00	-24.76	V	AV
High Channel-2462MHz							
4924.000	53.25	0.74	53.99	74.00	-20.01	H	PK
4924.000	31.69	0.74	32.43	54.00	-21.57	H	AV
7386.000	38.35	3.83	42.18	74.00	-31.82	H	PK
7386.000	27.19	3.83	31.02	54.00	-22.98	H	AV
4924.000	43.52	0.74	44.26	74.00	-29.74	V	PK
4924.000	31.12	0.74	31.86	54.00	-22.14	V	AV
7386.000	38.66	3.83	42.49	74.00	-31.51	V	PK
7386.000	26.99	3.83	30.82	54.00	-23.18	V	AV

Test Mode: 802.11n-HT40

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2422MHz							
4844.000	53.25	0.60	53.85	74.00	-20.15	H	PK
4824.000	38.25	0.60	38.85	54.00	-15.15	H	AV
7266.000	46.48	3.72	50.20	74.00	-23.80	H	PK
7266.000	32.56	3.72	36.28	54.00	-17.72	H	AV
4844.000	54.22	0.60	54.82	74.00	-19.18	V	PK
4824.000	39.42	0.60	40.02	54.00	-13.98	V	AV
7266.000	48.81	3.72	52.53	74.00	-21.47	V	PK
7266.000	34.78	3.72	38.50	54.00	-15.50	V	AV
Middle Channel-2437MHz							
4874.000	52.53	0.66	53.19	74.00	-20.81	H	PK
4874.000	37.88	0.66	38.54	54.00	-15.46	H	AV
7311.000	44.88	3.76	48.64	74.00	-25.36	H	PK
7311.000	32.03	3.76	35.79	54.00	-18.21	H	AV
4874.000	53.74	0.66	54.40	74.00	-19.60	V	PK
4874.000	39.95	0.66	40.61	54.00	-13.39	V	AV
7311.000	45.78	3.76	49.54	74.00	-24.46	V	PK
7311.000	34.00	3.76	37.76	54.00	-16.24	V	AV
High Channel-2452MHz							
4904.000	52.65	0.72	53.37	74.00	-20.63	H	PK
4904.000	39.37	0.72	40.09	54.00	-13.91	H	AV
7356.000	45.63	3.81	49.44	74.00	-24.56	H	PK
7356.000	30.73	3.81	34.54	54.00	-19.46	H	AV
4904.000	54.84	0.72	55.56	74.00	-18.44	V	PK
4904.000	40.83	0.72	41.55	54.00	-12.45	V	AV
7356.000	48.18	3.81	51.99	74.00	-22.01	V	PK
7356.000	35.12	3.81	38.93	54.00	-15.07	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
EMI Test Receiver	R&S	ESVB	825471/005	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23

9.3 Test Procedure

According to the KDB 558074D01 v03r02, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 V03r02, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW $\geq$ 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.4 Environmental Conditions


Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.5 Summary of Test Results/Plots

Please refer to the test plots as below.


802.11b-Lowest Bandedge

Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	29.50	-3.71	25.79	54.00	-28.21	Average Detector
	2310.000	42.81	-3.71	39.10	74.00	-34.90	Peak Detector
2	2390.000	31.27	-3.54	27.73	54.00	-26.27	Average Detector
	2390.000	44.12	-3.54	40.58	74.00	-33.42	Peak Detector
3	2399.040	49.76	-3.51	46.25	54.00	-7.75	Average Detector
4	2400.000	49.20	-3.51	45.69	Delta =39.65dBc		Average Detector
5	2412.480	88.82	-3.48	85.34			Average Detector

802.11b-Highest Bandedge
Vertical (Worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	2461.600	87.03	-3.37	83.66	/	/	Average Detector
	2463.300	96.02	-3.36	92.66	/	/	Peak Detector
2	2483.500	Delta = 58.99dBc		24.67	54.00	-29.33	Average Detector
	2483.500			33.67	74.00	-40.33	Peak Detector
3	2500.000	29.17	-3.28	25.89	54.00	-28.11	Average Detector
	2500.000	41.43	-3.28	38.15	74.00	-35.85	Peak Detector

802.11g-Lowest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	29.51	-3.71	25.80	54.00	-28.20	Average Detector
	2310.000	41.73	-3.71	38.02	74.00	-35.98	Peak Detector
2	2390.000	33.32	-3.54	29.78	54.00	-24.22	Average Detector
	2390.000	47.51	-3.54	43.97	74.00	-30.03	Peak Detector
3	2400.000	43.36	-3.51	39.85	Delta =38.69dBc		Average Detector
4	2411.160	82.02	-3.48	78.54			Average Detector


802.11g-Highest Bandedge
Vertical (Worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2460.700	80.60	-3.37	77.23	/	/	Average Detector
	2463.450	91.85	-3.36	88.49	/	/	Peak Detector
2	2483.500	Delta = 46.90dBc		30.33	54.00	-23.67	Average Detector
	2483.500			41.59	74.00	-32.41	Peak Detector
3	2500.000	29.60	-3.28	26.32	54.00	-27.68	Average Detector
	2500.000	42.55	-3.28	39.27	74.00	-34.73	Peak Detector


802.11n-HT20-Lowest Bandedge

Vertical (Worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.000	29.43	-3.71	25.72	54.00	-28.28	Average Detector
	2310.000	42.34	-3.71	38.63	74.00	-35.37	Peak Detector
2	2390.000	34.55	-3.54	31.01	54.00	-22.99	Average Detector
	2390.000	51.10	-3.54	47.56	74.00	-26.44	Peak Detector
3	2400.000	44.09	-3.51	40.58	Delta =37.75dBc		Average Detector
4	2410.920	81.81	-3.48	78.33			Average Detector

802.11n-HT20-Highest Bandedge
Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2460.850	80.29	-3.37	76.92	/	/	Average Detector
	2461.400	91.78	-3.37	88.41	/	/	Peak Detector
2	2483.500	Delta =48.25dBc		28.67	54.00	-25.33	Average Detector
	2483.500			40.16	74.00	-33.84	Peak Detector
3	2500.000	29.63	-3.28	26.35	54.00	-27.65	Average Detector
	2500.000	41.59	-3.28	38.31	74.00	-35.69	Peak Detector

802.11n-HT40-Lowest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	29.35	-3.71	25.64	54.00	-28.36	Average Detector
	2310.000	41.55	-3.71	37.84	74.00	-36.16	Peak Detector
2	2390.000	35.14	-3.54	31.60	54.00	-22.40	Average Detector
	2390.000	48.65	-3.54	45.11	74.00	-28.89	Peak Detector
3	2400.000	38.12	-3.51	34.61	Delta =39.70dBc		Average Detector
4	2416.400	77.78	-3.47	74.31			Average Detector

802.11n-HT40-Highest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2450.230	75.67	-3.40	72.27	/	/	Average Detector
	2459.330	86.70	-3.38	83.32	/	/	Peak Detector
2	2483.500	Delta = 44.36dBc		27.91	54.00	-26.09	Average Detector
	2483.500			38.96	74.00	-35.04	Peak Detector
3	2500.000	30.39	-3.28	27.11	54.00	-26.89	Average Detector
	2500.000	43.57	-3.28	40.29	74.00	-33.71	Peak Detector

10. Conducted Emissions

10.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

10.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2014-05-28	2015-05-27
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2014-05-28	2015-05-27
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2014-05-28	2015-05-27


10.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

10.4 Basic Test Setup Block Diagram



10.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

10.6 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal

10.7 Summary of Test Results/Plots

According to the data in section 9.8, the EUT complied with the FCC Part 15.207 Conducted margin for a Class B device, with the *worst* margin reading of:


-2.53 dB at 0.3700 MHz in the **Line, Average** detector, 0.15-30MHz

10.8 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: Smart Phone
 Tested Model: F12
 Operating Condition: (WIFI)Transmitting
 Comment: AC 120V/60Hz

Test Specification: Neutral



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1	0.3700	35.88	9.50	45.38	48.50	-3.12	AVG
2	0.3740	41.19	9.50	50.69	58.41	-7.72	peak
3	0.4660	29.60	9.50	39.10	46.58	-7.48	AVG
4	0.7940	34.50	9.79	44.29	56.00	-11.71	peak
5	0.9300	22.68	9.93	32.61	46.00	-13.39	AVG
6	3.7300	38.27	10.00	48.27	56.00	-7.73	peak

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3700	36.47	9.50	45.97	48.50	-2.53	AVG
2	0.3740	42.90	9.50	52.40	58.41	-6.01	peak
3	0.4660	36.69	9.50	46.19	56.58	-10.39	peak
4	0.4660	29.65	9.50	39.15	46.58	-7.43	AVG
5	0.9220	23.39	9.92	33.31	46.00	-12.69	AVG
6	3.9620	34.64	10.00	44.64	56.00	-11.36	peak

***** END OF REPORT *****