#### **APPLICANT: Lucent Technologies, Inc.**

#### FCC ID: AS5ONEBTS-11



67 Whippany Road Whippany, NJ 07981

> Rudolf J. Pillmeier Telephone: 973-386-3837 E-Mail: rpillmeier@lucent.com June 22, 2005

Subject: Application for Certification under FCC ID: AS5ONEBTS-11, Covering the UMTS/W-CDMA Transceiver System Operating in the Cellular Radiotelephone Service, 869-894 MHz, Spectrum.

Mr. Sid Sanders, President Timco Engineering, Inc. 849 N. W. State Road 45, P. O. Box 370 Newberry, Florida 32669

### Dear Mr. Sanders:

Lucent Technologies' UMTS-CDMA Transceiver System (850) is designed to operate in the Lucent UMTS 850 Flexent® OneBTS<sup>TM</sup> Wireless Base Station, configured for 3S1C operation over the Cellular Frequency Spectrum 869-894 MHz. The objective of this application is to obtain FCC authorization as a new filing, under FCC ID: AS5ONEBTS-11, for operation in the Universal Mobile Telecommunications System (UMTS) with a single 5 MHz emission bandwidth carrier (4M10F9W), set to a maximum power level at the antenna terminal of 40 Watts (3-second) per carrier.

The UMTS850 Transceiver System consists of the principle RF components: (1) Crystal Reference Oscillator Module (OMA) 15 MHz, (2) UMTS-CDMA Multi-Carrier CDMA Radio MCR850, Model BNJ65, (3) C2PAM power amplifier, and (4) 25 MHz Dual Duplex (DDpx), low loss, transmit filter covering the Cellular Spectrum 869-894 MHz. These components are considered as a system due to (1) the DDpx filters providing RF feedback to the transceiver in the form of Closed Loop Gain Control (CLGC) to provide constant power over temperature, and (2) Lucent's proprietary Enhanced Digital Pre-Distortion (EDPD-UL) technology which enables software to communicate between the transceiver, power amplifier and the transmit filter to achieve this goal. The MCR850 transceiver can transmit either Voice with 20 active channels or Voice + HSDPA (High Speed Downlink Packet Access) with 24 active channels.

The UMTS feature was developed for the North America Region (NAR) deployment, and is also known as Wideband CDMA (W-CDMA). The transceiver can be converted from Multi-Carrier CDMA to Single Carrier UMTS (or UMTS to CDMA) by software alone, which can be performed at the installation site. There are no physical, hardware or circuit changes to the transceiver.

UMTS functionality for the MCR850 transceiver was developed in accordance to the guidelines of the ETSI TS 25.141 V5.9.0 (2004-09) standard: "Universal Mobile Telecommunications System (UMTS); Base Station Conformance Testing (FDD) (3GPP TS 25.141 version 5.9.0 Release 5)". The measurement exhibits attached to this application demonstrate full compliance with both FCC Part 22 Subpart H – Cellular Radiotelephone Service and with ETSI TS 25.141, following the procedural requirements specified in FCC Part 2 Subpart J – Equipment Authorization Procedures. The data summarized below is in the form presently used by the Commission's Radio Equipment List, Equipment Acceptable for Licensing.

Manufacturer	Lucent Technologies
Equipment Identification	AS5ONEBTS-11
Rules Part Number	Part 22, Subpart H – Cellular Radiotelephone Service
Frequency Ranges	Transmit 869–894 MHz
Output Power	40 Watts (+46 dBm) 3-second average at the Tx antenna terminal
Frequency Tolerance	$\pm 0.05 \text{ ppm}$
Emission Designator	4M10F9W

## **APPLICANT: Lucent Technologies, Inc.**

## FCC ID: AS5ONEBTS-11

Attached are the FCC Form 731 (Application for Equipment Authorization – Radio Frequency Devices) and the required measurement data and exhibits specific to this request for initial equipment authorization of the UMTS-CDMA Transceiver System (850) base station. The technical contact at Lucent Technologies will comply with any request for additional information should the need arise. The attached exhibits are assembled and presented in the sequence recommended by Timco Engineering, in accordance with the *Table of Contents* attachment.

Confidentiality is requested for the following exhibits:

Exhibit 5:	Internal Photographs
Exhibit 7:	Operational Description (Theory of Operation, Functional Description)
Exhibit 8:	Block Diagrams
Exhibit 9:	Schematic Diagrams
Exhibit 11:	UMTS FLEXENT® UMTS Macrocell Indoor - Operation, Administration and
	Maintenance Document
Exhibit 13:	Parts List, if Applicable

Sincerely,

Rudolf J. Pillmeier Technical Manager FCC/EMC Compliance Test Group Whippany, NJ

Att.

Table of Contents for the UMTS-CDMA Transceiver System (850) Certification Report

# **APPLICANT: LUCENT TECHNOLOGIES**

## FCC ID: AS50NEBTS-11

## TABLE OF CONTENTS

Cover Letter

Request for Confidentiality

Exhibit 1:	731 Form		
Exhibit 2:	FCC ID Label Sample and Location Information		
Exhibit 3:	FCC Required Information (Part 2.1033)		
Exhibit 4:	External Photographs		
Exhibit 5:	Internal Photographs -	LUCENT TECHNOLOGIES CONFIDENTIAL	
Exhibit 6:	Test Set Up Photographs		
Exhibit 7:	<b>Operational Description</b>	(Theory of Operation, Functional Description) - LUCENT TECHNOLOGIES CONFIDENTIAL	
Exhibit 8:	Block Diagrams -	LUCENT TECHNOLOGIES CONFIDENTIAL	
Exhibit 9:	Schematic Diagrams -	LUCENT TECHNOLOGIES CONFIDENTIAL	
Exhibit 10:	Test Report		
Exhibit 11:	UMTS FLEXENT® UMTS Macrocell Indoor – Operation, Administration and Maintenance Document –LUCENT TECHNOLOGIES CONFIDENTIAL		
Exhibit 12:	Tuning Procedure, if Appl	icable	
Exhibit 13:	Parts List, if Applicable	LUCENT TECHNOLOGIES CONFIDENTIAL	