Appendix A

RF Test Data for BT(BDR/EDR) (Conducted Measurement)

Product Name: Dual 6.5 inches Wireless Speaker with Lights

Trade Mark: aiwa

Test Model: AI6014-BLK

Environmental Conditions

Temperature:	25.2℃
Relative Humidity:	51.2%
ATM Pressure:	101Kpa
Test Engineer:	Simba Huang
Supervised by:	Seal Chen

Contents

Page

COVER PAGE

1 Maximum Conducted Peak Output Power 3
1.1 Test Result 3
1.2 Test Graphs 4
3 20dB Bandwidth 7
3.1 Test Result 7
3.2 Test Graphs 8
4 Carrier Frequency Separation 11
4.1 Test Result 11
4.2 Test Graphs 12
5 Hopping Channel Number 13
5.1 Test Result 13
5.2 Test Graphs 14
6 Dwell Time 15
6.1 Test Result 15
6.2 Test Graphs 16
7 Conducted Spurious Emissions and Band Edges Test 22
7.1 Test Result 22
7.2 Test Graphs 23
8 Band-edge for RF Conducted Emissions 33
8.1 Test Result 33

1 Maximum Conducted Peak Output Power

1.1 Test Result

Mode	Channel.	Maximum Peak Output Power [dBm]	Limit [dBm]	Verdict
GFSK	LCH	-0.97	21	Pass
	MCH	0.83	21	Pass
	HCH	1.85	21	Pass
π/4-DQPSK	LCH	-0.02	21	Pass
	MCH	1.75	21	Pass
	HCH	2.61	21	Pass

1.2 Test Graphs

GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



π/4-DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π/4-DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π/4-DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



2 20dB Bandwidth

2.1 Test Result

Mode	Channel.	20dB Bandwidth [MHz]	Limit [MHz]	Verdict
GFSK	LCH	0.950	Not Specified	Pass
	MCH	0.952	Not Specified	Pass
	HCH	0.952	Not Specified	Pass
π/4-DQPSK	LCH	1.297	Not Specified	Pass
	MCH	1.301	Not Specified	Pass
	HCH	1.302	Not Specified	Pass

2.2 Test Graphs

GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



π/4-DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π/4-DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π/4-DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



3 Carrier Frequency Separation

3.1 Test Result

Mode	Channel.	Carrier Frequency Separation [MHz]	20dB Bandwidth (MHz)	Limit [MHz]	Verdict
GFSK	MCH	0.992	0.952	>=0.952	Pass
π/4-DQPSK	MCH	1.008	1.302	>=0.868	Pass

3.2 Test Graphs

GFSK_DH5_HOPP_Ant1_NTNV



π/4-DQPSK_2DH5_HOPP_Ant1_NTNV



4 Hopping Channel Number

4.1 Test Result

Mode	Channel.	Number of Hopping Channel [N]	Limit [N]	Verdict
GFSK	Hop	79	>=15	PASS
π/4-DQPSK	Hop	79	>=15	PASS

4.2 Test Graphs

GFSK_DH5_HOPP_Ant1_NTNV



π/4-DQPSK_2DH5_HOPP_Ant1_NTNV



5 Dwell Time

5.1 Test Result

Mode	Packet	Channel	Duration of Single Pulse (ms)	Observation Period (s)	Num of Pulse in Observation Period	Dwell Time (ms)	Limit (ms)	Verdict
GFSK	DH5	LCH	0.388	31.600	319	123.772	<=400	Pass
		MCH	1.644	31.600	157	258.108	<=400	Pass
		HCH	2.894	31.600	96	277.824	<=400	Pass
π/4-DQPSK	2DH5	LCH	0.396	31.600	319	126.324	<=400	Pass
		MCH	1.648	31.600	160	263.680	<=400	Pass
		HCH	2.896	31.600	118	341.728	<=400	Pass

5.2 Test Graphs

GFSK_DH1_HOPP_Ant1_NTNV



GFSK_DH1_HOPP_Ant1_NTNV



GFSK_DH3_HOPP_Ant1_NTNV


GFSK_DH3_HOPP_Ant1_NTNV


GFSK_DH5_HOPP_Ant1_NTNV



GFSK_DH5_HOPP_Ant1_NTNV



π/4-DQPSK_2DH1_HOPP_Ant1_NTNV



π/4-DQPSK_2DH1_HOPP_Ant1_NTNV



π/4-DQPSK_2DH3_HOPP_Ant1_NTNV



π/4-DQPSK_2DH3_HOPP_Ant1_NTNV



π/4-DQPSK_2DH5_HOPP_Ant1_NTNV



π/4-DQPSK_2DH5_HOPP_Ant1_NTNV



6 Conducted Spurious Emissions and Band Edges Test

6.1 Test Result

Mode	Channel	Max. Level [dBc]	Limit [dBc]	Verdict
GFSK	LCH	-1.19	-20	Pass
	MCH	0.63	-20	Pass
	HCH	1.66	-20	Pass
π/4-DQPSK	LCH	-1.01	-20	Pass
	MCH	0.78	-20	Pass
	HCH	1.75	-20	Pass

Mode	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
GFSK	2402	DH5	1	1.66	-18.34	Pass
	2441	DH5	1	1.66	-18.34	Pass
	2480	DH5	1	1.66	-18.34	Pass
	HOPP	DH5	1	1.66	-18.34	Pass
π/4-DQPSK	2402	2DH5	1	1.75	-18.25	Pass
	2441	2DH5	1	1.75	-18.25	Pass
	2480	2DH5	1	1.75	-18.25	Pass
	HOPP	2DH5	1	1.75	-18.25	Pass
Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.						

6.2 Test Graphs

GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



π/4-DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π/4-DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π/4-DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



CSE

GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



GFSK_DH5_HOPP_Ant1_NTNV



GFSK_DH5_HOPP_Ant1_NTNV



π/4-DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π/4-DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π/4-DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π/4-DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



π/4-DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



π/4-DQPSK_2DH5_HOPP_Ant1_NTNV



π/4-DQPSK_2DH5_HOPP_Ant1_NTNV



7 Band-edge for RF Conducted Emissions

7.1 Test Result

Test Mode: GFKS										
Pol.	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
Low Channel: 2402MHz										
H	2390.00	46.45	29.15	3.41	34.01	45.00	74.00	-29.00	PK	PASS
H	2400.00	63.75	29.16	3.43	34.01	62.33	74.00	-11.67	PK	PASS
V	2390.00	47.34	29.15	3.41	34.01	45.89	74.00	-28.11	PK	PASS
V	2400.00	66.17	29.16	3.43	34.01	64.75	74.00	-9.25	PK	PASS
H	2390.00	36.19	29.15	3.41	34.01	34.74	54.00	-19.26	AV	PASS
H	2400.00	47.64	29.16	3.43	34.01	46.22	54.00	-7.78	AV	PASS
V	2390.00	36.39	29.15	3.41	34.01	34.94	54.00	-19.06	AV	PASS
V	2400.00	49.63	29.16	3.43	34.01	48.21	54.00	-5.79	AV	PASS
High Channel: 2480MHz										
H	2483.50	48.98	29.28	3.53	34.03	47.76	74.00	-26.24	PK	PASS
H	2500.00	47.47	29.30	3.56	34.03	46.30	74.00	-27.70	PK	PASS
V	2483.50	50.42	29.28	3.53	34.03	49.20	74.00	-24.80	PK	PASS
V	2500.00	48.81	29.30	3.56	34.03	47.64	74.00	-26.36	PK	PASS
H	2483.50	39.06	29.28	3.53	34.03	37.84	54.00	-16.16	AV	PASS
H	2500.00	36.55	29.30	3.56	34.03	35.38	54.00	-18.62	AV	PASS
V	2483.50	40.57	29.28	3.53	34.03	39.35	54.00	-14.65	AV	PASS
V	2500.00	36.77	29.30	3.56	34.03	35.60	54.00	-18.40	AV	PASS

Test Mode: π/4-DQPSK										
Pol.	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
Low Channel: 2402MHz										
H	2390.00	46.56	29.15	3.41	34.01	45.11	74.00	-28.89	PK	PASS
H	2400.00	63.88	29.16	3.43	34.01	62.46	74.00	-11.54	PK	PASS
V	2390.00	47.46	29.15	3.41	34.01	46.01	74.00	-27.99	PK	PASS
V	2400.00	66.31	29.16	3.43	34.01	64.89	74.00	-9.11	PK	PASS
H	2390.00	36.28	29.15	3.41	34.01	34.83	54.00	-19.17	AV	PASS
H	2400.00	47.73	29.16	3.43	34.01	46.31	54.00	-7.69	AV	PASS
V	2390.00	36.49	29.15	3.41	34.01	35.04	54.00	-18.96	AV	PASS
V	2400.00	49.73	29.16	3.43	34.01	48.31	54.00	-5.69	AV	PASS
High Channel: 2480MHz										
H	2483.50	49.10	29.28	3.53	34.03	47.88	74.00	-26.12	PK	PASS
H	2500.00	47.57	29.30	3.56	34.03	46.40	74.00	-27.60	PK	PASS
V	2483.50	50.56	29.28	3.53	34.03	49.34	74.00	-24.66	PK	PASS
V	2500.00	48.92	29.30	3.56	34.03	47.75	74.00	-26.25	PK	PASS
H	2483.50	39.15	29.28	3.53	34.03	37.93	54.00	-16.07	AV	PASS
H	2500.00	36.62	29.30	3.56	34.03	35.45	54.00	-18.55	AV	PASS
V	2483.50	40.67	29.28	3.53	34.03	39.45	54.00	-14.55	AV	PASS
V	2500.00	36.85	29.30	3.56	34.03	35.68	54.00	-18.32	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

------End------