



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01

Page: 1 of 24

TEST REPORT

Application No: SUCR2502000063WM
Applicant: Motorola Mobility LLC
Address of Applicant: 222 W,Merchandise Mart Plaza, Chicago IL 60654 USA
Manufacturer: Motorola Mobility LLC
Address of Manufacturer: 222 W,Merchandise Mart Plaza, Chicago IL 60654 USA
EUT Description: Mobile Cellular Phone
Model No.: XT2507-6(Retail), XT2507-3(Softbank) -----♣
♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: Motorola
FCC ID: IHDT56AU4
Standard(s): FCC 47 CFR Part 15, Subpart B
Date of Receipt: February 24, 2025
Date of Test: February 24, 2025 to February 26, 2025
Date of Issue: March 13, 2025

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301
Rev.: 01
Page: 2 of 24

Version

Revision Record			
Version	Description	Date	Remark
01	Original	March 13, 2025	/

Authorized for issue by:			
Tested By			
		Nature Shen / Project Manager	
Approved By			
		Cloud Peng/Technical Manager	



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301
Rev.: 01
Page: 3 of 24

Contents

Version..... 2

1 Test Summary 4

2 General Information 5

2.1 Description of Support Units..... 6

2.2 Test Location..... 7

2.3 Test Facility 7

2.4 Deviation from Standards..... 7

2.5 Abnormalities from Standard Conditions..... 7

3 Equipment List 8

4 Measurement Uncertainty 9

5 Emission Test Results..... 10

5.1 Conducted Emissions at Mains Terminals (150kHz-30MHz) 10

5.2 Radiated Emissions (30MHz-1GHz) 14

5.3 Radiated Emissions (above 1GHz) 18

6 Photographs 24

6.1 Test Setup 24



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01

Page: 4 of 24

1 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at Mains Terminals (150kHz-30MHz)	FCC 47 CFR Part 15, Subpart B	ANSI C63.4:2014	Class B	Pass
Radiated Emissions (30MHz-1GHz)	FCC 47 CFR Part 15, Subpart B	ANSI C63.4:2014	Class B	Pass
Radiated Emissions (above 1GHz)	FCC 47 CFR Part 15, Subpart B	ANSI C63.4:2014	Class B	Pass

Internal Source	Upper Frequency
Below 1.705MHz	30MHz
1.705MHz to 108MHz	1GHz
108MHz to 500MHz	2GHz
500MHz to 1GHz	5GHz
Above 1GHz	5th harmonic of the highest frequency or 40GHz, whichever is lower

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01

Page: 5 of 24

2 General Information

Product Name:	Mobile Cellular Phone		
Model No. (EUT):	XT2507-6(Retail), XT2507-3(Softbank)		
Trade Mark:	Motorola		
Hardware Version:	DVT2		
Software Version:	V2VV35.69		
IMEI:	RE/CE	Sample 1: 351794940007175/351794940007183 Sample 2: 351794940008314/351794940008322	
Frequency Bands:	Band	Tx (MHz)	Rx (MHz)
	GSM850	824~849	869~894
	GSM1900	1850~1910	1930~1990
	WCDMA Band II	1850~1910	1930~1990
	WCDMA Band IV	1710~1755	2110~2155
	WCDMA Band V	824~849	869~894
	LTE Band 2	1850~1910	1930~1990
	LTE Band 4	1710~1755	2110~2155
	LTE Band 5	824~849	869~894
	LTE Band 7	2500~2570	2620~2690
	LTE Band 12	699~716	729~746
	LTE Band 13	777~787	746~756
	LTE Band 17	704~716	734~746
	LTE Band 26 (814 to 824 MHz)	814~824	859~869
	LTE Band 26 (824 to 849 MHz)	824~849	869~894
	LTE Band 38	2570~2620	2570~2620
	LTE Band 41	2496~2690	2496~2690
	LTE Band 42	3400~3600	3400~3600
	LTE Band 66	1710~1780	2110~2200
	NR Band n5	824~849	869~894
	NR Band n41	2496~2690	2496~2690
	NR Band n66	1710~1780	2110~2200
	NR Band n77	3450~3550	3450~3550
		3700~3980	3700~3980
	NR Band n78	3450~3550	3450~3550
		3700~3800	3700~3800
	Wi-Fi 2.4G	2412~2462	2412~2462
	Bluetooth	2402~2480	2402~2480
	Wi-Fi 5G	5150~5850	5150~5850

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01

Page: 6 of 24

	Wi-Fi 6E	5925~6425	5925~6425
		6425~6525	6425~6525
		6525~6875	6525~6875
		6875~7125	6875~7125
	NFC	13.56	13.56
	WPC	NA	100 - 205
	GNSS(GPS+Glonass +Beidou+Galileo+SBAS)	NA	1559~1610, 1164-1215

Note:

1.As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

2.The two models named XT2507 - 6 and XT2507 - 3 are the same product except that their model names are different for different market segments.

Accessories Information				
AC Adapter 2	Brand Name	Motorola (AOHAI)	Model Name	MC-1251
	Power Rating	I/P: 100 - 240 Vac, 1700 mA, O/P: 5/9/15/20/5-20 Vdc, 3000/3000/3000/6250/6250 mA		
	Power Cord	0 meter, non-shielded cable, with w/o ferrite core		
AC Adapter 1	Brand Name	Motorola (Chenyang)	Model Name	MC-1251
	Power Rating	I/P: 100 - 240 Vac, 1700 mA, O/P: 5/9/15/20/5-20 Vdc, 3000/3000/3000/6250/6250 mA		
	Power Cord	0 meter, non-shielded cable, with w/o ferrite core		
USB Cable 1	Brand Name	Saibao	Model Name	SC18D71644
	Signal Line	1 meter, shielded cable, w/o ferrite core		
USB Cable 2	Brand Name	Luxshare	Model Name	SC18E08104
	Signal Line	1 meter, shielded cable, w/o ferrite core		

2.1 Description of Support Units

Description	Manufacturer	Model No.	Inventory No.
Router	Smauwave Technology Co.,Ltd	SRT 421	SUWI-04-34-01
Computer	Lenovo	T14	SUWI-03-33-04



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01

Page: 7 of 24

2.2 Test Location

All tests were performed at:

Company:	SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Address:	South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone
Post code:	215000
Test engineer:	King-p Li

2.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

- **FCC –Designation Number: CN1312**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an accredited testing laboratory.

Designation Number: CN1312.

Test Firm Registration Number: 717327

2.4 Deviation from Standards

None

2.5 Abnormalities from Standard Conditions

None

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01

Page: 8 of 24

3 Equipment List

CE Test System					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	1/15/2025	1/14/2026
Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-06	2/4/2024	2/3/2025
Artificial network	ROHDE&SCHWARZ	ENV216	SUWI-01-19-03	5/6/2024	5/5/2025
Artificial network	ROHDE&SCHWARZ	ENV216	SUWI-01-19-04	5/6/2024	5/5/2025
Measurement Software	Tonscend	JS32-CE 4.0.0.2	SUWI-02-09-05	NCR	NCR
Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/19/2024	11/18/2025
Radio Communication Analyzer	StarPoint	SP9500E	SUWI-01-28-02	11/19/2024	11/18/2025

RE Test System					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	6/3/2023	6/02/2026
Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-05	2/18/2024	2/17/2025
Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	5/8/2024	5/7/2025
Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-07	11/21/2024	11/20/2025
Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	1/15/2025	1/14/2026
Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	VULB 9168	SUWI-01-11-04	11/25/2023	11/24/2025
Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	5/13/2023	5/12/2025
Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9170	SUWI-01-11-03	5/12/2023	5/11/2025
Amplifier	Tonscend	TAP9K3G40	SUWI-01-14-01	1/16/2025	1/15/2026
Amplifier	Tonscend	TAP01018050	SUWI-01-14-02	1/16/2025	1/15/2026
Amplifier	Tonscend	TAP18040048	SUWI-01-14-03	1/20/2025	1/19/2026
Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/19/2024	11/18/2025
Measurement Software	Tonscend	JS32-RE V4.0.0.0	SUWI-02-09-04	NCR	NCR
Radio Communication Analyzer	StarPoint	SP9500E	SUWI-01-28-02	11/19/2024	11/18/2025

Remark: NCR=No Calibration Requirement.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301
Rev.: 01
Page: 9 of 24

4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Conduction Emission	± 2.9dB (150kHz to 30MHz)
2	Radiated Emission	± 4.8dB (30M -1GHz)
		± 4.8dB (1GHz to 18GHz)
		± 4.80dB (Above 18GHz)
Remark: The U _{lab} (lab Uncertainty) is less than U _{CISPR/ETSI} (CISPR/ETSI Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.		

5 Emission Test Results

5.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)

Test Requirement:	47 CFR Part 15, Subpart B		
Test Method:	ANSI C63.4:2014		
Frequency Range:	150kHz to 30MHz		
Receiver Setup:	RBW = 9kHz, VBW = 30kHz		
Limit:	Frequency Range (MHz)	Limit(dBμV)	
		Quasi-peak	average
	0.15M-0.5MHz	66 ~ 56*	56 ~ 46*
	0.5M-5MHz	56	46
	5M-30MHz	60	50
*Decreases with the logarithm of the frequency Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz			

2.1.1 E.U.T. Operation

Operating Environment:

Temperature:	22~23°C
Humidity:	44~46%RH
Atmospheric Pressure:	101kPa
Pretest these modes to find the worst case:	a: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+2.4GWLAN(Idle)+Camera(Rear)+GSM850 (RX) Low b: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+5GWLAN(Idle)+Camera(Front)+WCDMA Band 5(RX) Mid c: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+WLAN6E(Idle)+MP4+LTE Band 5 (RX) High d: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+2.4GWLAN(Idle)+NFC ON+LTE Band 12 (RX) Low e: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+5GWLAN(Idle)+GNSS+LTE Band 13 (RX) Mid f: Sample(2)+adapter(2)+usb Cable(2)+BT(Idle)+WLAN6e (Idle)+NFC ON+LTE Band 17 (RX) High g: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+2.4GWLAN (Idle)+NFC ON+LTE Band 26 (RX) Low h: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+5GWLAN (Idle)+NFC ON+SA Band 5 (RX) Mid
The worst case for final test:	b: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+5GWLAN(Idle)+Camera(Front)+WCDMA Band 5(RX) Mid

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250200006301

Rev.: 01

Page: 11 of 24

2.1.2 Test Setup Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.



2.1.3 Measurement Data


An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01

Page: 12 of 24




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01

Page: 13 of 24



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01

Page: 14 of 24

5.2 Radiated Emissions (30MHz-1GHz)

Test Requirement:	47 CFR Part 15, Subpart B		
Test Method:	ANSI C63.4:2014		
Frequency Range:	30MHz to 1GHz		
Measurement Distance:	3m		
Limit:	Frequency Range (MHz)	Limit(dBμV/m)	Detector
	30MHz -88MHz	40.0	Quasi-peak
	88MHz-216MHz	43.5	Quasi-peak
	216MHz-960MHz	46.0	Quasi-peak
	960MHz-1000MHz	54.0	Quasi-peak
Detector:	Peak for pre-scan (120kHz resolution bandwidth) 30M to1000MHz		

5.2.1 E.U.T. Operation

Temperature:	22~23°C
Humidity:	44~46% RH
Atmospheric Pressure:	101kPa
Pretest these modes to find the worst case:	<p>a: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+2.4GWLAN(Idle)+Camera(Rear)+GSM850 (RX) Low</p> <p>b: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+5GWLAN(Idle)+Camera(Front)+WCDMA Band 5(RX) Mid</p> <p>c: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+WLAN6E(Idle)+MP4+LTE Band 5 (RX) High</p> <p>d: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+2.4GWLAN(Idle)+NFC ON+LTE Band 12 (RX) Low</p> <p>e: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+5GWLAN(Idle)+GNSS+LTE Band 13 (RX) Mid</p> <p>f: Sample(2)+adapter(2)+usb Cable(2)+BT(Idle)+WLAN6e (Idle)+NFC ON+LTE Band 17 (RX) High</p> <p>g: Sample(1)+Transfer data between the EUT and the PC+USB cable(1)+BT(Idle)+2.4GWLAN(Idle)+LTE Band 26 (RX) Low</p> <p>h: Sample(2)+Transfer data between the EUT and the PC+USB cable(2)+BT(Idle)+2.4GWLAN(Idle)+SA Band 5 (RX) Mid</p> <p>i: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+5GWLAN(Idle)+WPC+LTE Band 13 (RX) Mid</p>
The worst case for final test:	d: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+2.4GWLAN(Idle)+NFC ON+LTE Band 12 (RX) Low

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250200006301

Rev.: 01

Page: 15 of 24

5.2.2 Test Setup Procedures

1. The EUT was placed in a semi Anechoic Chamber as show below
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna height is adjusted between 1 to 4 meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function with specified bandwidth with Maximum Hold Mode, and the trace was allowed to stabilize.
7. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.



5.2.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities. The three polarities of X,Y,Z were measured by EUT, but only the worst data had been displayed.

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01


Page: 16 of 24

Final Test Mode:

Mode d

Polarization:

Horizontal



Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	40.185	34.26	18.80	-33.86	19.20	40.00	20.80	196	33	Horizontal
2	51.0975	36.85	18.49	-33.68	21.67	40.00	18.33	254	38	Horizontal
3	66.375	38.49	17.23	-33.47	22.25	40.00	17.75	175	323	Horizontal
4	95.475	35.43	14.31	-33.19	16.55	43.50	26.95	263	360	Horizontal
5	123.12	34.06	17.24	-32.89	18.40	43.50	25.10	224	24	Horizontal
6	168.4675	34.36	18.57	-32.44	20.49	43.50	23.01	115	249	Horizontal
7	729.1275	54.47	25.80	-29.33	50.94	-	-	228	21	Horizontal

Remark:

- #7 30M-1G is system simulator signal which can be ignored
- The Quasi-Peak measurements were performed on the EUT.
- Value = Reading + AF + Factor:
 AF = Antenna Factor(dB/m)
 Factor = Cable Factor(dB) - Preamplifier (dB)
 Margin = Limit[dBμV/m] - Value[dBμV/m]

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01


Page: 17 of 24

Final Test Mode:

Mode d

Polarization:

Vertical



Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	44.065	44.35	18.81	-33.79	29.37	40.00	10.63	196	1	Vertical
2	49.1575	49.89	18.77	-33.70	34.95	40.00	5.05	254	276	Vertical
3	51.0975	46.35	18.49	-33.68	31.17	40.00	8.83	185	6	Vertical
4	66.375	39.53	17.23	-33.47	23.29	40.00	16.71	263	167	Vertical
5	78.7425	36.57	15.23	-33.35	18.45	40.00	21.55	224	339	Vertical
6	119.9675	38.24	16.79	-32.92	22.12	43.50	21.38	186	339	Vertical
7	726.2175	54.73	25.80	-29.35	51.18	-	-	122	209	Vertical

Remark:

- #7 30M-1G is system simulator signal which can be ignored
- The Quasi-Peak measurements were performed on the EUT.
- Value = Reading + AF + Factor:
 AF = Antenna Factor(dB/m)
 Factor = Cable Factor(dB) - Preamplifier (dB)
 Margin = Limit[dBμV/m] - Value[dBμV/m]



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01

Page: 18 of 24

5.3 Radiated Emissions (above 1GHz)

Test Requirement:	47 CFR Part 15, Subpart B		
Test Method:	ANSI C63.4:2014		
Frequency Range:	Above 1GHz		
Measurement Distance:	3m		
Limit:	Frequency (MHz)	Limit (dBμV/m)	Detector
	Above 1GHz	74	Peak
		54	Average
Detector:	Peak for pre-scan (1000kHz resolution bandwidth) 5th harmonic of the highest frequency or 40GHz, whichever is lower.		

5.3.1 E.U.T. Operation

Temperature:	22~23°C
Humidity:	44~46% RH
Atmospheric Pressure:	101kPa
Pretest these modes to find the worst case:	<p>a: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+2.4GWLAN(Idle)+Camera(Rear)+GSM850 (RX) Low</p> <p>b: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+5GWLAN(Idle)+Camera(Front)+WCDMA Band 5(RX) Mid</p> <p>c: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+WLAN6E(Idle)+MP4+LTE Band 5 (RX) High</p> <p>d: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+2.4GWLAN(Idle)+NFC ON+LTE Band 12 (RX) Low</p> <p>e: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+5GWLAN(Idle)+GNSS+LTE Band 13 (RX) Mid</p> <p>f: Sample(2)+adapter(2)+usb Cable(2)+BT(Idle)+WLAN6e (Idle)+NFC ON+LTE Band 17 (RX) High</p> <p>g: Sample(1)+Transfer data between the EUT and the PC+USB cable(1)+BT(Idle)+2.4GWLAN(Idle)+LTE Band 26 (RX) Low</p> <p>h: Sample(2)+Transfer data between the EUT and the PC+USB cable(2)+BT(Idle)+2.4GWLAN(Idle)+SA Band 5 (RX) Mid</p> <p>i: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+5GWLAN(Idle)+WPC+LTE Band 13 (RX) Mid</p>
The worst case for final test:	d: Sample(1)+adapter(1)+usb Cable(1)+BT(Idle)+2.4GWLAN(Idle)+NFC ON+LTE Band 12 (RX) Low

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250200006301

Rev.: 01

Page: 19 of 24

5.3.2 Test Setup Procedures

1. The EUT was placed in a full Anechoic Chamber as show below
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation
(Distance from antenna to EUT is 1m for measurements >18GHz).
4. The antenna height is adjusted between 1 to 4 meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak and AV Detect Function with specified bandwidth with Maximum Hold Mode, and the trace was allowed to stabilize.
7. At a measurement distance of 1 meter the limit line was increased by $20 \cdot \log(3/1) = 9.54 \text{ dB}$.



5.3.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Average measurements were conducted based on the peak sweep graph. The EUT was measured by Horn antenna with 2 orthogonal polarities.


The three polarities of X, Y, Z were measured by EUT, but only the worst data had been displayed.

Scan from 5th harmonic of the highest frequency or 40GHz, whichever is lower, the disturbance above 18GHz was very low. The points marked on below plots are the highest emissions could be found when testing, so only below points had been displayed.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301
Rev.: 01
Page: 20 of 24






SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01


Page: 21 of 24



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301
 Rev.: 01
 Page: 22 of 24

Final Test Mode: Mode d Polarization: Vertical



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	23975.025	42.94	38.51	-34.96	46.49	83.54	37.05	Vertical
2	29212.5	45.72	39.90	-37.15	48.47	83.54	35.07	Vertical
3	33819.5	47.52	41.41	-36.96	51.97	83.54	31.57	Vertical

Remark:

1. Level = Reading Level + AF + Factor:

AF = Antenna Factor(dB/m)


Factor = Cable Factor(dB) - Preamplifier gain(dB)

Margin = Limit[dBμV/m] – Level[dBμV/m]



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301
Rev.: 01
Page: 23 of 24





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250200006301

Rev.: 01

Page: 24 of 24

6 Photographs

6.1 Test Setup

Refer to Appendix A.1 15B Setup Photos.

---End of Report---