





NFC TEST REPORT

No.I20Z60959-IOT13

for

OnePlus Technology (Shenzhen) Co., Ltd.

Smart Phone

BE2028,BE2025,BE2026

FCC ID: 2ABZ2-EF170

with

Hardware Version: 16

Software Version: 10.5.5.BE88CB

Issued Date: 2020-10-13

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191. Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504 Email: cttl terminals@caict.ac.cn, website: www.caict.ac.cn





REPORT HISTORY

| Report Number | Revision | Description | Issue Date |
|-----------------|----------|-------------|------------|
| I20Z60959-IOT13 | Rev.0 | 1st edition | 2020-10-13 |





CONTENTS

| 1. | TEST LABORATORY | 4 |
|--|--|---|
|] | 1.1. INTRODUCTION & ACCREDITATION | 4 |
| 1 | 1.2. TESTING LOCATION | 4 |
| 1 | 1.3. TESTING ENVIRONMENT | 5 |
| 1 | 1.4. PROJECT DATA | 5 |
| 1 | 1.5. SIGNATURE | 5 |
| 2. | CLIENT INFORMATION | 6 |
| 2 | 2.1. APPLICANT INFORMATION | 6 |
| | 2.2. MANUFACTURER INFORMATION | 6 |
| 3. | EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) | 7 |
| | 3.1. ABOUT EUT | 7 |
| | 3.2. INTERNAL IDENTIFICATION OF EUT | 7 |
| | 3.3. INTERNAL IDENTIFICATION OF AE | 7 |
| | | |
| | 3.4. EUT SET-UPS | 8 |
| 4 . | 3.4. EUT SET-UPS | 8 |
| 4. | 3.4. EUT SET-UPS | 8 0 0 |
| 4. | 3.4. EUT SET-UPS | 8 10 .0 |
| 4. 4. 5. | 3.4. EUT SET-UPS | 8 0 0 .0 |
| 4. 4. 5. | 3.4. EUT SET-UPS | 8 10 10 11 |
| 4. 5. | 3.4. EUT SET-UPS | 8 10 10 11 11 .2 |
| 4. 5. 4. | 3.4. EUT SET-UPS | 8 10 10 11 11 2 .3 |
| 4. 5. 6. 7. | 3.4. EUT SET-UPS | 8 10 10 11 11 .2 .3 .4 |
| 4. 4. 5. 4. 6. 7. AN | 3.4. EUT SET-UPS | 8 10 10 11 11 12 .3 .4 .5 |
| 4. 4. 5. 4. 5. 4. 6. 7. AN | 3.4. EUT SET-UPS | 8 10 10 11 11 .2 .3 .4 .5 .6 |
| 4. 4. 5. 4. 6. 7. 4. 6. 7. 4. 4. 4. 4. 4. | 3.4. EUT SET-UPS 1 REFERENCE DOCUMENTS 1 4.1. DOCUMENTS SUPPLIED BY APPLICANT 1 4.2. REFERENCE DOCUMENTS FOR TESTING 1 TEST RESULTS 1 5.1. SUMMARY OF TEST RESULTS 1 5.2. STATEMENTS. 1 TEST FACILITIES UTILIZED 1 MEASUREMENT UNCERTAINTY 1 NNEX A: EUT PARAMETERS 1 NNEX B: DETAILED TEST RESULTS 1 NNEX C: PERSONS INVOLVED IN THIS TESTING 3 | 8 10 10 11 12 .3 .4 .5 .6 |





1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (ISED#: 24849). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Location 1: CTTL(huayuan North Road)

| Address: | No. 52, Huayuan North Road, Haidian District, Beijing, |
|----------|--|
| | P. R. China 100191 |

Location 2: CTTL(BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology Development Area, Beijing, P. R. China 100176

Location 3: CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China 100191





1.3. <u>Testing Environment</u>

| Normal Temperature: | 15-35℃ |
|---------------------------|--------------|
| Extreme Temperature: | -20/+50°C |
| Normal Relative Humidity: | 20-75% |
| Normal Air Pressure: | 86Kpa-106Kpa |

1.4. Project data

| Testing Start Date: | 2020-09-29 |
|---------------------|------------|
| Testing End Date: | 2020-10-10 |

1.5. Signature

Zhou Bin (Prepared this test report)

b

Pang Shuai (Reviewed this test report)

Zhu Liang (Approved this test report)





2. <u>Client Information</u>

2.1. Applicant Information

| Company Name: | OnePlus Technology (Shenzhen) Co., Ltd. |
|---------------|---|
| Address: | 18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen |
| City: | Shenzhen |
| Postal Code: | 1 |
| Country: | CHINA |
| Contact: | Ariel Cheng |
| Telephone: | 86 755 61898696-7023 |
| E-mail: | ariel.cheng@oneplus.com |

2.2. Manufacturer Information

| Company Name: | OnePlus Technology (Shenzhen) Co., Ltd. |
|---------------|---|
| Address: | 18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen |
| City: | Shenzhen |
| Postal Code: | 1 |
| Country: | CHINA |
| Contact: | Ariel Cheng |
| Telephone: | 86 755 61898696-7023 |
| E-mail: | ariel.cheng@oneplus.com |





3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

| Description | Smart Phone |
|--------------------------|---|
| Model name | BE2028,BE2025,BE2026 |
| Brand name | ONEPLUS |
| FCC ID | 2ABZ2-EF170 |
| CDMA Frequency Band(s) | Band class 0/1/10 |
| UMTS Frequency Band(s) | FDD I/II/IV/V/VIII |
| GSM Frequency Band(s) | GSM900/1800/1900/850 |
| E-UTRA Frequency Band(s) | FDD1/2/3/4/5/7/8/12/13/17/20/25/26/28/28a/28b/66/71 |
| | TDD38/39/40/41 |
| 5G NR FR1 Band(s) | n2/5/25/41/66/71 |
| Extreme Temperature | -10/+55°C |
| Nominal Voltage | 3.87V |
| Extreme High Voltage | 4.45V |
| Extreme Low Voltage | 3.45V |

Note: As declared by the manufacturer, the only difference among products BE2028, BE2025 and BE2026 is different model names for different clients. Except this, the others are the same.

3.2. Internal Identification of EUT

| EUT ID* | SN or IMEI | HW Version | SW Version | Date of receipt |
|---------|-----------------|------------|---------------|-----------------|
| 83a | 990016800151654 | 16 | 10.5.5.BE88CB | 2020-09-29 |
| 81a | 990016800151597 | 16 | 10.5.5.BE88CB | 2020-09-30 |

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

| AE ID* | Description | SN |
|--------|-------------|---------|
| AE1 | Battery | / |
| AE3 | Charger | / |
| AE4 | Charger | / |
| AE5 | Charger | / |
| AE6 | USB | / |
| AE7 | USB | 1 |
| AE8 | Charger | NO TEST |





| AE | 51 | |
|----|-----------------|--|
| | Model | BLP815 |
| | Manufacturer | / |
| | Length of cable | 1 |
| | | |
| AE | 53 | |
| | Model | WC0506A51JH |
| | Manufacturer | Huizhou Golden Lake Industrial Co,. Ltd. |
| | Length of cable | 1 |
| AE | Ξ4 | |
| | Model | WC030B51HK |
| | Manufacturer | SHENZHEN HUNTKEY ELECTRIC CO LTD |
| | Length of cable | / |
| AE | 5 | |
| | Model | WC0506A51GB |
| | Manufacturer | / |
| | Length of cable | / |
| AE | 56 | |
| | Model | / |
| | Manufacturer | / |
| | Length of cable | / |
| AE | 27 | |
| | Model | / |
| | Manufacturer | / |
| | Length of cable | 1 |
| AE | 58 | |
| | Model | WC0506A52GB |
| | Manufacturer | 1 |
| | Length of cable | / |
| | - | |

*AE ID: is used to identify the ancillary equipment in the lab internally.

3.4. EUT Set-ups

Table 1: Eut Set-ups

| EUT Set-up No. | Combination of EUT and AE | Remarks |
|----------------|----------------------------|---------|
| Set.NFC01-1 | 81a + AE1 + AE3 + AE6/ AE7 | |
| Set.NFC01-2 | 81a + AE1 + AE4 + AE6/ AE7 | |
| Set.NFC01-3 | 81a + AE1 + AE5 + AE6/ AE7 | |
| Set.NFC02 | 81a + AE1 | |
| Set. NFC03 | 83a | |





The Transmit State of NFC: the NFC function is on. The EUT will transmit the NFC data and command continuously during the test.

The Transmit state without modulation: The EUT will transmit the CW signal at the Hoperating frequency.





4. <u>Reference Documents</u>

4.1. Documents supplied by applicant

EUT parameters, referring to Annex A for detailed information, are supplied by the client or manufacturer, which are the bases of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

| Reference | Title | Version |
|----------------|--|---------|
| CFR 47 Part 2 | Part 2 — Frequency Allocations and Radio Treaty Matters; General Rules and Regulations. | 2018 |
| CFR 47 Part 15 | Part 15 — Radio Frequency Devices. | 2018 |
| | Subpart C — Intentional Radiators. | |
| | § 15.35 Measurement detector functions and bandwidths. | |
| | § 15.207 Conducted limits. | |
| | § 15.209 Radiated emission limits, general requirements. | |
| | § 15.215 Additional provisions to the general radiated emission limitations. | |
| | § 15.225 Operation within the band 13.110–14.010 MHz. | |
| ANSI C63.10 | American National Standard of Procedures for Compliance | 2013 |
| | Testing of Unlicensed Wireless Devices | |





5. Test Results

5.1. Summary of Test Results

| No | Test Cases | Clause in Regulation | Section in This Report | Verdict |
|--|---|--|---------------------------|---|
| 1 | Electric Field Strength of Fundamental Emissions | CFR 47 § 15.225(a) | D 4 | P(Set. NFC02) |
| 2 | Electric Field Strength of Outside the Allocated Bands | CFR 47 § 15.225(b) CFR 47 § 15.225(c) | В.1 | P(Set. NFC02) |
| 3 | Electric Field Radiated | CFR 47 § 15.209 | B.2 | P(Set. NFC01-1/ Set. NFC01-2/ Set. NFC01-3) |
| | Emissions | CFR 47 § 15.225(d) | В.3 | P(Set. NFC01-1/ Set. NFC01-2/ Set. NFC01-3) |
| 4 | Frequency Tolerance | CFR 47 § 15.225(e) | B.4 | P(Set. NFC03) |
| 5 | 20dB Bandwidth | CFR 47 § 15.215(c) | B.5 | P(Set. NFC03) |
| 6 | Conducted Emissions | CFR 47 § 15.207 | B.6 | P(Set. NFC01-1/ Set. NFC01-2/ Set. NFC01-3) |
| The measurement is carried out according to ANSI C63.10. See ANNEX B for details. | | | | |

Table 2: Summary of Test Results

Test Conditions:

For this report, all the test cases listed above were tested under normal Temperature, Voltage, humidity and Air Pressure except the Frequency Tolerance test case. The specific conditions of Frequency Tolerance test case are listed in section B.4.3

See Table 3 for terms for result verdict:





| Ρ | Pass, The EUT complies with the essential requirements in the standard. |
|----|---|
| NP | Not Perform, The test was not performed by CTTL |
| NA | Not Applicable, The test was not applicable |
| F | Fail, The EUT does not comply with the essential requirements in the standard |

Table 3 Terms for result verdict

5.2. Statements

The test cases listed in Section 5.1 of this report for the EUT specified in Section 3 were performed by CTTL according to the reference documents in Section 4.

The EUT meets all applicable requirements of the regulations and standards in Section 4.2.





6. Test Facilities Utilized

| NO. | NAME | TYPE | SERIES NUMBER | PRODUCER | CAL. DUE DATE | CAL. INTERVAL |
|-----|-------------------|----------|------------------|-----------------|------------------|------------------|
| 1. | Spectrum Analyzer | RSA3408A | B010277 | Tektronix | 2021-09-24 | 1 Year |
| 2. | Climatic chamber | SH242 | 93008658 | ESPEC | 2021-01-18 | 1 Year |
| 3. | Test Receiver | ESU26 | 100235 | Rohde & Schwarz | 2021-03-03 | 1 Year |
| 4. | BiLog Antenna | VULB9163 | 9163-1223 | Schwarzbeck | 2021-03-18 | 1 Year |
| 5. | LISN | ENV216 | 101200 | Rohde & Schwarz | 2021-05-17 | 1 Year |
| 6. | Test Receiver | ESCI 7 | 100344 | Rohde & Schwarz | 2021-02-26 | 1 Year |
| 7. | H-field Antenna | HFH2-Z2 | 829324/007 | R&S | 2020-12-03 | 1 Year |

Table 4: Test Facilities Utilized

| Test Item | Test Software and Version | Software Vendor |
|------------------------------|---------------------------|-----------------|
| Radiated Continuous Emission | EMC32 V9.01.00 | R&S |
| Conducted Emission | EMC32 V8.51 | R&S |





7. Measurement Uncertainty

Table 5: Measurement Uncertainty

| ltem | Uncertainty |
|----------------------------|-------------------------|
| Frequency Tolerance | <i>U</i> =77 Hz, k=2 |
| 20dB Bandwidth | <i>U</i> =77 Hz, k=2 |
| Radiated Emissions (<1GHz) | <i>U</i> =5.40 dB, k=2 |
| Conducted emission | <i>U</i> = 3.08 dB, k=2 |



/



ANNEX A: EUT parameters

©Copyright. All rights reserved by CTTL.





ANNEX B: Detailed Test Results

B.1. Electric Field Strength of Fundamental and Outside the Allocated bands

B.1.1. Reference

See Clause 4, Clause 5 of ANSI C63.10-2013 generally.

B.1.2. Measurement Methods

The transmitter carrier output levels (E-Field) from the EUT are measured in a semi-anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3m from the receiving antenna. The center of the receiving loop antenna is 1.0 meter above the ground. The E-field is measured with a shielded loop antenna connected to a measurement receiver. Detected E-field was maximized by rotating the EUT through 360° and adjusting the receiving antenna polarizations. The maximization processes were repeated with the EUT positioned respectively in its three orthogonal axes. The measurements were performed with the peak detector and if required, the quasi-peak detector.

The measurement bandwidth is:

| Table B-1: | Measurement | bandwidth |
|------------|-------------|-----------|
|------------|-------------|-----------|

| Frequency of Emission (MHz) | RBW/VBW |
|-----------------------------|-----------|
| 12.56-14.56 | 10/30 kHz |

The E-field measured at 3m is calculated as:

E-field $(dB\mu V/m) = Rx (dB\mu V) + Cable Loss (dB) + AF@3m (dB/m)$







Figure B-1: Measurement Setup

B.1.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of NFC(See 3.4).

The EUT is powered by a travel adapter.

During the measurements, the ambient temperature of the electromagnetic anechoic chamber is in the range of 15 ~ 25 $\,^\circ\!\mathrm{C}$.

B.1.4. Limits

| Table B-2: | Limits |
|------------|--------|
|------------|--------|

| Frequency Pange (MHz) | E-field Strength Limit @ 30 m | E-field Strength Limit @ 3 m | |
|--|-------------------------------|------------------------------|--|
| | (µ V/m) | (dBµV/m) | |
| 13.560 ± 0.007 | +15,848 | 124 | |
| 13.410 to 13.553 | +334 | 90 | |
| 13.567 to 13.710 | | | |
| 13.110 to 13.410 | +106 | 81 | |
| 13.710 to 14.010 | | | |
| Note: Where the limits have been defined at one distance, and a signal level measured at | | | |
| another, the limits have been extrapolated using the following formula: | | | |
| $Extrapolation(dB) = 40 log_{10} (Measurement Distance/Specification Distance)$ | | | |





B.1.5. Measurement Results

Measurement results of normal conditions see Figure B-2 for different set-ups of EUT. The results displayed take into account applicable antenna factors and cable losses.

Conclusions: Set.NFC02, PASS.



Figure B-2: Measurement results for Electric Field Strength of Fundamental and Outside the Allocated bands

B.2. Electric Field Radiated Emissions (< 30MHz)

B.2.1. Reference

See Clause 6.4 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

B.2.2. Measurement Methods

The transmitter carrier output levels (E-Field) from the EUT are measured in a semi-anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement

©Copyright. All rights reserved by CTTL.

Page 18 of 40





distance of 3m from the receiving antenna. The center of the receiving loop antenna is 1.0 meter above the ground. The E-field is measured with a shielded loop antenna connected to a measurement receiver. Detected E-field was maximized by rotating the EUT through 360° and adjusting the receiving antenna polarizations. The maximization processes were repeated with the EUT positioned respectively in its three orthogonal axes. The measurements were performed with the peak detector and if required, the quasi-peak detector.

The measurement bandwidth is:

| Frequency of Emission (MHz) | RBW/VBW |
|-----------------------------|------------|
| 0.009-0.15 | 100/300 Hz |
| 0.15-30 | 10/30 kHz |

Table B-3:Measurement bandwidth

The E-field measured at 3m is calculated as:

E-field (dBµV/m) = Rx (dBµV) + Cable Loss (dB) + AF@3m (dB/m)



Figure B-3: Measurement Setup

B.2.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of NFC(See 3.4).





The EUT is powered by a travel adapter.

During the measurements, the ambient temperature of the electromagnetic anechoic chamber is in the range of 15 ~ 25 $\,^\circ\!\mathrm{C}$.

B.2.4. Limits

| Fable | B-4: | Limits |
|-------|-------------|--------|
| | | |

| Frequency Pange (MHz) | E-field Strength Limit @ 30m | E-field Strength Limit @ 3m | | | |
|--|------------------------------|-----------------------------|--|--|--|
| | (mV/m) | (dBµV/m) | | | |
| 0.009-0.490 | 2400/F(kHz) | 129-94 | | | |
| 0.490-1.705 | 24000/F(kHz) | 74-63 | | | |
| 1.705-30 | 30 | 70 | | | |
| Note: Where the limits have been defined at one distance, and a signal level measured at another, the limits have been extrapolated using the following formula: | | | | | |
| Extrapolation(dB) = $40\log_{10}$ (Measurement Distance/Specification Distance) | | | | | |

B.2.5. Measurement Results

Measurement results of normal conditions see Figure B-4 for different set-ups of EUT. The results displayed take into account applicable antenna factors and cable losses.

Conclusions: Set.NFC01-1, PASS.







Figure B-4: Measurement results for Electric Field Radiated Emissions (< 30MHz) Conclusions: Set.NFC01-2, PASS.



Figure B-5: Measurement results for Electric Field Radiated Emissions (< 30MHz) Conclusions: Set.NFC01-3, PASS.







Figure B-6: Measurement results for Electric Field Radiated Emissions (< 30MHz)

B.3. Electric Field Radiated Emissions (≥30MHz)

B.3.1. Reference

See Clause 6.5 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

B.3.2. Measurement Methods

The electric field radiated emissions from the EUT are measured in a semi-anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 10m from the receiving antenna. The receiving antennas connected to a measurement receiver. In order to search for maximum field strength emitted from the EUT, the receiving antenna can be moved between the height of 1.0 m to 4.0 m. Detected E-field was maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna positions for both vertical and horizontal antenna polarizations. The maximization processes were repeated with the EUT positioned respectively in its three orthogonal axes. The measurements were performed with the peak detector and if required, the quasi-peak detector.

The measurement bandwidth is:

| Table B-5: | Measurement | bandwidth |
|------------|-------------|-----------|
| | | |

| Frequency of Emission (MHz) | RBW/VBW |
|-----------------------------|---------|
| 30-1000 | 120kHz |







Figure B-7: Measurement Setup

B.3.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of NFC(See 3.4).

The EUT had been connected to a travel adapter.

During the measurements, the ambient temperature of the electromagnetic anechoic chamber is in the range of $15 \sim 25$ °C.

B.3.4. Limits

| Frequency Range (MHz) | E-field Strength Limit @ 3m (mV/m) | E-field Strength Limit @ 3m (dBµV/m) | E-field Strength Limit @ 10m (dBµV/m) |
|--------------------------|--|--|---|
| 30-88 | 100 | 40 | 30 |
| 88-216 | 150 | 43.5 | 33.5 |
| 216-960 | 200 | 46 | 36 |
| 960-1000 | 500 | 54 | 44 |

Table B-6: Limits

B.3.5. Measurement Results

Measurement results of normal conditions see Figure B-6 for different set-ups of EUT. The results displayed take into account applicable antenna factors and cable losses.

Conclusions: Set.NFC01-1, PASS.





Full Spectrum



| Figure B-8: | Measurement | results for | Electric | Field | Radiated | Emissions | (≥30MHz) |
|-------------|-------------|-------------|----------|-------|----------|-----------|----------|
|-------------|-------------|-------------|----------|-------|----------|-----------|----------|

Final_Result

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) |
|--------------------|-----------------------|-------------------|----------------|----------------|-----|------------------|
| 40.670000 | 21.68 | 30.00 | 8.32 | 279.0 | V | 204.0 |
| 54.213000 | 18.64 | 30.00 | 11.36 | 99.0 | V | 191.0 |
| 67.770000 | 23.54 | 30.00 | 6.46 | 213.0 | V | 286.0 |
| 116.164000 | 9.65 | 33.50 | 23.87 | 125.0 | V | -8.0 |
| 176.276000 | 24.55 | 33.50 | 8.97 | 102.0 | V | 30.0 |
| 203.376000 | 15.23 | 33.50 | 18.29 | 103.0 | V | 182.0 |

Conclusions: Set.NFC01-2, PASS.





Full Spectrum



Figure B-9: Measurement results for Electric Field Radiated Emissions (≥30MHz)

Final_Result

| Frequency | QuasiPeak | Limit | Margin | Height | Pol | Azimuth |
|------------|-----------|----------|--------|--------|-----|---------|
| (MHz) | (dBµV/m) | (dBµV/m) | (dB) | (cm) | | (deg) |
| 40.670000 | 18.15 | 30.00 | 11.85 | 103.0 | V | 252.0 |
| 67.770000 | 19.60 | 30.00 | 10.40 | 226.0 | V | -11.0 |
| 94.893000 | 12.92 | 33.50 | 20.60 | 102.0 | V | 1.0 |
| 159.084000 | 14.23 | 33.50 | 19.29 | 97.0 | V | 61.0 |
| 176.276000 | 24.77 | 33.50 | 8.75 | 105.0 | V | 30.0 |
| 283.322000 | 13.52 | 36.00 | 22.50 | 107.0 | V | 120.0 |

Conclusions: Set.NFC01-3, PASS.





Full Spectrum



Figure B-10: Measurement results for Electric Field Radiated Emissions (≥30MHz)

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) |
|--------------------|-----------------------|-------------------|----------------|----------------|-----|------------------|
| 40.670000 | 14.74 | 30.00 | 15.26 | 135.0 | V | 300.0 |
| 67.793000 | 17.59 | 30.00 | 12.41 | 187.0 | V | -15.0 |
| 80.643000 | 7.23 | 30.00 | 22.77 | 199.0 | V | 30.0 |
| 109.942000 | 8.84 | 33.50 | 24.68 | 192.0 | V | -14.0 |
| 176.276000 | 22.45 | 33.50 | 11.07 | 103.0 | V | 97.0 |
| 460.056000 | 15.69 | 36.00 | 20.33 | 110.0 | V | 113.0 |

Final_Result





B.4. Frequency Tolerance

B.4.1. Reference

See Clause 6.8 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

B.4.2. Measurement Methods



Figure B-11: Measurement Setup

The transmitter output signal was picked up by coil antenna connected to the spectrum analyzer. The center frequency was measured with 30Hz RBW and 1kHz span.

During the test, the EUT was placed in a thermal chamber until thermal balance and lasting appropriate time.

B.4.3. EUT Operating Mode and Test Conditions

The measurement of EUT was carried out under the transmit state of without modulation(See 3.4).

EUT had not been connected to a travel adapter. The frequency stability was measured with the different voltage and temperature combinations:





- a) The nominal voltage 3.85V(See 3.1)was used and the temperature was varied from -20 $^{\circ}$ C to +50 $^{\circ}$ C in 10 $^{\circ}$ C increments using an environmental chamber.
- b) The 20°C was used and the voltages were 3.6V, 3.85V and 4.4V (The extreme low voltage ,the nominal voltage and the extreme high voltage defined in section 3.1).

The details were as following:

| Test items | Voltage | Temperature |
|------------------------|---------|--------------|
| Frequency | | -20 ℃ |
| stability with respect | | -10 ℃ |
| to ambient | | -10 0 |
| temperature | | 0 °C |
| | 3.87V | 10 ℃ |
| | | 20 ℃ |
| | | 30 ℃ |
| | | 40 ℃ |
| | | 50 ℃ |
| Frequency stability | 3.45V | |
| voltage | 3.87V | 20 ℃ |
| | 4.45V | |

Table B-7: Combinations of Voltage and Temperature

B.4.4. Test Layouts

See B.4.2.

B.4.5. Limits

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency.





B.4.6. Measurement Results

Measurement results see Table B-9 for different test conditions.

Conclusions: Set.NFC03, PASS.

| | | | Frequen | cy (MHz) | |
|-------------|---------|--------------|--------------|--------------|--------------|
| Temperature | Voltage | | 1 | | |
| | | Startup | 2 Min Later | 5 Min Later | 10 Min Later |
| | | | | | |
| -20°C | 3.87V | 13.559819375 | 13.559824375 | 13.559825625 | 13.559826250 |
| | | | | | |
| -10°C | 3.87V | 13.559828125 | 13.559828375 | 13.559828565 | 13.559828685 |
| | | | | | |
| 0°C | 3.87V | 13.559821250 | 13.559820625 | 13.559819375 | 13.559818750 |
| | | | | | |
| 10°C | 3.87V | 13.559808125 | 13.559803125 | 13.559801875 | 13.559801250 |
| | | | | | |
| 20°C | 3.87V | 13.559779375 | 13.559778125 | 13.559775625 | 13.559774375 |
| | | | | | |
| 30℃ | 3.87V | 13.559756250 | 13.559753125 | 13.559749375 | 13.559746875 |
| | | | | | |
| 40°C | 3.87V | 13.559725625 | 13.559723125 | 13.559716875 | 13.559715625 |
| | | | | | |
| 50℃ | 3.87V | 13.559711875 | 13.559709375 | 13.559708625 | 13.559707325 |
| | | | | | |
| 20°C | 3.45V | 13.559768750 | 13.559770625 | 13.559771875 | 13.559772025 |
| | | | | | |
| 20°C | 4.45 V | 13.559769375 | 13.559768750 | 13.559768925 | 13.559768975 |
| | | | | | |

| Table B-8: | Measurement results for Frequency Tol | lerance |
|------------|---------------------------------------|---------|
| | | |

| Tomporaturo | Voltago | Frequency Error (%) | | | | |
|--------------|---------|---------------------|-------------|-------------|--------------|--|
| remperature | voltage | Startup | 2 Min Later | 5 Min Later | 10 Min Later | |
| -20 ℃ | 3.87V | -0.001 | -0.001 | -0.001 | -0.001 | |
| -10 ℃ | 3.87V | -0.001 | -0.001 | -0.001 | -0.001 | |
| 0°C | 3.87V | -0.001 | -0.001 | -0.001 | -0.001 | |
| 10 ℃ | 3.87V | -0.001 | -0.001 | -0.001 | -0.001 | |
| 20 ℃ | 3.87V | -0.002 | -0.002 | -0.002 | -0.002 | |
| 30 ℃ | 3.87V | -0.002 | -0.002 | -0.002 | -0.002 | |

Page 29 of 40

©Copyright. All rights reserved by CTTL.





| 40 ℃ | 3.87V | -0.002 | -0.002 | -0.002 | -0.002 |
|-------------|-------|--------|--------|--------|--------|
| 50 ℃ | 3.87V | -0.002 | -0.002 | -0.002 | -0.002 |
| 20 ℃ | 3.45V | -0.002 | -0.002 | -0.002 | -0.002 |
| 20 ℃ | 4.45V | -0.002 | -0.002 | -0.002 | -0.002 |

B.4.7. Measurement Uncertainty

Measurement uncertainty: U =77 Hz, k=2

B.5. 20dB Bandwidth

B.5.1. Reference

See Clause 6.9 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

B.5.2. Measurement Methods

The transmitter output signal was picked up by coil antenna connected to the spectrum analyzer. The bandwidth of the center frequency was measured with 140Hz RBW, 420Hz VBW and 14kHz span.



Figure B-12: Measurement Setup





B.5.3. EUT Operating Mode and Test Conditions

The measurement of EUT was carried out under the transmit state of NFC (See 3.4).

EUT had not been connected to a travel adapter.

During the measurements, the ambient temperature was in the range of $15 \sim 25$ °C.

B.5.4. Test Layouts

See B.5.2.

B.5.5. Limits

The 20dB bandwidth shall be less than 80% of the permitted frequency band. For 13.56 MHz NFC, the permitted frequency band is 14kHz, so the limit is 11.2 kHz.

B.5.6. Measurement Results

Measurement results see Figure B-9.

Conclusions: Set.NFC03, PASS.









B.5.7. Measurement Uncertainty

Measurement uncertainty: U =77 Hz, k=2

B.6. Conducted emission

B.6.1. Reference

See Clause 6.2 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

B.6.2. Measurement Methods

The conducted emissions from the AC port of the EUT are measured in a shielding room. The EUT is connected to a Line Impedance Stabilization Network (LISN). An overview sweep with peak detection was performed. The measurements were performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver:

Quasi-Peak / Average Detector.

The measurement bandwidth is:

Table B-9:Measurement Bandwidth

| Frequency of Emission (MHz) | RBW/VBW |
|-----------------------------|---------|
| 0.15-30 | 9kHz |







Figure B-14: Measurement Setup

B.6.3. EUT Operating Mode and Test Conditions

The measurement of EUT is carried out under the transmit state of NFC(See 3.4).

The EUT is powered by a travel adapter.

During the measurements, the ambient temperature is in the range of $15 \sim 25$ °C.

B.6.4. Limits

| Frequency range (MHz) | Quasi-peak Limit (dBµV) | Average Limit (dBμV) |
|--------------------------|-------------------------|----------------------|
| 0.15 to 0.5 | 66 to 56 | 56 to 46 |
| 0.5 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

Table B-10: Limits





B.6.5. Measurement Results

Measurement results see Figure B-11.

Conclusions: Set.NFC01-1, PASS.



Note: the spike over the limit is the NFC carrier frequency and coming from the radio equipment.

Figure B-15: Measurement results for Conducted Emission

Final Result 1

| Frequency | QuasiPeak | PE | Line | Corr. | Margin | Limit |
|-----------|-----------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 0.415500 | 40.8 | GND | Ν | 10.0 | 16.8 | 57.5 |
| 0.451500 | 40.0 | GND | Ν | 10.0 | 16.8 | 56.8 |
| 1.594500 | 34.6 | GND | Ν | 10.0 | 21.4 | 56.0 |
| 3.471000 | 34.6 | GND | N | 10.1 | 21.4 | 56.0 |





| 3.768000 | 34.6 | GND | Ν | 10.1 | 21.4 | 56.0 |
|-----------|------|-----|---|------|------|------|
| 10.221000 | 40.2 | GND | Ν | 10.4 | 19.8 | 60.0 |

Final Result 2

| Frequency | Average | PE | Line | Corr. | Margin | Limit |
|-----------|---------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 0.415500 | 34.3 | GND | Ν | 10.0 | 13.2 | 47.5 |
| 0.456000 | 33.9 | GND | L1 | 10.0 | 12.9 | 46.8 |
| 1.630500 | 25.7 | GND | Ν | 10.0 | 20.3 | 46.0 |
| 3.520500 | 26.4 | GND | Ν | 10.1 | 19.6 | 46.0 |
| 3.727500 | 28.0 | GND | N | 10.1 | 18.0 | 46.0 |
| 10.347000 | 33.9 | GND | N | 10.4 | 16.1 | 50.0 |





Conclusions: Set.NFC01-2, PASS.



Note: the spike over the limit is the NFC carrier frequency and coming from the radio equipment. Figure B-16: Measurement results for Conducted Emission

| - | | r | 1 | | | |
|-----------|-----------|-----|------|-------|--------|--------|
| Frequency | QuasiPeak | PE | Line | Corr. | Margin | Limit |
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 0.514500 | 35.8 | GND | N | 10.0 | 20.2 | 56.0 |
| 1.608000 | 27.9 | GND | N | 10.0 | 28.1 | 56.0 |
| 2.526000 | 28.6 | GND | N | 10.1 | 27.4 | 56.0 |
| 2.994000 | 29.0 | GND | N | 10.1 | 27.0 | 56.0 |
| 4.875000 | 29.9 | GND | N | 10.2 | 26.1 | 56.0 |
| 10.234500 | 33.7 | GND | N | 10.4 | 26.3 | 60.0 |

Final Result 1

Final Result 2

| Frequency (MHz) | QuasiPeak (dBµV) | PE | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|--------------------|---------------------|-----|------|---------------|----------------|-----------------|
| 0.505500 | 31.1 | GND | N | 10.0 | 14.9 | 46.0 |





| 1.594500 | 22.4 | GND | Ν | 10.0 | 23.6 | 46.0 |
|-----------|------|-----|---|------|------|------|
| 3.457500 | 23.1 | GND | Ν | 10.1 | 22.9 | 46.0 |
| 3.898500 | 23.2 | GND | Ν | 10.1 | 22.8 | 46.0 |
| 10.234500 | 28.2 | GND | N | 10.4 | 21.8 | 50.0 |
| 27.118500 | 31.0 | GND | N | 10.9 | 19.0 | 50.0 |

Conclusions: Set.NFC01-3, PASS.



Note: the spike over the limit is the NFC carrier frequency and coming from the radio equipment. Figure B-17: Measurement results for Conducted Emission

Final Result 1

| Frequency | QuasiPeak | PE | Line | Corr. | Margin | Limit |
|-----------|-----------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 0.163500 | 40.1 | GND | L1 | 10.0 | 25.2 | 65.3 |
| 0.429000 | 33.0 | GND | L1 | 10.0 | 24.3 | 57.3 |
| 0.483000 | 39.3 | GND | L1 | 10.0 | 17.0 | 56.3 |
| 0.568500 | 32.5 | GND | L1 | 10.0 | 23.5 | 56.0 |





| 4.812000 | 30.0 | GND | Ν | 10.2 | 26.0 | 56.0 |
|----------|------|-----|---|------|------|------|
| 8.808000 | 37.4 | GND | Ν | 10.3 | 22.6 | 60.0 |

Final Result 2

| Frequency | QuasiPeak | PE | Line | Corr. | Margin | Limit |
|-----------|-----------|-----|------|-------|--------|--------|
| (MHz) | (dBµV) | | | (dB) | (dB) | (dBµV) |
| 0.163500 | 27.7 | GND | L1 | 10.0 | 27.5 | 55.3 |
| 0.375000 | 20.6 | GND | L1 | 10.0 | 27.7 | 48.4 |
| 0.456000 | 29.6 | GND | Ν | 10.0 | 17.2 | 46.8 |
| 0.487500 | 32.5 | GND | Ν | 10.0 | 13.7 | 46.2 |
| 0.568500 | 25.9 | GND | L1 | 10.0 | 20.1 | 46.0 |
| 9.190500 | 31.8 | GND | Ν | 10.3 | 18.2 | 50.0 |





ANNEX C: Persons involved in this testing

| Table C-1: | Persons | involved |
|------------|---------|----------|
| | | |

| Test Item | Tester |
|--|--------------|
| 20dB Bandwidth | Zhou Bin |
| Frequency Tolerance | Zhou Bin |
| Electric Field Strength of Fundamental and Outside the Allocated bands | Wang Huan |
| Electric Field Radiated Emissions (< 30MHz) | Wang Huan |
| Electric Field Radiated Emissions (≥30MHz) | Wang Huan |
| Conducted Emissions | Chen Tianwei |





ANNEX D: Accreditation Certificate



END OF REPORT