

■ Report No.: DDT-R21080304-2E03

■Issued Date: Aug. 20, 2021

RF EXPOSURE REPORT

FOR

Applicant	:	FengShun Peiying Electro-Acoustic Co., Ltd	
Address	•••	No.8, Fengda Road, Tangkeng Town Ind. Area, Fengshun County, Guangdong, China	
Equipment under Test	••	Digital Media Receiver	
Model No.		MPR2121	
Trade Mark	16	N/A	
FCC ID	4	2AFXA-MPR2121	
Manufacturer	••	FengShun Peiying Electro-Acoustic Co., Ltd	
Address	••	No.8, Fengda Road, Tangkeng Town Ind. Area, Fengshun County, Guangdong, China	

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, http://www.dgddt.com



Table of Contents

	Test report declares			3
1.	General information			5
1.1.	Description of Equipment	8	(8)	5
1.2.	Assess laboratory			5
2.	RF Exposure evaluation for FCC	<i>Y</i>		5

TEST REPORT DECLARE

Applicant	:	FengShun Peiying Electro-Acoustic Co., Ltd
Address No.8, Fengda Road, Tangkeng Town Ind. Area, Fengshun County, Guangdong, China		
Equipment under Test	:	Digital Media Receiver
Model No.	:	MPR2121
Trade mark	:	N/A
Manufacturer	-	FengShun Peiying Electro-Acoustic Co., Ltd
Address	.	No.8, Fengda Road, Tangkeng Town Ind. Area, Fengshun County, Guangdong, China

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R21080304-2E03		
Date of Receipt:	Aug. 03, 2021	Date of Test:	Aug. 03, 2021 ~ Aug. 20, 2021

Prepared By:

Jacky Huang/Engineer

Damon Hu/EMC Manager

Approved B

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions		Issue Date	Revised By
	Initial issue	(8)	Aug. 20, 2021	®
	201	201	aĎ	1

1. General information

1.1. Description of Equipment

EUT* Name	•••	Digital Media Receiver
Model Number	:	MPR2121
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	+12V~16VDC
Radio Specification	:	Bluetooth V5.0
Operation Frequency	:	2402 MHz - 2480 MHz
Modulation	1	GFSK, π/4-DQPSK, 8DPSK
Data Rate	:	1 Mbps, 2 Mbps, 3 Mbps
Antenna Gain	:	Maximum PK gain: 1.7 dBi
Sample Type	:	Series production

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,

Guangdong Province, China, 523808

Tel: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,

mm)] $[\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Worse case is as below: [2402MHz, 2.75dBm 1.88mW) output power]

 $(1.88/5) \cdot [\sqrt{2.402(GHz)}] = 0.583 < 3.0 \text{ for } 1-g \text{ SAR}$

Then SAR evaluation is not required

END OF REPORT