

# INTERTEK TESTING SERVICES

---

## RF Exposure

The equipment under test (EUT) is a Drone Stunt Glow 5inch LED operating at 2.4G Band. The EUT can be powered by DC 4.5V (3 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0dBi

The nominal conducted output power specified: -18.0 dBm ( $\pm 3$ dB)

The nominal radiated output power (e.i.r.p) specified: -18.0 dBm ( $\pm 3$ dB)

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 77.5 dB $\mu$ V/m at 3m in the frequency 2450MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -17.73dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 74.7 dB $\mu$ V/m at 3m in the frequency 2475MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -20.53dBm

which is within the production variation.

The maximum conducted output power specified is -15.0dBm= 0.032mW

The source- based time-averaging conducted output power  
=0.032\* Duty cycle mW <0.032 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

$$\begin{aligned} P_{th}(\text{mW}) &= ERP_{20\text{cm}} * (d/20\text{cm})^x \quad (X = -\log_{10} \left( \frac{60}{ERP_{20\text{cm}} \sqrt{f}} \right)) \\ &= 3060 * (0.5/20)^{1.9} \text{ mW} \\ &= 2.72 \text{ mW} \end{aligned}$$

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 4.0725ms

Effective period of the cycle = 231.9 $\mu$ s x1 = 0.2319ms

DC =0.2319ms / 4.0725ms =0.0569 or 5.69%