RF Exposure / MPE Calculation

No.: 10800614H

Applicant : Yamaha Corporation

Type of Equipment: Network Module *Bluetooth part

Model No. : NW-01 FCC ID : A6RNW01A

Yamaha Corporation declares that Model: NW-01 complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091 (for mobile).

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "NW-01" as calculated

from (B) Limits for General Population / Uncontrolled Exposure of

TABLE 1- LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) of §1.1310 Radiofrequency radiation exposure limits.

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm^2 uncontrolled exposure limit. The Friis formula used was:

 $S = (P * G) / (4* \pi * r^2)$

Where

P = 0.63 mW (Maximum average output power)

G = 3.16 Numerical Antenna gain; equal to 5.0 dBi

r = 20.0 cm

For: NW-01 $S = 0.00040 \text{ mW/cm}^2$

Even taking into account the tolerance, this device can be satisfied with the limits.

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8999 Facsimile: +81 596 24 8124