

RF EXPOSURE EVALUATION

MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance v01.

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$
1.34-30	$3,450 R^2/f^2$
30-300	$3.83 R^2$
300-1,500	$0.0128 R^2 f$
1,500-100,000	$19.2 R^2$

R is the minimum separation distance in meters

f = frequency in MHz

Result

Mode	Frequency (MHz)	EIRP (dBm)	Tune Up EIRP (dBm)	Tune Up ERP (dBm)	Tune Up ERP (mW)	Evaluation Distance (m)	ERP Limit (mW)
2.4G Radio	2405-2480	-13.6	-13.0	-15.15	0.03	0.2	768

Note 1: The maximum E-Field is 81.60dBuV/m @ 3m, so the EIRP = (81.6-95.2)dBm=-13.6dBm

Note 2: The tune up EIRP was declared by the applicant.

Note 3: ERP=EIRP-2.15

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant