

RF Exposure Evaluation

LIMIT

© **Single transmitter:**

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

© **Simultaneous transmission:**

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤1.0.

EVALUATION METHOD

Transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm², **P_{out}** = output power to antenna in mW, **G** = gain of antenna in linear scale;

P_i = 3.1416, **R** = distance between observation point and center of the radiator in cm

TEST RESULT

☒ **Passed**

☐ **Not Applicable**

Type	Maximum Output Power(dBm) ^{#1}	Antenna Gain ^{#2} (dBi)	Minimum use distance (cm)	Power density (mW/cm ²)	Power density limit (mW/cm ²)	Result
LTE Band 2	25.00	1.19	20	0.083	1.000	PASS
LTE Band 4	24.50	1.19	20	0.074	1.000	PASS
LTE Band 12	25.00	1.19	20	0.083	0.466	PASS
LTE Band 13	24.50	1.19	20	0.074	0.518	PASS

Note:

#1: Refer to RF report.

#2: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, HTW lab has not verified the authenticity of its information.