

TEST REPORT
On behalf of

Savant Technologies LLC, dba GE Lighting, a Savant company

Product Name: ON/OFF Smart Plug

Model No.: CPLGSTDBLW1S

FCC ID: PUU-CPLGSTDBLW1S

Prepared For: Savant Technologies LLC, dba GE Lighting, a Savant company
1975 Noble Road Cleveland, Ohio United States 44112

Prepared By: Audix Technology (Shanghai) Co., Ltd.
3F, Building 34, No. 680 Guiping Rd.,
Caohejing, Hi-Tech Park,
Shanghai 200233, China

Tel: +86-21-64955500



File No. : C1D2404051
Report No. : ACI-F24119
Date of Test : 2024.06.28-07.08
Date of Report : 2024.07.15

The statement is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

TABLE OF CONTENTS

	Page
1 SUMMARY OF STANDARDS AND RESULTS.....	5
1.1 Description of Standards and Results.....	5
2 GENERAL INFORMATION.....	6
2.1 Description of Equipment Under Test.....	6
2.2 EUT Specifications Assessed in Current Report.....	7
2.3 Test Information	7
2.4 Duty Cycle Check	8
2.5 Sample Description	9
2.6 Supported equipment.....	9
2.7 Description of Test Facility	9
3 CONDUCTED EMISSION TEST	10
3.1 Test Equipment.....	10
3.2 Block Diagram of Test Setup	10
3.3 Conducted Emission Limits (§15.207).....	11
3.4 Test Configuration.....	11
3.5 Operating Condition of EUT	11
3.6 Test Procedures	11
3.7 Test Results	12
4 RADIATED EMISSION TEST.....	15
4.1 Test Equipment.....	15
4.2 Block Diagram of Test Setup	16
4.3 Radiated Emission Limit (§15.209)	17
4.4 Test Configuration.....	17
4.5 Operating Condition of EUT	17
4.6 Test Procedures	17
4.7 Test Results	19
5 99% OCCUPIED BANDWIDTH MEASUREMENT	50
5.1 Test Equipment.....	50
5.2 Block Diagram of Test Setup	50
5.3 Operating Condition of EUT	50
5.4 Test Procedure	50
5.5 Test Results	51
6 6 DB BANDWIDTH MEASUREMENT	56
6.1 Test Equipment.....	56
6.2 Block Diagram of Test Setup	56
6.3 Specification Limits (§15.247(a)(2)).....	56
6.4 Operating Condition of EUT	56
6.5 Test Procedure	56
6.6 Test Results	57
7 MAXIMUM OUTPUT POWER MEASUREMENT	62
7.1 Test Equipment.....	62
7.2 Block Diagram of Test Setup	62
7.3 Specification Limits ((§15.247(b)(3))	62

7.4	Operating Condition of EUT	62
7.5	Test Procedure	62
7.6	Test Results	63
8	EMISSION LIMITATIONS MEASUREMENT	68
8.1	Test Equipment.....	68
8.2	Block Diagram of Test Setup	68
8.3	Specification Limits (§15.247(d))	68
8.4	Operating Condition of EUT	68
8.5	Test Procedure.....	68
8.6	Test Results	70
9	POWER SPECTRAL DENSITY MEASUREMENT	83
9.1	Test Equipment.....	83
9.2	Block Diagram of Test Setup	83
9.3	Specification Limits (§15.247(e))	83
9.4	Operating Condition of EUT	83
9.5	Test Procedure.....	83
9.6	Test Results	84
10	ANTENNA REQUIREMENT.....	89
10.1	Specification Limits (§15.203).....	89
10.2	Result.....	89
11	MEASUREMENT UNCERTAINTY LIST	90
APPENDIX I PHOTOGRAPHS OF TEST		
APPENDIX II PHOTOGRAPHS OF EUT		

TEST REPORT

Applicant : Savant Technologies LLC, dba GE Lighting, a Savant company
EUT Description : ON/OFF Smart Plug
(A) Model No. : Refer to Sec.2.1
(B) Power Supply : 120V AC 60Hz
(C) Test Voltage : 120V/60Hz, DC3V3 from test fixture

Test Procedure Used:

*FCC RULES AND REGULATIONS PART 15 SUBPART C
AND ANSI C63.10-2013*

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report also shows that the EUT (M/N: Refer to Sec2.1), which was tested is technically compliance with the FCC limits.

This report applies to above tested Sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.

The test results for EUT's BLE function are contained in No.ACI-F24120 report.

Date of Test : 2024.06.28-07.08 Date of Report : 2024.07.15

Producer : Huimin Yan
HUIMIN YAN / Assistant

Review : LVY LV
LVY LV / Deputy Assistant Manager

 For and on behalf of
Audix Technology (Shanghai) Co., Ltd.
Kamp Chen
Signatory :
Authorized Signature(s) KAMP CHEN / Manager

1 SUMMARY OF STANDARDS AND RESULTS

1.1 Description of Standards and Results

The result is determined according to the decision rules of customer selection in the ASC-403 application service form.

1. According to IEC GUIDE 115 Procedure 2 and ILAC-G8, the uncertainties value is not used in determining the PASS/FAIL results.

2. If the required specification or standard already contains the decision rules, it will be carried out in accordance with the regulations or standard documents or the requirements of the competent units. If the required specification or standard does not contain a decision rule, the same paragraph 1.

3. If your company has a required decision rule, it will be implemented in accordance with the requirements and ISO/IEC Guide 98-4 specifications.

The EUT have been tested according to the applicable standards as referenced below:

Description / Test Item	Test Standard	Results	Meets Limit
EMISSION			
Conducted Emission	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.207
Radiated Emission	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.209(a) 15.205(a)(c)
6 dB Bandwidth Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(a)(2)
Maximum Output Power Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(b)(3)
Emission Limitations Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(d)
Band Edge Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(d)
Power Spectral Density Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(e)
Antenna Requirement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.203
N/A is an abbreviation for Not Applicable.			

2 GENERAL INFORMATION

2.1 Description of Equipment Under Test

Description : ON/OFF Smart Plug

Type of EUT : ☒ Production ☐ Pre-product ☐ Pro-type

Model Number : CPLGSTDBLW1MS

Radio Tech : BLE 4.2;
IEEE 802.11 b/g/n.

Channel Freq. : BLE: 2402MHz-2480MHz;
802.11b/g/n20: 2412MHz-2462MHz;
802.11n40: 2422MHz-2452MHz.

Modulation : BLE: GFSK;
802.11b: DSSS (CCK, DQPSK, DBPSK);
802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK).

Antenna Info. : Antenna Type: PCB Antenna
Antenna Gain: 3.34 dBi

Applicant : Savant Technologies LLC, dba GE Lighting, a Savant company
1975 Noble Road Cleveland, Ohio United States 44112

Manufacturer : same as Applicant

Factory#1 : Sichuan Hongrui Electric Co., Ltd
Mianyan Export Processing Zone, Mianyan, Sichuan,
China

Factory#2 : VIETNAM CHANGHONG ELECTRIC COMPANY
LIMITED
Workshop W4(leased by WWWHP), Land plot 4.2B,
Dinh Vu Industrial Zone, Dong Hai 2 Ward, Hai An
District, Haiphong City, VN.

2.2 EUT Specifications Assessed in Current Report

Mode	Modulation	Data Rate(Mbps)
802.11b	DS (DQPSK, DBPSK, CCK)	Up to 11
802.11g	OFDM (64-QAM, 16-QAM, QPSK, BPSK)	Up to 54
802.11n-HT 20	OFDM (64-QAM, 16-QAM, QPSK, BPSK)	Up to 72.2
802.11n-HT 40	OFDM (64-QAM, 16-QAM, QPSK, BPSK)	Up to 150

Channel List			
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

2.3 Test Information


The test software “ EspRFTestTool_v2.8_Manual.exe” was used to control EUT work in TX mode, Power Index and select test channel.

Mode	data rate (Mbps)	Attenuator Setting	Test Channel		Frequency (MHz)
802.11b	11	12	Low:	1	2412
		12	Middle:	6	2437
		12	High:	11	2462
802.11g	6	0	Low:	1	2412
		0	Middle:	6	2437
		0	High:	11	2462
802.11n20	MCS0	0	Low:	1	2412
		0	Middle:	6	2437
		0	High:	11	2462
802.11n40	MCS0	8	Low:	3	2422
		8	Middle:	6	2437
		8	High:	9	2452

2.4 Duty Cycle Check

Mode	Transmission Duration (ms)	Transmission Period (ms)	Duty Cycle (%)	Duty Cycle Correct Factor
802.11b	3.168	3.192	99.25	N/A
802.11g	5.48	5.51	99.46	N/A
802.11n20	5.08	5.104	99.53	N/A
802.11n40	2.466	2.49	99.04	N/A





2.5 Sample Description

Test Item	Model Number	Sample Number	Date of receipted
Conducted Emission	CPLGSTDBLW1MS	E20240624477-01/02	2024.06.24
Radiated Emission	CPLGSTDBLW1MS	E20240624477-01/02	2024.06.24
Conducted RF Test	CPLGSTDBLW1MS	E20240624477a-01/02	2024.06.24

2.6 Supported equipment

- Brand

:

Acer
- Product Name:

:

Notebook PC
- Model Name

:

TravelMate P238 series
- Model Number

:

N15W8
- Product Name

:

Test Fixture
- Product Function

:

USB to TTL

2.7 Description of Test Facility

- Name of Firm

:

Audix Technology (Shanghai) Co., Ltd.
- Site Location

:

3F, Building 34, No. 680 Guiping Rd.,
Caohejing, Hi-Tech Park,
Shanghai 200233, China
- Accredited by NVLAP, Lab Code

:

200371-0
- FCC Designation Number

:

CN5027
- Test Firm Registration Number

:

954668

3 CONDUCTED EMISSION TEST


3.1 Test Equipment

The following test equipments are used during the conducted emission test in a shielded room:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Test Receiver	R&S	ESCI	101302	2024.02.22	1 Year
2.	Artificial Mains Network (AMN)	R&S	ESH2-Z5	843890/011	2024.02.22	1 Year
3.	Fixed Attenuator	SHYL	TTS-1	001	2024.02.22	1 Year
4.	50Ω Coaxial Switch	Anritsu	MP59B	6200655085	2024.02.22	1 Year
5.	Coaxial Cable	Audix	CE Cable	CE-SH1-001	2024.02.22	1 Year
6.	Software	Audix	e3	e3.v9.210616	--	--

3.2 Block Diagram of Test Setup

3.2.1 Conducted Disturbance Test Setup



3.3 Conducted Emission Limits (§15.207)

Frequency Range (MHz)	Limits dB(μV)	
	Quasi-peak	Average
0.15 ~ 0.5	66~56	56~46
0.5 ~ 5	56	46
5 ~ 30	60	50
NOTE 1 – The lower limit shall apply at the transition frequencies. NOTE 2 – The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz~0.50 MHz		

3.4 Test Configuration

The EUT (listed in Sec.2.1) was installed as shown on Sec.3.2 to meet FCC requirement and operating in a manner which tends to maximize its emission level in a normal application.

3.5 Operating Condition of EUT

3.5.1 Setup the EUT as shown in Sec. 3.2.

3.5.2 Turn on the power of all equipment.

3.5.3 Turn the EUT on the test mode, and then test.

3.6 Test Procedures

The EUT was placed upon a non-metallic table, which is 0.8 m above the horizontal conducting ground plane and 0.4 m from a vertical reference plane. The EUT was connected to the power mains through an Artificial Mains Network (AMN) to provide a 50 Ω coupling impedance for the measuring equipment. Both sides of AC line (Line & Neutral) were checked to find out the maximum conducted emission according to FCC Part 15 Subpart C and ANSI C63.10: 2013 requirements during conducted disturbance test.

The I.F. bandwidth of Test Receiver ESCI was set at 9 kHz.

The frequency range from 150 kHz to 30 MHz was checked.

Test with a dummy load in lieu of the antenna to determine compliance with Section 15.207 limits within the transmitter's fundamental emission band. (According to KDB 174176 D01 Line Conducted FAQ)

The test modes were done on conducted disturbance test and all the test results are listed in Sec. 3.7

3.7 Test Results

< **PASS** >

The frequency and amplitude of the highest conducted emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Worst case emission:

No.	Operation	Mode	Channel	Frequency (MHz)	Data Page
1.	Transmitting	802.11b	1	2412	P13-14

NOTE 1 – Emission Level = Read Level + AMN Factor + Aux Factor + Cable Loss


Margin = Limits - Emission Level

NOTE 2 – “QP” means “Quasi-Peak” values


NOTE 3 – The emission levels which not reported are too low against the official limit.

Worst case emission

Test Date:	2024.06.28	Temp./Hum.:	22°C/51%RH	Test By:	Jarey
------------	------------	-------------	------------	----------	-------

Mode: 802.11b CH2412MHz**Polarization at Line**

Frequency (MHz)	Meter Reading dB (μV)	AMN Factor (dB)	Aux Factor (dB)	Cable Loss (dB)	Emission Level dB (μV)	Limits dB (μV)	Margin (dB)	Remark
0.210	38.02	0.10	9.49	0.10	47.71	63.19	15.48	QP
0.210	26.23	0.10	9.49	0.10	35.92	53.19	17.27	Average
0.247	38.31	0.10	9.49	0.10	48.00	61.87	13.87	QP
0.247	26.23	0.10	9.49	0.10	35.92	51.87	15.95	Average
0.275	38.12	0.10	9.49	0.10	47.81	60.96	13.15	QP
0.275	25.41	0.10	9.49	0.10	35.10	50.96	15.86	Average
0.448	36.48	0.15	9.49	0.11	46.23	56.92	10.69	QP
0.448	26.25	0.15	9.49	0.11	36.00	46.92	10.92	Average
0.535	37.19	0.20	9.49	0.11	46.99	56.00	9.01	QP
0.535	25.43	0.20	9.49	0.11	35.23	46.00	10.77	Average
0.829	35.06	0.20	9.49	0.13	44.88	56.00	11.12	QP
0.829	25.21	0.20	9.49	0.13	35.03	46.00	10.97	Average

Mode: 802.11b CH2412MHz**Polarization at Neutral**

Frequency (MHz)	Meter Reading dB (μV)	AMN Factor (dB)	Aux Factor (dB)	Cable Loss (dB)	Emission Level dB (μV)	Limits dB (μV)	Margin (dB)	Remark
0.244	39.18	0.10	9.49	0.10	48.87	61.95	13.08	QP
0.244	27.42	0.10	9.49	0.10	37.11	51.95	14.85	Average
0.316	38.05	0.10	9.49	0.10	47.74	59.81	12.07	QP
0.316	29.43	0.10	9.49	0.10	39.12	49.81	10.69	Average
0.390	38.87	0.10	9.49	0.11	48.57	58.07	9.50	QP
0.390	30.29	0.10	9.49	0.11	39.98	48.07	8.09	Average
0.461	37.62	0.10	9.49	0.11	47.32	56.67	9.35	QP
0.461	29.46	0.10	9.49	0.11	39.16	46.67	7.51	Average
0.541	36.85	0.10	9.49	0.11	46.55	56.00	9.45	QP
0.541	28.48	0.10	9.49	0.11	38.19	46.00	7.81	Average
2.123	34.00	0.20	9.49	0.14	43.83	56.00	12.17	QP
2.123	27.43	0.20	9.49	0.14	37.26	46.00	8.74	Average

4 RADIATED EMISSION TEST


4.1 Test Equipment

The following test equipment are used during the radiated emission test in a semi-anechoic chamber:


Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Preamplifier	Agilent	8447D	2944A10548	2024.02.22	1 Year
2.	Preamplifier	HP	8449B	3008A00864	2024.02.22	1 Year
3.	EXA Signal Analyzer	Agilent	N9010A	MY52221182	2023.08.09	1 Year
4.	Test Receiver	R&S	ESCI	101303	2024.02.22	1 Year
5.	Bilog Antenna+ 6dB Attenuator	Schwarzbeck	VULB 9168+ EMCI-N-6-06	708+AT-N0638	2024.03.08	1 Year
6.	Horn Antenna	EMCO	3115	96074878	2023.08.02	1 Year
7.	Horn Antenna	EMCO	3116	00062643	2024.01.30	2 Year
8.	Cavity Band Rejection Filter	Microwave	WT-A3882-R10	WT200312-1-1	2024.02.22	1 Year
9.	Coaxial Switch	Anritsu	MP59B	6200655086	2024.02.22	1 Year
10.	Coaxial Cable	SCHAFFNER	RG 212U-MIL C 17+N1K50-EW06 30-N1K50-15m-1	RE-10m-001/ RE-15m-002	2024.02.22	1 Year
11.	Software	Audix	e3	e3.v9.210616	--	--

4.2 Block Diagram of Test Setup


4.2.1 EUT & Peripherals



4.2.2 Below 1GHz



4.2.3 Above 1GHz



4.3 Radiated Emission Limit (§15.209)

Frequency (MHz)	Distance (m)	Field strength limits (μV/m)	
		(μV/m)	(μV/m)
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
Above 960	3	500	54.0
NOTE 1 - Emission Level dB (μV/m) = 20 log Emission Level (μV/m) NOTE 2 - The tighter limit applies at the band edges. NOTE 3 - Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system. NOTE 4 - The limits shown are based on Quasi-peak value detector below or equal to 1GHz and Average value detector above 1GHz. NOTE 5 - Above 1 GHz, the limit on peak emission is 20 dB above the maximum permitted average emission limit applicable to the EUT			

4.4 Test Configuration

The EUT (listed in Sec.2.1) and the simulators (listed in Sec.2.2) were installed as shown on Sec.4.2 to meet FCC requirements and operating in a manner that tends to maximize its emission level in a normal application.

4.5 Operating Condition of EUT

4.5.1 Setup the EUT as shown in Sec. 4.2.

4.5.2 Connect the EUT and the TTL terminal of Test Fixture through three HCI cables of EUT, as follows (3V3 to 3V3, TX to RXD, RX to TXD, GND to GND). Plug the USB terminal of Test Fixture to the USB port of Notebook PC.

4.5.3 Use the software as section 2.3 to select the test mode, then test.

4.5.4 Repeat step 4.5.3 and 4.5.4, until the test of all modes finished.

4.6 Test Procedures

Radiated emission test applies to harmonics/spurs that fall in the restricted bands listed in Section 15.205. The maximum permitted average field strength is listed in Section 15.209. A pre-amp is necessary for this measurement. For measurement above 1 GHz, set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.

The EUT was placed on a turntable. Below 1 GHz, the table height is 80 cm above the reference ground plane. Above 1 GHz, the table height is 1.5 m. The turntable rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. The antenna moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (Calibrated Bilog Antenna) or Horn antenna was used as

receiving antenna. Both horizontal and vertical polarizations of the antenna were set on measurement. In order to find the maximum emission, all of the interference cables were manipulated according to ANSI C63.10: 2013 requirements during radiated emission test.

The bandwidth of Test Receiver R&S ESCI was set at 120 kHz from 30MHz to 1000MHz.

The bandwidth of Agilent N9010A was set at 1MHz for above 1GHz.

The frequency range from 30 MHz to 25 GHz (Up to 10th harmonics from fundamental frequency) was checked.

All the test results are listed in Sec.4.7.

4.7 Test Results

<PASS>

The frequency and amplitude of the highest radiated emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Frequency range: below 1GHz (Worst case emission)

No.	Operation	Mode	Channel	Frequency	Data Page
1.	Transmitting	802.11b	6	2437 MHz	P20-21

Frequency range: above 1GHz

No.	Operation	Mode	Channel	Frequency	Data Page
1.	Transmitting	802.11b	1	2412 MHz	P22-23
2.			6	2437 MHz	P24-25
3.			11	2462 MHz	P26-27
4.		802.11g	6	2437 MHz	P28-29
5.		802.11n20	6	2437 MHz	P30-31
6.		802.11n40	6	2437 MHz	P32-33

Band-Edge and Restricted bands:

No.	Operation	Mode	Channel	Frequency	Data Page
1.	Transmitting	802.11b	1	2412 MHz	P34-35
2.			11	2462 MHz	P36-37
3.		802.11g	1	2412 MHz	P38-39
4.			11	2462 MHz	P40-41
5.		802.11n20	1	2412 MHz	P42-43
6.			11	2462 MHz	P44-45
7.		802.11n40	3	2422 MHz	P46-47
8.			9	2452 MHz	P48-49

NOTE 1 – Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin = Limits - Emission Level.

NOTE 2 – “QP” means “Quasi-Peak” values

NOTE 3 – 0° was the table front facing the antenna. Degree is calculated from 0° clockwise facing the antenna.

NOTE 4 – The emission levels which not reported are too low against the official limit.

NOTE 5 – The emission levels recorded below is data of EUT configured in Standing direction, for this direction was the maximum emission direction during the test. The data of Side & Lying direction are too low against the official limit to be reported.

NOTE 6 – All reading are Quasi-Peak values below or equal to 1GHz, Peak and Average values above 1GHz.


For above 1GHz test, if the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.

NOTE 7 – The frequency range 2310-2390MHz & 2483.5-2500MHz were tested for Restricted bands.

Radiated emission < 1GHz


Test Date:	2024.07.07	Temp./Hum.:	22°C/51%RH	Test By:	Jarey
------------	------------	-------------	------------	----------	-------

Mode: 802.11b CH2437MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
148.181	32.16	19.12	1.33	29.41	23.20	43.50	20.30	QP
168.414	33.61	18.76	1.44	29.34	24.47	43.50	19.03	QP
192.419	36.42	16.26	1.56	29.30	24.94	43.50	18.56	QP
480.528	37.01	23.11	2.44	29.42	33.13	46.00	12.87	QP
640.611	30.38	26.00	2.85	28.84	30.40	46.00	15.60	QP
800.382	29.45	28.10	3.14	28.00	32.69	46.00	13.31	QP



Mode: 802.11b CH2437MHz**Polarization at Horizontal**

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
144.082	40.79	19.00	1.32	29.44	31.67	43.50	11.83	QP
168.119	42.35	18.79	1.44	29.34	33.24	43.50	10.26	QP
180.649	39.67	17.44	1.50	29.30	29.31	43.50	14.19	QP
192.419	46.40	16.26	1.56	29.30	34.92	43.50	8.58	QP
264.282	38.26	17.97	1.78	29.03	28.98	46.00	17.02	QP
480.528	43.96	23.11	2.44	29.42	40.09	46.00	5.91	QP

Radiated Emission > 1GHz

Test Date:	2024.07.07	Temp./Hum.:	22°C/51%RH	Test By:	Jarey
------------	------------	-------------	------------	----------	-------



Mode: 802.11b CH2412MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3216.375	43.66	31.10	6.08	36.20	44.64	74.00	29.36	Peak
4822.875	47.00	33.04	7.64	35.40	52.28	74.00	21.72	Peak
4822.875	40.43	33.04	7.64	35.40	45.71	54.00	8.29	Average
6189.250	38.80	34.56	8.59	35.34	46.60	74.00	27.40	Peak
7987.000	38.83	37.23	10.30	35.60	50.75	74.00	23.25	Peak
9555.250	37.75	38.20	11.10	35.43	51.62	74.00	22.38	Peak
17742.880	34.29	46.99	15.91	33.08	64.11	74.00	9.89	Peak
17742.880	18.43	46.99	15.91	33.08	48.25	54.00	5.75	Average



Mode: 802.11b CH2412MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3214.250	47.53	31.10	6.08	36.20	48.51	74.00	25.49	Peak
4822.875	52.29	33.04	7.64	35.40	57.57	74.00	16.43	Peak
4822.875	45.24	33.04	7.64	35.40	50.52	54.00	3.48	Average
6386.875	41.77	34.55	8.76	35.38	49.70	74.00	24.30	Peak
8337.625	38.01	38.05	10.42	35.60	50.89	74.00	23.11	Peak
9895.250	38.42	38.38	11.37	35.33	52.83	74.00	21.17	Peak
17808.750	35.20	47.11	16.01	33.06	65.26	74.00	8.74	Peak
17808.750	18.42	47.11	16.01	33.06	48.48	54.00	5.52	Average



Mode: 802.11b CH2437MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3188.750	47.63	31.06	6.06	36.22	48.52	74.00	25.48	Peak
4873.875	47.65	33.34	7.69	35.37	53.31	74.00	20.69	Peak
4873.875	40.46	33.34	7.69	35.37	46.13	54.00	7.87	Average
7251.750	37.61	36.60	9.53	35.53	48.22	74.00	25.78	Peak
8567.125	39.18	38.17	10.50	35.60	52.24	74.00	21.76	Peak
9899.500	38.15	38.40	11.37	35.33	52.60	74.00	21.40	Peak
17785.380	34.91	47.07	15.98	33.06	64.89	74.00	9.11	Peak
17785.380	18.39	47.07	15.98	33.06	48.37	54.00	5.63	Average



Mode: 802.11b CH2437MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3248.250	46.16	31.10	6.11	36.19	47.18	74.00	26.82	Peak
4873.875	52.77	33.34	7.69	35.37	58.43	74.00	15.57	Peak
4873.875	44.96	33.34	7.69	35.37	50.62	54.00	3.38	Average
6729.000	39.80	35.23	9.04	35.45	48.63	74.00	25.37	Peak
8518.250	38.71	38.20	10.48	35.60	51.79	74.00	22.21	Peak
9929.250	37.65	38.40	11.39	35.32	52.12	74.00	21.88	Peak
17732.250	34.59	46.96	15.90	33.08	64.37	74.00	9.63	Peak
17732.250	19.06	46.96	15.90	33.08	48.84	54.00	5.16	Average



Mode: 802.11b CH2462MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3195.125	42.87	31.08	6.06	36.21	43.80	74.00	30.20	Peak
4922.750	48.12	33.36	7.74	35.34	53.88	74.00	20.12	Peak
4922.750	41.41	33.36	7.74	35.34	47.17	54.00	6.83	Average
6797.000	37.95	35.31	9.09	35.46	46.89	74.00	27.11	Peak
8545.875	37.92	38.20	10.49	35.60	51.00	74.00	23.00	Peak
9937.750	38.49	38.40	11.40	35.32	52.97	74.00	21.03	Peak
17651.500	35.66	46.61	15.78	33.10	64.94	74.00	9.06	Peak
17651.500	19.37	46.61	15.78	33.10	48.65	54.00	5.35	Average



Mode: 802.11b CH2462MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3282.250	46.49	31.29	6.15	36.17	47.76	74.00	26.24	Peak
4922.750	53.40	33.36	7.74	35.34	59.16	74.00	14.84	Peak
4922.750	44.84	33.36	7.74	35.34	50.60	54.00	3.40	Average
7190.125	38.33	36.08	9.46	35.52	48.36	74.00	25.64	Peak
8509.750	38.38	38.20	10.48	35.60	51.46	74.00	22.54	Peak
9848.500	38.61	38.20	11.33	35.34	52.80	74.00	21.20	Peak
17630.250	35.48	46.48	15.75	33.11	64.60	74.00	9.40	Peak
17630.250	19.15	46.48	15.75	33.11	48.27	54.00	5.73	Average



Mode: 802.11g CH2437MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3188.750	46.93	31.06	6.06	36.22	47.83	74.00	26.17	Peak
4876.000	48.46	33.36	7.69	35.37	54.14	74.00	19.86	Peak
4876.000	40.55	33.36	7.69	35.37	46.23	54.00	7.77	Average
6586.625	39.31	34.77	8.92	35.42	47.59	74.00	26.41	Peak
7311.250	40.88	36.67	9.60	35.53	51.61	74.00	22.39	Peak
9748.625	38.93	38.10	11.25	35.37	52.91	74.00	21.09	Peak
17757.750	35.69	47.02	15.93	33.07	65.57	74.00	8.43	Peak
17757.750	18.87	47.02	15.93	33.07	48.75	54.00	5.25	Average



Mode: 802.11g CH2437MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
4873.875	51.42	33.34	7.69	35.37	57.08	74.00	16.92	Peak
4873.875	43.44	33.34	7.69	35.37	49.11	54.00	4.89	Average
7319.750	44.07	36.72	9.60	35.53	54.86	74.00	19.14	Peak
7319.750	32.61	36.72	9.60	35.53	43.40	54.00	10.60	Average
9746.500	39.71	38.10	11.25	35.37	53.68	74.00	20.32	Peak
9746.500	31.57	38.10	11.25	35.37	45.55	54.00	8.45	Average
17766.250	34.57	47.03	15.95	33.07	64.48	74.00	9.52	Peak
17766.250	18.46	47.03	15.95	33.07	48.37	54.00	5.63	Average



Mode: 802.11n20 CH2437MHz



Polarization at Horizontal



Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3190.875	48.63	31.06	6.06	36.21	49.54	74.00	24.46	Peak
4871.750	47.66	33.33	7.69	35.37	53.31	74.00	20.69	Peak
4871.750	39.57	33.33	7.69	35.37	45.21	54.00	8.79	Average
6182.875	38.68	34.53	8.58	35.34	46.45	74.00	27.55	Peak
8201.625	37.99	37.70	10.38	35.60	50.47	74.00	23.53	Peak
9529.750	38.57	38.28	11.08	35.44	52.49	74.00	21.51	Peak
17721.630	34.87	46.94	15.88	33.08	64.61	74.00	9.39	Peak
17721.630	18.69	46.94	15.88	33.08	48.43	54.00	5.57	Average

Mode: 802.11n20 CH2437MHz





Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
4873.875	52.29	33.34	7.69	35.37	57.96	74.00	16.04	Peak
4873.875	44.53	33.34	7.69	35.37	50.19	54.00	3.81	Average
7319.750	43.53	36.72	9.60	35.53	54.32	74.00	19.68	Peak
7319.750	35.55	36.72	9.60	35.53	46.34	54.00	7.66	Average
9748.625	41.16	38.10	11.25	35.37	55.14	74.00	18.86	Peak
9748.625	33.22	38.10	11.25	35.37	47.20	54.00	6.80	Average
17745.000	35.22	46.99	15.92	33.07	65.05	74.00	8.95	Peak
17745.000	18.52	46.99	15.92	33.07	48.35	54.00	5.65	Average

Mode: 802.11n40 CH2437MHz**Polarization at Horizontal**


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3526.625	42.04	31.55	6.36	36.08	43.88	74.00	30.12	Peak
4873.875	44.11	33.34	7.69	35.37	49.77	74.00	24.23	Peak
6178.625	38.96	34.51	8.58	35.34	46.71	74.00	27.29	Peak
7370.750	38.72	36.90	9.66	35.54	49.74	74.00	24.26	Peak
8796.625	38.13	37.90	10.57	35.60	51.00	74.00	23.00	Peak
9880.375	37.71	38.32	11.36	35.33	52.05	74.00	21.95	Peak
17715.250	34.79	46.93	15.87	33.08	64.50	74.00	9.50	Peak
17715.250	18.48	46.93	15.87	33.08	48.20	54.00	5.80	Average

Mode: 802.11n40 CH2437MHz**Polarization at Vertical**

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
3248.250	46.11	31.10	6.11	36.19	47.14	74.00	26.86	Peak
4895.125	47.48	33.47	7.71	35.36	53.30	74.00	20.70	Peak
4895.125	39.55	33.47	7.71	35.36	45.37	54.00	8.63	Average
6204.125	39.95	34.61	8.60	35.34	47.82	74.00	26.18	Peak
8033.750	37.80	37.20	10.32	35.60	49.72	74.00	24.28	Peak
9748.625	38.57	38.10	11.25	35.37	52.55	74.00	21.45	Peak
17772.630	34.19	47.05	15.96	33.07	64.12	74.00	9.88	Peak
17772.630	18.42	47.05	15.96	33.07	48.35	54.00	5.65	Average


Band-Edge and Restricted bands:

Test Date:	2024.07.03	Temp./Hum.:	22°C/51%RH	Test By:	Jarey
------------	------------	-------------	------------	----------	-------

Mode: 802.11b CH2412MHz

Polarization at Horizontal


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2365.445	55.40	28.46	5.37	36.89	52.34	74.00	21.66	Peak
2390.000	54.23	28.56	5.39	36.86	51.32	74.00	22.68	Peak

Mode: 802.11b CH2412MHz

Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2368.240	42.82	28.47	5.37	36.88	39.78	54.00	14.22	Average
2390.000	42.25	28.56	5.39	36.86	39.33	54.00	14.67	Average


Mode: 802.11b CH2412MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2345.685	55.07	28.37	5.35	36.91	51.88	74.00	22.12	Peak
2390.000	54.11	28.56	5.39	36.86	51.20	74.00	22.80	Peak


Mode: 802.11b CH2412MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2374.545	42.45	28.50	5.37	36.88	39.45	54.00	14.55	Average
2390.000	42.13	28.56	5.39	36.86	39.22	54.00	14.78	Average


Mode: 802.11b CH2462MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	53.33	28.63	5.47	36.77	50.67	74.00	23.33	Peak
2495.650	55.13	28.68	5.48	36.75	52.54	74.00	21.46	Peak


Mode: 802.11b CH2462MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	42.12	28.63	5.47	36.77	39.45	54.00	14.55	Average
2495.830	42.32	28.68	5.48	36.75	39.73	54.00	14.27	Average


Mode: 802.11b CH2462MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	53.06	28.63	5.47	36.77	50.40	74.00	23.60	Peak
2485.270	55.30	28.64	5.47	36.76	52.65	74.00	21.35	Peak


Mode: 802.11b CH2462MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	41.71	28.63	5.47	36.77	39.05	54.00	14.95	Average
2495.560	42.10	28.68	5.48	36.75	39.51	54.00	14.49	Average


Mode: 802.11g CH2412MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2379.095	58.20	28.52	5.38	36.87	55.23	74.00	18.77	Peak
2390.000	62.46	28.56	5.39	36.86	59.54	74.00	14.46	Peak


Mode: 802.11g CH2412MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2363.170	42.73	28.45	5.36	36.89	39.65	54.00	14.35	Average
2390.000	46.36	28.56	5.39	36.86	43.45	54.00	10.55	Average


Mode: 802.11g CH2412MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2379.550	58.26	28.52	5.38	36.87	55.29	74.00	18.71	Peak
2390.000	65.89	28.56	5.39	36.86	62.98	74.00	11.02	Peak


Mode: 802.11g CH2412MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2379.550	43.90	28.52	5.38	36.87	40.92	54.00	13.08	Average
2390.000	48.52	28.56	5.39	36.86	45.61	54.00	8.39	Average


Mode: 802.11g CH2462MHz



Polarization at Horizontal


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	60.74	28.63	5.47	36.77	58.07	74.00	15.93	Peak
2489.620	57.33	28.66	5.47	36.76	54.70	74.00	19.30	Peak

Mode: 802.11g CH2462MHz




Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	44.33	28.63	5.47	36.77	41.67	54.00	12.33	Average
2490.010	42.81	28.66	5.47	36.76	40.18	54.00	13.82	Average

Mode: 802.11g CH2462MHz

Polarization at Vertical


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	65.06	28.63	5.47	36.77	62.40	74.00	11.60	Peak
2488.840	60.93	28.66	5.47	36.76	58.30	74.00	15.70	Peak

Mode: 802.11g CH2462MHz

Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	46.82	28.63	5.47	36.77	44.16	54.00	9.84	Average
2488.480	44.36	28.65	5.47	36.76	41.73	54.00	12.27	Average


Mode: 802.11n20 CH2412MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2350.820	55.67	28.40	5.35	36.90	52.53	74.00	21.47	Peak
2390.000	55.99	28.56	5.39	36.86	53.08	74.00	20.92	Peak


Mode: 802.11n20 CH2412MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2377.275	42.79	28.51	5.38	36.87	39.80	54.00	14.20	Average
2390.000	43.79	28.56	5.39	36.86	40.88	54.00	13.12	Average


Mode: 802.11n20 CH2412MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2379.355	55.77	28.52	5.38	36.87	52.79	74.00	21.21	Peak
2390.000	62.54	28.56	5.39	36.86	59.63	74.00	14.37	Peak


Mode: 802.11n20 CH2412MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2379.485	43.53	28.52	5.38	36.87	40.55	54.00	13.45	Average
2390.000	48.11	28.56	5.39	36.86	45.20	54.00	8.80	Average


Mode: 802.11n20 CH2462MHz



Polarization at Horizontal


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	53.73	28.63	5.47	36.77	51.06	74.00	22.94	Peak
2491.390	54.70	28.67	5.48	36.76	52.08	74.00	21.92	Peak

Mode: 802.11n20 CH2462MHz




Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	43.48	28.63	5.47	36.77	40.82	54.00	13.18	Average
2489.800	42.65	28.66	5.47	36.76	40.02	54.00	13.98	Average

Mode: 802.11n20 CH2462MHz

Polarization at Vertical


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	65.01	28.63	5.47	36.77	62.34	74.00	11.66	Peak
2489.020	59.83	28.66	5.47	36.76	57.20	74.00	16.80	Peak

Mode: 802.11n20 CH2462MHz

Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	46.71	28.63	5.47	36.77	44.04	54.00	9.96	Average
2488.750	44.25	28.66	5.47	36.76	41.62	54.00	12.38	Average


Mode: 802.11n40 CH2422MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2387.155	68.35	28.55	5.39	36.86	65.42	74.00	8.58	Peak
2390.000	64.54	28.56	5.39	36.86	61.63	74.00	12.37	Peak


Mode: 802.11n40 CH2422MHz



Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2379.810	46.51	28.52	5.38	36.87	43.53	54.00	10.47	Average
2390.000	48.81	28.56	5.39	36.86	45.89	54.00	8.11	Average


Mode: 802.11n40 CH2422MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2379.355	55.27	28.52	5.38	36.87	52.29	74.00	21.71	Peak
2390.000	58.10	28.56	5.39	36.86	55.19	74.00	18.81	Peak


Mode: 802.11n40 CH2422MHz



Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2370.190	43.89	28.48	5.37	36.88	40.86	54.00	13.14	Average
2390.000	44.32	28.56	5.39	36.86	41.41	54.00	12.59	Average


Mode: 802.11n40 CH2452MHz



Polarization at Horizontal


Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	62.79	28.63	5.47	36.77	60.13	74.00	13.87	Peak
2489.740	63.42	28.66	5.47	36.76	60.80	74.00	13.20	Peak

Mode: 802.11n40 CH2452MHz




Polarization at Horizontal

Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
2483.500	47.77	28.63	5.47	36.77	45.11	54.00	8.89	Average
2489.590	47.18	28.66	5.47	36.76	44.55	54.00	9.45	Average

Mode: 802.11n40 CH2452MHz

Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μ V)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μ V/m)	Limits dB (μ V/m)	Margin (dB)	Remark
2483.500	57.59	28.63	5.47	36.77	54.93	74.00	19.07	Peak
2488.660	56.58	28.65	5.47	36.76	53.95	74.00	20.05	Peak

Mode: 802.11n40 CH2452MHz

Polarization at Vertical

Frequency (MHz)	Meter Reading dB (μ V)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μ V/m)	Limits dB (μ V/m)	Margin (dB)	Remark
2483.500	45.61	28.63	5.47	36.77	42.95	54.00	11.05	Average
2488.600	44.41	28.65	5.47	36.76	41.77	54.00	12.23	Average

5 99% OCCUPIED BANDWIDTH MEASUREMENT

5.1 Test Equipment

The following test equipment was used during the Emission Bandwidth measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2023.08.09	1 Year
2.	RF Cable	Mini-Circuits	FLC-3FT-SM SM+	22022838	2023.08.09	1 Year
3.	20 dB Attenuator	Mini-Circuits	BW-S20W2+	001	2023.09.21	1 Year

5.2 Block Diagram of Test Setup



5.3 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

5.4 Test Procedure

The transmitter output was connected to the spectrum analyzer. The bandwidth of 99% power bandwidth was measure by spectrum analyzer with settings: Span = between 1.5 times and 5.0 times of the OBW, RBW = 1% to 5% of the OBW, VBW $\geq 3 \times$ RBW, Detector = Peak, Trace = Max Hold. Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

The test procedure is defined in ANSI C63.10-2013 (the 6.9.3 Measurement Procedure “Occupied bandwidth—power bandwidth (99%) measurement procedure” was used).

5.5 Test Results

PASSED.

All the test results are attached in next pages.

(Test Date: 2024.07.05-08 Temperature: 23°C Humidity: 51 %)

Mode	Channel	Frequency (MHz)	99% Bandwidth (MHz)
802.11b	1	2412	13.066
	6	2437	13.057
	11	2462	13.053
802.11g	1	2412	16.471
	6	2437	16.431
	11	2462	16.457
802.11n20	1	2412	17.015
	6	2437	17.037
	11	2462	17.017
802.11n40	3	2422	32.433
	6	2437	32.41
	9	2452	32.42

802.11b

CH2412



CH2437



CH2462



802.11g


CH2412



CH2437



CH2462



802.11n20

CH2412



CH2437



CH2462



802.11n40

CH2422



CH2437



CH2452



6 6 dB BANDWIDTH MEASUREMENT

6.1 Test Equipment

The following test equipment was used during the Emission Bandwidth measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2023.08.09	1 Year
2.	RF Cable	Mini-Circuits	FLC-3FT-SM SM+	22022838	2023.08.09	1 Year
3.	20 dB Attenuator	Mini-Circuits	BW-S20W2+	001	2023.09.21	1 Year

6.2 Block Diagram of Test Setup

The Same as Section. 5.2.

6.3 Specification Limits (§15.247(a)(2))

The minimum 6 dB bandwidth shall be at least 500 kHz.

6.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

6.5 Test Procedure

The transmitter output was connected to the spectrum analyzer. The bandwidth of the fundamental frequency was measure by spectrum analyzer with settings: RBW = 100kHz, VBW $\geq 3 \times$ RBW.

The 6 dB bandwidth is defined as the total spectrum the power of which is lower than peak power minus 6 dB .

The test procedure is defined in ANSI C63.10-2013 (the 11.8.2 Measurement Procedure “Option 2” was used).

6.6 Test Results

PASSED.

All the test results are attached in next pages.

(Test Date: 2024.07.05 Temperature: 23°C Humidity: 51 %)

Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit
802.11b	1	2412	9.141	500 kHz
	6	2437	9.145	500 kHz
	11	2462	9.12	500 kHz
802.11g	1	2412	15.86	500 kHz
	6	2437	15.85	500 kHz
	11	2462	15.85	500 kHz
802.11n20	1	2412	15.87	500 kHz
	6	2437	15.88	500 kHz
	11	2462	15.86	500 kHz
802.11n40	3	2422	30.16	500 kHz
	6	2437	30.16	500 kHz
	9	2452	30.15	500 kHz

802.11b

CH2412



CH2437




CH2462



802.11g

CH2412



CH2437



CH2462



802.11n20

CH2412



CH2437



CH2462



802.11n40

CH2422



CH2437



CH2452



7 MAXIMUM OUTPUT POWER MEASUREMENT

7.1 Test Equipment

The following test equipment was used during the maximum peak output power measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2023.08.09	1 Year
2.	RF Cable	Mini-Circuits	FLC-3FT-SM SM+	22022838	2023.08.09	1 Year
3.	20 dB Attenuator	Mini-Circuits	BW-S20W2+	001	2023.09.21	1 Year

7.2 Block Diagram of Test Setup

The Same as Section. 5.2.

7.3 Specification Limits ((§15.247(b)(3))

The Limits of maximum Peak Output Power for digital modulation in 2400-2483.5 MHz is: 1 Watt. (30 dBm)

7.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

7.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

Method AVGSA-1 uses trace averaging with the EUT transmitting at full power throughout each sweep.

The procedure for this method is as follows:

- Set span to at least 1.5 times the OBW.
- Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto.
- Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at the maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no OFF intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.”
- Trace average at least 100 traces in power averaging (rms) mode.
- Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power

function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

The test procedure is defined in ANSI C63.10-2013 (11.9.2.2.2 Measurement Procedure “ Method AVGSA-1” was used).

7.6 Test Results

PASSED.


All the test results are listed below.

(Test Date: 2024.07.05-08 Temperature: 23°C Humidity: 51 %)


Mode	Channel	Frequency (MHz)	Maximum conducted (average) Output Power (dBm)	Limit
802.11b	1	2412	14.37	30 dBm
	6	2437	14.59	30 dBm
	11	2462	14.19	30 dBm
802.11g	1	2412	16.16	30 dBm
	6	2437	16.2	30 dBm
	11	2462	16.12	30 dBm
802.11n20	1	2412	15.16	30 dBm
	6	2437	15.37	30 dBm
	11	2462	15.23	30 dBm
802.11n40	3	2422	14.51	30 dBm
	6	2437	14.72	30 dBm
	9	2452	14.63	30 dBm

802.11b


CH2412



CH2437




CH2462




802.11g


CH2412



CH2437




CH2462




802.11n20


CH2412



CH2437




CH2462




802.11n40


CH2422



CH2437



CH2452



8 EMISSION LIMITATIONS MEASUREMENT

8.1 Test Equipment

The following test equipment was used during the emission limitations test:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2023.08.09	1 Year
2.	RF Cable	Mini-Circuits	FLC-3FT-SM SM+	22022838	2023.08.09	1 Year
3.	20 dB Attenuator	Mini-Circuits	BW-S20W2+	001	2023.09.21	1 Year

8.2 Block Diagram of Test Setup

The Same as Section. 5.2.

8.3 Specification Limits (§15.247(d))

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). (※This test result attaching to Section. 3.7)

8.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

8.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

Establish a reference level by using the following procedure:

- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 times the DTS bandwidth.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to

establish the reference level.

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

Scan up through 10th harmonic.

The test procedure is defined in ANSI C63.10-2013 (11.11.2 Reference level measurement and 11.11.3 Emission level measurement was used).

8.6 Test Results

PASSED.

The test data was attached in the next pages.

(Test Date: 2024.07.05-08 Temperature: 23°C Humidity: 51 %)

Mode	Channel	Frequency (MHz)	Data Page
802.11b	1	2412	P71
	6	2437	P72
	11	2462	P73
802.11g	1	2412	P74
	6	2437	P75
	11	2462	P76
802.11n20	1	2412	P77
	6	2437	P78
	11	2462	P79
802.11n40	3	2422	P80
	6	2437	P81
	9	2452	P82


802.11b

CH2412


Reference Level



Lower Edge



Emission Level





802.11b

CH2437

Reference Level



Emission Level




802.11b

CH2462



Reference Level



Higher Edge




Emission Level




802.11g

CH2412



Reference Level



Lower Edge




Emission Level





802.11g

CH2437

Reference Level



Emission Level




802.11g

CH2462



Reference Level



Higher Edge



Emission Level




802.11n20

CH2412



Reference Level



Lower Edge




Emission Level





802.11n20

CH2437

Reference Level




Emission Level




802.11n20

CH2462



Reference Level



Higher Edge




Emission Level




802.11n40

CH2422



Reference Level



Higher Edge



Emission Level




802.11n40

CH2437

Reference Level



Emission Level



802.11n40

CH2452



Reference Level



Higher Edge



Emission Level



9 POWER SPECTRAL DENSITY MEASUREMENT

9.1 Test Equipment

The following test equipment was used during the power spectral density measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2023.08.09	1 Year
2.	RF Cable	Mini-Circuits	FLC-3FT-SM SM+	22022838	2023.08.09	1 Year
3.	20 dB Attenuator	Mini-Circuits	BW-S20W2+	001	2023.09.21	1 Year

9.2 Block Diagram of Test Setup

The Same as section 5.2.

9.3 Specification Limits (§15.247(e))

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band. The same method of determining the conducted output power shall be used to determine the power spectral density.

9.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

9.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

Method AVGPSD-1 uses trace averaging with EUT transmitting at full power throughout each sweep.

The following procedure may be used when the maximum (average) conducted output power was used to determine compliance to the fundamental output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has a power averaging (rms) detector, then it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously ($D \geq 98\%$), or else sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter OFF time to be considered):

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to at least 1.5 times the OBW.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = power averaging (rms) or sample detector (when rms not available).
- Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
- Sweep time = auto couple.
- Employ trace averaging (rms) mode over a minimum of 100 traces.

- i) Use the peak marker function to determine the maximum amplitude level.
- j) If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

The test procedure is defined in ANSI C63.10-2013 (11.10.5 Measurement Procedure “Method AVGPSD-1” was used).

9.6 Test Results

PASSED.


All the test results are attached in next pages.

(Test Date: 2024.07.05 Temperature: 23°C Humidity: 51 %)


Mode	Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limit
802.11b	1	2412	-12.693	8 dBm
	6	2437	-12.589	8 dBm
	11	2462	-11.956	8 dBm
802.11g	1	2412	-12.925	8 dBm
	6	2437	-12.436	8 dBm
	11	2462	-12.435	8 dBm
802.11n20	1	2412	-11.255	8 dBm
	6	2437	-11.542	8 dBm
	11	2462	-11.561	8 dBm
802.11n40	3	2422	-15.114	8 dBm
	6	2437	-15.128	8 dBm
	9	2452	-14.908	8 dBm

802.11b


CH2412



CH2437




CH2462




802.11g


CH2412



CH2437



CH2462



802.11n20

CH2412



CH2437




CH2462




802.11n40


CH2422



CH2437



CH2452



10 ANTENNA REQUIREMENT

10.1 Specification Limits (§15.203)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 Result

According to KDB 353028 D1, the following describes the three ways that can be used to demonstrate compliance to Section 15.203:

- a) Antenna permanently attached.
- b) Unique (non-standard) antenna connector.
- c) Professional installation.

For this product, the antenna is:

- ☒ Antenna permanently attached
- ☐ Unique (non-standard) antenna connector
- ☐ Professional installation
- ☐ not meet any of ways list above

that

- ☒ compliant
- ☐ not compliant

with the requirement of Section 15.203.

11 MEASUREMENT UNCERTAINTY LIST

The measurement uncertainty was estimated for test on the EUT according to CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage of K=2.

The uncertainties value is not used in determining the PASS/FAIL results.

Test Items/Facilities	Frequency/Equipment/Unit	Uncertainty
Conducted Emission No.1 Shielded Room	9kHz~150kHz	±3.1 dB
	150kHz~30MHz	±2.6 dB
Conducted Emission No.3 Shielded Room	9kHz~150kHz	±3.1 dB
	150kHz~30MHz	±2.6 dB
Radiated Emission	30MHz~200MHz, Horizontal	±3.8 dB
	30MHz~200MHz, Vertical	±4.1 dB
	200MHz~1000MHz, Horizontal	±3.6 dB
	200MHz~1000MHz, Vertical	±5.1 dB
	1GHz~6GHz	±5.3 dB
	6GHz~18GHz	±5.3 dB
	18GHz~40GHz	±3.5 dB
Output Power Test	50MHz~18GHz	0.77 dB
Power Density Test	9kHz~6GHz	1.08 dB
RF Frequency Test	9kHz~40GHz	6×10^{-4}
Bandwidth Test	9kHz~6GHz	1.5×10^{-3}
RF Radiated Power Test	30MHz~1000MHz	3.06 dB
Conducted Output Power Test	50MHz~18GHz	0.83 dB
AC Voltage(<10kHz) Test	120V~230V	0.04 %
DC Power Test	0V~30V	0.4 %
Temperature	-40°C~+100°C	0.52 °C
Humidity	30%~95%	2.6 %