



Prüfbericht - Nr.: Test Report No.	14008233 001	Seite 1 von 13 Page 1 of 13	
Auftraggeber: Applicant	IDT Technology Ltd. Block C, 9/F., Kaiser Estate, Phase 1 41 Man Yue Street Hunghom, Kowloon Hong Kong		
Gegenstand der Prüfung: Test item	Low Power Transmitter		
Bezeichnung: Identification	RTGR368NA	Serien-Nr.: Serial No.	Engineering sample
Wareneingangs-Nr.: Receipt No.	041220020	Eingangsdatum: Date of receipt	20.12.2004
Prüfart: Testing location	TÜV Rheinland Hong Kong Ltd. Unit 8, 25 th Floor, Skyline Tower, 39 Wang Kwong Road, Kowloon Bay Kowloon, Hong Kong Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong		
Prüfgrundlage: Test specification	FCC Part 15, Subpart C		
Prüfergebnis: Test Result	Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage. The above mentioned product was tested and passed .		
geprüft / tested by:	kontrolliert / reviewed by:		
02.03.2005 Prudence Poon		02.03.2005 Thomas Berns	
Datum Date	Name Name	Unterschrift Signature	Datum Date
Sonstiges: FCC ID NMTRTGR368NA-01			
Other Aspects			
Abkürzungen:	OK, Pass, P = entspricht Prüfgrundlage	Abbreviations:	OK, Pass, P = passed
	Fail, F = entspricht nicht Prüfgrundlage		Fail, F = failed
	N/A = nicht anwendbar		N/A = not applicable
	NT = nicht getestet		NT = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicate in extracts. This test report does not entitle to carry any safety mark on this or similar products.			

Test Summary

Radiated Emission of Carrier Frequency

Result: Pass

Spurious Radiated Emissions

Result: Pass

Bandwidth Measurement

Result: Pass

Contents

General Remarks	4
Complementary Materials.....	4
List of Test and Measurement Instruments.....	5
General Product Information	6
Product Function and Intended Use.....	6
Circuit Description	6
Ratings and System Details	6
Independent Operation Modes.....	7
Submitted Documents	7
Related Submittal(s) Grants	7
Test Set-up and Operation Mode.....	8
Principle of Configuration Selection	8
Test Operation and Test Software	8
Special Accessories and Auxiliary Equipment	8
Countermeasures to achieve EMC Compliance.....	8
Test Methodology	9
Radiated Emission	9
Field Strength Calculation.....	9
Test Results	10
Radiated Emission of Carrier Frequency Section 15.231(b).....	10
Spurious Radiated Emissions Section 15.231(b).....	11
Bandwidth Measurement Section 15.231(c).....	13

General Remarks

Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix 1: Test Results

Appendix 2: Test Setup

Appendix 3: EUT External Photo

Appendix 4: EUT Internal Photo

Appendix 5: FCCID Label, Block Diagram, Schematics and User manual.

List of Test and Measurement Instruments

Kind of Equipment	Manufacturer	Type	S/N
Test Receiver	Rohde & Schwarz	ESVS30	842807/009
Biconical Antenna	Rohde & Schwarz	HK116	841489/015
Log.-Periodic Antenna	Rohde & Schwarz	HL223	841516/017
Double Ridge Horn Antenna	EMCO	3115	9002-3351
Double Ridge Horn Antenna	EMCO	3115	9002-3347
Signal Generator	Rohde & Schwarz	SMY 01	844146/024
Signal Generator	Rohde & Schwarz	SMY 01	844146/023
Spectrum Analyzer	Rohde & Schwarz	FSP30	1093.4495K30

General Product Information

Product Function and Intended Use

The equipment under test (EUT) is a transmitter for a weather station operating at 433.92 MHz. The EUT sense the temperature and humidity level, then transmit this information to the associated weather station.

A transmitter transmits signal for every 39 seconds, and the signal on period is about 0.39ms. It activated automatically shall cease transmission within 2 seconds after activation. Hence it operates 92 times per hour.

FCC ID NMTRTGR368NA-01

Model	Product description
RTGR368NA	Remote Thermo-Hygrometer Sensor

Circuit Description

This unit is composed of Temperature (H5) and Humidity (H6) detecting section, RCC receiving section (U1) and transmitter section.

Transmitter is made of Q5 as a Colpitts oscillator, where X1, the 433.92MHz SAW resonator provides the centre frequency/. L2, L4, C16, C17 and C18 perform as the matching network. R29, R30 and R31 perform as the attenuator.

Ratings and System Details

	Transmitter
Operated Frequency	: 433.92 MHz
Frequency deviation of Crystal	: $\pm 75\text{KHz}$
Number of channels	: 5
Type of antenna	: Integral antenna
Power supply	: Battery operated 3.0V
Ports	: none
Protection Class	: III
Equipment Class	: B

Independent Operation Modes

The basic operation modes are:

- Reset Button : Press to reset all value to default values.
- Channel selection.
- °C/F display format selection.
- Search button: Press to enable the auto-search for RF signal.

For further information refer to User Manual

Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- FCC ID label

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

Countermeasures to achieve EMC Compliance

The test sample, which has been tested, contained the noise suppression parts as described in the Circuit Diagram or the Technical Construction File. No additional measures were employed to achieve compliance.

Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in section 7.1.1 and 7.1.2 of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

$$\text{System Factor} = CF + FA - PA.$$

Where FS = Peak Value of Field Strength in dBuV/m at 3 meters.

R = Peak Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Average value of FS = FS –Average factor.

Average Factor = 20 log duty cycle.

Test Results

Radiated Emission of Carrier Frequency

Section 15.231(b)

RESULT:
Pass

Test Specification : FCC Part 15 Section 15.231(b1 and b2)
 Test Method : ANSI 63.4-2003
 Measurement Location : Semi Anechoic Chamber
 Measurement Distance : 3m
 Detector Function : Peak
 Measurement BW : 100 kHz
 Supply Voltage : DC 3.0V
 Channel under test : Channel 1 with worst case emission.

Polarization: Vertical

Value	Frequency	System Factor	Measured Field strength at 3m (pk)	Average Factor	Net Field strength at 3m	Limit	Delta to Limit
	(MHz)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
Peak	433.95	18.1	86.4	-	86.4	100.8	-14.4
Average	433.95	18.1	86.4	-7.0	79.4	80.8	-1.4

Polarization: Horizontal

Value	Frequency	System Factor	Measured Field strength at 3m (pk)	Average Factor	Net Field strength at 3m	Limit	Delta to Limit
	(MHz)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
Peak	433.95	18.1	84.2	-	84.2	100.8	-16.60
Average	433.95	18.1	84.2	-7.0	77.2	80.8	-3.60

Remark; The calculation of average factor is shown in appendix 1 page 4.

Limit
Section 15.231(b2)

Frequency within the band (MHz)	Peak Emission		Average Emission	
	(microvolt/meter)	dBuV/m	(microvolt/meter)	dBuV/m
433.95	109,979	100.8	10,997	80.8

According to section 15.35(b), When average radiated emission measurements are specified, including emission measurement below 1000MHz, there also is limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated.

Spurious Radiated Emissions**Section 15.231(b)****RESULT:****Pass**

Test Specification : FCC Part 15 Section 15.231(b1 and b3)
 Test Method : ANSI 63.4-2003
 Measurement Location : Semi Anechoic Chamber
 Measurement Distance : 3m
 Detector Function : Peak
 Measurement BW : 100 kHz
 Supply Voltage : DC 3.0V
 Measuring Frequency Range : 30-4500MHz

Polarization: Vertical

Frequency (MHz)	Reading (Pk) (dBuV/m)	Antenna Factor (dBuV/m)	System Factor (dB)	Field strength at 3m (pk) (dBuV/m)	Average Factor (dB)	Field strength at 3m (av) (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
867.81	20.93	22.20	2.67	45.80	-7.0	38.80	60.80	-22.00
*1301.85	37.40	24.90	-33.70	28.60	-7.0	21.60	54.00	-32.40
1735.58	32.41	26.50	-33.30	25.61	-7.0	18.61	60.80	-42.19
2169.76	30.69	27.80	-32.56	25.93	-7.0	18.93	60.80	-41.87
2603.48	29.17	28.88	-31.18	26.87	-7.0	19.87	60.80	-40.93
3037.68	33.96	30.00	-29.73	34.23	-7.0	27.23	60.80	-33.57
3471.62	31.93	31.20	-31.09	32.04	-7.0	25.04	60.80	-35.76
*3905.57	31.37	32.50	-30.35	33.52	-7.0	26.52	54.00	-27.48
4339.52	30.39	32.45	-29.91	32.93	-7.0	25.93	60.80	-34.87

Polarization: Horizontal

Frequency (MHz)	Reading (Pk) (dBuV/m)	Antenna Factor (dBuV/m)	System Factor (dB)	Field strength at 3m (pk) (dBuV/m)	Average Factor (dB)	Field strength at 3m (av) (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
867.81	20.23	22.20	2.67	45.10	-7.0	38.10	60.80	-22.70
*1301.85	35.31	24.90	-33.70	26.51	-7.0	19.51	54.00	-34.49
1735.58	32.19	26.50	-33.30	25.39	-7.0	18.39	60.80	-42.41
2169.76	29.96	27.80	-32.56	25.20	-7.0	18.20	60.80	-42.60
2603.71	29.61	28.88	-31.18	27.31	-7.0	20.31	60.80	-40.49
3037.68	35.00	30.00	-29.73	35.27	-7.0	28.27	60.80	-32.53
3471.62	32.28	31.20	-31.09	32.39	-7.0	25.39	60.80	-35.41
*3905.54	32.17	32.50	-30.35	34.32	-7.0	27.32	54.00	-26.68
4339.52	31.17	32.45	-29.91	33.71	-7.0	26.71	60.80	-34.09

Remark: ' * ' indicates the frequency of the emissions fall into the restricted band.

Limit**Section 15.231(b3)**

Frequency (MHz)	Field strength (microvolt/meter)	Field strength (dB μ V/m)	Measurement distance (meters)
433.950	1,099	$20 \cdot \log(1099) = 60.8$	3

Section 15.209

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

Limit for Radiated Emission under Section 15.209:

Frequency (MHz)	Field strength (microvolt/meter)	Field strength (dB μ V/m)	Measurement distance (meters)
30-88	100	$20 \cdot \log(100) = 40.0$	3
88-216	150	$20 \cdot \log(150) = 43.5$	3
216-960	200	$20 \cdot \log(200) = 46.0$	3
960-2500	500	$20 \cdot \log(500) = 54.0$	3

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.

Bandwidth Measurement

Section 15.231(c)

RESULT:

Pass

Test Specification	:	FCC Part 15 section 15.231(c)
Port of Testing	:	Antenna port
Detector Function	:	Peak
Supply Voltage	:	DC 3.0V

Refer to the data graph, the 20dB points at lower edge and at higher edge are 8.8KHz and 7.2KHz respectively apart from the centre modulated carrier, the bandwidth of the emission is 0.003 % of the centre frequency. Therefore, the EUT meets the requirement of section 15.231(c).

For test results refer to Appendix 1, page 1.

Limit

Section 15.231(c)

The bandwidth of the emission shall be no wider than 0.25% if the center frequency for devices operating above 70MHz and below 900MHz.