

FCC RF Exposure

EUT Description: Smart Watch

Model No.: VT3 Lite, DT3 Lite, VT4, VT4 Plus, VT4 Pro, VT4+, VT4 Lite, VT4 Mini, VT5, VT6, VT7, VT8, VT9, DT4, DT4 Plus, DT4 Pro, DT4 +, DT4 Lite, DT4 Mini, CS201C

FCC ID: 2AQ3A-VT3LITE

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max power of channel, including tune - up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

Result = $P/D^2 \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn - up power in mw

D = Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

2.4G

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit	SAR Test Exclusion
BLE	-1.893	-2 ± 1	-1/ 0.79	5	0.24882	3.0	Pass
Note: PK Output power= conducted power. Conducted power see the test report HK2011173574-E , antenna gain=2.93dBi							

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.24882 which is ≤ 3 , RF Exposure testing is not required.

Note: Exclusion Thresholds Results = $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

f(GHz) is the RF channel transmit frequency in GHz

Distance = 5mm