

# 1 RF Exposure Report

## 1.1 RF Exposure Measurement

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

## 1.2 RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b) showed in Table 1.

Table 1: Limits for Maximum Permissible Exposure (MPE) as per FCC

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

F or  $f$  = Frequency in MHz

## RF Exposure

Reference Test Report No:  
ULR-TC568821300000017F

Seite 2 von 2  
Page 2 of 2

### 1.2.1 Friss Formula

Friss Transmission Formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

### 1.2.2 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual.

Note:  $\pm 1$  dB tune up value is considered for MPE calculation.

Protocol: LTE & GSM

## Test Results

Manufacturer has declared the tune-up value as  $\pm 1$  dB is considered in MPE calculation.

**Antenna type:** Wide Band Antenna(2dBi for above 1GHz Bands, -1.95dBi for below 1GHz Bands)

Cellular protocol	Band	Cell Bandwidth (MHz)	Measured Frequency (MHz)	Maximum measured RF output power at antenna terminal (dBm)	Tune-up tolerance (dB)	Antenna Gain in Linear Scale	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
LTE	2	10	1855	23.21	1	1.5849	0.0831	1.0
	4	10	1750	22.92	1	1.5849	0.0778	1.0
	12	10	711	23.88	1	0.6382	0.0391	0.474
	13	5	799.5	22.96	1	0.6382	0.0316	0.533
	26	10	844	23.98	1	0.6382	0.0400	0.563

Cellular protocol	Band	Measured Frequency (MHz)	Maximum measured RF output power at antenna terminal (dBm)	Tune-up tolerance (dB)	Antenna Gain in Linear Scale	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
GSM	850	824.2	32.46	1	0.6382	0.3548	0.549
	1900	1850.2	30.31	1	1.5849	0.33863	1.0