

## PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.pctest.com



# **HEARING AID COMPATIBILITY**

**Applicant Name:** 

LG Electronics MobileComm U.S.A. Inc. 1000 Sylvan Avenue Englewood Cliffs, NJ 07632 **United States** 

**Date of Testing:** 03/14/2018 - 03/29/2018 Test Site/Location: PCTEST Lab, Columbia, MD, USA

**Test Report Serial No.:** 1M1802260032-12-R5.ZNF

FCC ID: ZNFG710VM

APPLICANT: LG ELECTRONICS MOBILECOMM U.S.A. INC.

Scope of Test: Audio Band Magnetic Testing (T-Coil)

Application Type: Certification CFR §20.19(b) FCC Rule Part(s): **HAC Standard:** ANSI C63.19-2011

285076 D01 HAC Guidance v05

285076 D02 T-Coil testing for CMRS IP v03

**DUT Type:** Portable Handset Model: LM-G710VM

Additional Model(s): LMG710VM, G710VM, LG-G710PM, LGG710PM, G710PM, LG-

> G710ULM, LGG710ULM, G710ULM Pre-Production Sample [S/N: 07215]

C63.19-2011 HAC Category: T3 (SIGNAL TO NOISE CATEGORY)

Note: This revised Test Report (S/N: 1M1802260032-12-R5.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and has been tested in accordance with the specified measurement procedures. Test results reported herein relate only to the item(s) tested. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. North American Bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Test Device Serial No.:





FCC ID: ZNFG710VM	PCTEST TELEVISION OF THE	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 1 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 10107

# TABLE OF CONTENTS

1.	INTRODUCTION	3
2.	DUT DESCRIPTION	4
3.	ANSI C63.19-2011 PERFORMANCE CATEGORIES	6
4.	METHOD OF MEASUREMENT	8
5.	VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION	18
6.	VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION	22
7.	OTT VOIP TEST SYSTEM AND DUT CONFIGURATION	25
8.	FCC 3G MEASUREMENTS	28
9.	T-COIL TEST SUMMARY	30
10.	MEASUREMENT UNCERTAINTY	43
11.	EQUIPMENT LIST	44
12.	TEST DATA	45
13.	CALIBRATION CERTIFICATES	75
14.	CONCLUSION	82
15.	REFERENCES	83
16.	TEST SETUP PHOTOGRAPHS	85

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 2 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 2 01 01

#### 1. INTRODUCTION

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-86581 to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

## Compatibility Tests Involved:

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index

The hearing aid must be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.



Figure 1-1 Hearing Aid in-vitu

<sup>&</sup>lt;sup>1</sup> FCC Rule & Order, WT Docket 01-309 RM-8658

FCC ID: ZNFG710VM	PETEST	HAC (T-COIL) TEST REPORT	(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 3 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 3 01 67

© 2018 PCTEST Engineering Laboratory, Inc.

**REV 3.2.M** 

# 2. DUT DESCRIPTION



FCC ID: ZNFG710VM

Applicant: LG Electronics MobileComm U.S.A. Inc.

1000 Sylvan Avenue

Englewood Cliffs, NJ 07632

**United States** 

Model: LM-G710VM

Additional Model(s): LMG710VM, G710VM, LG-G710PM, LGG710PM, G710PM,

LG-G710ULM, LGG710ULM, G710ULM

Serial Number: 07215 HW Version: Rev.B

SW Version: G710VM\_LAMPOR180129

Antenna: Internal Antenna
DUT Type: Portable Handset

#### I. LTE Band Selection

This device supports the following pair of LTE bands with similar frequencies: LTE B12 & B17, B2 & B25, B4 & B66. These pairs of LTE bands have the same target power and share the same transmission path. Since the supported frequency span for the smaller LTE bands are completely covered by the larger LTE bands, only the larger LTE bands (LTE B66, B25, and B12) were evaluated for hearing-aid compliance.

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 4 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 4 01 67

# **Table 2-1**ZNFG710VM HAC Air Interfaces

ZNFG/TOVM FIAC All IIItelfaces						
Air-Interface	Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Name of Voice Service	
	835	VO	Yes	Yes: WIFI or BT	CMRS Voice*	
CDMA	1900	VO	163	res. Wiri of Bi	CIVINS VOICE	
	EvDO	VD	Yes	Yes: WIFI or BT	Google Duo**	
	850	VO	Yes	Yes: WIFI or BT	CMRS Voice*	
GSM	1900	VO	163	res. Wiri Oi Bi	CIVINS VOICE	
	GPRS/EDGE	VD	Yes	Yes: WIFI or BT	Google Duo**	
	850					
UMTS	1700	VD	Yes	Yes: WIFI or BT	CMRS Voice*	
UIVITS	1900					
	HSPA	VD	Yes	Yes: WIFI or BT	Google Duo**	
	700 (B12)	VD	Yes	Yes Yes: WIFI or BT	VoLTE*, Google Duo**	
	700 (B17)					
	780 (B13)					
	850 (B5)					
LTE (FDD)	850 (B26)					
	1700 (B4)					
	1700 (B66)					
	1900 (B2)					
	1900 (B25)					
LTE (TDD)	2600 (B41)	VD	Yes	Yes: WIFI or BT	VoLTE*, Google Duo**	
	2450					
	5200 (U-NII 1)					
WIFI	5300 (U-NII 2A)	VD	Yes	Yes: CDMA, GSM, UMTS, or LTE	VoWIFI**, Google Duo**	
	5500 (U-NII 2C)					
	5800 (U-NII 3)					
BT	2450	DT	No	Yes: CDMA, GSM, UMTS, or LTE	N/A	
	Type Transport  /O = Voice Only  * Reference level in accordance with 7.4.2.1 of ANSI C63.19-2011 and July 2012 C63 VoLTE  Interpretation.				11 and July 2012 C63 VoLTE	

DT = Digital Data - Not intended for CMRS Service

VD = CMRS and IP Voice over Data Transport

Interpretation.

\*\* Reference level is -20dBm0 in accordance with FCC KDB 285076 D02

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 5 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 3 01 07

# 3. ANSI C63.19-2011 PERFORMANCE CATEGORIES

## I. MAGNETIC COUPLING

## **Axial and Radial Field Intensity**

All orientations of the magnetic field, in the axial and radial position along the measurement plane shall be  $\geq$  -18 dB(A/m) at 1 kHz in a 1/3 octave band filter per §8.3.1.

## **Frequency Response**

The frequency response of the axial component of the magnetic field shall follow the response curve specified in EIA RS-504-1983, over the frequency range 300 Hz – 3000 Hz per §8.3.2.




Figure 3-1
Magnetic field frequency response for Wireless Devices with an axial field ≤-15 dB(A/m) at 1 kHz




Figure 3-2
Magnetic Field frequency response for wireless devices with an axial field that exceeds
-15 dB(A/m) at 1 kHz

FCC ID: ZNFG710VM	PCTEST TELEVISION OF THE	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 6 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 6 01 67

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 01/11/2018

## **Signal Quality**

The table below provides the signal quality requirement for the intended audio magnetic signal from a wireless device. Only the RF immunity of the hearing aid is measured in T-coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. The only criterion that can be measured is the RF immunity in T-coil mode. This is measured using the same procedure as the audio coupling mode at the same levels.

The signal quality of the axial and radial components of the magnetic field was used to determine the T-coil mode category.

Catagony	Telephone RF Parameters		
Category	Wireless Device Signal Quality [(Signal + Noise)-to-noise ratio in dB]		
T1	0 to 10 dB		
T2	10 to 20 dB		
Т3	20 to 30 dB		
T4	> 30 dB		
Table 3-1  Magnetic Coupling Parameters			

Note: The FCC limit for SNNR is 20dB and the test data margins will indicate a margin from the FCC limit for compliance.

FCC ID: ZNFG710VM	PETEST	HAC (T-COIL) TEST REPORT	<u>்</u> டி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 7 of 97
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 7 of 87

# 4. METHOD OF MEASUREMENT

# I. Test Setup

The equipment was connected as shown in an acoustic/RF hemi-anechoic chamber:




Figure 4-1
Validation Setup with Helmholtz Coil




Figure 4-2 T-Coil Test Setup

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 8 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage o oi oi

## II. Scanning Mechanism

Manufacturer: TEM

Accuracy: ± 0.83 cm/meter

Minimum Step Size:

0.1 mm

Maximum speed
6.1 cm/sec

Line Voltage:
115 VAC

Line Frequency:
60 Hz

Material Composite: Delrin (Acetal)

Data Control: Parallel Port

Dynamic Range (X-Y-Z): 45 x 31.75 x 47 cm

Dimensions: 36" x 25" x 38" Operating Area: 36" x 49" x 55"

Reflections: < -20 dB (in anechoic chamber)




Figure 4-3 RF Near-Field Scanner

## III. ITU-T P.50 Artificial Voice

Manufacturer: ITU-T


Active Frequency 100 Hz – 8 kHz

Range:


Stimulus Type: Male and Female, no spaces

Single Sample Duration: 20.96 seconds

Activity Level: 100%



**Figure 4-4** Spectral Characteristic of full P.50



Temporal Characteristic of full P.50

FCC ID: ZNFG710VM	PETEST	HAC (T-COIL) TEST REPORT	(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 9 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 9 01 67

ABM1 Measurement Block Diagram:



ABM2 Measurement Block Diagram:



Figure 4-6 Magnetic Measurement Processing Steps

#### IV. **Test Procedure**

- 1. Ambient Noise Check per C63.19 §7.3.1
  - a. Ambient interference was monitored using a Real-Time Analyzer between 100-10,000 Hz with 1/3 octave filtering.
  - "A-weighting" and Half-Band Integration was applied to the measurements.
  - Since this measurement was measured in the same method as ABM2 measurements, this level was verified to be more than 10 dB below the lowest measurement signal (which is the highest ABM2 measurement for a T4 WD). Therefore the maximum noise level for a T4 WD with an ABM1 = -18 dBA/m is:

- 2. Measurement System Validation(See Figure 4-1)
  - The measurement system including the probe, pre-amplifier and acquisition system were validated as an entire system to ensure the reliability of test measurements.
  - **ABM1 Validation**

The magnetic field at the center of the Helmholtz coil is given by the equation (per C63.19 Annex D.10.1):

$$H_c = \frac{NI}{r\sqrt{1.25^3}} = \frac{N(\frac{V}{R})}{r\sqrt{1.25^3}}$$

Where  $H_c$  = magnetic field strength in amperes per meter N = number of turns per coil

For the Helmholtz Coil, N=20; r=0.08m; R=10.2Ω and using V=18mV:

$$H_c = \frac{20 \cdot (\frac{0.018}{10.2})}{0.08 \cdot \sqrt{1.25^3}} = 0.316A/m \approx -10dB(A/m)$$

Therefore a pure tone of 1kHz was applied into the coils such that 18mV was observed across the resistor. The voltmeter used for measurement was verified to be capable of measurements in the audio band range. This theoretically generates an expected field of -10 dB(A/m) in the center of the Helmholtz coil which was used to validate the probe measurement at -10dB(A/m). This was verified to be within ± 0.5 dB of the -10dB(A/m) value (see Page 41).

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 10 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 10 01 67

© 2018 PCTEST Engineering Laboratory, Inc.

c. Frequency Response Validation

The frequency response through the Helmholtz Coil was verified to be within 0.5 dB relative to 1kHz, between 300 – 3000 Hz using the P.50 signal as shown below:




Figure 4-7 Frequency Response Validation

## d. ABM2 Measurement Validation

WD noise measurements are filtered with A-weighting and Half-Band Integration over a frequency range of 100Hz – 10kHz to process ABM2 measurements. Below is the verification of the system processing A-weighting and Half-Band integration between system input to output within 0.5 dB of the theoretical result:

Table 4-1
ABM2 Frequency Response Validation

	HBI, A -	HBI, A -	
f (Hz)	Measured	Theoretical	dB Var.
	(dB re 1kHz)	(dB re 1kHz)	
100	-16.180	-16.170	-0.010
125	-13.257	-13.250	-0.007
160	-10.347	-10.340	-0.007
200	-8.017	-8.010	-0.007
250	-5.925	-5.920	-0.005
315	-4.045	-4.040	-0.005
400	-2.405	-2.400	-0.005
500	-1.212	-1.210	-0.002
630	-0.349	-0.350	0.001
800	0.071	0.070	0.001
1000	0.000	0.000	0.000
1250	-0.503	-0.500	-0.003
1600	-1.513	-1.510	-0.003
2000	-2.778	-2.780	0.002
2500	-4.316	-4.320	0.004
3150	-6.166	-6.170	0.004
4000	-8.322	-8.330	0.008
5000	-10.573	-10.590	0.017
6300	-13.178	-13.200	0.022
8000	-16.241	-16.270	0.029
10000	-19.495	-19.520	0.025

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	<b>(1)</b> LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 11 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 110167







Figure 4-8 **ABM2 Frequency Response Validation** 

The ABM2 result is a power sum from 100Hz to 10kHz with half-band integration and Aweighting. To verify the power sum measurement, a power sum over the full band was measured and verified to track with the source level (See Figure 4-9). Therefore the setup in this step was used to verify the power sum post-processing for ABM2 measurements. See below block diagram:



The power summed output results for a known input were compared to the multi-meter results to verify any deviation in the post-processing implemented with the power-sum.

Table 4-2 **ABM2 Power Sum Validation** 

WN Input (dBV)	Power Sum (dBV)	Multimeter-Full (dBV)	Dev (dB)
-60	-60.36	-60.2	0.16
-50	-50.19	-50.13	0.06
-40	-40.14	-40.03	0.11
-30	-30.13	-30.01	0.12
-20	-20.12	-20	0.12
-10	-10.14	-10	0.14

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 12 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 12 01 67

© 2018 PCTEST Engineering Laboratory, Inc.




Figure 4-10
ABM2 Power Sum Validation

- 3. Measurement Test Setup
  - a. Fine scan above the WD (TEM)
    - i. A multitone signal was applied to the handset such that the phone acoustic output was stable within 1dB over the probe settling time and with the acoustic output level at the C63.19 specified levels (below). The measurement step size was in 2 mm increments at a distance of 10 mm between the surface of the wireless device as shown below (note that in Figure 4-12, the grid is not to scale but merely a graphical representation of the coordinate system in use):




Figure 4-11 Measurement Distance




Figure 4-12 Measurement Grid

- ii. After scanning, the planar field maximum point was determined. The position of the probe was moved to this location to setup the test using the SoundCheck system.
- iii. These steps were repeated for all T-coil orientations (axial and radial) per Figure 4-15 after a T-coil orientation was fully measured with the SoundCheck system.
- b. Speech Signal Setup to Base Station Simulator
  - i. C63.19 Table 7-1 states audio reference input levels for various technologies:

Standard	Technology	Input Level (dBm0)
TIA/EIA/IS-2000	CDMA	-18
J-STD-007	GSM (217)	-16
T1/T1P1/3GPP	UMTS (WCDMA)	-16
iDEN <sup>TM</sup>	TDMA (22 and 11 Hz)	-18

FCC ID: ZNFG710VM	PCTEST TELEVISION OF THE	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 13 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 13 01 07

© 2018 PCTEST Engineering Laboratory, Inc.

- ii. See Section 5 and 6 for more information regarding CMW500 audio level settings for Voice Over LTE (VoLTE), and Voice Over WIFI (VoWIFI) testing.
- iii. See Section 7 for more information regarding audio level settings for Over-The-Top (OTT) Voice Over IP (VoIP) Testing.

## c. Real-Time Analyzer (RTA)

i. The Real-Time Analyzer was configured to analyze measurements using 1/3 Octave band weighted filtering.

## d. WD Radio Configuration Selection

i. The device was chosen to be tested in the worst-case ABM2 condition (see below for GSM, see Section 8 for more information regarding worst-case configurations for CDMA and UMTS. LTE configuration information can be found in Section 5. WIFI configuration information can be found in Section 6 and 7.):




Figure 4-13 **Vocoder Analysis for ABM Noise for GSM** 

### 4. Signal Quality Data Analysis

- a. Narrow-band Magnetic Intensity
  - i. The standard specifies a 1kHz 1/3 octave band minimum field intensity for a sine tone. The ABM1 measurements were evaluated at 1kHz with 1/3 octave band filtering over an averaged period of 10 seconds.

## b. Frequency Response

- i. The appropriate frequency response curve was measured to curves in Figure 3-1 or Figure 3-2 between 300 - 3000 Hz using digital linear averaging (limit lines chosen according to measurement found in step 4a). A linear average over 3x the length of the artificial voice signal (3x sampling) was performed. A 10 second delay was configured in the measurement process of the stimulus to ensure handset vocoder latency effects and echo cancellation devices (if any) were appropriately stabilized during measurements.
- ii. The appropriate post-processing was applied according to the system processing chain illustrated in Figure 4-7. All R10 frequencies were plotted with respect to 0dB at 1kHz value and aligned with respect to the EIA-504 mask.
- iii. The margin is represented by the closest measured data point on the curve to the EIA-504 limit lines, in dB.

## c. Signal Quality Index

i. Ensuring the WD was at maximum RF power, maximum volume, backlight off, display on, maximum contrast setting, keypad lights on (when possible) with no

FCC ID: ZNFG710VM	PCTEST TELEVISION OF THE	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 14 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 14 01 67

- audio signal through the vocoder, the WD was measured over at least 100 Hz 10,000 Hz, maximized over 5 seconds with a 50ms sample time for the ABM2 measurement (5 second time period is used in noise measurements under standards such as IEEE 269, etc.).
- ii. After applying half-band integration and A-weighting to the result, a power sum was applied over each 1/3 octave bandwidth frequency for an ABM2 value.
- This result was subtracted from the ABM1 result in step a, to obtain the Signal Quality.

## V. Test Setup




Figure 4-14
Audio Magnetic Field Test Setup

### VI. Deviation from C63.19 Test Procedure

Non-conducted RF connection due to inaccessible RF ports.

## VII. Air Interface Technologies Tested

All air interfaces which support voice capabilities over a managed CMRS or pre-installed OTT VoIP applications were tested for T-coil. See Table 2-1 for more details regarding which modes were tested.

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 15 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 13 01 07

# VIII. Wireless Device Channels and Frequencies

## 1. 2G/3G Modes

The frequencies listed in the table below are those that lie in the center of the bands used for cellular telephony. Low, middle and high channels were tested in each band for FCC compliance evaluation to ensure the maximum emission is captured across the entire band. Only middle channels were evaluated for data modes since circuit-switched voice modes were worst-case.

> Table 4-3 **Center Channels and Frequencies**

Test frequencies & associated channels				
Channel	Frequency (MHz)			
Secondary Cellular 8	20			
564 (CDMA)	820.10			
Cellular 850				
384 (CDMA)	836.52			
190 (GSM)	836.60			
4183 (UMTS)	836.60			
AWS 1750				
1412 (UMTS)	1730.40			
PCS 1900				
600 (CDMA)	1880			
661 (GSM)	1880			
9400 (UMTS)	1880			

## 2. 4G (LTE) Modes

The middle channel for every band and bandwidth combination was tested for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. Low-mid and mid-high channels are additionally tested for LTE TDD. The middle channel and supported bandwidths from the worst-case band according to Table 7-6 was additionally evaluated with OTT VoIP for each probe orientation. See Tables 9-5 to 9-12 and 9-20 to 9-21 for LTE bandwidths and channels.

### 3. WIFI

The middle channel for each 802.11 standard was tested for each probe orientation. The 2.4GHz 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels. The 5GHz 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested on higher U-NII bands as well as applicable low and high channels. See Tables 9-13 to 9-16 and 9-22 to 9-25 for WIFI standards and channels.

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 16 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 10 01 67

#### IX. **Test Flow**

The flow diagram below was followed (From C63.19):




Figure 4-15 C63.19 T-Coil Signal Test Process

FCC ID: ZNFG710VM	PETEST VANISHEEMS LANGESTON, INC.	HAC (T-COIL) TEST REPORT	(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 17 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 17 01 07

© 2018 PCTEST Engineering Laboratory, Inc.

**REV 3.2.M** 

#### **VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION** 5.

#### I. Test System Setup for VoLTE over IMS T-coil Testing

## Equipment Setup

The general test setup used for VoLTE over IMS is shown below. The callbox used when performing VoLTE over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 5-1 Test Setup for VoLTE over IMS T-Coil Measurements

## 2. Audio Level Settings

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for VoLTE over IMS T-coil testing, -16dBm0 shall be used for the normal speech input level\*. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE over IMS connection.

\* http://c63.org/documents/misc/posting/new\_interpretations.htm

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	டுடி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 18 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 10 01 01

© 2018 PCTEST Engineering Laboratory, Inc.

**REV 3.2.M** 

#### II. **DUT Configuration for VoLTE over IMS T-coil Testing**

## 1. Radio Configuration

An investigation was performed to determine the modulation and RB configuration to be used for testing. 64QAM, 1RB, 0RB offset was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different radio configurations:

> Table 5-1 Vol TE over IMS SNNR by Radio Configuration

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
1882.5	26365	20	QPSK	1	0	-0.09	-54.14	54.05
1882.5	26365	20	QPSK	1	50	0.08	-54.24	54.32
1882.5	26365	20	QPSK	1	99	0.12	-54.33	54.45
1882.5	26365	20	QPSK	50	0	-0.03	-55.11	55.08
1882.5	26365	20	QPSK	50	25	0.21	-55.08	55.29
1882.5	26365	20	QPSK	50	50	-0.27	-55.45	55.18
1882.5	26365	20	QPSK	100	0	0.09	-53.64	53.73
1882.5	26365	20	16QAM	1	0	0.18	-49.87	50.05
1882.5	26365	20	16QAM	1	50	0.05	-49.94	49.99
1882.5	26365	20	16QAM	1	99	0.25	-50.60	50.85
1882.5	26365	20	16QAM	50	0	-0.14	-54.77	54.63
1882.5	26365	20	16QAM	50	25	0.16	-54.90	55.06
1882.5	26365	20	16QAM	50	50	0.18	-54.90	55.08
1882.5	26365	20	16QAM	100	0	0.12	-54.20	54.32
1882.5	26365	20	64QAM	1	0	0.05	-48.73	48.78
1882.5	26365	20	64QAM	1	50	-0.08	-50.15	50.07
1882.5	26365	20	64QAM	1	99	-0.27	-51.29	51.02
1882.5	26365	20	64QAM	50	0	0.09	-53.98	54.07
1882.5	26365	20	64QAM	50	25	-0.02	-54.40	54.38
1882.5	26365	20	64QAM	50	50	-0.23	-53.82	53.59
1882.5	26365	20	64QAM	100	0	0.06	-53.30	53.36


## 2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The WB AMR 6.60kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

> Table 5-2 AMR Codec Investigation - VolTE over IMS

	Airii	oace iii v		VOLIL OVCI IIIIO			
Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	1.00	0.14	2.38	2.61		Axial Band 25 20MHz BW	26365
ABM2 (dBA/m)	-50.07	-50.16	-48.10	-49.70	Avial		
Frequency Response	Pass	Pass	Pass	Pass	Axiai		
S+N/N (dB)	51.07	50.30	50.48	52.31			

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC = "Max Power"



**Audio Band Magnetic Curve Measurement Block Diagram** 

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	<b>LG</b>	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 19 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 19 01 67

## 3. LTE TDD Uplink-Downlink Configuration Investigation for VoLTE over IMS

An investigation was performed to determine the worst-case Uplink-Downlink configuration for VoLTE over IMS T-Coil testing.

Per 3GPP TS 36.211, the total frame length for each TDD radio frame of length  $T_f = 307200 \cdot T_s$ = 10 ms, where T<sub>s</sub> is a number of time units equal to 1/(15000 x 2048) seconds. Additionally, each radio frame consists of 10 subframes, each of length 30720 · T<sub>s</sub> = 1 ms, and subframes can be designated as uplink (U), downlink (D), or special subframe (S), depending on the Uplink-Downlink configuration as indicated in Table 4.2-2 of 3GPP TS 36.211. In the transmission duty factor calculation, the special subframe configuration with the shortest UpPTS duration within the special subframe is used and will be applied for measurement. From 3GPP TS 36.211 Table 4.2-1, the shortest UpPTS is 2192 · Ts which occurs in the normal cyclic prefix and special subframe configuration 4.

See table below outlining the calculated transmission duty cycles for each Uplink-Downlink configuration:

> Table 5-3 **Uplink-Downlink Configurations for Type 2 Frame Structures**

	Dennik Bowinink Com				- 7 17							
Uplink-downlink configuration	Downlink-to-Uplink				Su	bfram	e numb	er				Calculated Transmission
configuration	Switch-point periodicity	0	1	2	3	4	5	6	7	8	9	Duty Cycle (%)
0	5 ms	D	S	U	U	U	D	S	J	J	U	61.4%
1	5 ms	D	S	U	U	D	D	S	J	J	D	41.4%
2	5 ms	D	S	U	D	D	D	S	J	D	D	21.4%
3	10 ms	D	S	U	U	U	D	D	D	D	D	30.7%
4	10 ms	D	S	U	U	D	D	D	D	D	D	20.7%
5	10 ms	D	S	U	D	D	D	D	D	D	D	10.7%
6	5 ms	D	S	U	U	U	D	S	U	U	D	51.4%

### Power Class 3 Uplink-Downlink Configuration Investigation

Power class 3 was evaluated with the following radio configuration: channel 40620, 20MHz BW, 64QAM, 1RB, 0RB Offset. For Power Class 3, all configurations (0-6) are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 2 was used as the worst-case configuration for Power Class 3 VoLTE over IMS T-Coil testing. See table below for the SNNR comparison between each Uplink-Downlink configuration:

Table 5-4 Power Class 3 VoLTE over IMS SNNR by UL-DL Configuration

				_ • • • •		,	<u> </u>	• • •	
Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2593.0	40620	20	64QAM	1	0	0	0.04	-42.84	42.88
2593.0	40620	20	64QAM	1	0	1	0.12	-41.56	41.68
2593.0	40620	20	64QAM	1	0	2	0.17	-40.16	40.33
2593.0	40620	20	64QAM	1	0	3	0.20	-43.90	44.10
2593.0	40620	20	64QAM	1	0	4	0.81	-44.82	45.63
2593.0	40620	20	64QAM	1	0	5	0.17	-43.81	43.98
2593.0	40620	20	64QAM	1	0	6	0.28	-42.18	42.46

FCC ID: ZNFG710VM	PETEST VANISHEEMS LANGESTON, INC.	HAC (T-COIL) TEST REPORT	<u>்</u> ட்டி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 20 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 20 01 67

## b. Power Class 2 Uplink-Downlink Configuration Investigation

Power Class 2 was evaluated with the following radio configuration: channel 40620, 20MHz BW, 64QAM, 1RB, 0RB Offset. For Power Class 2, configurations 1-5 are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 2 was used as the worst-case configuration for Power Class 2 VoLTE over IMS T-Coil testing. See table below for the SNNR comparison between each Uplink-Downlink configuration:

Table 5-5
Power Class 2 VoLTE over IMS SNNR by UL-DL Configuration

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2593.0	40620	20	64QAM	1	0	1	0.43	-37.12	37.55
2593.0	40620	20	64QAM	1	0	2	0.51	-35.92	36.43
2593.0	40620	20	64QAM	1	0	3	0.40	-38.95	39.35
2593.0	40620	20	64QAM	1	0	4	0.09	-38.89	38.98
2593.0	40620	20	64QAM	1	0	5	0.55	-38.78	39.33

Note: LTE TDD B41 Power Class 2 only supports UL-DL configurations 1-5, not 0 or 6.

## c. Conclusion

Per the investigations above, UL-DL Configuration 2 was used to evaluate Power Class 3 VoLTE over IMS and UL-DL Configuration 2 was used to evaluate Power Class 2 VoLTE over IMS.

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 21 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 210101

#### **VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION** 6.

#### I. Test System Setup for VoWIFI over IMS T-coil Testing

### Equipment Setup

The general test setup used for VoWIFI over IMS, or CMRS WIFI Calling, is shown below. The callbox used when performing VoWIFI over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 6-1 Test Setup for VoWIFI over IMS T-Coil Measurements

## 2. Audio Level Settings

According to KDB 285076 D02 released by the FCC OET regarding the appropriate audio levels to be used for VoWIFI over IMS T-Coil testing, -20dBm0 shall be used for the normal speech input level2. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the VoWIFI over IMS connection.

<sup>2</sup> FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 22 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 22 01 01

© 2018 PCTEST Engineering Laboratory, Inc.

**REV 3.2.M** 

#### **DUT Configuration for VoWIFI over IMS T-coil Testing** II.

## 1. Radio Configuration

An investigation was performed on all applicable data rates and modulations to determine the radio configuration to be used for testing. See tables below for SNNR comparison between radio configurations in each 802.11 standard:

> Table 6-1 802.11b SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
802.11b	6	DSSS	1	-5.29	-42.07	36.78
802.11b	6	DSSS	2	-5.40	-42.68	37.28
802.11b	6	CCK	5.5	-5.55	-43.03	37.48
802.11b	6	CCK	11	-5.33	-43.16	37.83

Table 6-2 802.11g/a SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
802.11g	6	BPSK	6	-5.44	-49.47	44.03
802.11g	6	BPSK	9	-5.88	-49.94	44.06
802.11g	6	QPSK	12	-5.58	-50.40	44.82
802.11g	6	QPSK	18	-5.28	-49.64	44.36
802.11g	6	16-QAM	24	-5.81	-51.36	45.55
802.11g	6	16-QAM	36	-5.81	-52.06	46.25
802.11g	6	64-QAM	48	-5.33	-51.33	46.00
802.11g	6	64-QAM	54	-5.84	-51.38	45.54

Table 6-3 802.11n/ac 20MHz BW SNNR by Radio Configuration

Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
802.11n	20	40	BPSK	6.5	-5.50	-51.78	46.28
802.11n	20	40	QPSK	13	-5.86	-51.72	45.86
802.11n	20	40	QPSK	19.5	-5.46	-52.11	46.65
802.11n	20	40	16-QAM	26	-5.62	-52.08	46.46
802.11n	20	40	16-QAM	39	-5.87	-53.41	47.54
802.11n	20	40	64-QAM	52	-5.55	-53.04	47.49
802.11n	20	40	64-QAM	58.5	-5.77	-52.09	46.32
802.11n	20	40	64-QAM	65	-5.48	-53.12	47.64
802.11ac	20	40	256-QAM	78	-5.68	-54.62	48.94

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	⊕ LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 23 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 23 01 67

Table 6-4 802.11n/ac 40MHz BW SNNR by Radio Configuration

002.1 III/ac +0MI12 BW SMMX by Radio Configuration								
Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]	
802.11n	40	38	BPSK	13.5	-5.55	-52.36	46.81	
802.11n	40	38	QPSK	27	-5.45	-51.48	46.03	
802.11n	40	38	QPSK	40.5	-5.79	-52.74	46.95	
802.11n	40	38	16-QAM	54	-5.93	-52.22	46.29	
802.11n	40	38	16-QAM	81	-5.53	-52.41	46.88	
802.11n	40	38	64-QAM	108	-5.41	-53.48	48.07	
802.11n	40	38	64-QAM	121.5	-5.75	-53.51	47.76	
802.11n	40	38	64-QAM	135	-5.49	-53.53	48.04	
802.11ac	40	38	256-QAM	162	-5.53	-52.39	46.86	
802.11ac	40	38	256-QAM	180	-5.63	-53.74	48.11	


## 2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The WB AMR 6.6kbps setting was used for the audio codec on the CMW500 for VoWIFI over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

> Table 6-5 **AMR Codec Investigation – VoWIFI over IMS**

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band	Standard	Channel
ABM1 (dBA/m)	-4.32	-5.11	-2.67	-2.94		al 2.4GHz	802.11b	6
ABM2 (dBA/m)	-44.46	-43.68	-44.31	-43.93	Avial			
Frequency Response	Pass	Pass	Pass	Pass	- Axial			
S+N/N (dB)	40.14	38.57	41.64	40.99				

Mute on; Backlight off; Max Volume; Max Contrast



**Audio Band Magnetic Curve Measurement Block Diagram** 

FCC ID: ZNFG710VM	PETEST	HAC (T-COIL) TEST REPORT	<b>LG</b>	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 24 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 24 01 07

#### 7. OTT VOIP TEST SYSTEM AND DUT CONFIGURATION

#### I. Test System Setup for OTT VolP T-Coil Testing

## 1. OTT VoIP Application

Google Duo is a pre-installed application on the DUT which allows for VoIP calls in a held-to-ear scenario. Duo uses the OPUS audio codec and supports a bitrate range of 6kb/s to 64kb/s. All air interfaces capable of a data connection were evaluated with Google Duo.

### 2. Equipment Setup

A CMW500 callbox was used to perform OTT VoIP T-coil measurements. The Data Application Unit (DAU) of the CMW500 was connected to the internet and allowed for an IP data connection on the DUT. An auxiliary VoIP unit was used to initiate an OTT VoIP call to the DUT. The auxiliary VoIP unit allowed for the configuration and monitoring of the OTT VoIP codec bitrate during a call. Both high and low bitrate settings were evaluated in to determine the worst-case configuration.

## Audio Level Settings

According to KDB 285076 D02, the average speech level of -20dBm0 shall be used for protocols not specifically listed in Table 7.1 of ANSI C63.19-2011 or the ANSI C63.19-2011 VoLTE interpretation3. The auxiliary VoIP unit allowed for monitoring the signal input level to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the OTT VoIP call.

#### II. **DUT Configuration for OTT VolP T-Coil Testing**

### 1. Codec Configuration

An investigation was performed for each applicable data mode to determine the audio codec configuration to be used for testing. The 64kbps codec setting was used for the audio codec on the auxiliary VoIP unit for OTT VoIP T-Coil testing. See below tables for comparisons between codec data rates on all applicable data modes:

> Table 7-1 Codec Investigation - OTT VolP (EvDO)

	OII (EVDC	· /			
Codec Setting:	64kbps	6kbps	Orientation	Channel	
ABM1 (dBA/m)	9.54	9.37			
ABM2 (dBA/m)	-51.55	-52.14	Axial	600	
Frequency Response	Pass	Pass	Axiai	000	
S+N/N (dB)	61.09	61.51			

<sup>&</sup>lt;sup>3</sup> FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 25 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 23 01 07

Table 7-2 Codec Investigation - OTT VoIP (EDGE)

Codec Setting:	64kbps	6kbps	Orientation	Channel			
ABM1 (dBA/m)	10.27	10.03					
ABM2 (dBA/m)	-33.11	-34.02	Axial	661			
Frequency Response	Pass	Pass	Axiai	001			
S+N/N (dB)	43.38	44.05					

Table 7-3 Codec Investigation - OTT VolP (HSPA)

Oddec investigation – OTT voil (not A)								
Codec Setting:	64kbps	6kbps	Orientation	Channel				
ABM1 (dBA/m)	10.67	10.19	9					
ABM2 (dBA/m)	-51.81	-52.59	Axial	9400				
Frequency Response	Pass	Pass	Avidi	3400				
S+N/N (dB)	62.48	62.78						

Table 7-4 Codec Investigation - OTT VolP (LTE)

	oace inves	1.94	011 7011	<u> </u>	
Codec Setting:	64kbps	6kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	11.16	10.78			
ABM2 (dBA/m)	-44.71	-45.13	Axial	LTE Band 13	23230
Frequency Response	Pass	Pass	Axiai	10MHz	
S+N/N (dB)	55.87	55.91			

Table 7-5 Codec Investigation - OTT VoIP (WIFI)

Codec Setting:	64kbps	6kbps	Orientation	Band	Standard	Channel
ABM1 (dBA/m)	9.56	9.51		2.4GHz		6
ABM2 (dBA/m)	-40.00	-40.48	Avial		802.11b	
Frequency Response	Pass	Pass	Axial			
S+N/N (dB)	49.56	49.99				

- Mute on; Backlight off; Max Volume; Max Contrast
- Radio Configurations can be found in Section 9.II.H




Figure 7-1 **Audio Band Magnetic Curve Measurement Block Diagram** 

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	<b>LG</b>	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 26 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 20 01 67

## 2. LTE FDD Band Investigation

An investigation was performed to determine the worst-case LTE FDD band for OTT VoIP T-Coil testing. LTE Band 13 was evaluated for OTT VoIP over LTE T-Coil testing. See table below for the SNNR comparison between each LTE FDD band.

> Table 7-6 OTT VoIP (LTE) SNNR by LTE FDD Band

	011 ton (212) 011111													
Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]					
12	707.5	23095	10	64QAM	1	0	11.00	-47.11	58.11					
13	782.0	23230	10	64QAM	1	0	10.98	-45.02	56.00					
5	793.0	23330	10	64QAM	1	0	11.08	-46.44	57.52					
26	836.5	26865	15	64QAM	1	0	10.93	-47.25	58.18					
66	1732.5	132322	20	64QAM	1	0	10.90	-46.21	57.11					
25	1882.5	26365	20	64QAM	1	0	11.10	-45.40	56.50					

## 3. LTE FDD Uplink Carrier Aggregation for OTT VolP

LTE FDD ULCA was evaluated with the worst-case bandwidth and channel combination from Table 7-6. The PCC radio configuration was channel 20525, 10MHz BW, 64QAM, 1RB, 0RB Offset. The SCC radio configuration was channel 20453, 5MHz BW, 64QAM, 1RB, 24RB Offset. This radio configuration satisfied the configuration requirements of the applicable LTE CA combination. See results below:

> Table 7-7 LTE FDD SNNR for OTT VolP Uplink Carrier Aggregation

				_	—	<b>,,</b>				• P	<b></b> u		,99.0	gauo	•			
ſ			PCC									SCC						
	Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL/DL) Channel	PCC (UL/DL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	ISCC (III /DL)	SCC (UL/DL) Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
	CA_5B	LTE B5	10	20525	836.5	64QAM	1	0	LTE B5	5	20453	829.3	64QAM	1	24	9.42	-49.70	59.12

## 4. LTE TDD Uplink Carrier Aggregation for OTT VoIP

LTE TDD ULCA was evaluated with the worst-case bandwidth and channel combination from Table 9-21. The PCC radio configuration was channel 40185, 15MHz BW, 64QAM, 1RB, 0RB Offset. The SCC radio configuration was channel 40035, 15MHz BW, 64QAM, 1RB, 74RB Offset. UL-DL configuration 2 was used for evaluation. This radio configuration satisfied the configuration requirements of the applicable LTE CA combination. See results below:

> Table 7-8 LITE TDD SNNR for OTT VolP Unlink Carrier Aggregation

					יוט טוי		, 0 ,		Opii	iik Oa	11101 7	79916	gatioi	•			
		PCC						SCC									
Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL/DL) Channel	PCC (UL/DL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]		SCC (UL/DL) Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
CA_41C	LTE B41	15	40185	2549.5	64QAM	1	99	LTE B41	15MHz	40035	2534.5	64QAM	1	74	9.20	-40.07	49.27

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	டுடி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 27 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 21 01 01

#### FCC 3G MEASUREMENTS 8.

#### I. **CDMA Test Configurations**

Radio Configuration 1, Service Option 3 (thick, green data curve) was used for the testing as the worstcase configuration for the handset due to vocoder gating from the EVRC logic. See below plot for ABM noise comparison between operational field service options and radio configurations for a CDMA2000 handset:





Figure 8-1 **CDMA Audio Band Magnetic Noise** 

Table 8-1 FCC 3G ABM Measurements for ZNFG710VM (CDMA)

			O7 10 VIII \			
Configuration:	RC1/SO3	RC3/SO3	RC4/SO3	Orientation	Channel	
ABM1 (dBA/m)	2.69	1.76	1.10		384	
ABM2 (dBA/m)	-45.79	-55.99	-55.36	Axial		
Frequency Response	Pass	Pass	Pass	Axiai		
S+N/N (dB)	48.48	57.75	56.46			

- Mute on; Backlight off; Max Volume; Max Contrast
- Power Control Bits = "All Up"



**Audio Band Magnetic Curve Measurement Block Diagram** 

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 28 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 20 01 07

© 2018 PCTEST Engineering Laboratory, Inc.

**REV 3.2.M** 

## **II.** UMTS Test Configurations

AMR at 12.2kbps, 13.6kbps SRB was used for the testing as the worst-case configuration for the handset. See below plot for ABM noise comparison between vocoder rates:





Figure 8-3
UMTS Audio Band Magnetic Noise

Table 8-2 Codec Investigation - UMTS

Codec Setting:	AMR 12.2kbps	AMR 7.95kbps	AMR 4.75kbps	Orientation	Channel	
ABM1 (dBA/m)	1.47	1.47	1.35		9400	
ABM2 (dBA/m)	-56.14	-56.25	-56.36	Axial		
Frequency Response	Pass	Pass	Pass	Axiai	3400	
S+N/N (dB)	57.61	57.72	57.71			

- Mute on; Backlight off; Max Volume; Max Contrast
- · TPC="All 1s"



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	€ LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 29 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 29 01 67

Table 9-1 **Consolidated Tabled Results** 

Consolidated Tabled Results											
			esponse rgin	•	netic / Verdict		SNNR dict	Margin from FCC Limit	C63.19-2011		
000.44	0.0 41	8.3	3.2	8.3	3.1	8.3	3.4	(dB)	Rating		
C63.18	9 Section	Axial	Radial	Axial	Radial	Axial	Radial				
	Secondary Cellular	PASS	NA	PASS	PASS	PASS	PASS				
CDMA	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-18.11	T4		
	PCS	PASS	NA	PASS	PASS	PASS	PASS				
	Secondary Cellular	PASS	NA	PASS	PASS	PASS	PASS				
EvDO (OTT VoIP)	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-34.41	T4		
	PCS	PASS	NA	PASS	PASS	PASS	PASS				
GSM	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-3.51	Т3		
	PCS	PASS	NA	PASS	PASS	PASS	PASS	-5.51	13		
EDGE	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-15.07	T4		
(OTT VoIP)	PCS	PASS	NA	PASS	PASS	PASS	PASS	-10.07	1.4		
	Cellular	PASS	NA	PASS	PASS	PASS	PASS				
UMTS	AWS	PASS	NA	PASS	PASS	PASS	PASS	-25.53	T4		
	PCS	PASS	NA	PASS	PASS	PASS	PASS				
HSPA	Cellular	PASS	NA	PASS	PASS	PASS	PASS				
(OTT VoIP)	AWS	PASS	NA	PASS	PASS	PASS	PASS	-33.77	T4		
	PCS	PASS	NA	PASS	PASS	PASS	PASS				
	B12	PASS	NA	PASS	PASS	PASS	PASS				
	B13	PASS	NA	PASS	PASS	PASS	PASS				
LTE FDD	B26	PASS	NA	PASS	PASS	PASS	PASS	-13.37	T4		
	B5	PASS	NA	PASS	PASS	PASS	PASS	10.07			
	B66	PASS	NA	PASS	PASS	PASS	PASS				
	B25	PASS	NA	PASS	PASS	PASS	PASS				
LTE FDD (OTT VoIP)	B13	PASS	NA	PASS	PASS	PASS	PASS	-23.72	Т4		
LTE TDD	B41	PASS	NA	PASS	PASS	PASS	PASS	-4.74	Т3		
LTE TDD (OTT VoIP)	B41	PASS	NA	PASS	PASS	PASS	PASS	-19.24	T4		
	802.11b	PASS	NA	PASS	PASS	PASS	PASS				
WLAN	802.11g	PASS	NA	PASS	PASS	PASS	PASS	-16.36	Т4		
WLAN	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-10.30	14		
	802.11ac	PASS	NA	PASS	PASS	PASS	PASS				
	802.11b	PASS	NA	PASS	PASS	PASS	PASS				
WLAN	802.11g	PASS	NA	PASS	PASS	PASS	PASS	-29.56	Т4		
(OTT VoIP)	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-23.50	14		
	802.11ac	PASS	NA	PASS	PASS	PASS	PASS				
	802.11a	PASS	NA	PASS	PASS	PASS	PASS				
U-NII	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-15.66	T4		
	802.11ac	PASS	NA	PASS	PASS	PASS	PASS	<del></del>			
11 ****	802.11a	PASS	NA	PASS	PASS	PASS	PASS				
U-NII (OTT VoIP)	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-28.33	T4		
	802.11ac	PASS	NA	PASS	PASS	PASS	PASS				

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	(f) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 30 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 30 01 07

© 2018 PCTEST Engineering Laboratory, Inc.

## I. Raw Handset Data

Table 9-2
Raw Data Results for CDMA

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		476	4.33	-45.26		2.00	49.59	20.00	-29.59	T4	
	Axial	564	3.58	-44.77	-60.81	2.00	48.35	20.00	-28.35	T4	2.4, 3.0
Secondary		684	3.15	-46.34		2.00	49.49	20.00	-29.49	T4	
Cellular		476	-3.04	-43.42			40.38	20.00	-20.38	T4	
	Radial	564	-4.34	-44.73	-60.53	N/A	40.39	20.00	-20.39	T4	2.4, 2.2
		684	-3.84	-44.45			40.61	20.00	-20.61	T4	
	Axial	1013	3.83	-43.34	-60.81	2.00	47.17	20.00	-27.17	T4	
		384	3.46	-45.45		2.00	48.91	20.00	-28.91	T4	2.4, 3.0
Cellular		777	3.05	-42.50		2.00	45.55	20.00	-25.55	T4	
Gendiai		1013	-4.50	-44.39	-60.53 N/A		39.89	20.00	-19.89	T4	
	Radial	384	-3.20	-43.37		40.17	20.00	-20.17	T4	2.4, 2.2	
		777	-4.48	-42.59			38.11	20.00	-18.11	T4	
		25	3.70	-44.24		2.00	47.94	20.00	-27.94	T4	
	Axial	600	2.75	-45.94	-60.81	2.00	48.69	20.00	-28.69	T4	2.4, 3.0
PCS		1175	3.23	-45.31		2.00	48.54	20.00	-28.54	T4	
763		25	-3.95	-44.38			40.43	20.00	-20.43	T4	
	Radial	600	-3.74	-45.84	-60.53	N/A	42.10	20.00	-22.10	T4	2.4, 2.2
		1175	-4.22	-45.34			41.12	20.00	-21.12	T4	

Table 9-3
Raw Data Results for GSM

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		128	2.89	-33.62		1.35	36.51	20.00	-16.51	T4	
	Axial	190	2.88	-33.04	-61.05	1.34	35.92	20.00	-15.92	T4	2.4, 3.0
GSM850		251	2.88	-31.77		1.37	34.65	20.00	-14.65	T4	
GSIVIOSU		128	-5.41	-31.35			25.94	20.00	-5.94	T3	
Ra	Radial	190	-5.43	-30.77	-60.53	N/A	25.34	20.00	-5.34	T3	2.4, 2.2
		251	-5.35	-29.68			24.33	20.00	-4.33	T3	
		512	2.80	-31.14		1.36	33.94	20.00	-13.94	T4	
	Axial	661	2.76	-31.12	-61.05	1.35	33.88	20.00	-13.88	T4	2.4, 3.0
GSM1900		810	2.77	-31.40		1.37	34.17	20.00	-14.17	T4	
G3W1900		512	-5.31	-28.96			23.65	20.00	-3.65	T3	
	Radial	661	-5.38	-28.89	-60.53	N/A	23.51	20.00	-3.51	T3	2.4, 2.2
		810	-5.34	-29.37			24.03	20.00	-4.03	T3	

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 31 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 31 01 67

Table 9-4
Raw Data Results for UMTS

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates	
		4132	1.74	-55.86		2.00	57.60	20.00	-37.60	T4		
	Axial	4183	1.67	-56.26	-61.05	2.00	57.93	20.00	-37.93	T4	2.4, 3.0	
UMTS V		4233	1.67	-54.61		2.00	56.28	20.00	-36.28	T4		
C.III C V		4132	-6.59	-53.37			46.78	20.00	-26.78	T4	ļ	
	Radial	4183	-6.58	-52.68	-60.53	N/A	46.10	20.00	-26.10	T4	2.4, 2.2	
		4233	-6.54	-52.33			45.79	20.00	-25.79	T4		
		1312	1.70	-55.81		2.00	57.51	20.00	-37.51	T4		
	Axial	1412	1.63	-55.72	-61.05	2.00	57.35	20.00	-37.35	T4	2.4, 3.0	
UMTS IV		1513	1.61	-55.68		2.00	57.29	20.00	-37.29	T4		
OMITO IV		1312	-6.58	-53.42	2			46.84	20.00	-26.84	T4	
	Radial	1412	-6.60	-53.14	-60.53	N/A	46.54	20.00	-26.54	T4	2.4, 2.2	
		1513	-6.59	-53.42			46.83	20.00	-26.83	T4		
		9262	1.72	-56.50		2.00	58.22	20.00	-38.22	T4		
	Axial	9400	1.65	-56.38	-61.05	2.00	58.03	20.00	-38.03	T4	2.4, 3.0	
UMTS II		9538	1.65	-55.60		2.00	57.25	20.00	-37.25	T4		
OWISI		9262	-6.58	-52.50			45.92	20.00	-25.92	T4	2.4, 2.2	
	Radial	9400	-6.60	-52.32	-60.53	N/A	45.72	20.00	-25.72	T4		
		9538	-6.62	-52.15			45.53	20.00	-25.53	T4	·	

# Table 9-5 Raw Data Results for LTE B12

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates	
		10MHz	23095	-0.14	-48.67		2.00	48.53	20.00	-28.53	T4		
	Axial	5MHz	23095	0.00	-49.27	-60.81	2.00	49.27	20.00	-29.27	T4	2.4, 3.0	
	Axiai	3MHz	23095	0.03	-49.85	-00.01	2.00	49.88	20.00	-29.88	T4	2.4, 5.0	
LTE Band		1.4MHz	23095	-0.32	-49.16		2.00	48.84	20.00	-28.84	T4		
12		10MHz	23095	-8.98	-44.46			35.48	20.00	-15.48	T4		
	Radial	5MHz	23095	-9.05	-44.84	60.53	NI/A	35.79	20.00	-15.79	T4	2.4. 2.2	
	radiai	3MHz	23095	-9.26	-45.12	-60.53	-60.53 N/A	IN/A	35.86	20.00	-15.86	T4	2.4, 2.2
		1.4MHz	23095	-9.13	-45.58			36.45	20.00	-16.45	T4		

# Table 9-6 Raw Data Results for LTE B13

I	Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)		Test Coordinates
		Axial	10MHz	23230	-0.03	-46.50	-60.81	2.00	46.47	20.00	-26.47	T4	2.4, 3.0
LT	E Band	Axiai	5MHz	23230	-0.11	-47.30	-00.01	2.00	47.19	20.00	-27.19	T4	2.4, 3.0
	13	Dodial	10MHz	23230	-9.02	-42.67	-60.53	N/A	33.65	20.00	-13.65	T4	2.4. 2.2
	Radial	5MHz	23230	-8.92	-42.83	-60.55	IN/A	33.91	20.00	-13.91	T4	2.4, 2.2	

# Table 9-7 Raw Data Results for LTE B26

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		15MHz	26865	-0.14	-47.24		2.00	47.10	20.00	-27.10	T4	
		10MHz	26865	-0.06	-49.52		1.98	49.46	20.00	-29.46	T4	
	Axial	5MHz	26865	-0.11	-47.45	-60.81	1.96	47.34	20.00	-27.34	T4	2.4, 3.0
		3MHz	26865	-0.22	-48.81		2.00	48.59	20.00	-28.59	T4	
LTE Band		1.4MHz	26865	-0.11	-46.52		2.00	46.41	20.00	-26.41	T4	
26		15MHz	26865	-8.95	-43.61			34.66	20.00	-14.66	T4	
		10MHz	26865	-9.15	-44.89			35.74	20.00	-15.74	T4	
	Radial	5MHz	26865	-9.08	-45.06	-60.53	N/A	35.98	20.00	-15.98	T4	2.4, 2.2
		3MHz	26865	-8.94	-45.01			36.07	20.00	-16.07	T4	
		1.4MHz	26865	-8.94	-43.97			35.03	20.00	-15.03	T4	

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 32 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 32 01 01

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

## Table 9-8 **Raw Data Results for LTE B5**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		10MHz	20525	-0.31	-47.46		2.00	47.15	20.00	-27.15	T4	
	Axial	5MHz	20525	-0.15	-47.46	-60.81	2.00	47.31	20.00	-27.31	T4	2.4, 3.0
	Axiai	3MHz	20525	-0.43	-48.12	-00.61	2.00	47.69	20.00	-27.69	T4	2.4, 3.0
LTE Band 5		1.4MHz	20525	-0.16	-45.81		2.00	45.65	20.00	-25.65	T4	
LIE Ballu 5		10MHz	20525	-9.14	-43.98			34.84	20.00	-14.84	T4	
	Padial	5MHz	20525	-9.12	-44.17	60.53	NI/A	35.05	20.00	-15.05	T4	2.4. 2.2
Radial	3MHz	20525	-9.38	-43.73	-60.53	-60.53 N/A	34.35	20.00	-14.35	T4	2.4, 2.2	
		1.4MHz	20525	-9.25	-43.27			34.02	20.00	-14.02	T4	

## Table 9-9 **Raw Data Results for LTE B66**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates				
		20MHz	132322	-0.29	-47.74		2.00	47.45	20.00	-27.45	T4					
		15MHz	132322	0.02	-47.67		2.00	47.69	20.00	-27.69	T4					
		10MHz	132322	-0.23	-48.87		2.00	48.64	20.00	-28.64	T4					
	Axial	5MHz	132647	0.02	-44.94	-60.81	2.00	44.96	20.00	-24.96	T4	2.4, 3.0				
	Axiai	5MHz	132322	-0.17	-45.71	-00.61	2.00	45.54	20.00	-25.54	T4	2.4, 3.0				
		5MHz	131997	-0.12	-46.94		2.00	46.82	20.00	-26.82	T4					
	3MHz	132322	-0.36	-48.99		1.97	48.63	20.00	-28.63	T4						
LTE Band		1.4MHz	132322	-0.17	-47.02		2.00	46.85	20.00	-26.85	T4					
66		20MHz	132322	-8.96	-42.65			33.69	20.00	-13.69	T4					
		15MHz	132322	-8.84	-42.97			34.13	20.00	-14.13	T4					
		10MHz	132322	-8.83	-43.20			34.37	20.00	-14.37	T4					
	Radial	5MHz	132647	-8.78	-42.77	-60.53	N/A	33.99	20.00	-13.99	T4	2.4, 2.2				
	Radiai	5MHz	132322	-8.73	-42.10		-60.53	-60.53			IWA	33.37	20.00	-13.37	T4	2.4, 2.2
		5MHz	131997	-8.64	-43.07							34.43	20.00	-14.43	T4	
		3MHz	132322	-8.82	-44.03									35.21	20.00	-15.21
		1.4MHz	132322	-8.94	-42.98			34.04	20.00	-14.04	T4					

## **Table 9-10 Raw Data Results for LTE B25**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates						
		20MHz	26365	0.09	-48.48		2.00	48.57	20.00	-28.57	T4							
		15MHz	26365	-0.07	-48.55		2.00	48.48	20.00	-28.48	T4							
	Axial	10MHz	26365	-0.03	-47.63	-60.81	2.00	47.60	20.00	-27.60	T4	2.4, 3.0						
	Axiai	5MHz	26365	-0.24	-49.29	-00.61	2.00	49.05	20.00	-29.05	T4	2.4, 5.0						
		3MHz	26365	-0.13	-47.04		2.00	46.91	20.00	-26.91	T4							
LTE Band		1.4MHz	26365	-0.15	-48.99		2.00	48.84	20.00	-28.84	T4							
25		20MHz	26365	-8.84	-44.79			35.95	20.00	-15.95	T4							
		15MHz	26365	-8.76	-43.43	Ī		34.67	20.00	-14.67	T4							
	Radial	10MHz	26365	-8.63	-43.17	-60.53	-60.53	-60.53	-60.53	-60.53 N/A	NI/A	34.54	20.00	-14.54	T4	2.4, 2.2		
		5MHz	26365	-8.93	-44.60						-60.53	-60.53	-60.53	-60.53	-60.53	-60.53	-60.53	-60.53
	3MHz	26365	-8.58	-43.37	7		34.79	20.00	-14.79	T4								
	1.4MHz	26365	-8.71	-43.83			35.12	20.00	-15.12	T4								

## **Table 9-11** Raw Data Results for LTE B41 Power Class 3

				Data it	Journey 19		O	o uuoo	•			
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	40620	-0.10	-41.87		2.00	41.77	20.00	-21.77	T4	
	Axial	15MHz	40620	0.14	-40.65	-60.81	2.00	40.79	20.00	-20.79	T4	2.4, 3.0
	Axiai	10MHz	40620	-0.41	-40.07	-00.61	2.00	39.66	20.00	-19.66	T4	2.4, 3.0
LTE Band		5MHz	40620	-0.34	-41.57		2.00	41.23	20.00	-21.23	T4	
41		20MHz	40620	-9.09	-40.48			31.39	20.00	-11.39	T4	
	Radial	15MHz	40620	-9.11	-39.71	-60.53	N/A	30.60	20.00	-10.60	T4	2.4, 2.2
	Naulai	10MHz	40620	-8.94	-40.36	-00.55	IN/A	31.42	20.00	-11.42	T4	2.4, 2.2
		5MHz	40620	-9.07	-40.82			31.75	20.00	-11.75	T4	

FCC ID: ZNFG710VM	PETEST	HAC (T-COIL) TEST REPORT	⊕ LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 33 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 33 01 67

Table 9-12
Raw Data Results for LTE B41 Power Class 2

			itan	Dutu IN	counto i	JILILD	<del>711000</del>	oluss.	_							
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates				
		20MHz	40620	-0.32	-36.94		2.00	36.62	20.00	-16.62	T4					
		15MHz	40620	-0.30	-37.73		2.00	37.43	20.00	-17.43	T4					
		10MHz	40620	-0.44	-38.69		2.00	38.25	20.00	-18.25	T4					
	Axial	5MHz	41490	-0.55	-37.01	-60.81	1.99	36.46	20.00	-16.46	T4	2.4, 3.0				
	Axiai	5MHz	41055	-0.51	-38.54	-00.01	2.00	38.03	20.00	-18.03	T4	2.4, 3.0				
		5MHz	40620	-0.42	-36.98		2.00	36.56	20.00	-16.56	T4					
		5MHz	40185	-0.19	-36.62		2.00	36.43	20.00	-16.43	T4					
LTE Band		5MHz	39750	-0.18	-38.81		2.00	38.63	20.00	-18.63	T4					
41		20MHz	40620	-9.12	-35.45			26.33	20.00	-6.33	Т3					
		15MHz	41490	-9.14	-33.88			24.74	20.00	-4.74	Т3					
		15MHz	41055	-9.05	-35.87			26.82	20.00	-6.82	Т3					
	Dadial	15MHz	40620	-9.23	-34.91	60.53	NI/A	25.68	20.00	-5.68	Т3	2.4, 2.2				
	Radial	15MHz	40185	-9.17	-34.24	-60.53	-60.53 N/A	-60.53	-60.53	-60.53	IN/A	25.07	20.00	-5.07	T3	2.4, 2.2
	15MHz	39750	-9.18	-38.45	<del>-</del>						29.27	20.00	-9.27	Т3		
		10MHz	40620	-9.17	-35.18			26.01	20.00	-6.01	T3					
	5MHz	40620	-9.16	-35.31			26.15	20.00	-6.15	Т3						

Table 9-13
Raw Data Results for 2.4GHz WIFI

	Orientation Channel ABM1 ABM2 Ambient Noise Response S+N/N FCC Limit FCC Lim													
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)		C63.19-2011 Rating	Test Coordinates			
		1	-5.51	-41.87		2.00	36.36	20.00	-16.36	T4				
	Axial	6	-5.68	-42.70	-60.81	2.00	37.02	20.00	-17.02	T4	2.4, 3.0			
WLAN		11	-5.28	-43.23		2.00	37.95	20.00	-17.95	T4				
802.11b		1	-13.27	-50.65			37.38	20.00	-17.38	T4				
	Radial	6	-13.98	-50.59	-60.53	N/A	36.61	20.00	-16.61	T4	2.4, 2.2			
		11	-13.24	-50.86			37.62	20.00	-17.62	T4	1			
WLAN	Axial	6	-5.17	-49.93	-60.81	2.00	44.76	20.00	-24.76	T4	2.4, 3.0			
802.11g	Radial	6	-13.83	-52.24	-60.53	N/A	38.41	20.00	-18.41	T4	2.4, 2.2			
WLAN	Axial	6	-5.27	-47.44	-60.81	2.00	42.17	20.00	-22.17	T4	2.4, 3.0			
802.11n	Radial	6	-13.23	-51.88	-60.53	N/A	38.65	20.00	-18.65	T4	2.4, 2.2			
WLAN	Axial	6	-5.40	-48.46	-60.81	2.00	43.06	20.00	-23.06	T4	2.4, 3.0			
802.11ac	Radial	6	-13.25	-50.81	-60.53	N/A	37.56	20.00	-17.56	T4	2.4, 2.2			

Table 9-14
Raw Data Results for 5GHz WIFI 802.11a

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		20MHz	1	36	-5.20	-52.19		2.00	46.99	20.00	-26.99	T4	
		20MHz	1	40	-5.46	-51.56		2.00	46.10	20.00	-26.10	T4	
	Axial	20MHz	1	48	-5.50	-52.15	-60.81	2.00	46.65	20.00	-26.65	T4	2.4, 3.0
	Axiai	20MHz	2A	56	-5.46	-51.98	-00.01	2.00	46.52	20.00	-26.52	T4	2.4, 5.0
		20MHz	2C	120	-5.28	-52.62		2.00	47.34	20.00	-27.34	T4	
		20MHz	3	157	-5.31	-51.83		2.00	46.52	20.00	-26.52	T4	
802.11a													
		20MHz	1	40	-13.36	-49.20			35.84	20.00	-15.84	T4	
		20MHz	2A	52	-13.52	-49.93			36.41	20.00	-16.41	T4	
	Radial	20MHz	2A	56	-13.22	-48.88	-60.53		35.66	20.00	-15.66	T4	2.4, 2.2
	Naulai	20MHz	2A	64	-13.17	-50.05	-00.55		36.88	20.00	-16.88	T4	2.4, 2.2
		20MHz	2C	120	-13.17	-49.94	-49.94		36.77	20.00	-16.77	T4	
		20MHz	3	157	-13.24	-50.95			37.71	20.00	-17.71	T4	

FCC ID: ZNFG710VM	lename: Test Dates: D	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename: Test Dates:		DUT Type:		Page 34 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 34 01 67

# Table 9-15 Raw Data Results for 5GHz WIFI 802.11n

	Fraguerry Margin from												
Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	Δvial	40MHz	1	38	-5.23	-52.71	-60.81	2.00	47.48	20.00	-27.48	T4	2.4, 3.0
	Axial	20MHz	1	40	-5.48	-52.59	-00.61	2.00	47.11	20.00	-27.11	T4	2.4, 5.0
802.11n													
	Radial	40MHz	1	38	-13.24	-50.40	-60.53	N/Δ	37.16	20.00	-17.16	T4	2.4. 2.2
Radia	Naulai	20MHz	1	40	-13.22	-50.43		-60.53 N/A	37.21	20.00	-17.21	T4	2.4, 2.2

# Table 9-16 Raw Data Results for 5GHz WIFI 802.11ac

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)		Test Coordinates
	Avial	40MHz	1	38	-5.29	-52.43	-60.81	2.00	47.14	20.00	-27.14	T4	2.4, 3.0
	Axial	20MHz	1	40	-5.54	-52.01	-00.01	1.99	46.47	20.00	-26.47	T4	2.4, 5.0
802.11ac													
	Radial	40MHz	1	38	-13.32	-51.22	60.53	N/A	37.90	20.00	-17.90	T4	2,4, 2,2
Radial	20MHz	1	40	-13.72	-49.91 -60.53	-60.53 N/A	36.19	20.00	-16.19	T4	2.4, 2.2		

# Table 9-17 Raw Data Results for EvDO (OTT VoIP)

Frequency Margin from											
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
Secondary Cellular	Axial	564	9.47	-51.69	-60.81	1.82	61.16	20.00	-41.16	T4	2.4, 3.0
EvDO	Radial	564	2.32	-52.09	-60.53	N/A	54.41	20.00	-34.41	T4	2.4, 2.2
Cellular	Axial	384	9.32	-50.68	-60.81	1.78	60.00	20.00	-40.00	T4	2.4, 3.0
EvDO	Radial	384	2.42	-52.43	-60.53	N/A	54.85	20.00	-34.85	T4	2.4, 2.2
PCS	Axial	600	9.30	-51.48	-60.81	1.82	60.78	20.00	-40.78	T4	2.4, 3.0
EvDO	Radial	600	2.25	-52.64	-60.53	N/A	54.89	20.00	-34.89	T4	2.4, 2.2

# Table 9-18 Raw Data Results for EDGE (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
EDGE850	Axial	190	10.60	-34.33	-60.81	1.71	44.93	20.00	-24.93	T4	2.4, 3.0
EDGE050	Radial	190	2.10	-33.25	-60.53	N/A	35.35	20.00	-15.35	T4	2.4, 2.2
EDGE1900	Axial	661	10.06	-33.29	-60.81	1.76	43.35	20.00	-23.35	T4	2.4, 3.0
EDGE 1900	Radial	661	1.91	-33.16	-60.53	N/A	35.07	20.00	-15.07	T4	2.4, 2.2

# Table 9-19 Raw Data Results for HSPA (OTT VoIP)

	Naw Data Results 101 110FA (OT 1 VOIF)												
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates		
HSPA V	Axial	4183	9.62	-52.06	-60.81	1.85	61.68	20.00	-41.68	T4	2.4, 3.0		
пога у	Radial	4183	2.32	-52.35	-60.53	N/A	54.67	20.00	-34.67	T4	2.4, 2.2		
HSPA IV	Axial	1412	9.73	-52.32	-60.81	1.80	62.05	20.00	-42.05	T4	2.4, 3.0		
HOPAIV	Radial	1412	2.38	-51.39	-60.53	N/A	53.77	20.00	-33.77	T4	2.4, 2.2		
HSPA II	Axial	9400	10.29	-51.88	-60.81	1.76	62.17	20.00	-42.17	T4	2.4, 3.0		
HOPAII	Radial	9400	2.27	-51.77	-60.53	N/A	54.04	20.00	-34.04	T4	2.4, 2.2		

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 35 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 33 01 67

© 2018 PCTEST Engineering Laboratory, Inc.

## **Table 9-20** Raw Data Results for LTE B13 (OTT VoIP)

				,								
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	Avial	10MHz	23230	11.05	-45.91	-60.81	1.51	56.96	20.00	-36.96	T4	2.4, 3.0
LTE Band	LTE Band Axial	5MHz	23230	10.55	-47.08	-60.81	1.52	57.63	20.00	20.00 -37.63	T4	2.4, 3.0
13	Radial	10MHz	23230	2.25	-41.47	60.53	N/A	43.72	20.00	-23.72	T4	2.4. 2.2
	Radiai	5MHz	23230	2.29	-44.29	-60.53	IN/A	46.58	20.00	-26.58	T4	2.4, 2.2

## **Table 9-21** Raw Data Results for LTE B41 Power Class 2 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates	
		20MHz	40620	10.11	-39.72		1.78	49.83	20.00	-29.83	T4		
		15MHz	41490	9.61	-38.64		1.70	48.25	20.00	-28.25	T4		
		15MHz	41055	9.13	-40.46		1.64	49.59	20.00	-29.59	T4		
	Axial	15MHz	40620	9.58	-39.87	-60.81	1.77	49.45	20.00	-29.45	T4	2.4, 3.0	
	Axiai	15MHz	40185	9.33	-37.54	-00.01	1.77	46.87	20.00	-26.87	T4	2.4, 3.0	
		15MHz	39750	9.48	-45.54		1.83	55.02	20.00	-35.02	T4		
		10MHz	40620	9.72	-40.46	] [	1.81	50.18	20.00	-30.18	T4		
LTE Band		5MHz	40620	9.67	-40.45		1.79	50.12	20.00	-30.12	T4		
41		20MHz	40620	1.91	-39.07			40.98	20.00	-20.98	T4		
		15MHz	41490	2.42	-36.82			39.24	20.00	-19.24	T4		
		15MHz	41055	2.56	-40.25			42.81	20.00	-22.81	T4		
	Radial	15MHz	40620	2.38	-37.29	29 -60.53 N/A 12 -58 80	N/A	39.67	20.00	-19.67	T4	0.4.00	
	Radiai	15MHz	40185	2.18	-37.12		-60.53	IWA	39.30	20.00	-19.30	T4	2.4, 2.2
		15MHz	39750	2.27	-39.58			41.85	20.00	-21.85	T4		
		10MHz	40620	2.71	-37.80				40.51	20.00	-20.51	T4	
		5MHz	40620	2.37	-39.44			41.81	20.00	-21.81	T4		

## **Table 9-22** Raw Data Results for 2.4GHz WIFI (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1	9.58	-39.98		1.72	49.56	20.00	-29.56	T4	
	Axial	6	10.71	-39.16	-60.81	1.75	49.87	20.00	-29.87	T4	2.4, 3.0
WLAN		11	9.39	-40.26		1.76	49.65	20.00	-29.65	T4	
802.11b		1	2.26	-49.11			51.37	20.00	-31.37	T4	
	Radial	6	2.35	-48.91	-60.53	N/A	51.26	20.00	-31.26	T4	2.4, 2.2
		11	2.43	-49.22			51.65	20.00	-31.65	T4	
WLAN	Axial	6	9.64	-43.25	-60.81	1.78	52.89	20.00	-32.89	T4	2.4, 3.0
802.11g	Radial	6	2.10	-50.09	-60.53	N/A	52.19	20.00	-32.19	T4	2.4, 2.2
WLAN	Axial	6	9.60	-41.08	-60.81	1.72	50.68	20.00	-30.68	T4	2.4, 3.0
802.11n	Radial	6	2.05	-50.26	-60.53	N/A	52.31	20.00	-32.31	T4	2.4, 2.2
WLAN	Axial	6	9.71	-45.48	-60.81	1.72	55.19	20.00	-35.19	T4	2.4, 3.0
802.11ac	Radial	6	2.14	-50.36	-60.53	N/A	52.50	20.00	-32.50	T4	2.4, 2.2

FCC ID: ZNFG710VM	PETEST VANISHEE LADERTON, INC.	HAC (T-COIL) TEST REPORT	⊕ LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 36 of 87	
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 30 01 07	

# **Table 9-23** Raw Data Results for 5GHz WIFI 802.11a (OTT VoIP)

	Naw Data Results for SOLIZ WILL SUZ. I Ta (S						(	··· ,						
Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates	
		20MHz	1	36	9.52	-47.48		1.78	57.00	20.00	-37.00	T4	2.4, 3.0	
		20MHz	1	40	9.41	-47.58		1.81	56.99	20.00	-36.99	T4		
	Axial	20MHz	1	48	9.63	-48.93 -48.58 -48.10	-60.81	1.80	58.56	20.00	-38.56	T4		
	Axiai	20MHz	2A	56	9.35		-00.01	1.62	57.93	20.00	-37.93	T4		
		20MHz	2C	120	9.59			1.69	57.69	20.00	-37.69	T4		
		20MHz	3	157	9.55	-48.89		1.80	58.44	20.00	-38.44	T4		
802.11a														
		20MHz	1	40	2.41	-46.60			49.01	20.00	-29.01	T4		
		20MHz	2A	52	2.18	-46.33			48.51	20.00	-28.51	T4		
	Radial	20MHz	2A	56	2.19	-46.14	-60.53		48.33	20.00	-28.33	T4	2.4, 2.2	
	ixaulai	20MHz	2A	64	2.17	-46.21	-00.00		48.38	20.00	-28.38	T4	2.4, 2.2	
		20MHz	2C	120	2.22	-46.31			48.53	20.00	-28.53	T4		
		20MHz	3	157	2.14	-46.24			48.38	20.00	-28.38	T4		

### **Table 9-24** Raw Data Results for 5GHz WIFI 802.11n (OTT VolP)

			IVAV	Data N	Courto	01 001	12 **** 1 0	, v Z. i i i i	(011 4	,, ,			
Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	Axial	40MHz	1	38	9.61	-49.90	-60.81	1.67	59.51	20.00	-39.51	T4	2.4, 3.0
	Anai	20MHz	1	40	9.43	-49.26	-00.01	1.82	58.69	20.00	-38.69	T4	2.4, 3.0
802.11n													
	Radial	40MHz	1	38	2.66	-48.12	-60.53	N/A	50.78	20.00	-30.78	T4	2.4. 2.2
	Naulai	20MHz	1	40	2.40	-47.56	-00.55	IN/A	49.96	20.00	-29.96	T4	2.4, 2.2

# **Table 9-25** Raw Data Results for 5GHz WIFI 802.11ac (OTT VoIP)

Mod	Orientatio	n Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	Axial	40MHz	1	38	9.51	-50.55	-60.81	1.57	60.06	20.00	-40.06	T4	2.4, 3.0
	Axiai	20MHz	1	40	10.29	-49.06	-00.61	1.87	59.35	20.00	-39.35	T4	2.4, 5.0
802.1	ac												
	Radial	40MHz	1	38	2.15	-49.62	-60.53	N/A	51.77	20.00	-31.77	T4	2.4, 2.2
K	Radiai	20MHz	1	40	2.29	-48.27	-00.53	IN/A	50.56	20.00	-30.56		2.4, 2.2

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 37 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 37 01 07

#### II. **Test Notes**

#### A. General

- 1. Phone Condition: Mute on; Backlight off; Max Volume; Max Contrast
- 2. 'Radial' orientation refers to radial transverse.
- 3. Hearing Aid mode (Phone→Call Settings→More→Hearing aids) as well as Noise Suppression mode (Phone -> Call Settings -> More -> Noise Suppression) was set to ON for Frequency Response compliance.
- 4. Speech Signal: ITU-T P.50 Artificial Voice
- 5. Bluetooth and WIFI were disabled for 2G/3G/4G modes while testing.
- 6. Licensed data modes and Bluetooth were disabled for WIFI modes while testing.
- 7. The Margin from FCC limit column indicates a margin from the FCC limit for compliance (T3).

#### B. CDMA

- 1. Power Configuration: Power Control Bits = "All Up"
- 2. Vocoder Configuration: RC1/SO3 (CDMA EVRC)

#### C. GSM

- 1. Power Configuration: GSM850: PCL=5, GSM1900: PCL=0;
- 2. Vocoder Configuration: EFR (GSM);

#### D. UMTS

- 1. Power Configuration: TPC= "All 1s";
- 2. Vocoder Configuration: AMR 12.2 kbps (UMTS);

#### E. LTE FDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 64QAM, 1RB, 0RB offset
- 3. Vocoder Configuration: WB AMR 6.60kbps
- 4. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 66 at 5MHz is the worst-case for both Axial and Radial probe orientations.

### F. LTE TDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 64QAM, 1RB, 0RB offset
- 3. Power Class 3 Uplink-Downlink configuration: 2
- 4. Power Class 2 Uplink-Downlink configuration: 2
- 5. Vocoder Configuration: WB AMR 6.60kbps
- 6. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low, low-mid, mid-high and high channels for those combinations, LTE Band 41 (Power Class 2) at 5MHz is the worst-case for the Axial probe orientation. LTE Band 41 (Power Class 2) at 15MHz bandwidth is the worst-case for the Radial probe orientation.

FCC ID: ZNFG710VM	HAC (T-COIL) TEST REPORT		⊕ LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 38 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 30 01 07

#### G. WIFI

- 1. Radio Configuration
  - a. 802.11b: DSSS, 1Mbps
  - b. 802.11g/a: BPSK, 6Mbps
  - c. 802.11n/ac 20MHz: QPSK, 13Mbps
  - d. 802.11n/ac 40MHz: QPSK, 27Mbps
- 2. Vocoder Configuration: WB AMR 6.6kbps
- 3. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11b is the worst-case for both Axial and Radial probe orientations.
- 4. The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. 802.11a (U-NII 1) is the worst-case for the Axial probe orientation. 802.11a (U-NII 2A) is the worst-case for the Radial probe orientation.


#### H. OTT VolP

- 1. Vocoder Configuration: 64kbps
- 2. EvDO Configuration
  - a. Revision: A
- 3. EDGE Configuration
  - a. MCS Index: 7
  - b. Number of TX slots: 2
- 4. HSPA Configuration:
  - a. Release: 6
  - b. 3GPP 34.121 Subtest 1
- 5. LTE FDD Configuration:
  - a. Power Configuration: TPC = "Max Power"
  - b. Radio Configuration: 64QAM, 1RB, 0RB offset
  - c. LTE Band 13 was the worst-case band from Table 7-6 and was used for testing both Axial and Radial probe orientations.
  - d. The worst-case bandwidth for each probe orientation is additionally tested on the low and high channels for those bandwidths. LTE Band 13 at 10MHz is the worst-case for both Axial and Radial probe orientations but only supports one channel. Therefore, no additional testing was performed.
- 6. LTE TDD Configuration:
  - a. Power Configuration: TPC = "Max Power"
  - b. Radio Configuration: 64QAM, 1RB, 0RB offset
  - c. Power Class 2 Uplink-Downlink configuration: 2
  - d. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low, low-mid, high-mid, and high channels for those combinations. LTE Band 41 (Powers Class 2) at 15MHz is the worst-case for both Axial and Radial probe orientations.
- 7. WIFI Configuration:
  - a. Radio Configuration
    - i. 802.11b: DSSS, 1Mbps
    - ii. 802.11g/a: BPSK, 6Mbps
    - iii. 802.11n/ac 20MHz; QPSK, 13Mbps
    - iv. 802.11n/ac 40MHz: QPSK, 27Mbps
  - b. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11b is the worst-case for both Axial and Radial probe orientations.


FCC ID: ZNFG710VM	HAC (T-COIL) TEST REPORT		(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 39 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 39 01 67

c. The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. 802.11a (U-NII 1) is the worst-case for the Axial probe orientation. 802.11a (U-NII 2A) is the worst-case for the Radial probe orientation.


# III. 1 kHz Vocoder Application Check



This model was verified to be within the linear region for ABM1 measurements at -18 dBm0 for CDMA. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -16 dBm0 for GSM, UMTS, and VoLTE over IMS. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -20 dBm0 for VoWIFI over IMS and OTT VoIP. This measurement was taken in the axial configuration above the maximum location.

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 40 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 40 01 07

# IV. T-Coil Validation Test Results

Table 9-26
Helmholtz Coil Validation Table of Results – 3/14/2018

ltem	Target	Result	Verdict
Axial			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.165	PASS
Environmental Noise	< -58 dBA/m	-61.05	PASS
Frequency Response, from limits	> 0 dB	0.80	PASS

Table 9-27
Helmholtz Coil Validation Table of Results – 3/21/2018

	Tielininoitz don vandation Table of Results – 5/21/2010								
Item	Target	Result	Verdict						
Axial									
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.171	PASS						
Environmental Noise	< -58 dBA/m	-60.81	PASS						
Frequency Response, from limits	> 0 dB 0.80		PASS						
Radial									
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.264	PASS						
Environmental Noise	< -58 dBA/m	-60.53	PASS						
Frequency Response, from limits	> 0 dB	0.80	PASS						

FCC ID: ZNFG710VM	HAC (T-COIL) TEST REPORT		<u>ு</u> டி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 41 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 410101

#### **ABM1 Magnetic Field Distribution Scan Overlays** ٧.




Figure 9-1 **T-Coil Scan Overlay Magnetic Field Distributions** 

### Notes:

- 1. Final measurement locations are indicated by a cursor on the contour plots.
- 2. See Test Setup Photographs for actual WD overlay.

FCC ID: ZNFG710VM	PCTEST'	HAC (T-COIL) TEST REPORT	<b>்</b> டு	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 42 of 87
1M1802260032-12-R5 7NF	03/14/2018 - 03/29/2018	Portable Handset		Faye 42 01 67

© 2018 PCTEST Engineering Laboratory, Inc.

**REV 3.2.M** 

# 10. MEASUREMENT UNCERTAINTY

Table 10-1
Uncertainty Estimation Table

Contribution	Data +/- %	Data +/- dB	Data Type	Probability distribution	Divisor	Standard uncertainty	Standard Uncertainty (dB)	
ABM Noise	7.0%	0.29	Std. Dev.	Normal k=1	1.00	7.0%		
RF Reflections	4.7%	0.20	Specification	Rectangular	1.73	2.7%		
Reference Signal Level	12.2%	0.50	Specification	Rectangular	1.73	7.0%		
Positioning Accuracy	10.0%	0.41	Uncertainty	Rectangular	1.73	5.8%		
Probe Coil Sensitivity	12.2%	0.50	Specification	Rectangular	1.73	7.0%		
Probe Linearity	2.4%	0.10	Std. Dev.	Normal k=1	1.00	2.4%		
Cable Loss	2.8%	0.12	Specification	Rectangular	1.73	1.6%		
Frequency Analyzer	5.0%	0.21	Specification	Rectangular	1.73	2.9%		
System Repeatability	5.0%	0.21	Std. Dev.	Normal k=1	1.00	5.0%		
WD Repeatability	9.0%	0.37	Std. Dev.	Normal k=1	1.00	9.0%		
Positioner Accuracy	1.0%	0.04	Specification	Rectangular	1.73	0.6%		
Combined standard uncertainty	Combined standard uncertainty, uc (k=1)							
Expanded uncertainty (k=2),	95% conf	idence le	/el			35.3%	1.31	

#### Notes:

- 1. Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297.
- All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.

Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid compatibility tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	டுடி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 43 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 43 01 01

# 11. EQUIPMENT LIST

Table 11-1 Equipment List

Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Latitude E6540	SoundCheck Acoustic Analyzer Laptop	4/11/2017	Annual	4/11/2018	7BFNM32
SoundConnect	Microphone Power Supply	N/A		N/A	0899-PS150
SoundConnect	Microphone Power Supply	12/2/2016	Biennial	12/2/2018	PS2612
Fireface UC	Soundcheck Acoustic Analyzer External Audio Interface	4/11/2017	Annual	4/11/2018	23528889
CMW500	Wideband Radio Communication Tester	1/19/2018	Annual	1/19/2019	162125
CMW500	Radio Communication Tester	7/14/2017	Annual	7/14/2018	140144
CMU200	Base Station Simulator	4/11/2017	Annual	4/11/2018	836371/0079
NC-100	Torque Wrench (8" lb)	9/1/2016	Biennial	9/1/2018	21053
C63.19	Helmholtz Coil	12/7/2016	Biennial	12/7/2018	925
Radial T-Coil Probe	Radial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1130
Axial T-Coil Probe	Axial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1124
	HAC System Controller with Software	N/A		N/A	N/A
	HAC Positioner	N/A		N/A	N/A

FCC ID: ZNFG710VM	PCTEST*	HAC (I-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 44 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 44 01 07

# 12. TEST DATA

FCC ID: ZNFG710VM	PCTEST	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 45 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 45 of 67



DUT: HH Coil - SN: 925


Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


#### Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

#### **Noise Spectrum**



# Frequency Response



#### Results

Verification 1kHz Intensity	-10.165 dB	•	Max/Min	-9.5/-10.5	
Verification ABM2	-61.05 dB	•	Maximum	-58.0	
Frequency Response Margin	800m dB	$\checkmark$	Tolerance curves	Aligned Data	

FCC ID: ZNFG710VM	PCTEST	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 46 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 40 of 67



DUT: HH Coil - SN: 925


Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


#### Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

#### **Noise Spectrum**



# Frequency Response



#### Results

Verification 1kHz Intensity	-10.171 dB	•	Max/Min	-9.5/-10.5	
Verification ABM2	-60.81 dB	•	Maximum	-58.0	
Frequency Response Margin	800m dB	$\checkmark$	Tolerance curves	Aligned Data	

FCC ID: ZNFG710VM	PETEST VANISHEEMS LANGESTON, INC.	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 47 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 47 01 67



DUT: HH Coil - SN: 925

Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


#### Equipment:

**Noise Spectrum** 


Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Helmholtz Coil – SN: 925; Calibrated: 12/07/2016

# -50.0 -55.0 -60.0



### Frequency Response



#### Results

Verification 1kHz Intensity	-10.264 dB	$\checkmark$	Max/Min	-9.5/-10.5
Verification ABM2	-60.53 dB	$\checkmark$	Maximum	-58.0
Frequency Response Margin	800m dB	$\checkmark$	Tolerance curves	Aligned Data

FCC ID: ZNFG710VM	PETEST VANISHEEMS LANGESTON, INC.	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 48 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 40 01 07



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

#### Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: CDMA Secondary Cellular

Channel: 564

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	<u>்</u> டி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 49 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 49 01 01



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

#### Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: CDMA Cellular

Channel: 777

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 50 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 30 01 67



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

#### Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: CDMA PCS

Channel: 25

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	<u>ு</u> டி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 51 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 31 01 07



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011


#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: GSM850Channel: 251

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	PETEST VANISHEEMS LANGESTON, INC.	HAC (T-COIL) TEST REPORT	⊕ LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 52 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 32 01 07



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011


#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: GSM1900Channel: 661

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	<u>ு</u> டி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 53 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 55 01 67



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011


#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: UMTS VChannel: 4233

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	<u>ு</u> டி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 54 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 54 01 07



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011


#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: UMTS IVChannel: 1513

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	<u>்</u> டி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 55 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 33 01 07



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011


#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: UMTS IIChannel: 9538

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	HAC (T-COIL) TEST REPORT		(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 56 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 50 01 67



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011


#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: LTE FDD Band 66Bandwidth: 5MHzChannel: 132647

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	PETEST	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 57 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 37 01 07



Type: Portable Handset Serial: 07215


Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

- Mode: LTE TDD Band 41 (PC2)
- Bandwidth: 5MHz
- Channel: 40185
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	PCTEST'	HAC (T-COIL) TEST REPORT	<b>(1)</b> LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 58 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 30 01 01



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

#### Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: 2.4GHz WIFIStandard: IEEE 802.11b

Channel: 1

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	PETEST VANISHEEMS LANGESTON, INC.	HAC (T-COIL) TEST REPORT	(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 59 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 39 01 67



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: 5GHz WIFI (U-NII 1)


Bandwidth: 20MHz

Standard: IEEE 802.11a

Channel: 40

Speech Signal: ITU-T P.50 Artificial Voice

# Noise Spectrum 10.0-0.0 -10.0 -20.0 --20.0 --30.0 --40.0 --90.0 --60.0 -70.0 -80.0 -90.0 -[Hz] Frequency Response 10.0 -7.5 5.0 25.



ABM1	-5.46	dB	•	Minimum	-18.0
ABM2	-51.56	dB	V	Maximum	0
SNNR	46.1	dB	<b>✓</b>	Minimum	20
Aligned Response - P.50	2	dB	$\checkmark$	Tolerance curves	Aligned Data

FCC ID: ZNFG710VM	HAC (T-COIL) TEST REPORT		(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 60 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 60 01 67



Type: Portable Handset Serial: 07215


Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

- VolP Application: Google Duo
- Mode: EDGE1900
- Channel: 661
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710VM	PETEST'	HAC (T-COIL) TEST REPORT	<b>(1)</b> LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 61 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 01 01 07



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

# Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: CDMA Secondary Cellular

Channel: 476



FCC ID: ZNFG710VM	PCTEST*	HAC (I-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 62 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 02 01 07



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011


# Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

 Mode: CDMA Cellular · Channel: 777

#### Noise Spectrum



#### Results

ABM1	-4.48 dB	Minim	-18.0	
ABM2	-42.59 dB	Maxim	num 0.0	
SNNR	38.11 dB	Minim	oum 20.0	

FCC ID: ZNFG710VM	PCTEST*	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 63 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 03 01 07



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

# Equipment:

ABM2

SNNR

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: CDMA PCSChannel: 25



-44.37 dB

40.43 dB

0

20

Maximum

Minimum

FCC ID: ZNFG710VM	PETEST	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 64 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 04 01 67



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

# Equipment:

ABM2

SNNR

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: GSM850Channel: 251



-29.68 dB

24.33 dB

0.0

20.0

Maximum

Minimum

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 65 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 03 01 67



Type: Portable Handset Serial: 07215


Measurement Standard: ANSI C63.19-2011

# Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: GSM1900Channel: 661



FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 66 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 60 01 67



Type: Portable Handset Serial: 07215


Measurement Standard: ANSI C63.19-2011

# Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: UMTS V
Channel: 4233



#### Results

-90.0 -100

ABM1	-6.54 dB	$\checkmark$	Minimum	-18.0
ABM2	-52.33 dB	•	Maximum	0.0
SNNR	45.79 dB	•	Minimum	20.0

1k [Hz]

FCC ID: ZNFG710VM	PCTEST*	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 67 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 07 01 07



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

# Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

### **Test Configuration:**

Mode: UMTS IVChannel: 1412



FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 68 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 66 01 67



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

# Equipment:

SNNR

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

### **Test Configuration:**

Mode: UMTS IIChannel: 9538



45.53 dB

20.0

Minimum

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	<u>்</u> டி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 69 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 69 01 67



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

 Mode: LTE FDD Band 66 Bandwidth: 5MHz Channel: 132322

#### Noise Spectrum



33.37 dB

Minimum

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	(t) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 70 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 70 01 67



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: LTE TDD Band 41 (PC2)

Bandwidth: 15MHzChannel: 41490

#### Noise Spectrum

SNNR



24.74 dB

20.0

Minimum

FCC ID: ZNFG710VM	PCTEST*	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 71 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye / 1 01 0/



Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

# Equipment:


Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

 Mode: 2.4GHz WIFI Standard: IEEE 802.11b

Channel: 6

#### Noise Spectrum



### Results

ABM1	-13.98 dB	$\checkmark$	Minimum	-18.0
ABM2	-50.6 dB	$\checkmark$	Maximum	0
SNNR	36.61 dB	$\checkmark$	Minimum	20

FCC ID: ZNFG710VM	PETEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 72 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 12 01 01



### **DUT: ZNFG710VM**

Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: 5GHz WIFI (U-NII 2A)

Bandwidth: 20MHzStandard: IEEE 802.11a

Channel: 56



#### PCTEST 2018

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 73 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		raye 13 01 01



### **DUT: ZNFG710VM**

Type: Portable Handset Serial: 07215

Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

VolP Application: Google Duo

Mode: EDGE1900Channel: 661



SNNR



35.07 dB

20.0


Minimum

#### PCTEST 2018

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 74 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Faye 14 01 01

# 13. CALIBRATION CERTIFICATES

FCC ID: ZNFG710VM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 75 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 75 01 67



FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 76 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		raye 10 01 01

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 01/11/2018

### HCATEMC\_TEM 1124\_Dec-07-2016



ISO/IEC 17025; 2005

1575 State Route 96, Victor NY 14564

Calibration Lab. Cert. # 1533.01

# REPORT OF CALIBRATION

**TEM Consulting LP Axial T Coil Probe** Model No.: Axial T Coil Probe Serial No.: TEM 1124

Company: PCTEST Engineering Lab. I. D. No: 80578

Probe Sensitivity measured with	Heimhalt	z Co11			
Helmholtz Coil;			Before & afte	r data same	: X
the number of turns on each coil;	10	No.			
the radius of each coil, in meters;	0.204	m	Laboratory Environ	ment:	
the current in the coils, in amperes.;	0.09	A	Ambient Temperature:	20.2	°C
Helmholtz Coll Constant;	7.09	A/m/V	Ambient Humidity:	31.4	% RH
Helmholtz Coil magnetic field;	5.98	A/m	Ambient Pressure:	99.1	кP«
			Calibration Date:	7-D•c-16	
Probe Sensitivity at	1000	H₂.			
Was	-60.23	a BV/A/m	Report Number:	27068	-3
	0.974	m V/A/m	Control Number:	27068	
Probe resistance	904	Onm.			

Graph represents Probes Frequency Response.

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.

Axial Probe Response Measured Probe Resp. 20 15 10 Magnitude (dB) 5 0 -5 -10 -15 10000 Freq. (Hz)

The above listed instrument was checked using calibration procedure documented in West Caldwell Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC Calibration Laboratories Inc. procedure :

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements or ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 7-Dec-2016 Measurements performed by: Felix Christopher Calibrated on WCCL system type 9700 Ray. 7.0 Jan. 24, 2014 Day. # 1038 HCATEMC

### Page 1 of 2

FCC ID: ZNFG710VM	PETEST	HAC (1-COIL) 1EST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 77 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Page 11 01 61

© 2018 PCTEST Engineering Laboratory, Inc.

### HCATEMC\_TEM 1124\_Dec-07-2016

### West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

## Calibration Data Record

Model No.: Axial T Coil Probe TEM Consulting LP Axial T Coil Probe Serial No.: TEM 1124

Company: PCTEST Engineering Lab.

Test	Function	Tolera	nce	Me	easured valu	ies
				Before	Out	Remarks
1.0	Probe Sensitivity at	1000 Hz.	d BV/A/m	-60.23		
			aВ			
2.0	Probe Level Linearity		6	6.03		
		R•f. (0 aB)	0	0.00		
			-6	-6.03		
			-12	-12.05		
			Hz			
3.0	Probe Frequency Response		100	-19.8		
			126	-18.0		
			158	-16.0		
			200	-13.9		
			251	-12.0		
			316	-9.9		
			398	-8.0		
			501	-6.0		
			631	-4.0		
			794	-2.0		
		Ror. (0 a B)	1000	0.0		
			1259	2.0		
			1585	4.0		
			1995	6.0		
			2512	7.9		
			3162	9.9		
			3981	11.9		
			5012	13.9		
			6310	15.9		
			7943	18.0		
			10000	20.2		

Instruments used for calibr	etion:		Date or Cal.	Traceability No.	Du o Doto
HP	34401A	S/N 36064102	1-Oct-2016	,287708	1-Oot-2017
HP	34401A	S/N 36102471	1-Oct-2016	,287708	1-Oct-2017
HP	33120A	S/N 36043716	1-Oct-2016	.287708	1-Oct-2017
B&K	2133	S/N 1583254	1-Oat-2016	683/284413-14	1-Oot-2017

Cal. Date: 7-Dec-2016

Tested by: Felix Christopher

Calibrated on WCCL system type 9700


Rav. 7.0 Jan. 24, 2014 Dac. # 1038 HCATEMC

### Page 2 of 2

FCC ID: ZNFG710VM	PETEST	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 78 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 70 01 67

© 2018 PCTEST Engineering Laboratory, Inc.

**REV 3.2.M** 



FCC ID: ZNFG710VM	PETEST:	HAC (T-COIL) TEST REPORT	LG.	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 79 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 19 01 01



ISO/IEC 17025; 2005

1575 State Route 96, Victor NY 14564

Calibration Lab. Cert. # 1533.01

Ray. 7.0 Jan. 24, 2014 Day. # 1038 HORTEMO


## REPORT OF CALIBRATION

**TEM Consulting LP Radial T Coil Probe** Model No.: Radial T Coil Probe Serial No.: TEM-1130

Company: PCTEST Engineering Lab. I. D. No: 80579

Probe Sensitivity measured wit	h Helmholt	:z Co11			
Helmholtz Coil;			Before & afte	r data same	: <b>X</b>
the number of turns on each coil;	10	No.			
the radius of each coil, in meters;	0.204	m	Laboratory Environ	ment:	
the current in the coils, in amperes.;	0.09	A	Ambient Temperature:	20.2	°C
Helmholtz Coll Constant;	7.09	A/m/V	Ambient Humidity:	31.4	% RH
Helmholtz Coil magnetic field;	5.98	A/m	Ambient Pressure:	99.1	кP«
			Calibration Date:	7-D•c-16	
Probe Sensitivity at	1000	Hz.			
was	-60.27	a BV/A/m	Report Number:	27068	-2
	0.969	m V/A/m	Control Number:	27068	
Proberenistance	902	Oh m •			
above listed instrument meets or o	exceeds th	ne tested manufact	urer's specifications.		
Calibration is traceable through NIST test number:	s:	683/284413-14	•		

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC Calibration Laboratories Inc. procedure :

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements or ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 7-Dec-2016 Measurements performed by: Felix Christopher Calibrated on WCCL system type 9700

### Page 1 of 2

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT	⊕ LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 80 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 60 01 67

© 2018 PCTEST Engineering Laboratory, Inc.

### HCRTEMC\_TEM-1130\_Dec-07-2016

### West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

## Calibration Data Record

TEM Consulting LP Radial T Coil Probe

Model No.: Radial T Coil Probe

Serial No.: TEM-1130

Company: PCTEST Engineering Lab.

Test	Function	ction Tolera		Measured values		
				Before	Out	Remarks
1.0	Probe Sensitivity at	1000 Hz.	d BV/A/m	-60.27		
			aВ	2.22		
2.0	Probe Level Linearity	D (0 D)	6	6.03		
		R•f. (0 a B)	0	0.00		
			-6	-6.03		
			-12	-12.06		
			Hz			
3.0	Probe Frequency Response		100	-19.9		
			126	-18.0		
			158	-16.0		
			200	-13.9		
			251	-12.0		
			316	-10.0		
			398	-8.0		
			501	-6.0		
			631	-4.0		
		Ror. (0 a B)	794	-2.0		
		Ref. (U d D)	1000 1259	0.0 2.0		
			1585	4.0		
			1995	6.0		
			2512	7.9		
			3162	9.9		
			3981	11.9		
			5012	13.9		
			6310	15.9		
			7943	18.0		
			10000	20.2		

Instruments used for calibr	etion:		Date of Col.	Traceability No.	Due Dete
HP	34401A	S/N 36064102	1-Oct-2016	,287708	1-Oct-2017
HP	34401A	S/N 36102471	1-Oct-2015	,287708	1-Oct-2017
HP	33120A	S/N 36043716	1-Oct-2016	.287708	1-Oct-2017
B&K	2133	S/N 1583254	1-Oat-2016	683/284413-14	1-Oot-2017

Cal. Date: 7-Dec-2016

Tested by: Felix Christopher

Calibrated on WCCL system type 9700

Rav. 7.0 Jan. 24, 2014 Dac. # 1038 HCRTEMC

### Page 2 of 2

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 81 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		raye or or or

© 2018 PCTEST Engineering Laboratory, Inc.

**REV 3.2.M** 

### 14. CONCLUSION

The measurements indicate that the wireless communications device complies with the HAC limits specified in accordance with the ANSI C63.19 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

The measurement system and techniques presented in this evaluation are proposed in the ANSI standard as a means of best approximating wireless device compatibility with a hearing-aid. The literature is under continual re-construction.

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 82 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		Fage 02 01 01

#### 15. REFERENCES

- ANSI C63.19-2011, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids.", New York, NY, IEEE, May 2011
- FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v05," September 13, 2017
- FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017 3.
- FCC Public Notice DA 06-1215, Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard, June 6, 2006
- 5 FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
- Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 6.
- Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," Wireless Telephones and Hearing Aids: New Challenges for Audiology, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
- Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices, "IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
- Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
- 10. Byme, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, Ear and Hearing 7:257-265, 1986.
- 11. Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells, " U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
- 12. Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1013, July 1981,
- EHIMA GSM Project, Development phase, Project Report (1st part) Revision A. Technical-Audiological Laboratory and Telecom Denmark, October 1993.
- 14. EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.
- 15. EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
- 16. HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.
- 17. Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
- 18. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
- Joyner, K. H, et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
- Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
- 21. Kecker, W. T., Crawford, M. L., and Wilson, W. A., "Contruction of a Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Nov. 1978.

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 83 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 63 01 67

- 22. Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7<sup>th</sup> International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.
- 23. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
- 24. Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
- 25. Ma, M. A., Sreenivashiah, I., and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technial Note 1040, July 1981.
- 26. McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
- 27. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
- Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January 1993.
- 29. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
- 30. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

FCC ID: ZNFG710VM	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 84 of 87
1M1802260032-12-R5.ZNF	03/14/2018 - 03/29/2018	Portable Handset		rage 64 01 67