



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR
352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	MIDLAND RADIO CORPORATION
	5900 PARRETTA DRIVE KANSAS CITY MISSOURI 64120 USA
FCC ID	MMAMXT115
MODEL NUMBER	MXT115
PRODUCT DESCRIPTION	MOBILE GMRS TRANSCEIVER
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Cory Leverett

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669



Authorized Signatory Name:

Cory Leverett

Engineering Project Manager

Date: 10/24/2016

Applicant: MIDLAND RADIO CORPORATION

FCC ID: MMAMXT115

Report: V:\M\MIDLAND_MMA\1998AUT16\1998AUT16RF EXP MPE RPT.DOCX

RF Exposure Requirements

General information

Device type: MOBILE GMRS TRANSCEIVER

Antenna

Configuration	Antenna p/n	Type	Max. Gain (dBi)
Fixed mounted	Any	Unity	2.15

Operating configuration and exposure conditions:

The conducted output power is shown in the table below. Typical use qualifies for a maximum duty cycle factor of 100%.

MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.11310, Table 1.

Applicant: MIDLAND RADIO CORPORATION

FCC ID: MMAMXT115

Report: V:\M\MIDLAND_MMA\1998AUT16\1998AUT16RF EXP MPE RPT.DOCX

Minimum Separation Distance for Mobile or Fixed Devices General Population/Uncontrolled Exposure					
---	--	--	--	--	--

Insert values in yellow highlighted boxes to determine Minimum Separation Distance

Max Power	20.65	W	<i>equals</i>	Max Power	20650	mW
Duty Cycle	50	%	<i>equals</i>	Duty Factor	0.5	numeric
Antenna Gain	2.15	dBi	<i>equals</i>	Gain numeric	1.64059	numeric
Coax Loss	0	dB		Gain - Coax Loss	1.64059	numeric
Power Density	0.3	mW/cm ²				

Enter power Density from the chart to the right

Rule Part 1.1310, Table 1 (B)

Frequency	467.725	MHz		Frequency range	Power density	Enter this value
				MHz	mW/cm²	mW/cm²
				0.3-1.34	100	100
				1.34-30	180/f ²	0.0
				30-300	0.2	0.2
				300-1,500	f/1500	0.3
				1,500-100,000	1	1

f = frequency in MHz

Minimum Separation Distance	67 cm	0.67 m
------------------------------------	--------------	---------------

Minimum Separation in Inches 26.37022 Inches