

MPE REPORT

Report No.: SRTC2019-9004(F)- 19012903(I)

Product Name: Fi Smart Collar - Charging Base

Product Model: FB1

Applicant: Barking Labs Corp.

Manufacturer: Barking Labs Corp.

Specification: FCC Part §2.1091, §2.1093, §1.1307(b), §1.1310

FCC ID: 2ARXN-FB1

The State Radio_monitoring_center Testing Center (SRTC)

No.80 Beilishi Road Xicheng District Beijing, China

Tel: 86-10-57996181 Fax: 86-10-57996288

CONTENTS

<u>1 GENERAL INFORMATION</u>	2
1.1 NOTES OF THE TEST REPORT	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY	2
1.3 APPLICANT'S DETAILS	2
1.4 MANUFACTURER'S DETAILS	2
<u>2 DESCRIPTION OF THE DEVICE UNDER TEST</u>	3
2.1 FINAL EQUIPMENT BUILD STATUS	3
<u>3 REFERENCE SPECIFICATION</u>	4
<u>4 RESULT SUMMARY</u>	5
<u>5 TEST RESULTS</u>	6
5.1 AVERAGE POWER OUTPUT	6
5.2 CALCULATION RESULT	9

1 GENERAL INFORMATION

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, Beijing P.R. China
City:	Beijing
Country or Region:	P.R. China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiaf@srtc.org.cn

1.3 Applicant's details

Company:	Barking Labs Corp.
Address:	53 Bridge St., Suite 103
City:	Brooklyn, NY
Country or Region:	USA
Contacted person:	Bob Blake
Tel:	+1-914-249-9347
Fax:	---
Email:	bob@tryfi.com

1.4 Manufacturer's details

Company:	Barking Labs Corp.
Address:	53 Bridge St., Suite 103
City:	Brooklyn, NY
Country or Region:	USA
Contacted person:	Bob Blake
Tel:	+1-914-249-9347
Fax:	---
Email:	bob@tryfi.com

2 DESCRIPTION OF THE DEVICE UNDER TEST

2.1 Final Equipment Build Status

Bluetooth BLE

Frequency Range	2.402GHz~2.480GHz
Number of Channel	40
Modulation Type	GFSK
Channel Spacing	2MHz
Data Rate	1Mbps
Power Supply	Charger
Antenna Type	PCB Antenna
Antenna Gain	0.9 dBi
HW Version	Rev.A
SW Version	1.0

WLAN



Operating Band(s):	2.412GHz~2.462GHz
Number of Channel For 20MHz	11
Modulation Type:	DBPSK/DQPSK/CCK/BPSK/QPSK/16QAM/64QAM
Duplex Mode	TDD
Channel Spacing	5MHz
Data Rate	802.11b:1Mbps-11Mbps 802.11g:6Mbps-54Mbps 802.11n HT20:MCS0-MCS7
Power Supply	Charger
Antenna Type	PCB Antenna
Antenna Gain	0.9 dBi
Software Revision:	1.0
Hardware Revision:	Rev.A

3 REFERENCE SPECIFICATION

Specification	Version	Title
2.1091	Sept. 20, 2017	Radiofrequency radiation exposure evaluation: mobile devices.
2.1093	Sept. 20, 2017	Radiofrequency radiation exposure evaluation: portable devices.
1.1307(b)	Apr. 22, 1986	Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.
1.1310	June 4, 2013	Radiofrequency radiation exposure limits.
KDB447498	October 23, 2015	RF exposure procedures and equipment authorization policies for mobile and portable devices

4 RESULT SUMMARY

No.	Test case	FCC reference
1	MPE Calculation	FCC Part §2.1091, FCC Part §2.1093, FCC Part §1.1307(b) FCC Part §1.1310 KDB 447498

This Test Report Is Issued by: Mr. PENG Zhen 	Checked by: Mr. LI Bin 
Tested by: Mr. CHANG Tianyu 	Issued date: 20190301

SS

5 TEST RESULTS

5.1 Average Power Output

5.1.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

5.1.2 Test Description

A transmitter antenna terminal of EUT is connected to the power meter. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

5.1.3 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v04 – Section 9.2.3

5.1.4 Test Settings

The maximum average conducted output power may be measured using a broadband average RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.

2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.

3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.


b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.

c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

d) Adjust the measurement in dBm by adding $10\log(1/x)$, where x is the duty cycle to the measurement result.

5.1.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



5.1.6 Test Result

BT BLE output power

Modulation type	Average Power Output (dBm)		
	2402MHz (Ch0)	2440MHz (Ch19)	2480MHz (Ch39)
GFSK (LE 1Mbps)	2.22	2.36	2.14

2.4GHz Output Power test result

Modulation type	Average power output (dBm)		
	2412MHz	2437MHz	2462MHz
11b	16.98	16.84	17.52
11g	16.26	15.89	16.78
11n HT20	16.02	15.74	16.65

5.2 Calculation result

FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

(A) Limits for Occupational/Controlled Exposure ☐

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

(B) Limits for General Population/Uncontrolled Exposure ☒

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz *Plane-wave equivalent power density

Calculation procedure:

According to §2.1091, §2.1093, §1.1307(b) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The $S = PG / (4\pi R^2)$

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Mode/Band	Freq (GHz)	Power		Antenna Gain		R (cm)	S (mW/cm ²)	Limits (mW/cm ²)
		(dBm)	(mW)	(dBi)	(Numeric)			
BLE	2.440	2.36	1.72	0.9	1.23	20	0.0004	1.00
WLAN/2.4GHz	2.462	17.52	56.49	0.9	1.23	20	0.013	1.00

Note: 1mW/cm² from §1.1310 Table 1.

According to the KDB447498 D01 section 7.1 determine the device is exclusion from SAR test.

---End of Test Report---