

CUSTOMER

KFT-107

ROHS

SPECIFICATION FOR APPROVAL

MODEL NO. : RC 25X2.5-12mm-10.1uH-01

KEFEITE NO. : 107-RC25X2.5-0.08X24PX14TS-35mm-10.1uH-01

CUSTOMER P/N: M16S

DATE : 2022/09/30

REV : A1

※产品符合: ☒RoHS ☐PAHS ☐6P ☐REACH

PLEASE RETURN TO US COPY OF "SPECIFICATION FOR APPROVAL" WITH YOUR APPROVED SIGNATURES.

	"√"	CUSTOMER'S SIGNATURE	NOTE
FULL APPROVED			
CONDITIONAL APPROVED			
REJECTED			

SHENZHEN KEFEITE ELELECTRONICS CO., LTD

FactoryAddress:2/F, Guantiancommunity, Shenzhen. New era industrial area
C Building

TEL:86-755-27352660

FAX:86-755-27352742

HTTP:WWW.Kefeite.net



SHENZHEN KEFEITE ELECTRONICS CO., LTD

[illegible]


NOTES :



SHENZHEN KEFEITE ELECTRONICS CO., LTD

CUSTOMER:	KFT-107	VERSION:	A1
CUSTOMER NO:	M16S	PAGE:	3/5
KFT P/N:	107-RC25X2.5-0.08X240X14TS-35mm-10.1uH-01	Date:	2022/09/30

1. CONFIGURATION&DIMENSIONS:

	A	14.1±0.2mm
	B	20±0.2mm
	C	25.0mm MAX
	D	35±1.5mm
	E	2~4mm
	F	2.8mm MAX

1. Outgo line: cross outgoing line, pasted reversely on the magnetic sheet

2. Magnet is installed in the center hole with the "s" Pole facing upwards (7.8x2.5mm≥3200GS)


3. Double sided adhesive tape on the back of the product

4. F Size thickness does not include release paper

2. ELECTRICAL CHARACTER:

PROJECT	SPECIFICATIONS	TEST CONDITIONS	TEST INSTRUMENT
(Ls) Coil	4.8±10%uH	100KHZ/1.0V	CH1062
(Ls)Coil+Core	10.1±10%uH	100KHZ/1.0V	CH1062
(RDC)	≤280mΩ	At:25℃	HG2512

3. SCHEMATIC



4. PART NUMBERING:PRODUCT IDENTIFICATION

107 RC25X2.5 0.08X24PX14TS 35mm 10.1uH01

Serial number
Inductance
Line Length
Wire Diameter
Magnetic Sheet Specification
Customer number

DRAWN BY:	CHECKED BY:	Q. C DEPT:	APPROVED BY:
FI GO	QIONJINFU		W. J. J



SHENZHEN KEFEITE ELECTRONICS CO., LTD

CUSTOMER:	KFT-107	VERSION:	A1
CUSTOMER NO:	M16S	PAGE:	4/5
KFT P/N:	107-RC25X2.5-0.08X240X14TS-35mm-10.1uH-01	Date:	2022/09/30

5. MATERIAL LIST:

NO	ITEM	DESCRIPTION	RATING	SUPPLIERS	UL NO.	REMARK
1	WIRE	Acetone line	155℃	SHANTOU SHENGANG ELECTRICAL INDUSTRIAL CO., LTD	E239508	
2	SOLDER	99.3/0.7		SHENZHEN Hong Xing Wei solder Limited		
3	CORE	25/7.7/2.5		Changxing BO Cheng Electronics CO., LTD		
4	EPOXY	1603HFR-HS		DONGBU FINE CHEMICAL CO LTD		
5	Strong Magnet	7.8X2.5>3000GS		DONGBU FINE CHEMICAL CO LTD		

6. GENERAL SPECIFICATION:

- 1 Tested at 1.0KHZ/0.25Vrms, 0 Adc.
Average current for 40℃ temperature rise from 25℃.
- 2 Saturation current(Isat):
Inductance drop:10% typ at Isat.
- 3 Heat rating current(Irms):
 $L@I_{rms} = \Delta T \leq 40^{\circ}\text{C}$.
- 4 Electrical specifications at 25℃
- 5 Storage Temp:-40℃....+85℃
- 6 Operating Temp:-40℃....+85℃

DRAWN BY:	CHECKED BY:	Q. C DEPT:	APPROVED BY:
FI GO	QIONJINFU		W. J. J 