

FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data (worst case):

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
Wi-Fi 802.11b	2412-2462	2.0	1.58	19.00	79.43	20	0.0250	1.0
Wi-Fi 802.11g		2.0	1.58	18.50	70.79	20	0.0222	1.0
Wi-Fi 802.11n-HT20		2.0	1.58	18.00	63.10	20	0.0198	1.0
Wi-Fi 802.11n-HT40	2422-2452	2.0	1.58	15.50	35.48	20	0.0112	1.0
BLE	2402-2480	2.0	1.58	4.50	2.82	20	0.0009	1.0
BT	2402-2480	2.0	1.58	7.00	5.01	20	0.0016	1.0

Note 1: Wi-Fi and BT /BLE cannot transmit simultaneously.

Note 2: The tune-up is declared by manufacturer.

Conclusion: The device meets MPE at distance 20cm.