

APPLICANT

X-10 USA, Inc.
19823, 58th Place S.
Kent, WA 98032

MANUFACTURER

X-10 Electronics Shenzhen Co. Ltd.
X-10 Building
Labour Industrial District
Shenzhen, Xixiang, Bao An
Guang Dong, China, 518102

TEST SPECIFICATION: FCC Rules and Regulations Part 15, Subpart C, Para. 15.231

TEST PROCEDURE: ANSI C63.4:2001

TEST SAMPLE DESCRIPTION

BRANDNAME: X-10 USA, Inc. MODEL: FWMD

TYPE: Pulsed Transmitter

POWER REQUIREMENTS: 2 "AAA" Batteries

FREQUENCY OF OPERATION: 418 MHz

TESTS PERFORMED

Para. 15.231(b), Radiated Emissions, Fundamental and Harmonics

Para. 15.231(b), Radiated Emissions, Spurious Case

Para. 15.35, Duty Cycle Determination

Para. 15.231(c), Occupied Bandwidth

**Retlif Testing Laboratories**

Test Report No. R-10116-1
FCC ID: B4SFWMD

REPORT OF MEASUREMENTS

Applicant: X-10 (USA), Inc.
Device: Pulsed Transmitter
FCC ID: B4SFWMD
Power Requirements: 2 "AAA" Batteries
Applicable Rule Section: Part 15, Subpart C, Section 15.231

TEST RESULTS

15.231 (a): This device is used as a security transmitter.

15.231 (a)(1) & 15.231(a)(2): The transmitter is automatically operated and ceases transmission within 5 seconds after deactivation.

15.231 (a)(3): The transmitter does not perform periodic transmissions.

15.231 (b): The fundamental field strength did not exceed 10,333 $\mu\text{V/M}$ (Average) at a test distance of 3 meters. In addition, the requirements of section 15.35 for averaging pulsed emissions and for limiting peak emissions were met.

The field strength of harmonic and spurious emissions did not exceed 1,033 $\mu\text{V/M}$ (AVERAGE).

DETERMINATION OF FIELD STRENGTH LIMITS

The field strength limits shown below are found in Section 15.231.

| Frequency | | | Limit | |
|-----------|---|-----|-------|------|
| F1 | = | 260 | 3750 | = L1 |
| Fo | = | 418 | | Lo |
| F2 | = | 470 | 12500 | = L2 |



Retlif Testing Laboratories

Test Report No. R-10116-1
FCC ID: B4SFWMD

REPORT OF MEASUREMENTS (continued)

The formula below was utilized to determine the limits:

$$\text{Limit} = L1 + [(F0-F1)(L2-L1)/(F2-F1)]$$

Solving yields:

$$\text{Fundamental Limit} = 10,333 \mu\text{V/M (AVERAGE) @ 3 Meters}$$

$$\text{Harmonic Limit} = 1,033 \mu\text{V/M (AVERAGE) @ 3 Meters}$$

DUTY CYCLE DETERMINATION

The unit's RF output was directly coupled to the input of the spectrum analyzer. The analyzer was set for a frequency span of 0Hz. The sweep time was then adjusted in order to display one full pulse train. The transmitter on time was then summed and compared to the time for one full cycle in order to obtain the duty cycle.

$$\text{Transmitter On Time} = 43.7 \text{ milliseconds (maximum)}$$

$$\text{Transmitter Cycle Time} = 115.5 \text{ milliseconds}$$

$$\text{Transmitter Duty Cycle} = 36.4 \%$$

See separate e-file plots named dutycycle.pdf for additional information.



Retlif Testing Laboratories

Test Report No. R-10116-1
FCC ID: B4SFWMD

SPECTRUM ANALYZER DESENSITIZATION CONSIDERATIONS

Due to the nature of the emissions being measured, care was taken to ensure that the resolution bandwidth of the spectrum analyzer was adequate to provide accurate measurements. The following formula was utilized:

Setting pulse desensitization equal to zero and utilizing the minimum observed pulse width of 650 μ s yields a minimum required bandwidth of 1,026 Hz. FCC specified bandwidths of 100 kHz and 1 MHz were utilized below and above 1 GHz, respectively.

GENERAL NOTES

1. All readings were taken utilizing a peak detector function at a test distance of 3 meters.
2. The duty cycle was applied to the peak readings in order to determine the average value of the emissions.
3. The frequency range was scanned from 30 MHz to 4.18 GHz. All emissions not reported were more than 20 dB below the specified limit.



Retlif Testing Laboratories

Test Report No. R-10116-1
FCC ID: B4SFWMD

EQUIPMENT LIST

FCC Part 15, Subpart C, Paragraph 15.231

| EN | Type | Manufacturer | Description | Model No. | Cal Date | Due Date |
|------|-------------------------|-------------------|----------------------|--------------|------------|------------|
| 067 | Open Area Test Site | Retlif | 3 Meter | RNY | 10/01/2003 | 10/01/2006 |
| 128 | Double Ridged Guide | Electro-Mechanics | 1 GHz - 18 GHz | 3105 | 06/13/2003 | 06/13/2004 |
| 133 | Broadband Pre-Amplifier | Electro-Metrics | 10 kHz - 1 GHz, 26dB | BPA-1000 | 06/12/2003 | 06/12/2004 |
| 141 | Spectrum Analyzer | Hewlett Packard | 100 Hz - 40 GHz | 8566B | 07/23/2003 | 01/23/2004 |
| 141A | Graphics Plotter | Hewlett Packard | N/A | 7470A | 03/05/2003 | 03/05/2004 |
| 141B | Quasi-Peak Adaptor | Hewlett Packard | 100 Hz - 1 GHz | 85650A | 07/23/2003 | 01/23/2004 |
| 206B | 6.0 dB Attenuator | Texscan | 0 - 1.0 GHz | FP-50 - 6 dB | 06/12/2003 | 06/12/2004 |
| 543 | Preamplifier | Hewlett Packard | 1.0 GHz - 26.5 GHz | 8449B | 07/24/2003 | 07/24/2004 |
| 617 | Interference Analyzer | Electro-Metrics | 10 kHz - 1 GHz | EMC-30 | 09/30/2003 | 09/30/2004 |
| 767 | Biconilog | EMCO | 26 - 2000 MHz | 3142B | 09/04/2003 | 09/04/2004 |



Retlif Testing Laboratories

Test Report No. R-10116-1

FCC ID: B4SFWMD

FCC 15.231(b)

RADIATED EMISSIONS, FUNDAMENTAL & SPURIOUS CASE

(See separate e-file named Refundharm.pdf & REspur.pdf)



Retlif Testing Laboratories

Test Report No. R-10116-1

FCC ID: B4SFWMD

FCC 15.231©)

OCCUPIED BANDWIDTH

(See separate e-file named occbw.pdf)



Retlif Testing Laboratories

Test Report No. R-10116-1

FCC ID: B4SFWMD

FCC 15.231©)

DUTY CYCLE

(See separate e-file named dutycycle.pdf)



Retlif Testing Laboratories

Test Report No. R-10116-1

FCC ID: B4SFWMD

Test Setup Photograph



Retlif Testing Laboratories

Test Report No. R-10116-1
FCC ID: B4SFWMD