


SEAJIC®

魅宝便携式磁吸支架

OTH-AB403磁吸支架



扫码观看操作视频讲解

网址: www.dgsmtech.com


执行标准: Q/OSSL 001-2019


中国制造


RoHS

CE


FC







产品介绍



三脚架拉手

手柄套筒

磁吸圈

转动支架

连接支架

引磁环

铝合金杆杆

三脚架

分体式遥控器

拍照/开关键

打开三脚架

第一步:

按压产品底部的三角按钮松开三脚架。

第二步:

转动支架调整至垂直。

第三步:

一只手握住手柄套筒, 另一只手持住手机支架拉手柄拉至合适长度。松出灯杆时, 三脚架支架即会展开。

收起支架


一只手握住手柄套筒, 另一只手持拉杆调节高度。

请勿将手柄拉打到底部的三脚架, 以免造成产品损伤。

将手柄套筒推回拉杆底部处从而完成展开三脚架以及支架收回。


遥控分离

本品所使用的蓝牙遥控器采用可分离式设计, 取出遥控器时先取出部分拉杆, 然后向上推出蓝牙遥控器并缓慢取出。当长期不使用本品时请取出部分拉杆并取下遥控器。



蓝牙连接

长按拍照/开关键3秒发射灯没亮, 开启蓝牙配对模式, 打开手机蓝牙位置, 搜索并连接“SEAJIC-C”连接成功后闪光灯亮, 发射拍照/开关键可在相机模式中遥控拍照。



规格参数:

产品尺寸: 60x49x243mm

展开尺寸: 135mm

产品重量: 275g

蓝牙距离: 10m


电池容量: 50mAh

产品材质: ABS(防火) PC(防火) 铝合金

SEAJIC®

Portable MagSafe Stand

OTH-AB403magsafe stand



Scan code to watch operation video explanation

Web:www.dgsmtech.com


Standard Q/OSSL 001-2019


Made in China


RoHS

CE


FC







Product Introduction



pull handle

Handle sleeve

Magnetic ring

Bracket rotating part

Connecting bracket

Ring magnet

aluminum alloy telescopic rod

Tripod

Remote controller

Shutter/power button

Release Tripod

Step 1:

Press the triangle button on the bottom of the tripod to release tripod legs.

Step 2:

Unfold the phone holder to be upright.

Step 3:

Hold the handle sleeve with one hand and the pull handle of the phone holder with the other hand to pull out the telescopic rod. Adjust to desired height. Tripod legs will open automatically as the telescopic rod being pulled out.

Fold Tripod

Hold the handle sleeve with one hand and push the telescopic rod back in.


Attention

Do not pull legs to open tripod.

Push the handle sleeve all the way down so that the tripod legs are fully opened and stable.


Detach/Attach Remote Controller & Charging

The remote controller of this product is detachable. Pull the center not to leave space for sliding out the Bluetooth Remote Controller. Slide the Bluetooth Remote back in the slot to attach the remote with the tripod.  
When the battery is low, detach the remote controller and charge with the Micro-USB charger in the package.



Connect Bluetooth

Long press the shutter/power button on the remote controller for 3 seconds until the green light flashes. On your device, go to Settings->Bluetooth and turn on Bluetooth. Find "SEAJIC" to connect. When pairing is completed, the green light will go off.



Short press the shutter/power button to take pictures when the connected smartphone is in camera mode.  
Long press for 3 seconds again to turn off the Bluetooth.

Specifications

Tripod Parameters:

Boundary dimension: 60x49x243mm

Developed dimension: 135mm

Weight: 275g

Material: ABS (fireproof) PC (fireproof) Aluminum alloy

Bluetooth transmission distance: 10m

Battery capacity: 50mAh

FCC Caution

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates noise and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-Reorient or relocate the receiving antenna.

-Increase the separation between the equipment and receiver.

-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

AB403磁吸支架  
成品尺寸: 165x90mm  
80g书写纸 单黑印

PDF  
A686