


1. Peak-Average Ratio

1.1 GSM850


1.1.1 Test Result

Band: GSM850						
ENV	Mode		Frequency (MHz)	Peak-Average Ratio (dB)		Verdict
	Network	Subset		Result	Limit	
NTNV	GPRS	4 TX Slots	824.2	4.15	<=13	Pass
			836.6	4.04	<=13	Pass
			848.8	4.07	<=13	Pass
	EGPRS	4 TX Slots	824.2	6.77	<=13	Pass
			836.6	9.92	<=13	Pass
			848.8	9.90	<=13	Pass


1.1.2 Test Graph




GSM850 GPRS HCH 848.8MHz 4 TX Slots NTNV




GSM850 EGPRS LCH 824.2MHz 4 TX Slots NTNV



GSM850_EGPRS_MCH_836.6MHz_4_TX_Slots_NTNV



GSM850_EGPRS_HCH_848.8MHz_4_TX_Slots_NTNV




2. Peak-Average Ratio

2.1 PCS1900


2.1.1 Test Result

Band: PCS1900						
ENV	Mode		Frequency (MHz)	Peak-Average Ratio (dB)		Verdict
	Network	Subset		Result	Limit	
NTNV	GPRS	4 TX Slots	1850.2	3.75	<=13	Pass
			1880	3.67	<=13	Pass
			1909.8	3.68	<=13	Pass
	EGPRS	4 TX Slots	1850.2	6.62	<=13	Pass
			1880	6.94	<=13	Pass
			1909.8	6.67	<=13	Pass


2.1.2 Test Graph




PCS1900 GPRS HCH 1909.8MHz 4 TX Slots NTN



PCS1900_EGPRS_LCH_1850.2MHz_4 TX Slots NTN



PCS1900 EGPRS MCH 1880MHz 4 TX Slots NTN



PCS1900 EGPRS HCH 1909.8MHz 4 TX Slots NTN

