

## RF Exposure Report

**Report No.:** SA150107E07B

**FCC ID:** PPD-QCNFA364AH

**Test Model:** QCNFA364A

**Received Date:** Jan. 26, 2015

**Test Date:** Feb. 04 to May 07, 2015

**Issued Date:** May 12, 2015

**Applicant:** Qualcomm Atheros, Inc.

**Address:** 1700 Technology Drive, San Jose, CA 95110

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin  
Chu Hsien 307, Taiwan R.O.C.

**Test Location (1):** No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin  
Chu Hsien 307, Taiwan R.O.C.

**Test Location (2):** No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin  
Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



## Table of Contents

<b>Release Control Record</b>	<b>3</b>
<b>1 Certificate of Conformity</b>	<b>4</b>
<b>2 RF Exposure</b>	<b>5</b>
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
<b>3 Antenna Gain</b>	<b>6</b>
<b>4 Calculation Result</b>	<b>7</b>



A D T

### Release Control Record

Issue No.	Description	Date Issued
SA150107E07B	Original release.	May 12, 2015



A D T

## 1 Certificate of Conformity

**Product:** 802.11a/b/g/n/ac + BT 4.1 M.2 2230 Type Card

**Brand:** Qualcomm Atheros

**Test Model:** QCNFA364A

**Sample Status:** ENGINEERING SAMPLE

**Applicant:** Qualcomm Atheros, Inc.

**Test Date:** Feb. 04 to May 07, 2015

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Phoenix Huang , **Date:** May 12, 2015  
Phoenix Huang / Specialist

**Approved by :** May Chen , **Date:** May 12, 2015  
May Chen / Manager

## 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

## 2.4 Antenna Gain

The antenna gain was declared by client; please refer to the following table:

Transmitter Circuit	Brand	Model	Ant. Type	2.4GHz Gain with cable loss (dBi)	5GHz Gain with cable loss (dBi)	2.4GHz Cable Loss (dBi)	5G Cable Loss (dBi)	Connector Type	Cable Length (mm)
Chain (0)	WNC	81-EBJ15.005	PIFA	3.00	Band 1&2: 2.56	1.15	Band 1&2: 1.70	IPEX	300
					Band 3: 4.76		Band 3: 1.74		
					Band 4: 4.76		Band 4: 1.79		
Chain (1)	WNC	81-EBJ15.005	PIFA	3.62	Band 1&2: 3.08	1.15	Band 1&2: 1.70	IPEX	300
					Band 3: 3.31		Band 3: 1.74		
					Band 4: 2.42		Band 4: 1.79		

Note: 1. Above antenna gains of antenna are Total (H+V).

### 3 Calculation Result

**For WLAN: 15.247 (2.4GHz):**

#### 802.11b

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2472	23.51	224.404	6.63	20	0.20548	1.00

NOTE: 1. Directional gain = 3.62dBi + 10log(2) = 6.63dBi  
2. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

#### 802.11g

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2472	22.51	178.25	6.63	20	0.16321	1.00

NOTE: 1. Directional gain = 3.62dBi + 10log(2) = 6.63dBi  
2. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

#### VHT20

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2472	22.51	178.25	6.63	20	0.16321	1.00

NOTE: 1. Directional gain = 3.62dBi + 10log(2) = 6.63dBi  
2. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

#### VHT40

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2422-2462	21.51	141.59	6.63	20	0.12965	1.00

NOTE: 1. Directional gain = 3.62dBi + 10log(2) = 6.63dBi  
2. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

## For WLAN: 15.247 (5GHz):

### 802.11a

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5745 - 5825	23.01	200	7.77	20	0.23810	1.00

NOTE: 1. 5725~5850MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi  
2. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

### 802.11ac (VHT20)

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5745 - 5825	23.01	200	7.77	20	0.23810	1.00

NOTE: 1. 5725~5850MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi  
2. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

### 802.11ac (VHT40)

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5755 - 5795	23.01	200	7.77	20	0.23810	1.00

NOTE: 1. 5725~5850MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi  
2. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

### 802.11ac (VHT80)

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5775	22.01	158.866	7.77	20	0.18913	1.00

NOTE: 1. 5725~5850MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi  
2. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table



## For WLAN: 15.407 (5GHz):

### 802.11a

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5180 - 5240, 5260 - 5320	22.01	158.866	6.09	20	0.12846	1.00
5500 - 5720	22.01	158.866	7.77	20	0.18913	1.00

NOTE: 1. 5150~5350MHz: Directional gain = 3.08dBi + 10log(2) = 6.09dBi  
2. 5470~5725MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi  
3. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

### 802.11ac (VHT20)

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5180 - 5240, 5260 - 5320	22.01	158.866	6.09	20	0.12846	1.00
5500 - 5720	22.01	158.866	7.77	20	0.18913	1.00

NOTE: 1. 5150~5350MHz: Directional gain = 3.08dBi + 10log(2) = 6.09dBi  
2. 5470~5725MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi  
3. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

### 802.11ac (VHT40)

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5190 - 5230, 5270 - 5310	22.01	158.866	6.09	20	0.12846	1.00
5510 - 5710	22.01	158.866	7.77	20	0.18913	1.00

NOTE: 1. 5150~5350MHz: Directional gain = 3.08dBi + 10log(2) = 6.09dBi  
2. 5470~5725MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi  
3. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

### 802.11ac (VHT80)

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5210, 5290	18.01	63.246	6.09	20	0.05114	1.00
5530 - 5690	21.01	126.192	7.77	20	0.15023	1.00

NOTE: 1. 5150~5350MHz: Directional gain = 3.08dBi + 10log(2) = 6.09dBi  
2. 5470~5725MHz: Directional gain = 4.76dBi + 10log(2) = 7.77dBi  
3. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

### For Bluetooth:

Frequency Band (MHz)	Max power Avg. (dBm)	Max power Avg. (mW)	Antenna gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2402-2480	11.5	14.125	3.62	20	0.00647	1.00

**NOTE:** 1. This power include tune-up tolerance range that specified in QCNFA364A Tune Up power table

### Conclusion:

Both of the Bluetooth and WLAN (5GHz) can transmit simultaneously, the formula of calculated the MPE is:

$$CPD_1 / LPD_1 + CPD_2 / LPD_2 + .....etc. < 1$$

**CPD** = Calculation power density

**LPD** = Limit of power density

Therefore, the worst-case situation is  $0.23810 / 1 + 0.00647 / 1 = 0.245$ , which is less than "1".

--- END ---