

# RF Exposure Report

**FCC ID: 2AC23-W2CM2510**

**Product :** WIFI Module

**Trade Name :** GSD

**Model Number :** W2CM2510

**Series Number :** W2CM2510P

**Firmware Version Identification Number (FVIN):** 1.1

## Issued for

Hui Zhou Gaoshengda Technology Co.,LTD

NO.75 Zhongkai Development Area, Huizhou, Guangdong, China

## Issued by

Shenzhen ATL Testing Technology Co., Ltd.

F/4, Building 10, Dayuan Industrial Zone, Xili Town, Nanshan District, Shenzhen,  
China

Tel.: +86-0755-26909822 Fax.: +86-0755-61605504

Website: [www.atllab.org](http://www.atllab.org)

*Note: This report shall not be reproduced except in full, without the written approval of Shenzhen ATL Testing Technology Co., Ltd.. This document may be altered or revised by Shenzhen ATL Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample*

## MPE Calculation

### 1. Antenna Gain:

WIFI PIFA Antenna: 2.412~2.462 GHz: 2.94 dBi

### 2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where

**S**: power density

**P**: power input to the antenna

**G**: power gain of the antenna in the direction of interest relative to an isotropic radiator.

**R**: distance to the center of radiation of the antenna

### 4. Test Result:

Worst Maximum MPE Result																	
Mode	N <sub>TX</sub>	Freq. (MHz)	Conducted Power(max) (dBm) [P]		ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]			Power Density Limit (mW/ cm <sup>2</sup> )	Result						
			Ant 1	Ant 2			Ant 1	Ant 2	Sum								
802.11b	1	2412	17.88	17.84	2.94	20	0.0240	0.0238	---	1.000	PASS						
		2437	17.85	17.79	2.94	20	0.0239	0.0235	---								
		2462	17.90	17.73	2.94	20	0.0241	0.0232	---								
802.11g	1	2412	17.64	17.59	2.94	20	0.0227	0.0225	---			1.000	PASS				
		2437	17.67	17.64	2.94	20	0.0229	0.0227	---								
		2462	17.74	17.68	2.94	20	0.0233	0.0229	---								
802.11n (HT20)	2	2412	11.39	10.57	2.94	20	0.0054	0.0045	0.0099					1.000	PASS		
		2437	11.30	10.34	2.94	20	0.0053	0.0042	0.0095								
		2462	11.26	10.28	2.94	20	0.0052	0.0042	0.0094								
802.11n (HT40)	2	2422	11.39	10.57	2.94	20	0.0054	0.0045	0.0099							1.000	PASS
		2437	11.30	10.34	2.94	20	0.0053	0.0042	0.0095								
		2452	11.26	10.28	2.94	20	0.0052	0.0042	0.0094								

Note:

(1) N<sub>TX</sub>= Number of Transmit Antennas

(2) RF Output power specifies that Maximum Conducted Peak Output Power.

**5. Conclusion:****FCC and IC:**

FCC: As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),  
IC: As specified in 4.2 RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

**Limits for General Population/ Uncontrolled Exposure**

Frequency Range (MHz)	Power density (mW/ cm <sup>2</sup> )
300-1,500	F/1500
1,500-100,000	1.0

For all the operating frequency band the MPE limit S: 1 mW/ cm<sup>2</sup>

The maximum MPE is calculated as 0.0241mW / cm<sup>2</sup> < limit 1 mW / cm<sup>2</sup>. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

**Note**

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----