

# **RF Exposure Report**

# On Behalf of

## Shenzhen Growatt New Energy Co., Ltd.

4-13/F. Building A, Sino-German(Europe) Industrial Park, Hangcheng Ave, Bao' an District, Shenzhen, China

> FCC ID: 2AAJ9-INFINITY1300P Model: INFINITY 1300 PRO, INFINITY1200

#### June 4, 2024

This Report Concerns:		Equipment Type: Portable Power Station
Test Engineer: <u>LBi Li /</u>		
Report Number:	QCT24ER-1	354E-04 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
Test Date:	March 1, 20	24 ~ June 4, 2024
Reviewed By:	Gordon Tan	1 (aurdin. Ton
Approved By:	Kendy Wang	g/ kur un
Prepared By:	Shenzhen C East of 1/F., Shuiku Road District, She Tel: 0755-2 Fax: 0755-2	<b>QC Testing Laboratory Co., Ltd.</b> Building E, Xinghong Science Park, No.111, d, Fenghuanggang, Xixiang Street, Bao'an mzhen, Guangdong, China 3008269 23726780

Report No.: QCT24ER-1354E-04

Page 1 of 10



# **Table of Contents**

_1 <sup>.</sup> 1.1	Product Description for Equipment under Test (EUT)	
1.2	System Test Configuration	5
° 1.3	Test Facility	6
5 1.4	Measurement Uncertainty	6
2. RE(	QUIREMENTS	<u></u>
2.1	Test Methodology	
2.2	٢ Limit	7
2.3	Method Of Measurement:	7
2.4	Test Setup	8
2.5	Measuring Instrument Used:	8
2.6	E Field And H Field Strength Test Result	8
2.7	Simultaneous Transmission for SAR Exclusion	9
3. TES	ST SETUP PHOTO	10

Report Number	Description	Issued Date
QCT24ER-1354E-04	Initial Issue	2024-6-4
Contentine of the state		S OCTOBILISTING C
AND OF THE THE OF THE	ESTIMATION OF CONTRACTOR OF CONT	AND COLLEGE
Chefting Contenting of	Stephenson States and	of the the time of the of the
C C C C C C C C C C C C C C C C C C C		a of the strange
THE OCTOBER OF CONTRACT	Still and a state still as a state state of the	STRA C STRAT
Strate in the second state in the second state is the second state	Contraction of the state of the	Sterles in the sector
Se chi chi chi ce chi chi	NO O CHERTING O CHERTING O CHERTING	NO OF THE THE A
Called Contraction of the contra	AST AND OF THE THE AS OF THE STAR OF OF THE	the the second second
Stephenson States	Contraction of the second of t	of the first in the of the
	and a children of the state of the state	a of the the the
Alt and a contraction of a contraction o	Charling of the start of the st	Strand Color Harris
of the state of th	Contraction of the state of the	of the strange of
	HAD COLLECTION COLLECTION COLLECTION	Ind a central the the
Shine of the shine of o	Charlen and a	LESTING OF LES
of the stand of the stand of the stand	C C LE LE LE C C LE LE LE C C LE LE LE	of the the state of
	STHE CONTRACTOR STHE STHE CONTRACTOR STATE	
TESTING C CHEINER C	the state of the s	A Star and a
of the state of th	C C LET LET LE C C LE LET LE C C LE LET LE C C C LE LET LE C C C LE LET LE C C C LE LE C C C LE LE C C C C LE C C C C	of the the start of
A C C L C C C C C C C C C C C C C C C C	Entropy of the state of the sta	IND COLLETE IND
6 8 0 19 2		

# **Revision History of This Test Report**

Report No.: QCT24ER-1354E-04

## **1. GENERAL INFORMATION**

### 1.1 Product Description for Equipment under Test (EUT)

EUT Description	Portable Power Station
Model No.	INFINITY 1300 PRO, INFINITY 1200
Tested Model	INFINITY 1300 PRO
Sample(s) Status	Engineer sample
Operation Frequency:	110.5kHz~205kHz
Modulation type:	ASK A ST A C C C C C C C C C C C C C C C C C C
Antenna Type:	Inductive loop coil Antenna
Antenna gain*1:	OdBi (Max)
Power supply:	Model: INFINITY 1300 PRO   Input: AC Input:100-120V~,50/60Hz, 15A, 1800W MAX   Vehicle Input:12-24V

Report No.: QCT24ER-1354E-04

## Shenzhen QC Testing Laboratory Co., Ltd.

	Battery Capacity: 1280Wh,51.2V, 25Ah
WPT Output Power:	15W C Ship C Ship C Ship C Ship Ship C Ship Ship C Ship Ship Ship Ship Ship Ship Ship Ship
Trade Mark:	GROWATT CALLSTING CONTRACTOR CONT
Applicant	Shenzhen Growatt New Energy Co., Ltd.
Address	4-13/F. Building A, Sino-German(Europe) Industrial Park, Hangcheng Ave, Bao' an District, Shenzhen, China
Manufacturer	Shenzhen Growatt New Energy Co., Ltd.
Address	4-13/F. Building A, Sino-German(Europe) Industrial Park, Hangcheng Ave, Bao' an District, Shenzhen, China
Sample No.	Y24C1354E01WC

Note: \*1This information provided by Manufacturer, SZ QC Lab is not responsible for the accuracy of this information.

## 1.2 System Test Configuration

### 1.2.1 Support Equipment

Manufacturer	Description	Model	Serial Number
EESON	Wireless charger load	2S & & A	THE STREET STREET

#### Report No.: QCT24ER-1354E-04

### Shenzhen QC Testing Laboratory Co., Ltd.

### 1.3 Test Facility

Test Firm : Shenzhen QC Testing Laboratory Co., Ltd.

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19. The testing quality system of our laboratory meets with ISO/IEC-17025 requirements. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS - Registration No.: L8464

The EMC Laboratory has been accredited by CNAS, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

A2LA Certificate Number: 6759.01

The EMC Laboratory has been accredited by A2LA, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

FCC Registration Number: 561109

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission.

IC Registration Number: 29628

CAB identifier: CN0141

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada.

#### 1.4 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes	
E-field	110.5kHz~205kHz	0.5V/m	ه ۲(۱) (۱)	
H-field	110.5kHz~205kHz	0.1A/m	(1) of	

Report No.: QCT24ER-1354E-04

### 2. Requirements

#### 2.1 Test Methodology

The tests documented in this report were performed in accordance with FCC CFR Title 47 Part 1 §1.1307, FCC CFR Title 47 Part 1 §1.1310, FCC CFR Title 47 Part 2 §2.1091 and KDB 680106 D01 Wireless Power Transfer v04

2.2 Limit

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
	(i) Limits for O	ccupational/Controlled E	xposure	
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500- 100,000			5	<6

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

(ii) Limits for General Population/Uncontrolled Exposure

0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500- 100,000			1.0	<30

f = frequency in MHz. \* = Plane-wave equivalent power density.

#### 2.3 Method Of Measurement:

- a) The RF exposure test was performed in shielded chamber.
- b) The geometric centre of probe was placed at 20 cm test distance surrounding the device and the top surface.
- c) The measurement probe used to search of highest strength.
- d) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- e) The EUT were measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.



2.4 Test Setup



Note: As bottom point is not required to test for desktop devices

#### 2.5 Measuring Instrument Used:

Test Equipment	Manufacturer	Model No.	SN.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
Exposure Level Tester	Narda	ELT-400	N-0231	June 24, 2023	June 23, 2024
Magnetic field probe 100cm <sup>2</sup>	Narda	ELT probe 100cm <sup>2</sup>	M0675	June 24, 2023	June 23, 2024
Broadband field Meter	Narda	NBM-550	E-1273	June 24, 2023	June 23, 2024
Broadband field Probe	Narda	EF0391	D-0891	June 24, 2023	June 23, 2024

### 2.6 E Field And H Field Strength Test Result

Test Mode	Description of the second s
Mode 1	Charging with 15 W wireless charging load (99% Load)
Mode 2	Charging with 15 W wireless charging load (50% Load)
Mode 3	Charging with 15 W wireless charging load (1% Load)

#### Mode 1

H-Filed Strength at 20 cm from the edges surrounding and the top surface of the EUT (A/m)

20cm				50%		
Test	Test	Test	Test	Test	Limits(A/m)	Limits(A/m)
Position A	Position B	Position C	Position D	Position E		
0.19	0.22	0.26	0.18	0.29	1.63	0.815

E-Filed Strength at 20 cm from the edges surrounding and the top surface of the EUT (V/m)

2				E09/			
ź	Test	Test	Test	Test	Test	Limits(V/m)	50%
1	Position A	Position B	Position C	Position D	Position E		
3	1.61	1.37	1.25		1.65	614	307

Mode 2

H-Filed Strength at 20 cm from the edges surrounding and the top surface of the EUT (A/m)

Limits(A/m)

imits(A/m) 50%

Report No.: QCT24ER-1354E-04

Page 8 of 10

Address: East of 1/F., Building E, Xinghong Science Park, No.111, Shuiku Road, Fenghuanggang, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China Tel: 0755-23008269 Fax: 0755-23726780 www.qctest.com.cn

20cm



#### Shenzhen QC Testing Laboratory Co., Ltd.

C R N	a l'all	6 6	AND OF AN	S & O A	S ST DO OU	AT AT A P
Test	Test	Test	Test	Test		Limits(A/m)
Position A	Position B	Position C	Position D	Position E		
0.17	0.20	0.18	0.19	0.27	1.63	0.815

E-Filed Strength at 20 cm from the edges surrounding and the top surface of the EUT (V/m)

			E00/			
Test	Test	Test	Test	Test	Limits(V/m)	50%
Position A	Position B	Position C	Position D	Position E		
1.56	1.42	1.26	1.22	0 1.54	614	307
	1 6 0	N 61 .0	05 14 14	G G X X		ST C L

#### Mode 3

H-Filed Strength at 20 cm from the edges surrounding and the top surface of the EUT (A/m)

			50%			
Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Limits(A/m)	Limits(A/m)
0.18	0.20	0.16	0.17	0.21	1.63	0.815

E-Filed Strength at 20 cm from the edges surrounding and the top surface of the EUT (V/m)

			F00/				
Test	Test	Test	Test	Test	Limits(V/m)	50%	
Position A	Position B	Position C	Position D	Position E			
1.48	1.28	1.19	1.17 ×	1.48	614	307	

#### 2.7 Simultaneous Transmission for SAR Exclusion

The WPT and BLE or 2.4G Wi-Fi can transmit at the same, need consider simultaneous transmission. The WiFi/BLE does not support simultaneous transmission, So record worst case Maximum Simultaneous transmission SAR Ratio for 2.4G Wi-Fi and WPT

Maximum SAR Ratio 2.4G Wi-Fi	Maximum SAR Ratio wPT	SAR ratio 2.4G Wi-Fi + SAR ratio WPT	Limit	Test Results	
0.0217	0.1806	0.2023	AN A A A	Pass	

Remark:1. Output power including tune-up tolerance;

2.Evaluate limits for WPT at Field-Strength Limit;

3.Max. SAR Ratio=Max. Evaluation Values/Sar Limit, So:

Maximum SAR Ratio BLE=0.0014/1=0.0014

Maximum SAR Ratio 2.4G Wi-Fi=0.0217/1=0.0217

Maximum SAR Ratio WPT=0.29/1.63+1.65/614=0.1806



## 3. Test Setup Photo



----End------

Report No.: QCT24ER-1354E-04