



Shenzhen Chenxing Electronic Technology Co., LTD

specification

PRODUCT SPECIFICATION FO R APPROVAL

customer name: Jiemaitai Industrial (Shenzhen) Co., LTD
CUSTOMER

product name: A11 coil
PRODUCT NAME

material code: 30231-0003-01
PART No.

size of product: WPC388 Circular coil + circular
PRODUCT SPEC magnetic sheet (slotted) magnetic sheet
specification: 43.5*5.3*1 double slot
Wire specification:
0.08*105*10Ts/out wire 40mm with
back adhesive

date: December 11,2021
DATE

Version model: December 11,2021
VERSION

REV 2.0

edition Revision	Change content Modified Content	person liable Principle	date Date	remarks Note
REV1.0	First release	Xue Lei	2020-12-28	
REV2.0	First release	Xue Lei	2021-12-11	Update the magnetic plate specification

Formulation / PREPARED BY	Audit / CHECKED BY	Approval / APPROVED BY

Customer signature and seal Authorized signature& company chop		
---	--	--

The product specification is attached. If you have any questions, please give us timely feedback. Thank you!

Company name: Shenzhen Chenxing Electronic Technology Co., LTD

Factory address: Building 1, 5th floor, Xinkecheng Science and Technology Industrial Park, No.51 Dabao Road, Xinnan Street, Bao an District, Shenzhen



Shenzhen Chenxing Electronic Technology Co., LTD

size of product SPECIFICATION

I. Product size

	The diameter of the magnetic sheet is A	$43.5\pm0.5\text{mm}$
	Outer diameter of coil B	$41.5\pm1\text{mm}$
	Inner diameter of coil C	$20.5\pm0.5\text{mm}$
	Product thickness D	$<2.5\text{mm}$
	Outline length E	$40\text{mm}\pm 3\text{mm}$
	Welding length F	$3\pm 1\text{mm}$
	The diameter of the hole in the magnetic plate is G	$5\pm0.3\text{mm}$
	Magnetic plate thickness	$1\pm0.1\text{mm}$
	Shape of the magnetic sheet	Circular double trough
	Back adhesive thickness	Ordinary double-sided tape

	Anti-crack black film	no
--	----------------------------------	----


Company name: Shenzhen Chenxing Electronic Technology Co., LTD

Factory address: Building 1, 5th floor, Xinkecheng Science and Technology Industrial Park, No.51 Dabao Road, Xin
an Street, Bao an District, Shenzhen



Shenzhen Chenxing Electronic Technology Co., LTD

II. Schematic diagram



3. Winding parameters

terminal TERMINAL		Wire diameter WIRE	number of turns Turns	direction of winding Winding Direction
S	F	Wire wrap 0.08*105P	10Ts	CCW

4. Electrical characteristics:

Temperature TEMPERATURE: $25 \pm 10^\circ \text{C}$, humidity RELATIVEHUMIDITY: $65 \pm 20\%$

project ITEM	terminal TERMINAL	standard SPECIFICATION	test condition TEST FREQUENCY	measuring and test instruments TEST EQUIPMENTS
IND.	S-F	$6.3\mu\text{H} \pm 10\%$	100KHz/1.0V	LCZMETER1062B

5. Product pictures




Company name: Shenzhen Chenxing Electronic Technology Co., LTD

Factory address: Building 1, 5th floor, Xinkecheng Science and Technology Industrial Park, No.51 Dabao Road,
Xin an Street, Bao an District, Shenzhen

Shenzhen Chenxing
Electronic Technology Co.,
LTD



6. Packaging description:



The size of the pearl cotton is 35*24.5*6.2 cm, each

Each pearl cotton has 40 cells,
each cell contains 6 PCS
products, a total of 240 PCS
products per box is packed in
three layers of pearl cotton;



Carton size: 36.5*25.5*21 CM,
each box contains 720 PCS
products.

Company name: Shenzhen Chenxing Electronic Technology Co., LTD

Factory address: 5th floor, Building 1, Xinkecheng Science and Technology Industrial Park, No.51
Dabao Road, Xin an Street, Bao an District, Shenzhen