



REPORT No.: SZ24110315W01

TEST REPORT

APPLICANT : Anker Innovations Limited

PRODUCT NAME : NEBULA X1

MODEL NAME : D2351

BRAND NAME : NEBULA

FCC ID : 2AOKB-D2351

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2024-12-11

TEST DATE : 2024-12-24 to 2025-01-21

ISSUE DATE : 2025-01-24

Edited by:

Su Xiaoxian

Su Xiaoxian (Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	5
1.2. Test Equipment List	6
1.3. Measurement Uncertainty	8
1.4. Testing Laboratory	8
2. General Description	9
2.1. Information of Applicant and Manufacturer	9
2.2. Information of EUT	9
2.3. Channel List of EUT	10
2.4. Test Configuration of EUT	11
2.5. Test Conditions	11
2.6. Test Setup Layout Diagram	11
3. Test Results	14
3.1. Antenna Requirement	14
3.2. Duty Cycle of Test Signal	15
3.3. Maximum Peak Conducted Output Power	16
3.4. Maximum Average Conducted Output Power	17
3.5. 6 dB Bandwidth	18
3.6. Conducted Spurious Emissions and Band Edge	19
3.7. Power Spectral Density	20
3.8. Conducted Emission	21
3.9. Restricted Frequency Bands	22
3.10. Radiated Emission	23
Annex A Test Data and Result	25



REPORT No.: SZ24110315W01

Change History		
Version	Date	Reason for change
1.0	2025-01-24	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle of Test Signal	Jan. 08, 2025	Li Zikai	PASS	No deviation
3	15.247(b)	Maximum Peak Conducted Output Power	Jan. 08, 2025	Li Zikai	PASS	No deviation
4	15.247(b)	Maximum Average Conducted Output Power	Jan. 08, 2025	Li Zikai	PASS	No deviation
5	15.247(a)	Bandwidth	Jan. 08, 2025	Li Zikai	PASS	No deviation
6	15.247(d)	Conducted Spurious Emission and Band Edge	Jan. 08, 2025	Li Zikai	PASS	No deviation
7	15.247(e)	Power Spectral Density	Jan. 08, 2025	Li Zikai	PASS	No deviation
8	15.207	Conducted Emission	Dec. 28, 2024	Fan Shengquan	PASS	No deviation
9	15.247(d)	Restricted Frequency Bands	Jan. 14, 2025	Gao Jianrou	PASS	No deviation
10	15.209, 15.247(d)	Radiated Emission	Jan. 08&14, 2025	Gao Jianrou	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013 and KDB 558074 D01 v05r02.

Note 2: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 3: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.



1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2024.02.19	2025.02.18
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2024.01.25	2025.01.24
LISN	8127449	NSLK 8127	Schwarzbeck	2024.02.02	2025.02.01
Pulse Limiter (10dB)	VTSD 9561 F- B #206	VTSD 9561-F	Schwarzbeck	2024.05.30	2025.05.29
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2024.07.02	2025.07.01

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	V2.0.0.0
TS+ -[JS36-RSE]	Tonscend	V3.0.0.0
TS+ -[JS32-CE]	Tonscend	V2.5.0.0
TS+	Tonscend	V5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2024.06.03	2025.06.02
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2024.07.03	2025.07.02
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	Anker Innovations Limited
Applicant Address:	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong
Manufacturer:	Anker Innovations Limited
Manufacturer Address:	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong

2.2. Information of EUT

Product Name:	NEBULA X1	
Sample No.:	1#, 2#, 3#	
Hardware Version:	V03	
Software Version:	V11.0.18.7	
Equipment Type:	Bluetooth LE	
Bluetooth Version:	5.1	
Modulation Type:	GFSK	
Data Rate:	1Mbps, 2Mbps	
Operating Frequency Range:	2402MHz-2480MHz	
Antenna Type:	Dipole Antenna	
Antenna Gain:	3.2dBi	
Accessory Information:	AC Adapter	
	Brand Name:	N/A
	Model No.:	NSA240EC-22010900
	Serial No.:	N/A
	Rated Output:	100-240V~ 50/60Hz, 2.5A
	Rated Input:	22.0V=10.9A
	Manufacturer:	Shenzhen JingQuanHua&Everrise Intelligent Electric Co., Ltd.

Note 1: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



2.3.Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT


The EUT is controlled by dedicated software to transmit at the default maximum power level.

2.5. Test Conditions


Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☐ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☒ Dipole Antenna ☐ PCB Antenna ☐ PIFA Antenna ☐ On-board Antenna	☒ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☐ Metal Shrapnel ☐ Layout

3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration(T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e.,no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 in this report.



3.4. Maximum Average Conducted Output Power

3.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

3.4.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.4.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.4. Test Result

Refer to Annex A.3 in this report.



3.5.6 dB Bandwidth

3.5.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.5.1.Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., $RBW = 100\text{ kHz}$, $VBW \geq 3 \times RBW$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq 6\text{ dB}$.

3.5.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.3.Test Result

Refer to Annex A.4 in this report.



3.6. Conducted Spurious Emissions and Band Edge

3.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.5 and A.6 in this report.



3.7. Power Spectral Density

3.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.7.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

3.7.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.4. Test Result

Refer to Annex A.7 in this report.

3.8. Conducted Emission

3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

3.8.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.8.4. Test Result

Refer to Annex A.8 in this report.



3.9. Restricted Frequency Bands

3.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.9.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4. Test Result

Refer to Annex A.9 in this report.

3.10. Radiated Emission

3.10.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2:For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.10.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.10.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.10.4.Test Result

Refer to Annex A.10 in this report.



Annex A Test Data and Result


A.1. Duty Cycle of Test Signal

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	62.9	2.01	2.56
NVNT	BLE 1M	2440	Ant1	63.49	1.97	2.5
NVNT	BLE 1M	2480	Ant1	62.9	2.01	2.56
NVNT	BLE 2M	2404	Ant1	33.33	4.77	4.76
NVNT	BLE 2M	2440	Ant1	33.87	4.7	4.76
NVNT	BLE 2M	2478	Ant1	33.87	4.7	4.76




Test Graphs

Duty Cycle NVNT BLE 1M 2402MHz Ant1




Duty Cycle NVNT BLE 1M 2440MHz Ant1






Duty Cycle NVNT BLE 1M 2480MHz Ant1




Duty Cycle NVNT BLE 2M 2404MHz Ant1






Duty Cycle NVNT BLE 2M 2440MHz Ant1



Duty Cycle NVNT BLE 2M 2478MHz Ant1




**A.2. Maximum Peak Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	8.25	0	8.25	0.00668	30	Pass
NVNT	BLE 1M	2440	Ant1	9.39	0	9.39	0.00869	30	Pass
NVNT	BLE 1M	2480	Ant1	9.61	0	9.61	0.00914	30	Pass
NVNT	BLE 2M	2404	Ant1	8.34	0	8.34	0.00682	30	Pass
NVNT	BLE 2M	2440	Ant1	8.98	0	8.98	0.00791	30	Pass
NVNT	BLE 2M	2478	Ant1	9.58	0	9.58	0.00908	30	Pass

Test Graphs


Peak Power NVNT BLE 1M 2402MHz Ant1



Peak Power NVNT BLE 1M 2440MHz Ant1




Peak Power NVNT BLE 1M 2480MHz Ant1



Peak Power NVNT BLE 2M 2404MHz Ant1



Peak Power NVNT BLE 2M 2440MHz Ant1



Peak Power NVNT BLE 2M 2478MHz Ant1



**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	5.9	2.01	7.91	0.00618	30	Pass
NVNT	BLE 1M	2440	Ant1	6.92	1.97	8.89	0.00774	30	Pass
NVNT	BLE 1M	2480	Ant1	7.29	2.01	9.3	0.00851	30	Pass
NVNT	BLE 2M	2404	Ant1	3.17	4.77	7.94	0.00622	30	Pass
NVNT	BLE 2M	2440	Ant1	3.83	4.7	8.53	0.00713	30	Pass
NVNT	BLE 2M	2478	Ant1	4	4.7	8.7	0.00741	30	Pass



Test Graphs

Average Power NVNT BLE 1M 2402MHz Ant1




Average Power NVNT BLE 1M 2440MHz Ant1






Average Power NVNT BLE 1M 2480MHz Ant1




Average Power NVNT BLE 2M 2404MHz Ant1






Average Power NVNT BLE 2M 2440MHz Ant1



Average Power NVNT BLE 2M 2478MHz Ant1




**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.6551	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.6562	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.6468	0.5	Pass
NVNT	BLE 2M	2404	Ant1	1.102	0.5	Pass
NVNT	BLE 2M	2440	Ant1	0.9487	0.5	Pass
NVNT	BLE 2M	2478	Ant1	1.102	0.5	Pass



Test Graphs


-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1




-6dB Bandwidth NVNT BLE 2M 2404MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2440MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2478MHz Ant1



**A.5. Conducted Spurious Emissions**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-48.53	-20	Pass
NVNT	BLE 1M	2440	Ant1	-48.98	-20	Pass
NVNT	BLE 1M	2480	Ant1	-48.34	-20	Pass
NVNT	BLE 2M	2404	Ant1	-47.66	-20	Pass
NVNT	BLE 2M	2440	Ant1	-48.53	-20	Pass
NVNT	BLE 2M	2478	Ant1	-47.54	-20	Pass

Test Graphs

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2404MHz Ant1 Ref




Tx. Spurious NVNT BLE 2M 2404MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2478MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2478MHz Ant1 Emission






REPORT No.: SZ24110315W01

A.6. Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-59.11	-20	Pass
NVNT	BLE 1M	2480	Ant1	-65	-20	Pass
NVNT	BLE 2M	2404	Ant1	-63.62	-20	Pass
NVNT	BLE 2M	2478	Ant1	-63.95	-20	Pass

Test Graphs

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref




Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Band Edge NVNT BLE 2M 2404MHz Ant1 Ref




Band Edge NVNT BLE 2M 2404MHz Ant1 Emission



Band Edge NVNT BLE 2M 2478MHz Ant1 Ref



Band Edge NVNT BLE 2M 2478MHz Ant1 Emission




**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-7.08	0	-7.08	8	Pass
NVNT	BLE 1M	2440	Ant1	-6.4	0	-6.4	8	Pass
NVNT	BLE 1M	2480	Ant1	-4.25	0	-4.25	8	Pass
NVNT	BLE 2M	2404	Ant1	-9.79	0	-9.79	8	Pass
NVNT	BLE 2M	2440	Ant1	-7.54	0	-7.54	8	Pass
NVNT	BLE 2M	2478	Ant1	-7.83	0	-7.83	8	Pass

Test Graphs

PSD NVNT BLE 1M 2402MHz Ant1




PSD NVNT BLE 1M 2440MHz Ant1




PSD NVNT BLE 1M 2480MHz Ant1



PSD NVNT BLE 2M 2404MHz Ant1



PSD NVNT BLE 2M 2440MHz Ant1



PSD NVNT BLE 2M 2478MHz Ant1





A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Adapter+U disk+loud speaker+PC1++PC adapter1+PC2+PC adapter2+HDMI cable1+HDMI cable2+BT TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V}] = U_R + L_{\text{Cable loss}} [\text{dB}] + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1500	49.13	47.30	66.00	56.00	Line	PASS
2	0.1950	45.06	41.35	63.82	53.82		PASS
3	0.2445	42.82	38.45	61.94	51.94		PASS
4	0.3615	32.20	28.34	58.69	48.69		PASS
5	2.5441	27.09	20.42	56.00	46.00		PASS
6	17.9817	34.89	28.94	60.00	50.00		PASS



(N Phase)


No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1500	47.79	45.90	66.00	56.00	Neutral	PASS
2	0.2445	44.18	39.22	61.94	51.94		PASS
3	0.3615	39.11	34.61	58.69	48.69		PASS
4	0.4830	39.79	35.75	56.29	46.29		PASS
5	0.6045	38.97	32.42	56.00	46.00		PASS
6	17.6984	34.99	29.18	60.00	50.00		PASS

A.9. Restricted Frequency Bands

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (Vertical) was recorded in this test report.

1Mbps


Plot for Channel 0



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2382.68	0.1	37.54	37.480	54.00	16.46	150	286	AV	PASS
2386.58	0.1	37.59	37.490	54.00	16.41	150	302	AV	PASS
2388.05	13.5	51.01	37.490	74.00	22.99	150	358	PK	PASS
2389.03	13.0	50.48	37.490	74.00	23.52	150	360	PK	PASS
2389.64	0.7	38.17	37.490	54.00	15.83	150	315	AV	PASS
2389.88	13.1	50.60	37.490	74.00	23.40	150	202	PK	PASS




Plot for Channel 39



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2483.76	1.8	40.09	38.270	54.00	13.91	150	279	AV	PASS
2484.00	14.4	52.62	38.270	74.00	21.38	150	279	PK	PASS
2485.44	1.2	39.51	38.270	54.00	14.49	150	279	AV	PASS
2485.44	14.3	52.60	38.270	74.00	21.40	150	342	PK	PASS
2487.80	13.6	51.90	38.270	74.00	22.10	150	262	PK	PASS
2487.99	1.2	39.50	38.270	54.00	14.50	150	275	AV	PASS

**2Mbps**


Plot for Channel 0



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2366.56	14.6	52.04	37.470	74.00	21.96	150	355	PK	PASS
2368.14	2.0	39.49	37.470	54.00	14.51	150	307	AV	PASS
2371.93	1.9	39.32	37.470	54.00	14.68	150	41	AV	PASS
2375.72	14.7	52.22	37.480	74.00	21.78	150	222	PK	PASS
2379.75	1.8	39.31	37.480	54.00	14.69	150	148	AV	PASS
2382.55	15.1	52.55	37.480	74.00	21.45	150	358	PK	PASS



Plot for Channel 39



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2483.76	1.7	39.94	38.270	54.00	14.06	150	313	AV	PASS
2483.86	18.1	56.36	38.270	74.00	17.64	150	257	PK	PASS
2484.00	17.1	55.35	38.270	74.00	18.65	150	313	PK	PASS
2484.67	17.2	55.48	38.270	74.00	18.52	150	257	PK	PASS
2485.11	1.7	39.94	38.270	54.00	14.06	150	313	AV	PASS
2486.31	1.6	39.90	38.270	54.00	14.10	150	0	AV	PASS



A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Field strength of fundamental:


Frequency (MHz)	Reading [dB μ V]	Level [dB μ V/m]	Factor [dB/m]	Detector	Antenna Polarity
2401.97	69.7	107.27	37.530	PK	Vertical

The field strength (the lowest) of fundamenta is more than 20dB higher than the unwanted emissions, in accordance with FCC part 15.215(b).




1Mbps

Plot for Channel 0




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
32.55	53.0	22.48	-30.470	40.00	17.52	150	280	PK	PASS
44.19	43.6	15.69	-27.870	40.00	24.31	150	320	PK	PASS
90.63	54.8	23.35	-31.420	43.50	20.15	150	330	PK	PASS
104.33	58.6	29.07	-29.510	43.50	14.43	150	280	PK	PASS
536.22	40.1	20.99	-19.130	46.00	25.01	150	190	PK	PASS
719.19	46.4	30.76	-15.650	46.00	15.24	150	50	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1069.35	48.3	45.70	-2.580	74.00	28.30	150	268	PK	PASS
1069.35	34.8	32.18	-2.580	54.00	21.82	150	9	AV	PASS
2460.32	39.0	44.96	5.950	54.00	9.04	150	110	AV	PASS
2461.21	43.8	49.73	5.950	74.00	24.27	150	110	PK	PASS
3169.29	55.1	44.55	-10.570	74.00	29.45	150	359	PK	PASS
3595.73	45.3	36.16	-9.150	54.00	17.84	150	86	AV	PASS
4799.62	49.2	43.99	-5.180	74.00	30.01	150	171	PK	PASS
5226.92	39.4	36.15	-3.220	54.00	17.85	150	79	AV	PASS
7205.69	40.4	45.42	5.030	54.00	8.58	150	255	AV	PASS
7205.69	45.2	50.23	5.030	74.00	23.77	150	79	PK	PASS
14552.90	35.0	55.10	20.080	74.00	18.90	150	264	PK	PASS
14747.05	25.8	46.01	20.190	54.00	7.99	150	224	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
32.55	50.7	20.24	-30.470	40.00	19.76	150	230	PK	PASS
45.76	47.3	18.96	-28.370	40.00	21.04	150	90	PK	PASS
90.50	53.1	21.59	-31.460	43.50	21.91	150	310	PK	PASS
104.21	46.7	17.12	-29.570	43.50	26.38	150	260	PK	PASS
387.81	40.4	17.77	-22.640	46.00	28.23	150	140	PK	PASS
719.19	50.3	34.68	-15.650	46.00	11.32	150	190	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1065.35	47.1	44.45	-2.620	74.00	29.55	150	281	PK	PASS
1101.80	35.1	32.77	-2.330	54.00	21.23	150	73	AV	PASS
2402.09	34.3	39.57	5.250	54.00	14.43	150	309	AV	N/A
2402.53	41.2	46.45	5.260	74.00	27.55	150	304	PK	N/A
2993.78	43.8	51.78	7.970	74.00	22.22	150	249	PK	PASS
3563.59	48.8	39.28	-9.510	54.00	14.72	150	101	AV	PASS
3584.16	53.2	43.93	-9.270	74.00	30.07	150	86	PK	PASS
7206.12	39.6	44.65	5.030	54.00	9.35	150	80	AV	PASS
7206.12	45.9	50.93	5.030	74.00	23.07	150	80	PK	PASS
8999.74	35.5	41.85	6.400	54.00	12.15	150	94	AV	PASS
14341.18	35.8	55.07	19.240	74.00	18.93	150	317	PK	PASS
14780.91	25.9	45.82	19.900	54.00	8.18	150	277	AV	PASS

Plot for Channel 19




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
32.55	52.0	21.51	-30.470	40.00	18.49	150	30	PK	PASS
45.76	44.9	16.53	-28.370	40.00	23.47	150	40	PK	PASS
90.50	54.7	23.26	-31.460	43.50	20.24	150	330	PK	PASS
104.21	57.7	28.17	-29.570	43.50	15.33	150	10	PK	PASS
719.19	45.5	29.84	-15.650	46.00	16.16	150	100	PK	PASS
901.42	39.7	28.21	-11.530	46.00	17.79	150	250	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1064.46	48.5	45.88	-2.620	74.00	28.12	150	342	PK	PASS
1149.81	34.5	32.49	-1.970	54.00	21.51	150	33	AV	PASS
1425.87	33.7	33.69	0.020	54.00	20.31	150	218	AV	PASS
1584.57	45.2	44.68	-0.530	74.00	29.32	150	227	PK	PASS
2439.88	49.7	55.48	5.820	74.00	18.52	150	282	PK	N/A
2439.88	47.1	52.95	5.820	54.00	1.05	150	287	AV	N/A
3168.86	56.3	45.69	-10.570	74.00	28.31	150	357	PK	PASS
3595.73	46.8	37.61	-9.150	54.00	16.39	150	102	AV	PASS
7319.69	44.7	48.99	4.270	74.00	25.01	150	40	PK	PASS
7319.69	36.8	41.06	4.270	54.00	12.94	150	204	AV	PASS
14692.19	25.2	45.80	20.580	54.00	8.20	150	80	AV	PASS
14843.05	35.9	55.21	19.290	74.00	18.79	150	188	PK	PASS



(Antenna Vertical, 30MHz to 1GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
32.55	52.2	21.76	-30.470	40.00	18.24	150	260	PK	PASS
45.76	47.5	19.14	-28.370	40.00	20.86	150	230	PK	PASS
55.95	46.6	18.57	-28.030	40.00	21.43	150	70	PK	PASS
90.50	54.4	22.98	-31.460	43.50	20.52	150	70	PK	PASS
339.92	40.3	16.01	-24.260	46.00	29.99	150	50	PK	PASS
719.06	49.6	33.93	-15.660	46.00	12.07	150	190	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1067.57	46.3	43.67	-2.600	74.00	30.33	150	351	PK	PASS
1094.69	36.8	34.46	-2.380	54.00	19.54	150	0	AV	PASS
1584.57	45.2	44.69	-0.530	74.00	29.31	150	98	PK	PASS
2439.88	52.0	57.86	5.820	74.00	16.14	150	296	PK	N/A
2440.32	49.6	55.46	5.820	54.00	-1.46	150	296	AV	N/A
2990.66	43.9	51.79	7.930	74.00	22.21	150	286	PK	PASS
3595.73	49.8	40.69	-9.150	54.00	13.31	150	94	AV	PASS
7319.27	39.0	43.31	4.270	54.00	10.69	150	263	AV	PASS
7320.12	45.5	49.72	4.270	74.00	24.28	150	155	PK	PASS
8999.74	36.5	42.91	6.400	54.00	11.09	150	94	AV	PASS
14200.18	36.4	54.81	18.440	74.00	19.19	150	124	PK	PASS
14732.05	26.1	46.39	20.320	54.00	7.61	150	79	AV	PASS

Plot for Channel 39




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
32.55	52.2	21.70	-30.470	40.00	18.30	150	200	PK	PASS
90.50	55.1	23.63	-31.460	43.50	19.87	150	180	PK	PASS
104.21	58.3	28.69	-29.570	43.50	14.81	150	320	PK	PASS
145.92	45.5	13.65	-31.800	43.50	29.85	150	120	PK	PASS
323.30	39.8	15.07	-24.770	46.00	30.93	150	200	PK	PASS
719.06	47.1	31.45	-15.660	46.00	14.55	150	60	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1064.90	48.9	46.31	-2.620	74.00	27.69	150	2	PK	PASS
1094.69	34.3	31.88	-2.380	54.00	22.12	150	244	AV	PASS
1424.98	34.2	34.24	0.000	54.00	19.76	150	221	AV	PASS
1584.57	45.1	44.53	-0.530	74.00	29.47	150	216	PK	PASS
2480.33	40.0	45.88	5.890	74.00	28.12	150	272	PK	N/A
2480.33	33.1	39.03	5.890	54.00	14.97	150	281	AV	N/A
3168.43	55.2	44.64	-10.560	74.00	29.36	150	356	PK	PASS
3595.73	46.9	37.73	-9.150	54.00	16.27	150	102	AV	PASS
4777.34	48.6	43.22	-5.370	74.00	30.78	150	172	PK	PASS
4851.48	39.4	34.63	-4.810	54.00	19.37	150	279	AV	PASS
14674.19	34.1	54.61	20.530	74.00	19.39	150	194	PK	PASS
14747.48	25.8	45.95	20.190	54.00	8.05	150	9	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
32.55	50.8	20.28	-30.470	40.00	19.72	150	40	PK	PASS
44.19	47.2	19.30	-27.870	40.00	20.70	150	320	PK	PASS
90.50	53.3	21.84	-31.460	43.50	21.66	150	280	PK	PASS
93.90	47.3	16.75	-30.590	43.50	26.75	150	260	PK	PASS
333.13	41.3	16.76	-24.510	46.00	29.24	150	310	PK	PASS
719.19	49.9	34.21	-15.650	46.00	11.79	150	50	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1070.24	46.1	43.55	-2.580	74.00	30.45	150	351	PK	PASS
1103.13	34.7	32.40	-2.310	54.00	21.60	150	351	AV	PASS
1584.13	44.3	43.73	-0.540	74.00	30.27	150	300	PK	PASS
2480.33	41.3	47.22	5.890	74.00	26.78	150	351	PK	N/A
2480.33	34.5	40.35	5.890	54.00	13.65	150	342	AV	N/A
3595.73	50.0	40.81	-9.150	54.00	13.19	150	101	AV	PASS
3595.73	52.8	43.60	-9.150	74.00	30.40	150	101	PK	PASS
5999.66	40.0	39.79	-0.160	54.00	14.21	150	149	AV	PASS
7439.70	43.7	48.28	4.630	74.00	25.72	150	142	PK	PASS
7440.13	38.3	42.88	4.630	54.00	11.12	150	132	AV	PASS
14304.75	35.6	55.18	19.570	74.00	18.82	150	232	PK	PASS
14691.76	25.9	46.45	20.580	54.00	7.55	150	117	AV	PASS

_____ END OF REPORT _____