



Testing Laboratory  
3787

# RADIO EXPOSURE TEST REPORT

**FCC ID** : Z3WAIR4981-41

**Equipment** : AT&T ALL Fi Booster

**Brand Name** : Airties

**Model Name** : Air4981-41

**Applicant** : AirTies Wireless Networks  
Sehit Mehmet Mikdat Uluunlu Sokagi No:23  
Esentepe, Sisli İstanbul, 34394 Turkey

**Manufacturer** : AirTies Wireless Networks  
Sehit Mehmet Mikdat Uluunlu Sokagi No:23  
Esentepe, Sisli İstanbul, 34394 Turkey

**Standard** : 47 CFR Part 2.1091

The product was received on Jul. 21, 2022, and testing was started from Jul. 26, 2022 and completed on Aug. 03, 2023. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Rex Liao

**Sporton International Inc. Hsinchu Laboratory**

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



## **Table of Contents**

|                                                 |          |
|-------------------------------------------------|----------|
| <b>History of this test report.....</b>         | <b>3</b> |
| <b>Summary of Test Result.....</b>              | <b>4</b> |
| <b>1 General Description .....</b>              | <b>5</b> |
| 1.1 EUT General Information .....               | 5        |
| 1.2 Antenna Information .....                   | 6        |
| 1.3 Table for EUT supports function.....        | 7        |
| 1.4 Accessories .....                           | 7        |
| 1.5 Applicable Standards .....                  | 7        |
| 1.6 Testing Location .....                      | 7        |
| <b>2 Maximum Permissible Exposure .....</b>     | <b>8</b> |
| 2.1 Limit of Maximum Permissible Exposure ..... | 8        |
| 2.2 MPE Calculation Method .....                | 8        |
| 2.3 MPE Exemption.....                          | 9        |
| 2.4 Calculated Result and Limit.....            | 10       |

### **Photographs of EUT v01**



## History of this test report

TEL : 886-3-656-9065  
FAX : 886-3-656-9085  
Report Template No.: CB-A1\_1 Ver1.1

Page Number : 3 of 10  
Issued Date : Aug. 28, 2023  
Report Version : 01



## Summary of Test Result

| Report Clause | Ref Std. Clause | Test Items          | Result (PASS/FAIL) | Remark |
|---------------|-----------------|---------------------|--------------------|--------|
| 2             | -               | Exposure evaluation | PASS               | -      |

**Conformity Assessment Condition:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the chapter "Measurement Uncertainty".

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

**Reviewed by: Sam Chen**

**Report Producer: Sophia Shiung**



# 1 General Description

## 1.1 EUT General Information

| RF General Information |                                                  |                                                  |                                                                                                                                                                                                 |
|------------------------|--------------------------------------------------|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Evaluation Mode        | Frequency Range (MHz)                            | Operating Frequency (MHz)                        | Modulation Type                                                                                                                                                                                 |
| 2.4GHz WLAN            | 2400-2483.5                                      | 2412-2462                                        | 802.11b: DSSS (DBPSK, DQPSK, CCK)<br>802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>VHT: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM)<br>802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) |
| 5GHz WLAN              | 5150-5250<br>5250-5350<br>5470-5725<br>5725-5850 | 5180-5250<br>5250-5320<br>5500-5720<br>5745-5825 | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)<br>802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)                                  |



## 1.2 Antenna Information

| Ant. | Port   |      | Brand      | Model Name | Antenna Type              | Connector        | Gain (dBi) |
|------|--------|------|------------|------------|---------------------------|------------------|------------|
|      | 2.4GHz | 5GHz |            |            |                           |                  |            |
| 1    | 1      | 1    | Galtronics | A00        | Off-Board Internal Dipole | I-PEX MHF (u.FL) | Note 1     |
| 2    | 2      | 2    | Galtronics | A11        | Off-Board Internal Dipole | I-PEX MHF (u.FL) |            |

Note 1:

| Ant. | Antenna Gain (dBi) |           |         |         |        |
|------|--------------------|-----------|---------|---------|--------|
|      | WLAN 2.4GHz        | WLAN 5GHz |         |         |        |
|      |                    | UNII 1    | UNII 2A | UNII 2C | UNII 3 |
| 1    | 5.41               | 5.06      | 4.26    | 5.01    | 4.76   |
| 2    | 2.96               | 2.91      | 3.33    | 3.97    | 3.8    |

|      | Directional Gain (dBi) |           |         |         |        |
|------|------------------------|-----------|---------|---------|--------|
|      | WLAN 2.4GHz            | WLAN 5GHz |         |         |        |
|      |                        | UNII 1    | UNII 2A | UNII 2C | UNII 3 |
| 2T1S | 5.46                   | 5.11      | 4.47    | 5.29    | 4.79   |
| 2T2S | 5.41                   | 5.06      | 4.26    | 5.01    | 4.76   |

Note 2: The above information (excepting antenna gain) was declared by manufacturer.

Note 3: Maximum Directional Gain following KDB662911 D03.

### For 2.4GHz:

#### For IEEE 802.11b/g/n/VHT/ax mode (2TX/2RX):

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

#### For 5GHz UNII 1~3:

#### For IEEE 802.11a/n/ac/ax mode (2TX/2RX):

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.



### 1.3 Table for EUT supports function

| Function  | Supports type | Support Band  |
|-----------|---------------|---------------|
| AP Router | Master        | 2.4GHz / 5GHz |
| Mesh      | Master        | 5GHz          |

### 1.4 Accessories

| Accessories    |                         |            |                                                      |
|----------------|-------------------------|------------|------------------------------------------------------|
| Equipment Name | Brand Name              | Model Name | Rating                                               |
| Adapter        | AT&T<br>(mfg. by DELTA) | EPS24R0-16 | INPUT: 120V~0.725A Max 60Hz<br>Output: 12V, 2.0A 24W |

### 1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

### 1.6 Testing Location

| Testing Location Information                              |                                                                                                                                                                                                                                                |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Lab. : Sporton International Inc. Hsinchu Laboratory |                                                                                                                                                                                                                                                |
| Hsinchu<br>(TAF: 3787)                                    | ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)<br>TEL: 886-3-656-9065 FAX: 886-3-656-9085<br>Test site Designation No. TW3787 with FCC.<br>Conformity Assessment Body Identifier (CABID) TW3787 with ISED. |



## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | *(100)                                   | <6                                                               |
| 3.0-30                | 1842/f                            | 4.89/f                            | *(900/f <sup>2</sup> )                   | <6                                                               |
| 30-300                | 61.4                              | 0.163                             | 1.0                                      | <6                                                               |
| 300-1500              | -                                 | -                                 | f/300                                    | <6                                                               |
| 1500-100,000          | -                                 | -                                 | 5                                        | <6                                                               |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | *(100)                                   | <30                                                              |
| 1.34-30               | 824/f                             | 2.19/f                            | *(180/f <sup>2</sup> )                   | <30                                                              |
| 30-300                | 27.5                              | 0.073                             | 0.2                                      | <30                                                              |
| 300-1500              | -                                 | -                                 | f/1500                                   | <30                                                              |
| 1500-100,000          | -                                 | -                                 | 1.0                                      | <30                                                              |

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$





## 2.3 MPE Exemption

Option (A): 1.1307(b)(3)(i)(A): Available maximum time-averaged power is < 1 mW

Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= P<sub>th</sub>.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

Option (C): 1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance

$R$  between the person and the antenna / radiating structure, where  $R > \lambda / 2 \pi$ .

| Single RF Sources Subject to Routine Environmental Evaluation |                       |
|---------------------------------------------------------------|-----------------------|
| RF Source frequency (MHz)                                     | Threshold ERP (watts) |
| 0.3-1.34                                                      | $1,920 R^2$ .         |
| 1.34-30                                                       | $3,450 R^2/f^2$ .     |
| 30-300                                                        | $3.83 R^2$ .          |
| 300-1,500                                                     | $0.0128 R^2 f$ .      |
| 1,500-100,000                                                 | $19.2 R^2$ .          |
| Note: $R$ is in meters, $f$ is in MHz.                        |                       |



## 2.4 Calculated Result and Limit

### Exposure Environment: General Population / Uncontrolled Exposure

| Mode     | DG<br>(dBi) | Power<br>(dBm) | EIRP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>EIRP<br>(dBm) | Distance<br>(cm) | S<br>(mW/cm <sup>2</sup> ) | S Limit<br>(mW/cm <sup>2</sup> ) | Option | TL EIRP<br>(dBm) |
|----------|-------------|----------------|---------------|-------------------|--------------------------|------------------|----------------------------|----------------------------------|--------|------------------|
| 2.4G;G1D | 5.41        | 26.29          | 31.70         | 0.50              | 32.20                    | 20               | 0.33016                    | 1.00000                          | B      | 37.006           |
| 5.2G;D1D | 5.06        | 27.12          | 32.18         | 0.50              | 32.68                    | 20               | 0.36875                    | 1.00000                          | B      | 37.006           |
| 5.3G;D1D | 4.47        | 23.92          | 28.39         | 0.50              | 28.89                    | 20               | 0.15407                    | 1.00000                          | B      | 37.006           |
| 5.6G;D1D | 5.29        | 23.94          | 29.23         | 0.50              | 29.73                    | 20               | 0.18695                    | 1.00000                          | B      | 37.006           |
| 5.8G;D1D | 4.79        | 28.02          | 32.81         | 0.50              | 33.31                    | 20               | 0.42631                    | 1.00000                          | B      | 37.006           |

### Simultaneous Transmission Analysis Mode: WLAN 2.4GHz + WLAN 5GHz

| Mode           | DG<br>(dBi) | Power<br>(dBm) | EIRP<br>(dBm) | Tolerance<br>(dB) | Tune-up EIRP<br>(dBm) | Distance<br>(cm) | S<br>(mW/cm <sup>2</sup> ) | Limit<br>(mW/cm <sup>2</sup> ) | Option | TL EIRP<br>(dBm) | TL Ratio |
|----------------|-------------|----------------|---------------|-------------------|-----------------------|------------------|----------------------------|--------------------------------|--------|------------------|----------|
| 2.4G;G1D       | 5.41        | 26.29          | 31.70         | 0.50              | 32.20                 | 20               | 0.33016                    | 1.00000                        | B      | 37.006           | 0.3307   |
| 5.8G;D1D       | 4.79        | 28.02          | 32.81         | 0.50              | 33.31                 | 20               | 0.42631                    | 1.00000                        | B      | 37.006           | 0.4270   |
| Sum TL Ratio_B | 0.7577      |                |               |                   |                       |                  |                            |                                |        |                  |          |
| Ratio Limit    | 1           |                |               |                   |                       |                  |                            |                                |        |                  |          |

Note: The above antenna gain was declared by manufacturer.

————THE END————