

AppendixA: Effective (Isotropic) Radiated Power Output Data

Test Result(WCDMA)

Band	Type	Channel	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
Band2	Voice	9262	23.63	22.63	33.01	PASS
Band2	TestMode	9262	23.68	22.68	33.01	PASS
Band2	TestMode	9400	23.77	22.77	33.01	PASS
Band2	Voice	9400	23.64	22.64	33.01	PASS
Band2	TestMode	9538	23.76	22.76	33.01	PASS
Band2	Voice	9538	23.69	22.69	33.01	PASS
Band4	Voice	1312	23.29	22.09	30.00	PASS
Band4	TestMode	1312	23.43	22.23	30.00	PASS
Band4	Voice	1413	23.49	22.29	30.00	PASS
Band4	TestMode	1413	23.53	22.33	30.00	PASS
Band4	TestMode	1513	23.54	22.34	30.00	PASS
Band4	Voice	1513	23.49	22.29	30.00	PASS
Band5	Voice	4132	23.31	17.71	38.45	PASS
Band5	TestMode	4132	23.33	17.73	38.45	PASS
Band5	TestMode	4183	23.44	17.84	38.45	PASS
Band5	Voice	4183	23.46	17.86	38.45	PASS
Band5	Voice	4233	23.38	17.78	38.45	PASS
Band5	TestMode	4233	23.38	17.78	38.45	PASS

Test Result(HSDPA)

Band	Channel	SubTest	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
Band2	9262	1	22.69	21.69	33.01	PASS
Band2	9262	2	22.17	21.17	33.01	PASS
Band2	9262	3	22.22	21.22	33.01	PASS
Band2	9262	4	22.16	21.16	33.01	PASS
Band2	9400	1	22.77	21.77	33.01	PASS
Band2	9400	2	22.28	21.28	33.01	PASS
Band2	9400	3	22.29	21.29	33.01	PASS
Band2	9400	4	22.26	21.26	33.01	PASS
Band2	9538	1	22.73	21.73	33.01	PASS
Band2	9538	2	22.27	21.27	33.01	PASS
Band2	9538	3	22.28	21.28	33.01	PASS
Band2	9538	4	22.26	21.26	33.01	PASS

Band4	1312	1	22.48	21.28	30.00	PASS
Band4	1312	2	22.00	20.8	30.00	PASS
Band4	1312	3	22.03	20.83	30.00	PASS
Band4	1312	4	22.00	20.8	30.00	PASS
Band4	1413	1	22.57	21.37	30.00	PASS
Band4	1413	2	22.07	20.87	30.00	PASS
Band4	1413	3	22.09	20.89	30.00	PASS
Band4	1413	4	22.07	20.87	30.00	PASS
Band4	1513	1	22.57	21.37	30.00	PASS
Band4	1513	2	22.08	20.88	30.00	PASS
Band4	1513	3	22.11	20.91	30.00	PASS
Band4	1513	4	22.07	20.87	30.00	PASS
Band5	4132	1	22.55	16.95	38.5	PASS
Band5	4132	2	22.04	16.44	38.5	PASS
Band5	4132	3	22.09	16.49	38.5	PASS
Band5	4132	4	22.02	16.42	38.5	PASS
Band5	4183	1	22.63	17.03	38.5	PASS
Band5	4183	2	22.12	16.52	38.5	PASS
Band5	4183	3	22.17	16.57	38.5	PASS
Band5	4183	4	22.15	16.55	38.5	PASS
Band5	4233	1	22.58	16.98	38.5	PASS
Band5	4233	2	22.07	16.47	38.5	PASS
Band5	4233	3	22.10	16.5	38.5	PASS
Band5	4233	4	22.06	16.46	38.5	PASS

Test Result(HSUPA)

Band	Channel	SubTest	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
Band2	9262	1	20.62	19.62	33.01	PASS
Band2	9262	2	21.11	20.11	33.01	PASS
Band2	9262	3	21.66	20.66	33.01	PASS
Band2	9262	4	20.65	19.65	33.01	PASS
Band2	9262	5	22.67	21.67	33.01	PASS
Band2	9400	1	20.70	19.7	33.01	PASS
Band2	9400	2	21.22	20.22	33.01	PASS
Band2	9400	3	21.72	20.72	33.01	PASS
Band2	9400	4	20.73	19.73	33.01	PASS
Band2	9400	5	22.74	21.74	33.01	PASS
Band2	9538	1	20.69	19.69	33.01	PASS
Band2	9538	2	21.19	20.19	33.01	PASS
Band2	9538	3	21.69	20.69	33.01	PASS

Band2	9538	4	20.71	19.71	33.01	PASS
Band2	9538	5	22.71	21.71	33.01	PASS
Band4	1312	1	20.45	19.25	30.00	PASS
Band4	1312	2	20.93	19.73	30.00	PASS
Band4	1312	3	21.44	20.24	30.00	PASS
Band4	1312	4	20.47	19.27	30.00	PASS
Band4	1312	5	22.47	21.27	30.00	PASS
Band4	1413	1	20.53	19.33	30.00	PASS
Band4	1413	2	21.04	19.84	30.00	PASS
Band4	1413	3	21.52	20.32	30.00	PASS
Band4	1413	4	20.55	19.35	30.00	PASS
Band4	1413	5	22.55	21.35	30.00	PASS
Band4	1513	1	20.51	19.31	30.00	PASS
Band4	1513	2	21.03	19.83	30.00	PASS
Band4	1513	3	21.54	20.34	30.00	PASS
Band4	1513	4	20.54	19.34	30.00	PASS
Band4	1513	5	22.55	21.35	30.00	PASS
Band5	4132	1	20.54	14.94	38.5	PASS
Band5	4132	2	20.96	15.36	38.5	PASS
Band5	4132	3	21.50	15.9	38.5	PASS
Band5	4132	4	20.55	14.95	38.5	PASS
Band5	4132	5	22.56	16.96	38.5	PASS
Band5	4183	1	20.60	15	38.5	PASS
Band5	4183	2	21.05	15.45	38.5	PASS
Band5	4183	3	21.58	15.98	38.5	PASS
Band5	4183	4	20.63	15.03	38.5	PASS
Band5	4183	5	22.63	17.03	38.5	PASS
Band5	4233	1	20.56	14.96	38.5	PASS
Band5	4233	2	20.97	15.37	38.5	PASS
Band5	4233	3	21.48	15.88	38.5	PASS
Band5	4233	4	20.54	14.94	38.5	PASS
Band5	4233	5	22.56	16.96	38.5	PASS

Remark: EIRP (dBm) = Conducted power (dBm) + Antenna Gain (dBi). (For Band 2 & 4)
ERP (dBm) = EIRP (dBm) - 2.15 (dB). (For Band5)


AppendixB:Peak-to-Average Ratio

Test Result(WCDMA)

Band	Channel	Peak-to-Average Ratio(dB)	Limit(dB)	Verdict
Band2	9400	2.96	13	PASS
Band4	1413	2.99	13	PASS
Band5	4183	2.96	13	PASS

Remark: All channel had been tested, but only the worst case data displayed in this report.

Test Graphs(WCDMA)




AppendixC:26dB Bandwidth andOccupied Bandwidth

Test Result(WCDMA)

Band	Channel	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit(kHz)	Verdict
Band2	9262	4.1418	4.694	---	PASS
Band2	9400	4.1439	4.693	---	PASS
Band2	9538	4.1481	4.699	---	PASS
Band4	1312	4.1473	4.683	---	PASS
Band4	1413	4.1476	4.685	---	PASS
Band4	1513	4.1485	4.690	---	PASS
Band5	4132	4.1574	4.701	---	PASS
Band5	4183	4.1547	4.704	---	PASS
Band5	4233	4.1578	4.713	---	PASS

Test Graphs(WCDMA)





AppendixD:Band Edge

Test Result(WCDMA)

Band	Channel	Frequency (MHz)	Result (dBm)	Limit(dBm)	Verdict
Band2	9262	1850.00	-19.19	-13	PASS
Band2	9538	1910.00	-18.25	-13	PASS
Band4	1312	1710.00	-21.15	-13	PASS
Band4	1513	1755.00	-21.57	-13	PASS
Band5	4132	824.00	-18.78	-13	PASS
Band5	4233	849.00	-19.48	-13	PASS

Test Graphs(WCDMA)



JianYan Testing Group Shenzhen Co., Ltd.

No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366


Project No.: JYTSZR2302075


AppendixE:Conducted SpuriousEmission


Test Result(WCDMA)


Band	Channel	Frequency Range (Mhz)	Frequency (dBm)	Result (dBm)	Limit (dBm)	Verdict
Band2	9262	0.009~0.15MHz	0.01	-53.65	-43	PASS
Band2	9262	0.15~30MHz	0.15	-46.26	-23	PASS
Band2	9262	30~1000MHz	911.31	-40.36	-13	PASS
Band2	9262	1000~20000MHz	19960.1	-24.7	-13	PASS
Band2	9400	0.009~0.15MHz	0.01	-52.86	-43	PASS
Band2	9400	0.15~30MHz	0.15	-43.1	-23	PASS
Band2	9400	30~1000MHz	954.41	-40.3	-13	PASS
Band2	9400	1000~20000MHz	19934.13	-24.77	-13	PASS
Band2	9538	0.009~0.15MHz	0.01	-54.34	-43	PASS
Band2	9538	0.15~30MHz	0.16	-44.43	-23	PASS
Band2	9538	30~1000MHz	962.88	-40.22	-13	PASS
Band2	9538	1000~20000MHz	19912.6	-24.42	-13	PASS
Band4	1312	0.009~0.15MHz	0.01	-52.97	-43	PASS
Band4	1312	0.15~30MHz	0.15	-44.2	-23	PASS
Band4	1312	30~1000MHz	884.44	-40.3	-13	PASS
Band4	1312	1000~20000MHz	19955.03	-25.33	-13	PASS
Band4	1413	0.009~0.15MHz	0.01	-52.59	-43	PASS
Band4	1413	0.15~30MHz	0.15	-43.78	-23	PASS
Band4	1413	30~1000MHz	930.19	-38.56	-13	PASS
Band4	1413	1000~20000MHz	19962.63	-24.29	-13	PASS
Band4	1513	0.009~0.15MHz	0.01	-53.43	-43	PASS
Band4	1513	0.15~30MHz	0.15	-45.9	-23	PASS
Band4	1513	30~1000MHz	421.43	-40.03	-13	PASS
Band4	1513	1000~20000MHz	19949.33	-24.96	-13	PASS
Band5	4132	0.009~0.15MHz	0.01	-53.29	-33	PASS
Band5	4132	0.15~30MHz	0.15	-44.64	-13	PASS
Band5	4132	30~1000MHz	374.48	-49.98	-13	PASS
Band5	4132	1000~10000MHz	5977.9	-29.67	-13	PASS
Band5	4183	0.009~0.15MHz	0.01	-52.03	-33	PASS
Band5	4183	0.15~30MHz	0.16	-44.56	-13	PASS
Band5	4183	30~1000MHz	725.72	-49.69	-13	PASS
Band5	4183	1000~10000MHz	6122.5	-30.9	-13	PASS
Band5	4233	0.009~0.15MHz	0.01	-54.09	-33	PASS
Band5	4233	0.15~30MHz	0.15	-45.88	-13	PASS
Band5	4233	30~1000MHz	993.92	-49.9	-13	PASS
Band5	4233	1000~10000MHz	6122.2	-30.85	-13	PASS


Test Graphs(WCDMA)














AppendixF:Frequency Stability

Test Result

Reference Frequency: WCDMA BAND V 12.2k RMC Middle channel=4183 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	-0.94	-0.001124	±2.5	Pass
	-20	-1.04	-0.001243		
	-10	-1.39	-0.001661		
	0	-0.51	-0.000610		
	10	-1.05	-0.001255		
	20	-1.23	-0.001470		
	30	-1.75	-0.002092		
	40	-1.65	-0.001972		
	50	-0.41	-0.000490		
Voltage					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-0.90	-0.001076	±2.5	Pass
	3.87	-1.44	-0.001721		
	4.45	-1.32	-0.001578		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: WCDMA BAND IV 12.2k RMC Middle Frequency=1413 channel=1732.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	-0.64	-0.000369	Within authorized band for BAND IV	Pass
	-20	-0.62	-0.000358		
	-10	-0.57	-0.000329		
	0	-1.28	-0.000739		
	10	0.01	0.000006		
	20	0.04	0.000023		
	30	-0.01	-0.000006		
	40	-0.26	-0.000150		
	50	0.44	0.000254		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-0.73	-0.000421	Within authorized band for BAND IV	Pass
	3.87	-0.11	-0.000063		
	4.45	0.34	0.000196		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: WCDMA BAND II 12.2k RMC Middle Frequency=9400 channel=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	2.81	0.001495	Within authorized band for BAND II	Pass
	-20	3.18	0.001691		
	-10	3.09	0.001644		
	0	3.37	0.001793		
	10	2.95	0.001569		
	20	3.70	0.001968		
	30	3.47	0.001846		
	40	3.55	0.001888		
	50	3.40	0.001809		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	3.37	0.001793	Within authorized band for BAND II	Pass
	3.87	2.80	0.001489		
	4.45	3.47	0.001846		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Appendix G: Modulation Characteristics

Test Result

Band	Channel	Result	Verdict
Band2	9400	PASS	PASS
Band4	1413	PASS	PASS
Band5	4183	PASS	PASS

Remark: All channel had been tested, but only the worst case data displayed in this report.

Test Graphs

