



**EMC Technologies Pty Ltd**

ABN 82 057 105 549  
57 Assembly Drive  
Tullamarine Victoria Australia 3043

Ph: + 613 9335 3333  
Fax: + 613 9338 9260  
email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION  
to  
FCC PART 15 Subpart C (Section 15.247) & RSS-210**

FCC ID: EJE-WL0010  
Industry Canada ID: 337J-WL0010

Test Sample: GOLAN INTEL Mini-PCI WLAN Module  
Model: WM3945ABG

Report Number: M060108\_Cert\_WM3945ABG\_DTS

Tested for: Fujitsu Australia Ltd.

Issue Date: 8<sup>th</sup> February 2006

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements which include the requirements of ISO/IEC 17025 and are traceable to national standards of measurement. This document shall not be reproduced, except in full. The certificate on page 3 may be reproduced in full.

NATA Accredited Laboratory Number:  
5292

**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**  
**EMC Technologies Report No. M060108\_Cert\_WM3945ABG\_DTS**  
**Issue Date: 8<sup>th</sup> February 2006**

**CONTENTS**

- 1.0 INTRODUCTION**
- 2.0 GENERAL INFORMATION**

**RESULTS – WLAN, WM3945ABG (802.11b, 802.11g and \*802.11a)**

- 3.0 CONDUCTED EMI MEASUREMENTS**
- 4.0 SPURIOUS EMI MEASUREMENTS**
- 5.0 PEAK OUTPUT POWER**
- 6.0 CHANNEL BANDWIDTH**
- 7.0 PEAK POWER SPECTRAL DENSITY**
- 8.0 RADIO FREQUENCY EXPOSURE**
- 9.0 ANTENNA REQUIREMENT**
- 10.0 COMPLIANCE STATEMENT**

**\*RESULTS of 802.11a (5.15 – 5.35 GHz Band)**

**Refer to Report No: M060108\_Cert\_WM3945ABG\_NII**

- APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**
- APPENDIX B: REPORT PHOTOGRAPHS**
- APPENDIX C: FUNCTIONAL DESCRIPTION**
- APPENDIX D: BLOCK DIAGRAM**
- APPENDIX E: SCHEMATICS**
- APPENDIX F: ANTENNA INFORMATION**
- APPENDIX G: SPECIFICATIONS**
- APPENDIX H: FCC LABELLING DETAILS**
- APPENDIX I: USER MANUAL**
- APPENDIX J: CHANNEL BANDWIDTH PLOTS**
- APPENDIX K: HARMONICS PLOTS**
- APPENDIX L: BANDEDGE PLOTS**
- APPENDIX M: PEAK POWER SPECTRAL DENSITY PLOTS**

**Attachment 1: RF Exposure Information**

**Attachment 2: FCC DOC for Fujitsu Notebooks**

**Attachment 3: FCC Part 15B Test Report (Report: FG06-016EAL)**



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**

**Report Number:** M060108\_Cert\_WM3945ABG\_DTS

**Test Sample:** GOLAN INTEL Mini-PCI WLAN Module  
**Model:** WM3945ABG  
**Manufacturer:** INTEL Corp

**FCC ID:** EJE-WL0010  
**Industry Canada ID:** 337J-WL0010  
**Equipment Type:** Intentional Radiator (Transceiver)

**Host Notebook Manufacturer:** Fujitsu Ltd.  
**Address:** Mobile Computing Division  
1-1 Kamikodanaka 4-Chome, Nakahara-Ku, Kawasaki, Japan  
**Contact:** Mr. Tsuyoshi Uchihara


**Tested for:** Fujitsu Australia Ltd

**Test Standards:** FCC Part 15, Subpart C – Intentional Radiators  
FCC Part 15.247: 2400 – 2483.5 MHz & 5725 – 5850 MHz Operation Band  
ANSI C63.4 – 2003  
OET Bulletin No. 65  
  
RSS-210 Issue 6 Low Power Licence-Exempt RadioCommunication Devices:  
6.2.2 (o) 2400 – 2483.5 MHz & 5725 – 5850 MHz Spread Spectrum  
  
RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and Portable  
Radio Transmitters with respect to Health Canada's Safety Code 6 for  
Exposure of Humans to Radio Frequency Fields

**Test Dates:** 10<sup>th</sup> January to 8<sup>th</sup> February 2006

**Test Officer:**   
Chieu Huynh - B.Eng (Hons) Electronics

**Attestation:** *I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.*

**Authorised Signatory:**   
Chris Zombolas  
Technical Director  
EMC Technologies Pty Ltd



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**

## 1.0 INTRODUCTION

Testing was performed on the INTEL Mini-PCI Wireless LAN Module (GOLAN 11a+b/g), Model: WM3945ABG installed in Fujitsu notebook PC.

The GOLAN WLAN module was originally certified by INTEL as a modular approval under FCC ID: PD9WM3945ABG (Canada ID: 1000M-WM3945ABG). The intention of this application is to get a Limited Modular approval for this WLAN module for use in Fujitsu notebook PCs. The Radio modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

The GOLAN WLAN supports IEEE 802.11b, IEEE 802.11g and IEEE802.11a (DTS & U-NII) configurations. Tests were performed in all three configurations.

The results for configurations IEEE 802.11b, IEEE 802.11g and IEEE802.11a (DTS: 5725 – 5850 MHz) are reported in this test report.

The results for IEEE 802.11a (U-NII) are reported separately.  
Refer to EMC Technologies' test report: M060108\_Cert\_WM3945ABG\_NII (U-NII)

The second transmitter in the notebook is a Bluetooth module, model: EYTF3CSFT. This Bluetooth transmitter is tested and certified under EMC Technologies report No: M060108\_Cert\_EYTF3CSFT with FCC ID: EJE-BT0001

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart C:	Rules for intentional radiators (particularly section 15.247)
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.247:	Operation in the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz

The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart C - Section 15.247.

The test sample also complied with the Industry Canada RSS-210 issue 6 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) and the RF exposure requirements of RSS-102.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 1.1 Summary of Results

### 1.1.1 FCC Subpart C, Section 15.247

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	Complies
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	Complies
15.247 (i)		Radio Frequency Hazard	Complies
15.247 (d)	6.2.2(o)(e1)	Out of Band Emissions	Complies
15.247 (e)	6.2.2(o)(iv)	Peak Power Spectral Density	Complies

### 1.1.2 FCC Subpart E, Section 15.407

FCC Part 15, Subpart E Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.407 (a)(1) (a)(2)	6.2.2(q1)	Peak Transmit Power	Complies
15.407 (a)(5)	6.2.2(q1)	Peak Power Spectral Density	Complies
15.407 (a)(6)		Peak Excursion	Complies
15.407 (b)	6.2.2(q1)	Undesirable Emission	Complies
15.407 (f)		Radio Frequency Hazard	Complies
15.407 (g)	6.4	Frequency Stability	Complies

Refer to EMC Technologies Report No: M060108\_Cert\_WM3945ABG\_NII

The measurement procedure used was in accordance with ANSI C63.4-2003 and OET Bulletin No. 65. The instrumentation conformed to the requirements of ANSI C63.2-1996.

## 1.2 Modifications by EMC Technologies

No modifications were required.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 2.0 GENERAL INFORMATION

(Information supplied by the Client)

### 2.1 EUT (WLAN) Details

<b>Transmitter:</b>	Mini-PCI Wireless LAN Module
<b>Wireless Module:</b>	GOLAN (11a+b/g)
<b>Model Number:</b>	WM3945ABG
<b>Manufacturer:</b>	Intel Corporation
<b>Modulation Type:</b>	Direct Sequence Spread Spectrum (DSSS for 802.11b) Orthogonal Frequency Division Multiplexing (OFDM for 802.11g) Orthogonal Frequency Division Multiplexing (OFDM for 802.11a)
<b>802.11a and 802.11g</b>	BPSK – 6Mbps, 9Mbps QPSK – 12Mbps, 18Mbps 16QAM – 24Mbps, 36Mbps 64QAM – 48Mbps, 54Mbps
<b>802.11b</b>	DBPSK – 1Mbps DQPSK – 2Mbps CCK – 5.5Mbps, 11Mbps
<b>Frequency Range:</b>	2.4 – 2483.5 GHz for 11b/g 5.15 - 5.35 GHz and 5.725 - 5.850 GHz for 11a
<b>Number of Channels:</b>	11 channels for 11b or 11g 13 channels for 11a
<b>Power Supply:</b>	3.3 VDC from PCI bus

**Frequency Allocation Table:**

Band	Channel	Lower Frequency	Upper Frequency	Americas	Europe	Japan	High Band
				SKU #1 MOW1	SKU #2 MOW2	SKU #3 Japan	SKU #4 ROW
802.11b/g	1-11	2.401 GHz	2.473 GHz	X	X	X	X
802.11b/g	12-13	2.467 GHz	2.483 GHz		X	X	X
802.11a	34-46	5.08 GHz	5.22 GHz		X	X	
802.11a	36-48	5.150 GHz	5.250 GHz	X	X		
802.11a	52-64	5.250 GHz	5.350 GHz	X	X		
802.11a	100-140	5.470 GHz	5.725 GHz		X		
802.11a	149-161	5.725 GHz	5.825 GHz	X			X
802.11a	165	5.815 GHz	5.835 GHz	X			X

**Channels Tested and Output power setting:**

Channel and Mode:	Output Power setting (average, dBm)
802.11b mode	
*Channels 1	16
*Channel 6 and 11	18
802.11g mode	
*Channel 1	16
*Channel 6	17
*Channel 11	15
802.11a mode	
**Channel 36	16
**Channels 52 and 64	17
*Channels 149, 157 and 165	17

\*Channels tested and reported in this report

\*\*Channels tested and reported in the U-NII submission (M060108\_Cert\_WM3945ABG\_NII)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 2.2 Operational Description

The GOLAN WLAN Module was individual tested in 3 Fujitsu host notebooks E8110, E8210 and S7110 to cover two antenna types

The Intel WLAN test software "CRTU" was used to transmit continuously during the tests. For Spurious and Harmonics tests both radio modules (WLAN and Bluetooth) were simultaneously transmitting.

## 2.3 Technical Specifications

Refer to Appendix G for details

## 2.4 Test Configuration

Conducted tests were performed at the WLAN Antenna ports.

Radiated tests were performed for measuring the harmonics and spurious from the transmitters.

Limited Modular Approval (LMA) details to cover the following Fujitsu notebook configurations:

Fujitsu Notebook Model	WLAN Module	WLAN Antenna	Comments
E8110	GOLAN WM3945ABG	2 x Inverted F antenna	All results are reported
E8210		2 x Inverted F antenna	
S7110		2 x Monopole Antenna	

Fujitsu Notebook Model	WLAN antenna type	WLAN antenna Peak gain [dBi]			
		2.4GHz band	5GHz low band	5GHz Mid band	5GHz High band
E8110	Inverted F	-0.99	-1.12	-0.56	-0.56
E8210	Inverted F	2.47	-0.44	0.38	0.38
S7110	Monopole	2.08	1.66	0.59	1.79

## 2.5 Host PC Details

### 2.5.1 S7110 Model Notebook

Host notebook : LifeBook S series  
 Model Name: S7110 / S7110D  
 Serial Number: Pre-production Sample  
 Manufacturer: FUJITSU LIMITED

CPU Type and Speed: Yonah-DC 2.16GHz  
 LCD 14" SXGA+ / 14" XGA  
 Wired LAN: Marvell 88E8055 : 10 Base-T/100 Base-TX/1000Base-T  
 Modem: Agere MDC1.5 modem Model: AM3(New)  
 Port Replicator Model: FPCPR63

AC Adapter Model: 80W: SEB100P2-19.0(Sanken) / SQ2N80W19P-01(Nagano)  
 64W: SED80N2-19.0(Sanken)  
 Voltage: 19 V  
 Current Specs: 4.22A, 3.37A  
 Watts: 80W, 64W

#### RADIO MODULES

Module # 1 WLAN (Golan IEEE802.11a+b/g)  
 WLAN Model No.: WM3945ABG  
 WLAN Manufacturer: Intel Corp.  
 Interface Type: Mini-Card Wireless LAN Module  
 Antenna Type: Monopole Antenna - Model: YCE-5008  
 Located on top edge of LCD screen (Left and Right)  
 Antenna gain: Refer to antenna data provided separately (Appendix F)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

<b>Module # 2:</b>	Bluetooth Module
<b>Model Number:</b>	EYTF3CSFT
<b>Manufacturer:</b>	TAIYO YUDEN
<b>Interface Type:</b>	USB
<b>Antenna Types:</b>	Yokowo Inverted F Antenna, Model: YCE-5250 Location: Under Left side of the Shift key, above the air vent
<b>Antenna gain:</b>	2.78 dBi
<b>Max. Output Power:</b>	4 dBm

## 2.5.2 E8110 Model Notebook

<b>Host notebook :</b>	LifeBook E series
<b>Model Name:</b>	E8110 / E8110D
<b>Serial Number:</b>	Pre-production Sample
<b>Manufacturer:</b>	FUJITSU LIMITED
<b>CPU Type and Speed:</b>	Yonah-DC 2.16GHz
<b>LCD</b>	15" SXGA+ / 15" XGA
<b>Wired LAN:</b>	Marvell 88E8055 : 10 Base-T/100 Base-TX/1000Base-T
<b>Modem:</b>	Agere MDC1.5 modem Model: AM3(New)
<b>Port Replicator Model:</b>	FPCPR63
<b>AC Adapter Model:</b>	SEB100P2-19.0(Sanken) / SQ2N80W19P-01(Nagano JRC)
<b>Voltage:</b>	19 V
<b>Current Specs:</b>	4.22A
<b>Watts:</b>	80W

### RADIO MODULES

<b>Module # 1:</b>	WLAN (Golan IEEE802.11a+b/g)
<b>WLAN Model Number:</b>	WM3945ABG
<b>WLAN Manufacturer:</b>	Intel Corp.
<b>Interface Type:</b>	Mini-Card Wireless LAN Module
<b>Antenna Types:</b>	Nissei Electric Inverted F Antenna - Model: CP115429(Left), CP115429(Right) Located on top edge of LCD screen (Left and Right)
<b>Antenna gain:</b>	Refer to antenna data provided separately (Appendix F)
<b>Module # 2:</b>	Bluetooth Module
<b>Model Number:</b>	EYTF3CSFT
<b>Manufacturer:</b>	TAIYO YUDEN
<b>Interface Type:</b>	USB
<b>Antenna Types:</b>	Yokowo Inverted F Antenna, Model: YCE-5250 Location: Under Left side of the Shift key, above the air vent
<b>Antenna gain:</b>	-0.22 dBi
<b>Max. Output Power:</b>	4 dBm





**2.5.3 E8210 Model Notebook**

<b>Host notebook :</b>	LifeBook E series
<b>Model Name:</b>	E8210 / E8210D
<b>Serial Number:</b>	Pre-production Sample
<b>Manufacturer:</b>	FUJITSU LIMITED
<b>CPU Type and Speed:</b>	Yonah-DC 2.16GHz
<b>LCD</b>	15"WUXGA / 15"WSXGA+ / 15"WXGA
<b>Wired LAN:</b>	Marvell 88E8055 : 10 Base-T/100 Base-TX/1000Base-T
<b>Modem:</b>	Agere MDC1.5 modem Model: AM3(New)
<b>Port Replicator Model:</b>	FPCPR63
<b>AC Adapter Model:</b>	SEB100P2-19.0(Sanken) / SQ2N80W19P-01(Nagano JRC)
<b>Voltage:</b>	19 V
<b>Current Specs:</b>	4.22A
<b>Watts:</b>	80W
<b>RADIO MODULES</b>	
<b>Module # 1:</b>	WLAN (Golan IEEE802.11a+b/g)
<b>WLAN Model Number:</b>	WM3945ABG
<b>WLAN Manufacturer:</b>	Intel Corp.
<b>Interface Type:</b>	Mini-Card Wireless LAN Module
<b>Antenna Types:</b>	Nissei Electric Inverted F Antenna Model: CP115431(Left), CP115431(Right) Located on top edge of LCD screen
<b>Antenna gain:</b>	Refer antenna data provided separately (Appendix F)
<b>Module # 2:</b>	Bluetooth Module
<b>Model Number:</b>	EYTF3CS FT
<b>Manufacturer:</b>	TAIYO YUDEN
<b>Interface Type:</b>	USB
<b>Antenna Types:</b>	Yokowo Inverted F Antenna, Model: YCE-5250 Location: Under Left side of the Shift key, above the air vent
<b>Antenna gain:</b>	-0.22 dBi
<b>Max. Output Power:</b>	4 dBm

**2.6 Block Diagram**

Refer to Appendix D - Block Diagram

**2.7 Support Equipment**

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG06-016EAL)

**2.8 Test Procedure**

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 1 and 3 metres from the EUT. OET Bulletin 65 dated June 2001 was used for reference.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 2.9 Test Facility

### 2.9.1 General

Radiated Emission measurements were performed at EMC Technologies open area test site (OATS) situated at Lerderderg Gorge, near the township of Bacchus Marsh in Victoria, Australia. Conducted measurements at an antenna ports were performed at EMC Technologies' laboratory in Tullamarine, Victoria Australia.

The above test sites have been accepted for testing by the Federal Communications Commission (FCC) - **FCC Registration Number 90560**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional).

**Industry Canada File Number IC 4161.**

### 2.9.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

***“FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E).”***

The current full scope of accreditation can be found on the NATA website: [www.nata.asn.au](http://www.nata.asn.au)  
It also includes a large number of emission, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Laboratory (NML) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A<sup>2</sup>LA).

## 2.10 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Laboratory (NML). All equipment calibration is traceable to Australia national standards at the National Measurements Laboratory. The reference antenna calibration was performed by NML and the working antennas (biconical and log-periodic) calibrated by the NATA approved procedures. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A

## 2.11 Ambients at OATS

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## RESULTS

### WLAN Module – WM3945ABG (802.11b, 802.11g and 802.11a (DTS))

#### 3.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.207  
Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG06-016EAL)

#### 4.0 SPURIOUS EMISSION MEASUREMENTS

##### 4.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.247(d).

Radiated emission measurements were performed to the limits as per section 15.209. The measurements were made at the open area test site.

The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report. The EMI Receiver was operated under software control via the PC Controller through the IEEE.488 Interface Bus Card Adaptor. The test frequency range was sub-divided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks while also permitting fast frequency scan times. Calibrated EMCO 3115, EMCO 3116 and ETS standard gain horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions between 30 - 1000 MHz, refer to Attachment 3 – FCC Part 15B Test Report (Report: FG06-016EAL).

The measurement of emissions above 1000 MHz, appearing in the restricted bands, was made using an average detector with a bandwidth of 1.0 MHz.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Quasi-Peak/Average Detectors. The software for cable losses automatically corrected the measurement data for each frequency range, antenna factors and preamplifier gain and all data was then stored on disk in sequential data files. This process was performed for both horizontal and vertical antenna polarisations.

##### 4.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

**E = V + AF - G + L** Where:

**E** = Radiated Field Strength in dBμV/m.

**V** = EMI Receiver Voltage in dBμV. (measured value)

**AF** = Antenna Factor in dB(m<sup>-1</sup>). (stored as a data array)

**G** = Preamplifier Gain in dB. (stored as a data array)

**L** = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

##### • Example Field Strength Calculation

Assuming a receiver reading of 34.0 dBμV is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$

Measurement uncertainty with a confidence interval of 95% is:

- Free radiation tests (1000 MHz – 18,000 MHz) ± 4.1 dB



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

### 4.3 Radiated Emissions (Spurious and Harmonics)

#### 4.3.1 Frequency Band: 1 – 40 GHz

All measurements above 1 GHz were initially made over a distance of 3 metres. This was decreased to 1.0 metre as the emission levels from the device were very low.

The 54 dB $\mu$ V/m limit at 3 metres has been converted to 64 dB $\mu$ V/m at 1 metre using a factor of 20 dB per decade where emissions were located in the restricted bands.

Measurements were performed on 3 Fujitsu host notebooks E8110, E8210 and S7110 and all test results are reported.

Testing was performed while both the WLAN transmitter and Bluetooth transmitter continuously operated. Harmonics related to the WLAN transmitter (2.4 – 2.4835 GHz and 5.725 – 5.850 GHz) are reported below. Harmonics in the frequency band (5.15 – 5.35 GHz), refer to M060108\_Cert\_WM3945ABG\_NII. Harmonics related to the Bluetooth transmitter refer to M060108\_Cert\_EYTF3CSFT.

##### 4.3.1.1 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 11 Mbps (CCK).

The EUT was operating at its highest channel (2462 MHz), the field strength at 2483.5 MHz was:  
 55.3 dB $\mu$ V/m peak and 42.4 dB $\mu$ V/m average (E8110 LifeBook).  
 52.4 dB $\mu$ V/m peak and 40.4 dB $\mu$ V/m average (S7110 LifeBook).  
 51.7 dB $\mu$ V/m peak and 40.0 dB $\mu$ V/m average (E8210 LifeBook).  
 The levels were > 20 dB below the maximum field strength of the in-band carrier.

The EUT was operating at its lowest channel (2412 MHz), the field strength at 2400 MHz was:  
 64.5 dB $\mu$ V/m peak and 56.1 dB $\mu$ V/m average (E8110 LifeBook).  
 60.7 dB $\mu$ V/m peak and 51.4 dB $\mu$ V/m average (S7110 LifeBook).  
 61.4 dB $\mu$ V/m peak and 53.3 dB $\mu$ V/m average (E8210 LifeBook).  
 The levels were > 20 dB below the maximum field strength of the in-band carrier.

#### Channel 1 - 2412 MHz

Frequency MHz	E8110 LifeBook Level (dB $\mu$ V/m)		S7110 LifeBook Level (dB $\mu$ V/m)		E8210 LifeBook Level (dB $\mu$ V/m)		Peak Limit dB $\mu$ V/m	Average Limit dB $\mu$ V/m	Result
	Peak Detector	Average Detector	Peak Detector	Average Detector	Peak Detector	Average Detector			
<b>2412</b>	<b>Transmitter Fundamental</b>								
<b>4824</b>	<b>60.1</b>	<b>46.8</b>	<b>58.0</b>	<b>44.6</b>	<b>56.3</b>	<b>44.1</b>	74.0	54.0	Pass
7236	46	35	46	35	46	35	-	-	-
9648	49	38	49	38	49	38	-	-	-
12060	53	41	53	41	53	41	74.0	54.0	Pass
14472	57	45	57	45	57	45	74.0	54.0	Pass
16884	56	45	56	45	56	45	-	-	-
19296	65	52	65	52	65	52	84.0*	64.0*	Pass
21708	69	56	69	56	69	56	-	-	-
24120	69	56	69	56	69	56	-	-	-
<b>2425.7</b>	<b>61.2</b>	<b>47.2</b>	<b>60.1</b>	<b>45.9</b>	<b>61.0</b>	<b>46.8</b>	-	-	-
<b>2397.9</b>	<b>59.1</b>	<b>43.7</b>	<b>58.4</b>	<b>43.1</b>	<b>58.1</b>	<b>44.1</b>	-	-	-
<b>2312</b>	<b>51.5</b>	<b>42.4</b>	<b>51.0</b>	<b>42.8</b>	<b>50.2</b>	<b>41.7</b>	74.0	54.0	Pass
<b>2512</b>	<b>48.7</b>	<b>39.6</b>	<b>45.8</b>	<b>37.6</b>	<b>46.9</b>	<b>38.3</b>	-	-	-

\*Limits were corrected for 1 metre measurement.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

**Channel 6 - 2437 MHz**

Frequency MHz	E8110 LifeBook Level (dBuV/m)		S7110 LifeBook Level (dBuV/m)		E8210 LifeBook Level (dBuV/m)		Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector	Peak Detector	Average Detector	Peak Detector	Average Detector			
<b>2437</b>	<b>Transmitter Fundamental</b>								
<b>4874</b>	<b>60.3</b>	<b>47.4</b>	<b>58.2</b>	<b>45.8</b>	<b>57.8</b>	<b>46.1</b>	74.0	54.0	Pass
7311	46	35	46	35	46	35	74.0	54.0	Pass
9748	49	38	49	38	49	38	-	-	-
12185	53	41	53	41	53	41	74.0	54.0	Pass
14622	57	45	57	45	57	45	-	-	-
17059	56	45	56	45	56	45	-	-	-
19496	65	52	65	52	65	52	84.0*	64.0*	Pass
21933	69	56	69	56	69	56	-	-	-
24370	69	56	69	56	69	56	-	-	-
<b>2451.3</b>	<b>61.9</b>	<b>47.7</b>	<b>60.1</b>	<b>43.5</b>	<b>58.3</b>	<b>43.1</b>	-	-	-
<b>2422.3</b>	<b>59.2</b>	<b>43.5</b>	<b>59.6</b>	<b>43.4</b>	<b>60.7</b>	<b>44.4</b>	-	-	-
<b>2337</b>	<b>51.0</b>	<b>43.2</b>	<b>50.1</b>	<b>42.3</b>	<b>49.6</b>	<b>41.5</b>	74.0	54.0	Pass
<b>2537</b>	<b>49.3</b>	<b>38.7</b>	<b>48.1</b>	<b>37.4</b>	<b>48.2</b>	<b>36.7</b>	-	-	-

\*Limits were corrected for 1 metre measurement.

**Channel 11 - 2462 MHz**

Frequency MHz	E8110 LifeBook Level (dBuV/m)		S7110 LifeBook Level (dBuV/m)		E8210 LifeBook Level (dBuV/m)		Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector	Peak Detector	Average Detector	Peak Detector	Average Detector			
<b>2462</b>	<b>Transmitter Fundamental</b>								
<b>4924</b>	<b>58.4</b>	<b>46.7</b>	<b>57.6</b>	<b>45.2</b>	<b>55.1</b>	<b>43.0</b>	74.0	54.0	Pass
7386	46	35	46	35	46	35	74.0	54.0	Pass
9848	49	38	49	38	49	38	-	-	-
12310	53	41	53	41	53	41	74.0	54.0	Pass
14772	57	45	57	45	57	45	-	-	-
17234	56	45	56	45	56	45	-	-	-
19696	65	52	65	52	65	52	84.0*	64.0*	Pass
22158	69	56	69	56	69	56	84.0*	64.0*	Pass
24620	69	56	69	56	69	56	-	-	-
<b>2476.3</b>	<b>59.4</b>	<b>45.7</b>	<b>59.8</b>	<b>46.4</b>	<b>57.5</b>	<b>44.1</b>	-	-	-
<b>2447</b>	<b>58.3</b>	<b>43.1</b>	<b>60.5</b>	<b>45.7</b>	<b>56.3</b>	<b>42.6</b>	-	-	-
<b>2360</b>	<b>50.0</b>	<b>39.5</b>	<b>49.2</b>	<b>38.6</b>	<b>48.8</b>	<b>36.0</b>	74.0	54.0	Pass

\*Limits were corrected for 1 metre measurement.

**Result:** 2<sup>nd</sup> harmonic and spurious emissions were recorded within the restricted bands of up to 25 GHz. Other harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). The worst case harmonics were complied with the FCC limits in sections 15.209 and 15.247 by a margin of 6.6 dB. The measurement uncertainty for radiated emissions in this band was  $\pm 4.1$  dB.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

**4.3.1.2 Configuration 802.11g**

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (BPSK).

The EUT was operating at its highest channel (2462 MHz), the field strength at 2483.5 MHz was:  
 73.2 dB $\mu$ V/m peak and 55.8 dB $\mu$ V/m average (E8110 LifeBook).  
 68.5 dB $\mu$ V/m peak and 50.9 dB $\mu$ V/m average (S7110 LifeBook).  
 70.1 dB $\mu$ V/m peak and 53.4 dB $\mu$ V/m average (E8210 LifeBook).  
 The levels were > 20 dB below the maximum field strength of the in-band carrier.

The EUT was operating at its lowest channel (2412 MHz), the field strength at 2400 MHz was:  
 87.5 dB $\mu$ V/m peak and 64.7 dB $\mu$ V/m average (E8110 LifeBook).  
 81.7 dB $\mu$ V/m peak and 59.6 dB $\mu$ V/m average (S7110 LifeBook).  
 85.6 dB $\mu$ V/m peak and 62.2 dB $\mu$ V/m average (E8210 LifeBook).  
 The levels were > 20 dB below the maximum field strength of the in-band carrier.

**Channel 1 - 2412 MHz**

Frequency MHz	E8110 LifeBook Level (dB $\mu$ V/m)		S7110 LifeBook Level (dB $\mu$ V/m)		E8210 LifeBook Level (dB $\mu$ V/m)		Peak Limit dB $\mu$ V/m	Average Limit dB $\mu$ V/m	Result
	Peak Detector	Average Detector	Peak Detector	Average Detector	Peak Detector	Average Detector			
<b>2412</b>	<b>Transmitter Fundamental</b>								
<b>4824</b>	<b>61.3</b>	<b>47.5</b>	<b>54.4</b>	<b>43.8</b>	<b>53.2</b>	<b>40.8</b>	74.0	54.0	Pass
7236	46	35	46	35	46	35	-	-	-
9648	49	38	49	38	49	38	-	-	-
12060	53	41	53	41	53	41	74.0	54.0	Pass
14472	57	45	57	45	57	45	74.0	54.0	Pass
16884	56	45	56	45	56	45	-	-	-
19296	65	52	65	52	65	52	84.0*	64.0*	Pass
21708	69	56	69	56	69	56	-	-	-
24120	69	56	69	56	69	56	-	-	-
<b>2312</b>	<b>53.6</b>	<b>45.0</b>	<b>51.8</b>	<b>43.1</b>	<b>51.6</b>	<b>41.7</b>	74.0	54.0	Pass
<b>2512</b>	<b>49.9</b>	<b>42.1</b>	<b>48.7</b>	<b>41.2</b>	<b>48.9</b>	<b>40.8</b>	-	-	-

\*Limits were corrected for 1 metre measurement.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

**Channel 6 - 2437 MHz**

Frequency MHz	E8110 LifeBook Level (dBuV/m)		S7110 LifeBook Level (dBuV/m)		E8210 LifeBook Level (dBuV/m)		Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector	Peak Detector	Average Detector	Peak Detector	Average Detector			
<b>2437</b>	<b>Transmitter Fundamental</b>								
<b>4874</b>	<b>60.8</b>	<b>47.0</b>	<b>52.7</b>	<b>42.2</b>	<b>51.6</b>	<b>40.3</b>	74.0	54.0	Pass
7311	46	35	46	35	46	35	74.0	54.0	Pass
9748	49	38	49	38	49	38	-	-	-
12185	53	41	53	41	53	41	74.0	54.0	Pass
14622	57	45	57	45	57	45	-	-	-
17059	56	45	56	45	56	45	-	-	-
19496	65	52	65	52	65	52	84.0*	64.0*	Pass
21933	69	56	69	56	69	56	-	-	-
24370	69	56	69	56	69	56	-	-	-
<b>2337</b>	<b>53.9</b>	<b>44.8</b>	<b>50.0</b>	<b>42.3</b>	<b>50.6</b>	<b>41.7</b>	74.0	54.0	Pass
<b>2537</b>	<b>49.6</b>	<b>41.6</b>	<b>46.7</b>	<b>40.1</b>	<b>47.8</b>	<b>40.3</b>	-	-	-

\*Limits were corrected for 1 metre measurement.

**Channel 11 - 2462 MHz**

Frequency MHz	E8110 LifeBook Level (dBuV/m)		S7110 LifeBook Level (dBuV/m)		E8210 LifeBook Level (dBuV/m)		Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector	Peak Detector	Average Detector	Peak Detector	Average Detector			
<b>2462</b>	<b>Transmitter Fundamental</b>								
<b>4924</b>	<b>60.0</b>	<b>46.3</b>	<b>51.4</b>	<b>40.7</b>	<b>50.7</b>	<b>40.0</b>	74.0	54.0	Pass
7386	46	35	46	35	46	35	74.0	54.0	Pass
9848	49	38	49	38	49	38	-	-	-
12310	53	41	53	41	53	41	74.0	54.0	Pass
14772	57	45	57	45	57	45	-	-	-
17234	56	45	56	45	56	45	-	-	-
19696	65	52	65	52	65	52	84.0*	64.0*	Pass
22158	69	56	69	56	69	56	84.0*	64.0*	Pass
24620	69	56	69	56	69	56	-	-	-
<b>2360</b>	<b>50.8</b>	<b>42.7</b>	<b>48.7</b>	<b>41.0</b>	<b>47.1</b>	<b>39.6</b>	74.0	54.0	Pass

\*Limits were corrected for 1 metre measurement.

**Result:** 2<sup>nd</sup> harmonic and spurious emissions were recorded within the restricted bands of up to 25 GHz. Other harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). The worst case harmonics were complied with the FCC limits in sections 15.209 and 15.247 by a margin of 6.5 dB. The measurement uncertainty for radiated emissions in this band was  $\pm 4.1$  dB.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.



**4.3.1.3 Configuration 802.11a (5.725 – 5.850 MHz)**

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

The EUT was operating at its highest channel (5825 MHz), the field strength at 5850 MHz was:

66.5 dB $\mu$ V/m peak and 55.6 dB $\mu$ V/m average (E8110 LifeBook).

62.8 dB $\mu$ V/m peak and 52.3 dB $\mu$ V/m average (S7110 LifeBook)

64.4 dB $\mu$ V/m peak and 53.1 dB $\mu$ V/m average (E8210 LifeBook)

The levels were > 20 dB below the maximum field strength of the in-band carrier.

The EUT was operating at its lowest channel (5745 MHz), the field strength at 5725 MHz was:

71.4 dB $\mu$ V/m peak and 59.7 dB $\mu$ V/m average (E8110 LifeBook).

68.7 dB $\mu$ V/m peak and 55.5 dB $\mu$ V/m average (S7110 LifeBook)

67.5 dB $\mu$ V/m peak and 55.6 dB $\mu$ V/m average (E8210 LifeBook)

The levels were > 20 dB below the maximum field strength of the in-band carrier.

**Channel 149 - 5745 MHz**

Frequency MHz	E8110 LifeBook Level (dBuV/m)		S7110 LifeBook Level (dBuV/m)		E8210 LifeBook Level (dBuV/m)		Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector	Peak Detector	Average Detector	Peak Detector	Average Detector			
<b>5745</b>	<b>Transmitter Fundamental</b>								
11490	53	40	53	40	53	40	74.0	54.0	Pass
17235	56	43	56	43	56	43	-	-	-
22980	69	56	69	56	69	56	84.0*	64.0*	Pass
28725	79	67	79	67	79	67	-	-	-
34470	80	68	80	68	80	68	-	-	-
<b>4932</b>	<b>59.8</b>	<b>47.3</b>	<b>51.3</b>	<b>42.3</b>	<b>51.8</b>	<b>42.0</b>	74.0	54.0	Pass
<b>5545</b>	<b>55.1</b>	<b>43.6</b>	-	-	-	-	-	-	-
<b>5394</b>	<b>54.0</b>	<b>43.3</b>	-	-	-	-	74.0	54.0	Pass
<b>4701</b>	-	-	<b>52.4</b>	<b>43.6</b>	-	-	74.0	54.0	Pass

\*Limits were corrected for 1 metre measurement.

**Channel 157 - 5785 MHz**

Frequency MHz	E8110 LifeBook Level (dBuV/m)		S7110 LifeBook Level (dBuV/m)		E8210 LifeBook Level (dBuV/m)		Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector	Peak Detector	Average Detector	Peak Detector	Average Detector			
<b>5785</b>	<b>Transmitter Fundamental</b>								
11570	53	40	53	40	53	40	74.0	54.0	Pass
17355	56	43	56	43	56	43	-	-	-
23140	69	56	69	56	69	56	-	-	-
28925	79	67	79	67	79	67	-	-	-
34710	80	68	80	68	80	68	-	-	-
<b>4821.7</b>	<b>61.4</b>	<b>48.4</b>	<b>53.7</b>	<b>43.4</b>	<b>54.6</b>	<b>44.1</b>	74.0	54.0	Pass
<b>4943</b>	<b>58.6</b>	<b>47.1</b>	<b>52.2</b>	<b>41.0</b>	-	-	74.0	54.0	Pass
<b>5424.5</b>	<b>55.9</b>	<b>43.8</b>	-	-	<b>52.3</b>	<b>41.0</b>	74.0	54.0	Pass
<b>5540.2</b>	-	-	<b>54.8</b>	<b>45.1</b>	-	-	-	-	-



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.



**Channel 165 - 5825 MHz**

Frequency MHz	E8110 LifeBook Level (dBuV/m)		S7110 LifeBook Level (dBuV/m)		E8210 LifeBook Level (dBuV/m)		Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector	Peak Detector	Average Detector	Peak Detector	Average Detector			
<b>5825</b>	<b>Transmitter Fundamental</b>								
11650	53	40	53	40	53	40	74.0	54.0	Pass
17475	56	43	56	43	56	43	-	-	-
23300	69	56	69	56	69	56	-	-	-
29125	79	67	79	67	79	67	-	-	-
34950	80	68	80	68	80	68	-	-	-
<b>4854.7</b>	<b>61.0</b>	<b>48.8</b>	<b>56.7</b>	<b>44.8</b>	<b>55.8</b>	<b>44.2</b>	74.0	54.0	Pass
<b>4978.1</b>	<b>55.1</b>	<b>43.0</b>	<b>50.0</b>	<b>38.2</b>	-	-	74.0	54.0	Pass
<b>5221.5</b>	-	-	<b>56.1</b>	<b>44.5</b>	-	-	-	-	-

**Result:** Spurious emissions were recorded within the restricted bands of up to 40 GHz. Harmonics were low and confirmed with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Emissions were complied with the FCC limits in section 15.209 and 15.247 by a margin of 5.2 dB. The measurement uncertainty for radiated emissions in this band was  $\pm 4.1$  dB.

**4.3.2 Frequency Band: 30 - 1000 MHz**

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG06-016EAL).



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

#### 4.3.3 RF Conducted Measurements at the Antenna Terminal

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

D1 line indicates the 20 dB limit below the highest level of the transmitter

**Results:** Complies.

##### **Configuration 802.11a (5.725 – 5.850 GHz)**

Refer to Appendix K1 for Harmonics plots

##### **Configuration 802.11b**

Refer to Appendix K2 for Harmonics plots

##### **Configuration 802.11g**

Refer to Appendix K3 for Harmonics plots

#### 4.3.4 Band Edge Measurements

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

D1 line indicates the 20 dB limit below the highest level of the transmitter

**Results:** Complies.

##### **Configuration 802.11a (5.725 – 5.850 GHz)**

Refer to Appendix L1 for Band Edge plots

##### **Configuration 802.11b**

Refer to Appendix L2 for Band Edge plots

##### **Configuration 802.11g**

Refer to Appendix L3 for Band Edge plots



## 5.0 PEAK OUTPUT POWER - Section 15.247 (b)(3)

Testing was performed in accordance with the requirements of FCC Part 15.247(b)(3).

Measurements were performed while the WLAN transmitter continuously transmitted.

The peak output power measurement was performed using the integration method as per test method # 3 of DA 02-2138. The resolution bandwidth of 1 MHz was used. The video bandwidth of 30 kHz was used ( $VBW \geq 1/T$ , where T (worst case) = 230  $\mu$ S).

Variation by +/- 15% of the supply voltage, in accordance with Section 15.31(e), to the computer power supply did not vary the output power observed.

### 5.1 Configuration 802.11a

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in peak power were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54Mbps (64QAM).

Frequency MHz	P dBm	Limit dBm	P mW	Limit mW	Result
5745	17.3	30	53.7	1000	Complies
5785	17.9	30	61.7	1000	Complies
5825	17.5	30	56.2	1000	Complies

### 5.2 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). Power with CCK modulation (rate = 11 Mbps) was observed to be slightly worst. Final testing was performed while the transmitter continuously operating with the modulation rate of 11 Mbps (CCK).

Frequency MHz	P dBm	Limit dBm	P mW	Limit mW	Result
2412	14.1	30	25.7	1000	Complies
2437	15.3	30	33.9	1000	Complies
2462	15.6	30	36.3	1000	Complies

### 5.3 Configuration 802.11g

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in peak power were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54Mbps (64QAM).

Frequency MHz	P dBm	Limit dBm	P mW	Limit mW	Result
2412	16.4	30	43.7	1000	Complies
2437	17.1	30	51.3	1000	Complies
2462	16.0	30	39.8	1000	Complies



## 6.0 CHANNEL BANDWIDTH

Testing was performed in accordance with the requirements of FCC Part 15.247(a)(2)

In the bands 2400 - 2483.5 MHz and 5725 - 5850 MHz, the minimum 6 dB bandwidth was at least 500 kHz. The 6 dB bandwidth was measured while the transmitter continuously transmitted.

The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised

The minimum 6 dB bandwidth is at least 500 kHz

### 6.1 Configuration 802.11a

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

Frequency MHz	Bandwidth MHz	Result	6 dB Bandwidth Plots
5745	16.6	Complies	Appendix J1
5785	16.6	Complies	Appendix J1
5825	16.6	Complies	Appendix J1

### 6.2 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operating with the modulation rate of 11 Mbps (CCK).

Frequency MHz	Bandwidth MHz	Result	6 dB Bandwidth Plots
2412.0	9.0	Complies	Appendix J2
2437.0	9.0	Complies	Appendix J2
2462.0	9.0	Complies	Appendix J2

### 6.3 Configuration 802.11g

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

Frequency MHz	Bandwidth MHz	Result	6 dB Bandwidth Plots
2412.0	16.6	Complies	Appendix J3
2437.0	16.6	Complies	Appendix J3
2462.0	16.6	Complies	Appendix J3



## 7.0 PEAK POWER SPECTRAL DENSITY - Section 15.247(e)

Testing was performed accordance with the requirements of FCC Part 15.247(e)

The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 3 kHz and the video bandwidth of 30 kHz were utilised

The specification limit is 8 dBm in any 3 kHz band during a continuous transmission.

### 7.1 Configuration 802.11a

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). Peak power spectral density with BPSK modulation (rate = 6 Mbps) was observed to be slightly worst. Final testing was performed while the transmitter continuously operated with the modulation rate of 6 Mbps (BPSK).

Frequency MHz	Level dBm	Limit dBm	Result	Spectral Density plots
5745	-9.3	8.0	Complies	Appendix M1
5785	-7.8	8.0	Complies	Appendix M1
5825	-8.5	8.0	Complies	Appendix M1

### 7.2 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). Peak power spectral density with CCK modulation (rate = 11 Mbps) was observed to be slightly worst. Final testing was performed while the transmitter continuously operating with the modulation rate of 11 Mbps (CCK).

Frequency MHz	Level dBm	Limit dBm	Result	Spectral Density plots
2412.0	-6.6	8.0	Complies	Appendix M2
2437.0	-6.5	8.0	Complies	Appendix M2
2462.0	-6.4	8.0	Complies	Appendix M2

### 7.3 Configuration 802.11g

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). Peak power spectral density with 64QAM modulation (rate = 54 Mbps) was observed to be slightly worst. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

Frequency MHz	Level dBm	Limit dBm	Result	Spectral Density plots
2412.0	-7.2	8.0	Complies	Appendix M3
2437.0	-7.9	8.0	Complies	Appendix M3
2462.0	-10.1	8.0	Complies	Appendix M3



## 8.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.247(i)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

Transmitter # 1: The WLAN antennas are located on the top edge of LCD screen (2 antennas left and right) and projected distance of greater than 20cm from user.

Transmitter # 2: The Bluetooth antenna is located under the LHS of keyboard (near Caps lock area) and projected distance of less than 20cm from user.

SAR is not required as the WLAN transmitter is mobile device and the power for the Bluetooth transmitter is below the low threshold.

The separation distance between the WLAN and BT antennas is greater than 20cm. Therefore, they are not co-located transmitters.

The MPE calculation shown below is the aggregate of WLAN and BT power densities.

In accordance with Section 1.1310, the Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure of 1.0 has been applied, i.e 1mW/cm<sup>2</sup>.

Friis transmission formula:  $P_d = (P \cdot G) / (4 \cdot \pi \cdot r^2)$

where:  $P_d$  = power density (mW/cm<sup>2</sup>)

$P$  = power input to the antenna (mW)

$G$  = antenna gain (numeric)

$r$  = distance to the center of radiation of the antenna (cm)

**The result was extracted from section 5.0 of this report (WLAN Module):**

Prediction frequency = **5785 MHz**

Maximum peak output power = 17.9 dBm = 61.7 mW

Antenna (Monopole) gain (max) = 1.79 dBi = 1.51 numeric

The power density calculated = 0.02 mW/cm<sup>2</sup>

Prediction frequency = **2437 MHz**

Maximum peak output power = 17.1 dBm = 51.3 mW

Antenna (Inverted F) gain (max) = 2.47 dBi = 1.77 numeric

The power density calculated = 0.02 mW/cm<sup>2</sup>

**The result was extracted from section 5.0 of M060108\_Cert\_EYTF3CSFT (BT Module):**

Prediction frequency = 2480 MHz

Maximum peak output power = 3.3 dBm = 2.1 mW

Antenna (Inverted F) gain (max) = 2.78 dBi = 1.9 numeric

The power density calculated = 0.001 mW/cm<sup>2</sup>

Therefore, the power density (WLAN + BT) = 0.021 mW/cm<sup>2</sup>

MPE limit for uncontrolled exposure at prediction frequency = 1 mW/cm<sup>2</sup>

**Results:** Calculations show that the Radio devices with described antennas complied with Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 9.0 ANTENNA REQUIREMENT

Testing to the requirements of FCC Part 15.203 was not applicable as this intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

## 10.0 COMPLIANCE STATEMENT

The INTEL Mini-PCI Wireless LAN Module (GOLAN 11a+b/g), Model: WM3945ABG installed in Fujitsu notebook PCs tested on behalf of Fujitsu Australia Ltd, **comply** with the requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators), Section 15.247 - Operation in the frequency band 2400 - 2483.5 MHz and 5725 – 5850 MHz.

The test sample also complies with the Industry Canada RSS-210 issue 6 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) 2400 – 2483.5 MHz Spread Spectrum requirements and the RF exposure requirements of RSS-102.

Results were as follows:

### FCC Subpart C, Section 15.247

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	<b>Not Applicable</b>
15.205	6.3	Operation in Restricted Band	<b>Complies</b>
15.207	6.6	Conducted Emissions	<b>Complies</b>
15.209	6.3	Radiated Emissions	<b>Complies</b>
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	<b>Complies</b>
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	<b>Complies</b>
15.247 (i)		Radio Frequency Hazard	<b>Complies</b>
15.247 (d)	6.2.2(o)(e1)	Out of Band Emissions	<b>Complies</b>
15.247 (e)	6.2.2(o)(iv)	Peak Power Spectral Density	<b>Complies</b>

The results for IEEE 802.11a (U-NII) is reported separately.

Refer to EMC Technologies' test report: M060108\_Cert\_WM3945ABG\_NII (U-NII)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## TEST REPORT APPENDICES

**APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**  
**APPENDIX B: REPORT PHOTOGRAPHS**  
**APPENDIX C: FUNCTIONAL DESCRIPTION**  
**APPENDIX D: BLOCK DIAGRAM**  
**APPENDIX E: SCHEMATICS**  
**APPENDIX F: ANTENNA INFORMATION**  
**APPENDIX G: SPECIFICATIONS**  
**APPENDIX H: FCC LABELLING DETAILS**  
**APPENDIX I: USER MANUAL**  
**APPENDIX J: CHANNEL BANDWIDTH PLOTS**  
**APPENDIX K: HARMONICS PLOTS**  
**APPENDIX L: BANDEDGE PLOTS**  
**APPENDIX M: PEAK POWER SPECTRAL DENSITY PLOTS**

**Attachment 1: RF Exposure Information**

**Attachment 2: FCC DOC for Fujitsu Notebooks**

**Attachment 3: FCC Part 15B Test Report (Report: FG06-016EAL)**



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.