



Acknowledgement

SPECIFICATION FOR APPROVAL

CUSTOMER NAME: 360

PRODUCT NAME: 2.4G 3.54dBiInternalantenna

CUSTOMER P/N:

Ren Feng P/N: U00T02S000N02806 REV: A

Internal structure: FPC


	MANUFACTURER SIGNATURE	CUSTOMER SIGNATURE
CHECKED BY:	Zhou Rongchuang	
AUDITOR BY:	Xiao-Lin Liu	
APPROVED BY:	Yao Dingjun	
DATE:	2023-02-21	

Resume

[illegible]

Contents

<i>Description</i>	<i>Page</i>
1、 Cover -----	1
2、 Resume -----	2
3、 Contents-----	3
4、 Specifications sheets-----	4
5、 End product chart-----	5
6、 Testing report -----	6 -8
7、 Material description -----	9



Main technical specifications

Main technical specifications		Main technical specifications	
Frequency Range (MHZ)	2400-2500MHZ	Frequency Range (MHZ)	2400-2500
Impedance(Ω)	50	Impedance(Ω)	50
Gain(dBi)	3.54	Gain(dBi)	3.54
Return Loss(dB)	≤ -9.5	Return Loss(dB)	≤ -9.5
VSWR	≤ 2.0	VSWR	≤ 2.0
Polarization	Linear, Vertical	Polarization	Linear, Vertical
Radiation	Omni-directional	Radiation	Omni-directional
Connector Type	terminal	Connector Type	terminal
Physical Properties		Physical Properties	
AntennaBase	FPC	Antenna Base	FPC
Operating Temp	-20℃~+70℃	Operating Temp	-20℃~+70℃
Storage Temp	-20℃~+70℃	Storage Temp	-20℃~+70℃


Antenna assembly diagram

External WIFI antenna







Antenna assembly diagram

Horizontal plane: XY plane






6. Testing report

6.1 Network analyzer test report



WIFI3-2.4G



6.2:Antenna gain,efficiency meter

Freq (MHz)	Effi (%)	Gain (dBi)
2400	75.51	2.84
2410	76.9	2.93
2420	77.5	3.04
2430	79.13	3.17
2440	79.95	3.26
2450	78.92	3.28
2460	77.5	3.36
2470	77.5	3.45
2480	77.9	3.54
2490	77.3	3.5
2500	76.5	3.43

七、 ROHS/ Raw Material List:

Meet RoHS requirements

Component number	Component name	material	quantity	unit	manufacturer	number	remarks
1	FPC	PI	1	PCS	junyi	/	
2	Back glue	Double-sided adhesive	1	PCS	junyi	/	