



TEST REPORT

Applicant: Zhejiang Okai Vehicle Co., Ltd

Address: No. 9, Xinxing Road, Xinbi Town, Jinyun County, Zhejiang, China

FCC ID: 2AYF8-SH10

Product Name: Smart Helmet

Model Number: SH10

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR22010035-00A

Date Of Issue: 2022-07-07

Reviewed By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 DESCRIPTION OF TEST CONFIGURATION.....	7
1.2.2 Support Equipment List and Details	7
1.2.3 Support Cable List and Details	7
1.2.4 Block Diagram of Test Setup.....	7
1.3 MEASUREMENT UNCERTAINTY	8
2. SUMMARY OF TEST RESULTS	9
3. REQUIREMENTS AND TEST PROCEDURES	10
3.1 AC LINE CONDUCTED EMISSIONS.....	10
3.1.1 Applicable Standard.....	10
3.1.2 EUT Setup.....	11
3.1.3 EMI Test Receiver Setup	11
3.1.4 Test Procedure	12
3.1.5 Corrected Amplitude & Margin Calculation.....	12
3.2 RADIATION SPURIOUS EMISSIONS.....	13
3.2.1 Applicable Standard.....	13
3.2.2 EUT Setup.....	13
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	14
3.2.4 Test Procedure	14
3.2.5 Corrected Amplitude & Margin Calculation.....	14
3.3 20 dB BANDWIDTH.....	15
3.3.1 Applicable Standard.....	15
3.3.2 EUT Setup.....	15
3.3.3 Test Procedure	15
3.4 CHANNEL SEPARATION	16
3.4.1 Applicable Standard.....	16
3.4.2 EUT Setup.....	16
3.4.3Test Procedure	16
3.5 NUMBER OF HOPPING FREQUENCY	17
3.5.1 Applicable Standard.....	17
3.5.2 EUT Setup.....	17
3.5.3Test Procedure	17
3.6 TIME OF OCCUPANCY(DWELL TIME).....	18
3.6.1 Applicable Standard.....	18
3.6.2 EUT Setup.....	18
3.6.3Test Procedure	18
3.7 PEAK OUTPUT POWER.....	19
3.7.1 Applicable Standard.....	19

3.7.2 EUT Setup.....	19
3.7.3 Test Procedure	19
3.8 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	20
3.8.1 Applicable Standard.....	20
3.8.2 EUT Setup.....	20
3.8.3 Test Procedure	20
3.9 ANTENNA REQUIREMENT.....	21
3.9.1 Applicable Standard.....	21
3.9.2 Judgment	21
4. TEST DATA AND RESULTS	22
4.1 AC LINE CONDUCTED EMISSIONS.....	22
4.2 RADIATION SPURIOUS EMISSIONS.....	23
4.3 20 dB EMISSION BANDWIDTH:	31
4.4 CHANNEL SEPARATION:	35
4.5 NUMBER OF HOPPING FREQUENCY:	39
4.6 TIME OF OCCUPANCY(DWELL TIME):.....	41
4.7 PEAK CONDUCTED OUTPUT POWER:	45
4.8 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE:	46
5. RF EXPOSURE EVALUATION	53
5.1 APPLICABLE STANDARD.....	53
5.2 PROCEDURE.....	53
5.2 PROCEDURE.....	53
5.3 MEASUREMENT RESULT	55

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Smart Helmet
EUT Model:	SH10
Operation Frequency:	2402-2480 MHz
Maximum Peak Output Power (Conducted):	3.93dBm
Modulation Type:	GFSK, π/4-DQPSK, 8DPSK
Rated Input Voltage:	DC3.8V from battery
Serial Number:	CR22010035-RF-S1
EUT Received Date:	2022.6.6
EUT Received Status:	Good

Operation Frequency Detail:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	41	2443
...
...
..	...	78	2480
39	2441	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2402
Middle	2441
Highest	2480

Antenna Information Detail▲:

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range	§15.203 Requirement
PCB	50	-0.71 dBi/ 2.4~2.5GHz	Compliance

The Method of §15.203 Compliance:

- Antenna must be permanently attached to the unit.
- Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Power Cable	Unknown	Unknown	Unshielded, 1m

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer. EUT has two bluetooth modules, one is Main Control Module, and another is Audio Module. Only Audio Module use BDR/EDR mode.		
Equipment Modifications:	No		
EUT Exercise Software:	BK32xx RF Test		
The software “BK32xx RF Test” was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲ :			
Test Modes	Lowest	Middle	Highest
GFSK	3	3	3
$\pi/4$ -DQPSK	3	3	3
8DPSK	3	3	3

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
/	/	/	/	/	/

1.2.4 Block Diagram of Test Setup

Spurious Emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207(a)	AC line conducted emissions	Not applicable
FCC §15.205, §15.209, §15.247(d)	Radiated Spurious emissions	Compliant
FCC §15.247(a)(1)	20 dB bandwidth	Compliant
FCC §15.247(a)(1)	Channel separation	Compliant
FCC §15.247(a)(1)(iii)	Number of hopping Frequency	Compliant
FCC §15.247(a)(1)(iii)	Time of occupancy (dwell time)	Compliant
FCC §15.247(b)(1)	Peak output power measurement	Compliant
FCC §15.247(d)	Band edges	Compliant
FCC §15.203	Antenna requirement	Compliant
FCC §15.247 (i) & §1.1307	RF Exposure Evaluation	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.2.2 EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 20 dB Bandwidth

3.3.1 Applicable Standard

FCC §15.247 (a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

3.3.2 EUT Setup



3.3.3 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.


3.4 Channel Separation

3.4.1 Applicable Standard

FCC §15.247 (a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

3.4.2 EUT Setup



3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.


3.5 Number Of Hopping Frequency

3.5.1 Applicable Standard

FCC §15.247 (a)(1)(iii)

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.3

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize


It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

3.6 Time Of Occupancy(Dwell Time)

3.6.1 Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

3.6.2 EUT Setup



3.6.3 Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.


3.7 Peak Output Power

3.7.1 Applicable Standard

FCC §15.247 (b)(1)

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

3.7.2 EUT Setup



3.7.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
2. Add a correction factor to the display.


3.8 100 kHz Bandwidth of Frequency Band Edge

3.8.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.8.2 EUT Setup



3.8.3 Test Procedure

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.9 Antenna Requirement

3.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.9.2 Judgment

Please refer to the Antenna Information detail in Section 1.

4. TEST DATA AND RESULTS

4.1 AC Line Conducted Emissions

Not Applicable, the device was powered by battery when operating.

4.2 Radiation Spurious Emissions

Serial Number:	CR22010035-RF-S1	Test Date:	2022-06-24~2022-06-27
Test Site:	966-1, 966-2	Test Mode:	Transmitting
Tester:	Nick Tang, Gary Ling	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	25.9~27.4	Relative Humidity: (%)	47~62	ATM Pressure: (kPa)	100.4

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
R&S	Spectrum Analyzer	FSV40	101591	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2021-08-08	2022-08-07
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2021-11-10	2022-11-09
Audix	Test Software	E3	201021 (V9)	N/A	N/A
PASTERNACK	Horn Antenna	PE9852/2F-20	112002	2021-02-05	2024-02-04
AH	Preamplifier	PAM-1840VH	190	2021-11-19	2022-11-18
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2021-08-08	2022-08-07
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2021-08-08	2022-08-07
Mini Circuits	High Pass Filter	VHF-6010+	31119	2021-08-08	2022-08-07
Sunol Sciences	Antenna	JB6	A082520-5	2020-10-19	2023-10-18
R&S	EMI Test Receiver	ESR3	102724	2021-07-22	2022-07-21
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2021-07-18	2022-07-17
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2021-07-18	2022-07-17
Sonoma	Amplifier	310N	186165	2021-07-18	2022-07-17

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Please refer to the below table and plots.

Note: The device can be mounted in multiple orientations, test was performed with X,Y, Z Axis according to C63.10 Figure 8, the worst orientation was photographed and it's data was recorded.

1) 30MHz-1GHz(BDR Low channel was the worst)**Horizontal:**

No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	161.993	50.22	-12.49	37.73	43.50	5.77	QP
2	162.022	46.99	-12.49	34.49	43.50	9.01	QP
3	167.012	52.37	-12.93	39.44	43.50	4.06	QP
4	195.004	47.84	-12.93	34.91	43.50	8.59	QP
5	268.485	50.49	-12.35	38.14	46.00	7.86	Peak
6	460.727	45.04	-6.92	38.12	46.00	7.88	Peak

Vertical:

No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	37.416	38.51	-9.49	29.02	40.00	10.98	Peak
2	44.587	41.54	-14.22	27.32	40.00	12.68	Peak
3	167.237	48.02	-12.94	35.08	43.50	8.42	Peak
4	193.773	49.56	-13.13	36.43	43.50	7.07	Peak
5	472.176	44.02	-6.56	37.46	46.00	8.54	Peak
6	672.845	41.52	-4.28	37.24	46.00	8.76	Peak

2) 1-25GHz:*BDR Mode(GFSK):*


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2402 MHz							
2402.00	54.18	PK	H	31.51	85.69	N/A	N/A
2402.00	44.60	AV	H	31.51	76.11	N/A	N/A
2402.00	61.23	PK	V	31.51	92.74	N/A	N/A
2402.00	51.86	AV	V	31.51	83.37	N/A	N/A
2390.00	27.02	PK	V	31.46	58.48	74.00	15.52
2390.00	13.85	AV	V	31.46	45.31	54.00	8.69
4804.00	51.50	PK	V	10.91	62.41	74.00	11.59
4804.00	38.50	AV	V	10.91	49.41	54.00	4.59
7206.00	41.12	PK	V	14.22	55.34	74.00	18.66
7206.00	26.49	AV	V	14.22	40.71	54.00	13.29
4003.50	43.64	PK	V	9.34	52.98	74.00	21.02
4003.50	32.24	AV	V	9.34	41.58	54.00	12.42
Middle Channel: 2441 MHz							
2441.00	55.16	PK	H	31.61	86.77	N/A	N/A
2441.00	45.60	AV	H	31.61	77.21	N/A	N/A
2441.00	62.38	PK	V	31.61	93.99	N/A	N/A
2441.00	52.18	AV	V	31.61	83.79	N/A	N/A
4882.00	52.33	PK	V	11.07	63.40	74.00	10.60
4882.00	38.72	AV	V	11.07	49.79	54.00	4.21
7323.00	40.14	PK	V	14.80	54.94	74.00	19.06
7323.00	26.41	AV	V	14.80	41.21	54.00	12.79
4068.10	39.84	PK	V	9.47	49.31	74.00	24.69
4068.10	28.11	AV	V	9.47	37.58	54.00	16.42
9764.00	38.76	PK	V	18.55	57.31	74.00	16.69
9764.00	22.10	AV	V	18.55	40.65	54.00	13.35
High Channel: 2480 MHz							
2480.00	55.86	PK	H	31.64	87.50	N/A	N/A
2480.00	45.92	AV	H	31.64	77.56	N/A	N/A
2480.00	62.99	PK	V	31.64	94.63	N/A	N/A
2480.00	53.58	AV	V	31.64	85.22	N/A	N/A
2483.50	33.02	PK	V	31.64	64.66	74.00	9.34
2483.50	14.28	AV	V	31.64	45.92	54.00	8.08
4960.00	53.04	PK	V	11.23	64.27	74.00	9.73
4960.00	41.97	AV	V	11.23	53.20	54.00	0.80
7440.00	40.27	PK	V	15.26	55.53	74.00	18.47
7440.00	26.14	AV	V	15.26	41.40	54.00	12.60
4133.27	38.76	PK	V	9.50	48.26	74.00	25.74
4133.27	26.14	AV	V	9.50	35.64	54.00	18.36
9920.00	39.64	PK	V	18.73	58.37	74.00	15.63
9920.00	23.80	AV	V	18.73	42.53	54.00	11.47


EDR Mode ($\pi/4$ -DQPSK):

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2402 MHz							
2402.00	54.43	PK	H	31.51	85.94	N/A	N/A
2402.00	41.94	AV	H	31.51	73.45	N/A	N/A
2402.00	62.30	PK	V	31.51	93.81	N/A	N/A
2402.00	49.98	AV	V	31.51	81.49	N/A	N/A
2390.00	27.02	PK	V	31.46	58.48	74.00	15.52
2390.00	13.86	AV	V	31.46	45.32	54.00	8.68
4804.00	54.91	PK	V	10.91	65.82	74.00	8.18
4804.00	40.25	AV	V	10.91	51.16	54.00	2.84
7206.00	42.66	PK	V	14.22	56.88	74.00	17.12
7206.00	26.93	AV	V	14.22	41.15	54.00	12.85
4003.50	43.65	PK	V	9.34	52.99	74.00	21.01
4003.50	30.88	AV	V	9.34	40.22	54.00	13.78
Middle Channel: 2441 MHz							
2441.00	55.49	PK	H	31.61	87.10	N/A	N/A
2441.00	42.68	AV	H	31.61	74.29	N/A	N/A
2441.00	63.35	PK	V	31.61	94.96	N/A	N/A
2441.00	51.00	AV	V	31.61	82.61	N/A	N/A
4882.00	54.76	PK	V	11.07	65.83	74.00	8.17
4882.00	40.58	AV	V	11.07	51.65	54.00	2.35
7323.00	42.41	PK	V	14.80	57.21	74.00	16.79
7323.00	26.68	AV	V	14.80	41.48	54.00	12.52
4068.10	41.81	PK	V	9.47	51.28	74.00	22.72
4068.10	29.04	AV	V	9.47	38.51	54.00	15.49
High Channel: 2480 MHz							
2480.00	55.50	PK	H	31.64	87.14	N/A	N/A
2480.00	42.62	AV	H	31.64	74.26	N/A	N/A
2480.00	63.33	PK	V	31.64	94.97	N/A	N/A
2480.00	51.01	AV	V	31.64	82.65	N/A	N/A
2483.50	32.51	PK	V	31.64	64.15	74.00	9.85
2483.50	14.32	AV	V	31.64	45.96	54.00	8.04
4960.00	55.67	PK	V	11.23	66.90	74.00	7.10
4960.00	41.34	AV	V	11.23	52.57	54.00	1.43
7440.00	41.85	PK	V	15.26	57.11	74.00	16.89
7440.00	25.97	AV	V	15.26	41.23	54.00	12.77
9920.00	38.86	PK	V	18.73	57.59	74.00	16.41
9920.00	22.74	AV	V	18.73	41.47	54.00	12.53
4133.27	40.17	PK	V	9.50	49.67	74.00	24.33
4133.27	27.42	AV	V	9.50	36.92	54.00	17.08

EDR Mode(8DPSK):

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2402 MHz							
2402.00	54.39	PK	H	31.51	85.90	N/A	N/A
2402.00	41.47	AV	H	31.51	72.98	N/A	N/A
2402.00	62.24	PK	V	31.51	93.75	N/A	N/A
2402.00	50.00	AV	V	31.51	81.51	N/A	N/A
2390.00	28.29	PK	V	31.46	59.75	74.00	14.25
2390.00	13.86	AV	V	31.46	45.32	54.00	8.68
4804.00	54.56	PK	V	10.91	65.47	74.00	8.53
4804.00	40.33	AV	V	10.91	51.24	54.00	2.76
7206.00	43.82	PK	V	14.22	58.04	74.00	15.96
7206.00	27.88	AV	V	14.22	42.10	54.00	11.90
4003.50	43.83	PK	V	9.34	53.17	74.00	20.83
4003.50	31.38	AV	V	9.34	40.72	54.00	13.28
Middle Channel: 2441 MHz							
2441.00	55.37	PK	H	31.61	86.98	N/A	N/A
2441.00	42.53	AV	H	31.61	74.14	N/A	N/A
2441.00	63.17	PK	V	31.61	94.78	N/A	N/A
2441.00	51.01	AV	V	31.61	82.62	N/A	N/A
4882.00	53.85	PK	V	11.07	64.92	74.00	9.08
4882.00	40.03	AV	V	11.07	51.10	54.00	2.90
7323.00	45.63	PK	V	14.80	60.43	74.00	13.57
7323.00	29.71	AV	V	14.80	44.51	54.00	9.49
9764.00	38.34	PK	V	18.55	56.89	74.00	17.11
9764.00	22.91	AV	V	18.55	41.46	54.00	12.54
4068.10	40.46	PK	V	9.47	49.93	74.00	24.07
4068.10	27.66	AV	V	9.47	37.13	54.00	16.87
High Channel: 2480 MHz							
2480.00	55.79	PK	H	31.64	87.43	N/A	N/A
2480.00	42.83	AV	H	31.64	74.47	N/A	N/A
2480.00	63.42	PK	V	31.64	95.06	N/A	N/A
2480.00	51.31	AV	V	31.64	82.95	N/A	N/A
2483.50	31.80	PK	V	31.64	63.44	74.00	10.56
2483.50	14.31	AV	V	31.64	45.95	54.00	8.05
4960.00	56.13	PK	V	11.23	67.36	74.00	6.64
4960.00	42.09	AV	V	11.23	53.32	54.00	0.68
7440.00	41.69	PK	V	15.26	56.95	74.00	17.05
7440.00	25.97	AV	V	15.26	41.23	54.00	12.77
9920.00	37.24	PK	V	18.73	55.97	74.00	18.03
9920.00	21.88	AV	V	18.73	40.61	54.00	13.39
4133.27	39.76	PK	V	9.50	49.26	74.00	24.74
4133.27	26.85	AV	V	9.50	36.35	54.00	17.65

Worst Test plots(EDR Mode(8DPSK) high channel was the worst)



4.3 20 dB Emission Bandwidth:

Serial Number:	CR22010035-RF-S1	Test Date:	2022/6/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	George	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	99.9
----------------------	------	------------------------------	----	------------------------	------


Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	2021-08-08	2022-08-07


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Channel	Test Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Lowest	2402	1.028
	Middle	2441	1.028
	Highest	2480	1.028
EDR Mode ($\pi/4$ -DQPSK)	Lowest	2402	1.364
	Middle	2441	1.360
	Highest	2480	1.364
EDR Mode (8DPSK)	Lowest	2402	1.352
	Middle	2441	1.352
	Highest	2480	1.356







4.4 Channel Separation:

Serial Number:	CR22010035-RF-S1	Test Date:	2022/6/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	George	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	99.9
----------------------	------	------------------------------	----	------------------------	------


Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	2021-08-08	2022-08-07


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	Channel Separation (MHz)	Limits (MHz)
BDR Mode (GFSK)	2402	1.000	0.685
	2441	1.000	0.685
	2480	1.000	0.685
EDR Mode ($\pi/4$ -DQPSK)	2402	1.000	0.909
	2441	1.000	0.907
	2480	1.006	0.909
EDR Mode (8DPSK)	2402	1.000	0.901
	2441	1.000	0.901
	2480	1.000	0.904







4.5 Number Of Hopping Frequency:

Serial Number:	CR22010035-RF-S1	Test Date:	2022/6/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	George	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	99.9
----------------------	------	------------------------------	----	------------------------	------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	2021-08-08	2022-08-07

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Frequency Range (MHz)	Number of Hopping Channel	Limits
GFSK	2400-2483.5	79	≥15
π/4-DQPSK	2400-2483.5	79	≥15
8DPSK	2400-2483.5	79	≥15



4.6 Time Of Occupancy(Dwell Time):

Serial Number:	CR22010035-RF-S1	Test Date:	2022/6/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	George	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	99.9
----------------------	------	------------------------------	----	------------------------	------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	2021-08-08	2022-08-07


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Test Modes	Packet Type	Test Frequency (MHz)	Pulse width (ms)	Result (s)	Limit (s)
BDR Mode (GFSK)	DH1	2441	0.422	0.135	0.400
	DH3	2441	1.718	0.275	0.400
	DH5	2441	2.998	0.320	0.400
EDR Mode ($\pi/4$ -DQPSK)	2DH1	2441	0.398	0.127	0.400
	2DH3	2441	1.716	0.275	0.400
	2DH5	2441	2.998	0.320	0.400
EDR Mode (8DPSK)	3DH1	2441	0.406	0.130	0.400
	3DH3	2441	1.746	0.279	0.400
	3DH5	2441	3.014	0.321	0.400

Note:
DH1:Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s
DH3:Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s
DH5:Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s







4.7 Peak Conducted Output Power:

Serial Number:	CR22010035-RF-S1	Test Date:	2022/6/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	George	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	99.9
----------------------	------	------------------------------	----	------------------------	------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2021XA	MY54080015	2021/7/22	2022/7/21
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	2021/8/8	2022/8/7
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021/8/8	2022/8/7

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	Peak Conducted Output Power (dBm)	Limits (dBm)
BDR Mode (GFSK)	2402	1.74	21
	2441	1.18	21
	2480	0.51	21
EDR Mode (π/4-DQPSK)	2402	3.67	21
	2441	3.13	21
	2480	2.46	21
EDR Mode (8DPSK)	2402	3.93	21
	2441	3.47	21
	2480	2.82	21

4.8 100 kHz Bandwidth of Frequency Band Edge:


Serial Number:	CR22010035-RF-S1	Test Date:	2022/6/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	George	Test Result:	Pass


Environmental Conditions:					
Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	99.9


Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	2021-08-08	2022-08-07


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).














5. RF EXPOSURE EVALUATION

5.1 Applicable Standard

FCC §15.247 (i)

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §1.1307(b)(1) of this chapter.

5.2 Procedure

5.2 Procedure

According to §1.1307(b)(3)(ii)(B)

Simultaneous Transmission with both SAR-based and MPE-Based Test Exemptions

This case is described in detail in § 1.1307(b)(3)(ii)(B) and covers the situations where both SAR-based and MPE-based exemption may be considered for test exemption in fixed, mobile, or portable device exposure conditions. For these cases, a device with multiple RF sources transmitting simultaneously will be considered an RF exempt device if the condition of Formula (1) is satisfied.

$$P_{th} (\text{mW}) = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1 \quad (1)$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for P_{th} , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source *i* at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ = the exemption threshold power (P_{th}) according to [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for fixed, mobile, or portable RF source *i*.

ERP_j = the ERP of fixed, mobile, or portable RF source *j*.

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source *j*, at a distance of at least $\lambda/2\pi$ according to the applicable formula of [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section.

$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source *k* either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure\ Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source *k*, as applicable from [§ 1.1310 of this chapter](#).

5.3 Measurement Result

Radio	Frequency (MHz)	Distance (mm)	P _{th} (mW)	Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain (dBi)	The Greater of Conducted Power or ERP	
						dBm	mW
BLE Main Control Module	2402-2480	5	2.717	-10	-0.67	-10	0.10
BLE Audio Module	2402-2480	5	2.717	2	-0.71	2	1.58
BDR/EDR Audio Module	2402-2480	5	2.717	4	-0.71	4	2.51

Note:

The Value of Maximum Conducted Power including Tune-up Tolerance was declared by the customer.
Two Modules can transmit simultaneously.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k}$$

$$= ERP_{BLE\ main\ control\ module} / ERP_{th} + ERP_{audio\ module} / ERP_{th}$$

$$= 0.10/2.717 + 2.51/2.717$$

$$= 0.961$$

$$< 1.0$$

Result: The device compliant the SAR-Based Exemption at 5mm distances.

===== END OF REPORT =====