

CTC Laboratories, Inc. (FCC Designation Number: CN1208)

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755-27521059 Fax: +86-755-27521011 http://www.sz-ctc.org.cn

Maximum Permissible Exposure Evaluation

FCC ID: 2APN5BASICR4

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

EUT Specification

Applicant	Shenzhen Sonoff Technologies Co.,Ltd.			
Address	3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China			
Product Name:	Wi-Fi Smart Switch			
Trade Mark:	Sonoff			
Model/Type Reference:	BASICR4			
Listed Model(s):	BASICR4M			
Model Differences:	All these models are identical in the same PCB, layout, electrical circuit and enclosure. The difference is the model name, and the model BASICR4M support the Matter function.			
Frequency Band (Operating)	BLE: 2402~2480MHz WiFi: 2412-2462MHz			
Device Category	☐ Portable (<5mm separation) ☐ Mobile (>20cm separation) ☐ Fixed (>20cm separation) ☐ Others			
Exposure Classification	☐Occupational/Controlled exposure (S=5mW/cm²) ☐General Population/Uncontrolled exposure (S=1mW/cm²)			
Antenna Diversity	Single antenna ☐Multiple antennas ☐Tx diversity ☐Rx diversity ☐Tx/Rx diversity			
Antenna Gain (Max)	-0.8dBi			
Evaluation Applied				

Report No.: CTC20231627E03



Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)	
(A)	(A) Limits for Occupational/Controlled Exposure				
300-1500			F/300	<6	
1500-100000			5	<6	
(B) Limits for General Population/Uncontrolled Exposure					
300-1500			F/1500	<30	
1500-100000			1	<30	

Calculation Method

Friis transmission formula: Pd=(P_{out}*G)/(4*Pi*R²)

Where:

Pd= Power density in mW/cm²

P_{out}= output power to antenna in mW

G= gain of antenna in linear scale

Pi= 3.1416

R= distance between observation point and center of the radiator in cm

Pd limit of MPE is 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Mode	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Tune Up Tolerance (dB)	Max. Tune Up Power (dBm)	Power Density at 20cm (mW/cm²)	Limit (mW/cm²)
BLE	2440	-0.8	3.19	±1	4.00	0.0004	1
802.11g	2462	-0.8	21.58	±1	22.50	0.0294	1

The BLE and WiFi can transmit simultaneously.

Mode	Frequency (MHz)			Total Power density at 20cm (mW/cm2)	
BLE	2440	-0.8	0.0004	0.0298	1
802.11g	2462	-0.8	0.0294	0.0296	•

0

Note:

- 1. Calculate in the worst-case mode.
- 2. Max. Tune Up Power is declared by manufacturer, and used to calculate.
- 3. For a more detailed features description, please refer to the RF Test Report.

Tel.: (86)755-27521059 EN 中国国家认证认可监督管理委员会