

RF Exposure Report

Report No.: SA180830E03

FCC ID: 2APLE18300394

Test Model: VMB5000

Received Date: Sep. 04, 2018

Test Date: Sep. 28, 2018

Issued Date: Nov. 01, 2018

Applicant: Arlo Technologies, Inc.

Address: 2200 Faraday Ave. Suite 150, Carlsbad, CA 92008, United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result	7

Release Control Record

Issue No.	Description	Date Issued
SA180830E03	Original release.	Nov. 01, 2018

1 Certificate of Conformity

Product: Alro Gen5 Entry Hub

Brand: Arlo

Test Model: VMB5000

Sample Status: ENGINEERING SAMPLE

Applicant: Arlo Technologies, Inc.

Test Date: Sep. 28, 2018


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.


Prepared by :


Phoenix Huang / Specialist

Date:

Nov. 01, 2018

Approved by :


May Chen / Manager

Date:

Nov. 01, 2018

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Sub-GHz							
Ant No.	Brand	Model	Antenna Gain (dBi)	Frequency rang (MHz)	Antenna type	Connector type	
1	NA	902P00214N0	1.5	860~930	PIFA	NA	
Z-Wave							
Ant No.	Brand	Model	Antenna Gain (dBi)	Frequency rang (MHz)	Antenna type	Connector type	
1	NA	902P00213N0	2.5	860~930	PIFA	NA	
Zigbee							
Ant No.	Brand	Model	Antenna Gain (dBi)	Frequency rang (GHz)	Antenna type	Connector type	
1	INPAQ TECHNOLOGY CO., LTD.	ACA-5036-A2-CC-S	3.5	2.4~2.4835	CHIP	NA	
WLAN							
Ant No.	Brand	Model	Antenna Net Gain (dBi)	Frequency rang (GHz)	Antenna type	Connector type	Cable Length (mm)
1	NA	9 07X01052X0	2.5	2.4~2.4835	Dipole	i-pex	75
			1.8	5.15~5.25			
			2	5.25~5.35			
			2.2	5.47~5.725			
			1.6	5.725~5.85			
2	NA	9 07X00747X19	2.5	2.4~2.4835	Dipole	i-pex	90
			2.2	5.15~5.25			
			1.2	5.25~5.35			
			3.2	5.47~5.725			
			3.5	5.725~5.85			

2.5 Calculation Result

For Zigbee: The Maximum power was refer to the FCC test report (Report No.: RF180830E02A-3)

For Z-Wave: The Maximum power was refer to the FCC test report (Report No.: RF180830E02A-4)

For Sub-GHz: The Maximum power was refer to the FCC test report (Report No.: RF180830E02A-5)

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	2437	508.821	5.51	20	0.35999	1
WLAN U-NII-1	5200	571.179	5.01	20	0.36016	1
WLAN U-NII-3	5745	490.624	5.61	20	0.35520	1
Zigbee	2405	90.991	3.5	20	0.04053	1
Sub-GHz	915	92.89	1.5	20	0.02610	0.61

Note:

2.4GHz: The directional gain = 2.5dBi + 10log(2) = 5.51dBi

5GHz:

For U-NII-1 band: The directional gain = $10 \log[(10^{\text{Chain1}/20} + 10^{\text{Chain2}/20})^2 / 2] = 5.01\text{dBi}$

For U-NII-3 band: The directional gain = $10 \log[(10^{\text{Chain1}/20} + 10^{\text{Chain2}/20})^2 / 2] = 5.61\text{dBi}$

Z-Wave Field Strength Conversion:

Frequency (MHz)	Field Strength of Fundamental (dBuV/m) @3m	EIRP (dBm)	EIRP (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
908.4	93.9	-1.33	0.7362	20	0.00015	0.6056

Note: 1. Pout EIRP (dBm) = Field Strength of Fundamental (dBuV/m) - 95.23 (dB)

2. Power Density Limit = F/1500

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz + Zigbee + Sub-GHz + Z-Wave = 0.35999 / 1 + 0.36016 / 1 + 0.04053 / 1 + 0.02610 / 0.61 + 0.00015 / 0.6056 = 0.80371

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---