

KTL Radio Test Report	: 2G5762GUS2
Applicant	: Advantra
Apparatus Assessed	: AR100
Date Equipment Received Dates Of Test	: 22 nd July 2002 : 22 nd July 2002 to 24 th July 2002
Standard Tested To	: 47CFR Parts 2, 24 and 90

Summary:

The apparatus detailed above is compliant with the above standard as tested (see section 2.1 of this report for full details)

Mcherde

Authorised by

: : M Render, EMC and Radio Group Manager

Issue Date

: 10th October 2002

Authorised Copy Number : CD

Total number of pages : 33

Page

Contents

Section 1:	Introduction 1.1 General 1.2 Application for Certification (47CFR 2.1033) 1.3 Notes Relating To The Assessment 1.4 Variations In Test Methods	3 3 4 5 5
Section 2:	Results Summary 2.1 Result Table 2.2 Summary Of Compliance 2.3 Record Of Marginal Test Measurements	6 6 6
Appendix A	Formal Test Results A1 RF Power Output at terminals A2 Occupied Band width (896 MHz) A3 Occupied Bandwidth (899 MHz) A4 Occupied Band width (902 MHz) A5 Spurious Emissions at antenna terminals (896 MHz) A6 Spurious Emissions at antenna terminals (899 MHz) A7 Spurious Emissions at antenna terminals (902 MHz) A8 Transmitter Spurious Radiated Emissions (896 MHz) A9 Transmitter Spurious Radiated Emissions (900 MHz) A10 Transmitter Spurious Radiated Emissions (902 MHz) A11 Frequency Stability with Temperature Variation A12 Frequency Stability with Primary Voltage Variation	7 8 9 10 11 12 13 14 15 16 17 19
Appendix B:	Supporting Graphical Data	20
Appendix C:	Photographs	27
Appendix D:	Equipment Used For Testing	30
Appendix E:	Additional Information	33

Section 1:

Introduction

1.1 General

This report contains an assessment of an apparatus against 47CFR Parts 2, 24 and 90 based upon tests carried out on samples submitted to the Laboratory.

Test performed by:

KTL Saxon Way Priory Park West Hull HU13 9PB United Kingdom

Telephone:+44 (0) 1482 801801Fax:+44 (0) 1482 801806Email:ktl@ktl.com

K 9 anderson

Author(s)

K J Anderson, Senior EMC Group Engineer

This report must not be reproduced except in full without prior written permission of KTL.

1.2 Application for Certification (47CFR 2.1033)

2.1033 (c) (1)	Name of applicant Address of applicant Contact	:	Advantra International Flanders Language Valley 90 B-8900 leper Belgium Frédéric Boes/Luc Van Asch/Els Ollevier
2.1033 (c) (2)	FCC Identifier Model Type Number	:	O33AR100 AR100
2.1033 (c) (3)	Installation and Operating instructions	:	User Guide (separate document)
2.1033 (c) (4)	Types of emission	:	Direct FSK, 10KF1D
2.1033 (c) (5)	Frequency Range	:	929.000 to 942.000 MHz (RX) 896.000 to 902.000 MHz (TX)
2.1033 (c) (6)	Output power range	:	0.06 to 1.92 W
2.1033 (c) (7)	Maximum power rating	:	1.92 W
2.1033 (c) (8)	dc voltage applied to power	:	3.7 V
	dc current to power amplifie	r :	1.4 A
2.1033 (c) (9)	Tune up procedure for RF power	:	n/a
2.1033 (c) (10)	Schematic diagram	:	Contained in Separate Document
2.1033 (c) (11)	Label Information	:	Contained in Separate Document
2.1033 (c) (12)	Photographs	:	Contained in Appendix D
2.1033 (c) (13)	Description of modulation	:	Contained in Separate Document
2.1033 (c) (14)	Test results	:	Contained in Appendix A with supporting Graphical data in Appendix B
2.1033 (c) (15	External RF Power Amp	:	n/a
2.1033 (c) (16)	AM Broadcast Equipment	:	n/a

1.3 Notes Relating To The Assessment

With regard to this assessment, the following points should be noted:

- a) The apparatus was set up and exercised using the configurations, modes of operation and arrangements defined in this report only.
- b) All testing was performed under the following conditions:

DC Power Supply : 3.7 Vdc (where applicable) Barometric Pressure : 86 to 106 kPa

Note that temperature and humidity conditions can be found in the relevant test results appendix B.

- c) All dates used in this report are in the format dd/mm/yy.
- d) All testing was performed in accordance with ISO17025.

1.4 Variations In Test Methods

There were no variations from normal KTL test procedures. Testing was performed in accordance with the relevant parts of ANSI C63.4.

Section 2:

Results Summary

2.1 Result Table

The following table summarises the tests as described in 47CFR Parts 2, 24 and 90:

Test Type	Application	Reference clauses in 47CFR	Appendix No.s in this report	Notes
RF Power Output at terminals	RF Terminal	2.1046	A1	PASS
Occupied Bandwidth	RF Terminal	2.1049(i), 24.133(a)(2) & 90.210(j)	A2 to A4	PASS
Spurious emissions at antenna terminals	RF Terminal	2.1051& 90.210(j)	A5 to A7	PASS
Field strength of spurious radiation	Antenna	2.1053& 90.210(j)	A8 to A10	PASS
Frequency stability with temperature variation	RF Terminal	2.1055 (a)(i) & 24.135	A11	PASS
Frequency stability with primary voltage variation	RF Terminal	2.1055 (d)(i) & 24.135	A12	PASS

Note: The AR100 was tested in one single build state i.e. was not modified during the testing detailed in this test report.

2.2 Summary Of Compliance

The samples, as assessed, satisfied the relevant requirements of 47CFR Parts 2, 24 and 90, as detailed in section 2.1 of this test report.

2.3 Record Of Marginal Test Measurements

No marginal results were recorded during the assessment.

Appendix A

Formal Test Results

A1 RF Power Output at terminals

Ambient temperature	e 20°C
---------------------	--------

Relative humidity 61%

RF Terminal	47CFR 2.1046

Modulation: None

Carrier Frequency (MHz)	Analyser reading (dBm)	Attenuator and cable Loss (dB)	Carrier Power (dBm)	Carrier Power (W)
896.0000	22.0	10.3	32.3	1.7
899.0000	21.7	10.3	32.0	1.6
902.0000	22.2	10.3	32.5	1.8

Plots are contained in Appendix B, Figures B.1 to B.3

Equipment Details (refer to Appendix D for further details)

Apparatus Sample Number : S02

A2 Occupied Band width (896 MHz)

Ambient ten	nperature 20°C	Relative humidity 61%	
RF Terminal		47CFR 2.1049	
Carrier power	.32.3 dBm (1.7 W)		
Modulation: F1D			
Nominal carrier frequency:896	.0000 MHz		
All emissions are within the lim	nits defined in 47CF	R 90.210 (j)	
Emissions plots contained in A	oppendix B, Figures	3.4 and B.5	
Equipment Details (refer to)	Appendix D for furthe	er details)	
Apparatus Sample Number	: S02		
Test equipment used	: See Appendix D2.		

Ambient tempe	rature 20°C	Relative humidity 61%		
RF Terminal		47CFR 2.1049		
Carrier power32	.0 dBm (1.6 W)			
Modulation: F1D				
Nominal carrier frequency:899.00	Nominal carrier frequency:899.0000 MHz			
All emissions are within the limits defined in 47CFR 90.210 (j)				
Emissions plots contained in Appendix B, Figures B.6 and B.7				
Equipment Details (refer to App	endix D for further	details)		
Apparatus Sample Number : S	02			
Test equipment used : S	ee Appendix D2.			

A3 Occupied Bandwidth (899 MHz)

A4 Occupied Band width (902 MHz)

Ambient temperature 20°C	Relative humidity 61%
RF Terminal	47CFR 2.1049
Carrier power32.5 dBm (1.8 W)	
Modulation: F1D	
Nominal carrier frequency:902.0000 MHz	
All emissions are within the limits defined in 47CF	R 90.210 (j) and 47CFR 24.133 (a)
Emissions plots for 47 CFR 90.210(j) are contained Emissions plot for 47 CFR 24.133(a) is contained	ed in Appendix B, Figures B.8 and B.9 in Appendix B, Figure B.10
Equipment Details (refer to Appendix D for furth	ner details)
Apparatus Sample Number : S02	

A5 Spurious Emissions at antenna terminals (896 MHz)

Ambient temperature 21 °C Relative humidity 55% **RF** Terminal 47CFR 2.1051

Carrier Power 32.3 dBm

Modulation: F1D

Spurious Emission Levels dBm			
Frequency (MHz)	Spectrum Analyser Reading (dBm)	Substitution Signal Generator Level (dBm)	
1792	-46.33	-25.8	
2688	-61.33	-41.4	
6272	-66.83	-44.7	

Limit

 $P_{(dBm)} - (50+10 \log (P))$ P = Carrier power in watts = -20 dBm

Equipment Details (refer to Appendix D for further details)

Apparatus Sample Number : S02

A6 Spurious Emissions at antenna terminals (899 MHz)

Ambient temperature	21 °C	Relative humidity 55%	
RF Terminal		47CFR 2.1051	

Modulation: F1D

Spurious Emission Levels dBm			
Frequency (MHz)	Spectrum Analyser Reading (dBm)	Substitution Signal Generator Level (dBm)	
1800	-46.67	-26.3	
2700	-60.83	-40.5	
6300	-66.33	-44.8	

Limit $P_{(dBm)} - (50+10 \log P)$ P = Carrier power in watts = -20 dBm

Equipment Details (refer to Appendix D for further details)

Apparatus Sample Number : S02

A7 Spurious Emissions at antenna terminals (902 MHz)

Ambient temperature	21 °C	Relative humidity 55%
RF Terminal		47CFR 2.1051

Modulation: F1D

Spurious Emission Levels dBm			
Frequency (MHz)	Spectrum Analyser Reading (dBm)	Substitution Signal Generator Level (dBm)	
1804	-47.17	-26.7	
2706	-60.83	-40.5	
6314	-68.17	-46.4	

Limit $P_{(dBm)} - (50+10 \log P)$ P = Carrier power in watts = -20 dBm

Equipment Details (refer to Appendix D for further details)

Apparatus Sample Number : S02

A8 Transmitter Spurious Radiated Emissions (896 MHz)

Ambient temperature 20 °C

Antenna

Relative humidity 50%

47CFR 2.1053

Modulation: F1D

Spurious Emission Levels (effective radiated power dBm)				
Frequency (MHz)	Polarization of maximum emission(H/V)	Bandwidth (kHz)	Level (dBm)	
1792	V	1000	-35.8	
1792	Н	1000	-41.8	
2688	V	1000	-40.3	
3584	Н	1000	-38.0	
4480	V	1000	-39.0	
5376	Н	1000	-37.3	
6272	Н	1000	-37.3	

Limit

 $P_{(dBm)} - (50+10 \log P)$ = -20 dBm P = Carrier power in watts

Equipment Details (refer to Appendix D for further details)

Apparatus Sample Number : S02

A9 Transmitter Spurious Radiated Emissions (900 MHz)

Ambient temperature 20 °C

Relative humidity 50%

Antenna 47CFR 2.1053

Modulation: F1D

Spurious Emission Levels (effective radiated power dBm)				
Frequency (MHz)	Polarization of maximum emission(H/V)	Bandwidth* (kHz)	Level (dBm)	
1800	V	1000	-37.1	
2700	V	1000	-40.5	
3600	V	1000	-37.8	
4500	V	1000	-37.0	
5400	V	1000	-38.1	
6300	Н	1000	-32.6	

Limit

 $P_{(dBm)} - (50+10 \log P)$ = -20 dBm

P = Carrier power in watts

Equipment Details (refer to Appendix D for further details)

Apparatus Sample Number : S02

A10 Transmitter Spurious Radiated Emissions (902 MHz)

Ambient temperature 20 °C

Relative humidity 50%

Antenna 47CFR 2.1053

Modulation: F1D

Spurious Emission Levels (effective radiated power dBm)				
Frequency (MHz)	Polarization of maximum emission(H/V)	Bandwidth* (kHz)	Level (dBm)	
1804	V	1000	-35.4	
2706	V	1000	-27.0	
3608	Н	1000	-40.0	
4510	V	1000	-38.0	
5412	Н	1000	-38.6	
6314	Н	1000	-31.2	

Limit

 $P_{(dBm)} - (50+10 \log P)$ = -20 dBm

P = Carrier power in watts

Equipment Details (refer to Appendix D for further details)

Apparatus Sample Number : S02

A11 Frequency Stability with Temperature Variation

Ambient temperature	20 °C	Relative humidity	61%	
Antenna		47CFR 2.1	055(a)	

Nominal carrier frequency (normal test conditions) 901.25625 MHz

Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-40	-535.3	-0.59
-30	270.9	0.30
-20	294.3	0.33
-10	4.3	0.00
0	14.1	0.02
10	80.3	0.09
20	53.7	0.06
30	81.8	0.09
40	43.5	0.05
50	0.4	0.00
60	93.5	0.10
70	-53.1	-0.06
80	109.2	0.12
90	224.1	0.25

Limit: $\pm 1 \text{ ppm}$

Equipment Details (refer to Appendix D for further details)

Apparatus Sample Number : S02

A12 Frequency Stability with Primary Voltage Variation

Ambient temperature	20 °C	Relative humidity	61%
Antenna		47CFR 2.1	055(d)

3.7 V

Nominal carrier frequency (normal test conditions) 901.25625 MHz

Nominal primary supply voltage (V_{nom})

Primary Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.145 (V _{nom} x 0.85)	-23	-0.03
3.38 (V _{nom} x 0.9)	26.7	0.03
3.515 (V _{nom} x 0.95)	131.3	0.15
3.7 (V _{nom})	120.3	0.13
3.883 (V _{nom} x 1.05)	192	0.21
4.07 (V _{nom} x 1.1)	164.4	0.18
4.255 (V _{nom} x 1.15)	120.7	0.13
4.5 (V _{max})	213.7	0.24

Limit: ± 1 ppm

Equipment Details (refer to Appendix D for further details)

Apparatus Sample Number : S02

Appendix B:

Supporting Graphical Data



Figure B.1 – Carrier Power at 896MHz



Figure B.2 – Carrier Power at 899MHz



Figure B.3 – Carrier Power at 902 MHz



Figure B.4 – Occupied bandwidth at 896 MHz (1 MHz span)



Figure B.5 – Occupied bandwidth at 896MHz (50 kHz span)



Figure B.6 – Occupied bandwidth at 899 MHz (1 MHz span)



Figure B.7 – Occupied bandwidth at 899 MHz (50 kHz span)



Figure B.8 – Occupied bandwidth at 902 MHz (1 MHz span)



Figure B.9 – Occupied bandwidth at 902 MHz (50 kHz span) Part 90 Mask



Figure B.10 – Occupied bandwidth at 902 MHz (50 kHz span) Part 24 Mask



Figure B.11 – Frequency stability with temperature variation at 901.25625 MHz



Figure B.11 – Frequency stability with primary voltage variation at 901.25625 MHz

Appendix C:

Photographs

The following photographs were taken of the test samples:

- 1. Spurious emissions 30 MHz to 10 GHz
- 2. Spurious emissions 9 kHz to 30 MHz
- EUT Top view
 EUT Bottom view



Photograph 1



Photograph 2



Photograph 3



Photograph 4

Appendix D:

Equipment Used For Testing

To facilitate inclusion on each page of the test equipment used for related tests, each item of equipment used during testing (including test samples, support equipment, test equipment and ancillaries such as cables) are identified/numbered by the Test Laboratory.

D1) The following samples of apparatus were available for testing or use as drive equipment (and used as detailed in Appendix A):

Sample No.	Description	Identification
S01	AR100 RF Module	None
S02	AR100 RF Module	None
S03	AR100 RF Module	None
S04	Tescom TC 2000A Pager Pester	2000A120059
S05	Dell Latitude XP Laptop PC	98418
S06	PA1 PSU for S05 above	81407
S07	Devkit PCB V1.1 (host for S01 to S03)	None
S08	AR100 Programmer Interface	IP1964.67P0004

- **D2)** The following test equipment was available for use during testing (and used as detailed in appendix B):
- * Indicates equipment used.

Frequency stability :

RFG / REF	Туре	Description	Manufacturer	Used
S04	TC 2000A	Pager Tester	Tescom	*
RFG001	2A	Off Air Frequency Standard	Quartzlock	*
REF496	34401	Multimeter	HP	*
REF239	310	Power supply	Farnell	*
RFG327	СМТА	Radiocommunications analyser	R & S	
RFG 365		Temperature Chamber	JTS	*

RF Power output at terminals, Occupied Bandwidth and Spurious emissions at antenna terminals:

RFG / REF	Туре	Description	Manufacturer	Used
RFG127	HP8563E	Spectrum analyser	HP	*
RFG067	R3261A	Spectrum analyser	Advantest	
RFG214	ESAI	Analyser / Receiver	R&S	
REF496	34401	Multimeter	HP	
REF239	310	Power supply	Farnell	*
RFG 273	Model 2	Attenuator 20 dB	Wienschel	*

RFG No	Туре	Description	Manufacturer	Used
274	Lab 10	Large anechoic chamber	KTL	*
142	Lab 13	Medium anechoic Chamber		
	OATS	10m test site	KTL	
231	Blue Bilog	Bilog antenna	Chase	*
244	CBL6111			
095	3109	Bicon antenna	EMCO	
131		Bicon antenna		
132		Bicon antenna		
025	3146	Log periodic antenna	EMCO	
081		Log periodic antenna		
191		Log periodic antenna		
129		Horn antenna		*
130		Horn antenna		*
		Dipole set	EMCO	*
		Dipole set	EMCO	
007	8447F	Dual pre amp	HP	
008	8447D	Pre Amp	HP	*
307	8449B	Microwave pre amp	HP	*
067	R3261A	Spectrum analyser	Advantest	
127	HP8563E	Spectrum analyser	HP	*
214	ESAI	Spec Analyser/Test Receiver (LF/HF)	R & S	*
013	ESVP	Test Receiver	R&S	
126	ESVS 20	Test Receiver	R&S	
016	SMG	Signal generator	R&S	
227	MI2024	Signal generator	Marconi	
349	MI2032	Signal generator	Marconi	*
351		High pass filter set	Mini circuits	
276	N	RF coaxial cable 1.0m		
277	N	RF coaxial cable 1.0m		
280	N	RF coaxial cable 2.0m		
303	N	RF coaxial cable 2.0m		
249	Ν	RF coaxial cable 3.0m		*
255	N	RF coaxial cable		*
264	N	RF coaxial cable 1.0m		*
270	N	RF coaxial cable 4.5m		-
137	N	HF coaxial cable 2.0m		*
158	N	HF coaxial cable 7.0m		*
312	Adapter	HF coaxial cable		*
313	Adapter	HF coaxial cable		*
352	N	RF coaxial cable		
353	N	RF coaxial cable		
222	N	RF coaxial cable		
247	N	RF coaxial cable		
251	N	RF coaxial cable		
REF239	310	Power supply	Farnell	*

Field strength of spurious radiation (effective radiated power) :

Appendix E:

Additional Information

No additional information is included.