Rated RF power output:

Mode	The Tune-up power range(Customer Declared)(dBm)	Range(dBm)
2.4G WLAN 802.11b	14.50 ± 0.6	13.90 ~ 15.10
2.4G WLAN 802.11g	13.60 ± 0.2	13.40 ~ 13.80
2.4G WLAN 802.11n(HT20)	12.40 ± 0.7	11.70 ~ 13.10
5.2G WLAN 802.11a	7.90 ± 0.9	7.00 ~ 8.80
5.2G WLAN 802.11n(HT20)	7.20 ± 0.3	6.90 ~ 7.50
5.3G WLAN 802.11a	9.00 ± 0.1	8.90 ~ 9.10
5.3G WLAN 802.11n(HT20)	7.60 ± 0.6	7.00 ~ 8.20
5.6G WLAN 802.11a	7.70 ± 0.7	7.00 ~ 8.40
5.6G WLAN 802.11n(HT20)	6.60 ± 0.2	6.40 ~ 6.80
5.8G WLAN 802.11a	8.80 ± 0.1	8.70 ~ 8.90
5.8G WLAN 802.11n(HT20)	7.80 ± 0.5	7.30 ~ 8.30
Bluetooth BR/EDR	7.50 ± 0.9	6.60 ~ 8.40
Bluetooth BLE	7.10 ± 0.9	6.20 ~ 8.00

Note: These appropriate rated RF output power settings are stored in each device individually. The user has no possibility to change these settings later on, and during manufacturing each device will be individual calibrated. The measurement is done in fully calibrated setup, which is based on the base station simulator. Furthermore, the highest power level is verified afterwards in a call measurement on three channels(low, middle and high).