

FCC PART 15.225

TEST REPORT

For

WUXI IDATA TECHNOLOGY COMPANY LTD.

Floor 11,Building B1,Wuxi Binhu National Sensing Information Center,No.999 Gaolang East Road, Wuxi, China

FCC ID: 2ADE3IDATA60

Report Type: Original Report	Product Type: NEW MOBILE COMPUTER
Test Engineer: Lion Xiao	
Report Number: RSZ160114005-00A	
Report Date: 2016-02-17	
Reviewed By: Sula Huang RF Leader	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	4
JUSTIFICATION	4
EUT EXERCISE SOFTWARE	4
SUPPORT CABLE LIST AND DETAILS	4
BLOCK DIAGRAM OF TEST SETUP	4
SUMMARY OF TEST RESULTS.....	5
FCC§15.203 - ANTENNA REQUIREMENT.....	6
APPLICABLE STANDARD	6
ANTENNA CONNECTED CONSTRUCTION	6
FCC §15.207 – AC LINE CONDUCTED EMISSION	7
MEASUREMENT UNCERTAINTY	7
EUT SETUP	7
EMI TEST RECEIVER SETUP.....	8
TEST EQUIPMENT LIST AND DETAILS.....	8
TEST PROCEDURE	8
CORRECTED AMPLITUDE & MARGIN CALCULATION	9
TEST RESULTS SUMMARY	9
TEST DATA	9
FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST	12
APPLICABLE STANDARD	12
MEASUREMENT UNCERTAINTY	12
EUT SETUP	13
EMI TEST RECEIVER SETUP.....	13
CORRECTED AMPLITUDE & MARGIN CALCULATION	13
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC§15.225(E) - FREQUENCY STABILITY.....	16
APPLICABLE STANDARD	16
TEST PROCEDURE	16
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST DATA	16
FCC §15.215(C) – 20 DB EMISSION BANDWIDTH.....	18

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *WUXI IDATA TECHNOLOGY COMPANY LTD.*'s product, model number: *iData 60 (FCC ID: 2ADE3IDATA60)* (the "EUT") in this report was a *NEW MOBILE COMPUTER*, which was measured approximately: 18.3cm (L) x 6.9cm (W) x 3.5cm (H), rated input voltage: DC3.7V rechargeable Li-ion battery or DC5V charging from adapter.

Adapter information:

Model: FJ-SW1260502000UU

Input: 100-240V~ 50/60Hz 0.4A Max

Output: DC 5V, 2000mA

All measurement and test data in this report was gathered from production sample serial number: 160114005 (Assigned by BACL, Dongguan). The EUT was received on 2016-01-14.

Objective

This Type approval report is prepared on behalf of *WUXI IDATA TECHNOLOGY COMPANY LTD.* in accordance with Part 2, Subpart J, and Part 15, Subparts A, B and C of the Federal Communications Commission's rules.

The objective is to determine the compliance of the EUT with FCC rules, sec 15.203, 15.205, 15.207, 15.209 and 15.225.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ADE3IDATA60.

FCC Part 15C DSS submissions with FCC ID: 2ADE3IDATA60.

FCC Part 15C DTS submissions with FCC ID: 2ADE3IDATA60.

FCC Part 22H, 24E PCE submissions with FCC ID: 2ADE3IDATA60.

Test Methodology

This Type approval report is prepared on behalf of *WUXI IDATA TECHNOLOGY COMPANY LTD.* in accordance with Part 2- Subpart J, and Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a test mode


EUT Exercise Software

No software was performed under test.

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	no	no	1.1	USB Port of Adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207	AC Line Conducted Emission	Compliance
§15.225 §15.209 §15.205	Radiated Emission Test	Compliance
§15.225(e)	Frequency Stability	Compliance
§15.215(c)	20 dB Emission Bandwidth	Compliance

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Antenna Connected Construction

The EUT has one integral antenna arrangement, which was permanently attached and fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 – AC LINE CONDUCTED EMISSION

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner

FINAL

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-10-20	2016-10-20
R&S	Two-line V-network	ENV216	3560.6550.12	2015-11-26	2016-11-25
R&S	L.I.S.N	ESH2-Z5	892107/021	2015-07-16	2016-07-15
N/A	Coaxial Cable	1.8m	N/A	2015-05-06	2016-05-06
BACL	Test Software	EMC32	Version8.53.0	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

According FCC publication number 174176, for a device with a permanent antenna operating at or below 30 MHz, the measurements done with a suitable dummy load, in lieu of the permanent antenna under the following conditions: (1) perform the AC line conducted tests with the permanent antenna to determine compliance with the Section 15.207 limits outside the transmitter's fundamental emission band; (2) retest with a dummy load in lieu of the permanent antenna to determine compliance with the Section 15.207 limits within the transmitter's fundamental emission band.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF : voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

11.8 dB at 0.180171 MHz in the Line conducted mode

Test Data


Environmental Conditions

Temperature:	23.3 °C
Relative Humidity:	49 %
ATM Pressure:	101.3 kPa

The testing was performed by Lion Xiao on 2016-01-21.


Test Mode: Transmitting

AC 120V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.173134	51.8	9.000	L1	9.7	13.0	64.8	Compliance
0.180171	52.7	9.000	L1	9.7	11.8	64.5	Compliance
0.193566	48.3	9.000	L1	9.7	15.6	63.9	Compliance
0.232499	45.5	9.000	L1	9.7	16.9	62.4	Compliance
0.241949	45.2	9.000	L1	9.7	16.8	62.0	Compliance
0.295282	40.3	9.000	L1	9.7	20.1	60.4	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.171759	31.9	9.000	L1	9.7	23.0	54.9	Compliance
0.186006	37.4	9.000	L1	9.7	16.8	54.2	Compliance
0.193566	35.0	9.000	L1	9.7	18.9	53.9	Compliance
0.232499	30.3	9.000	L1	9.7	22.1	52.4	Compliance
0.251783	23.8	9.000	L1	9.7	27.9	51.7	Compliance
1.385415	25.4	9.000	L1	9.8	20.6	46.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.169044	47.4	9.000	N	9.7	17.6	65.0	Compliance
0.175915	51.5	9.000	N	9.7	13.2	64.7	Compliance
0.192030	48.3	9.000	N	9.7	15.6	63.9	Compliance
0.230654	43.6	9.000	N	9.7	18.8	62.4	Compliance
0.243884	43.8	9.000	N	9.7	18.2	62.0	Compliance
0.286019	38.0	9.000	N	9.7	22.6	60.6	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.175915	36.6	9.000	N	9.7	18.1	54.7	Compliance
0.192030	33.8	9.000	N	9.7	20.1	53.9	Compliance
0.230654	32.5	9.000	N	9.7	19.9	52.4	Compliance
0.243884	29.4	9.000	N	9.7	22.6	52.0	Compliance
1.239175	25.3	9.000	N	9.8	20.7	46.0	Compliance
1.385415	26.3	9.000	N	9.8	19.7	46.0	Compliance

FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST

Applicable Standard


As per FCC Part 15.225

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner

EUT Setup



The radiated emission tests were performed in the 3-meter chamber a test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part Subpart C limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 9 kHz to 1 GHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
9 kHz – 150 kHz	300 Hz	1 kHz	QP
150 kHz – 30 MHz	10 kHz	30 kHz	QP
30 MHz – 1000 MHz	100 kHz	300 kHz	QP

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corr. Ampl.}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
The Electro-Mechanics Company	Passive Loop Antenna	6512	9706-1206	2014-11-30	2017-11-29
N/A	Coaxial Cable	14m	N/A	2015-05-06	2016-05-06

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.225,15.209 with the worst margin reading of:

22.92 dB at 161.92 MHz in the Horizontal polarization

Test Data**Environmental Conditions**

Temperature:	15.3 °C
Relative Humidity:	62 %
ATM Pressure:	102.8 kPa

* The testing was performed by Lion Xiao on 2016-01-25.

Test mode: Transmitting

1) 9 kHz~30 MHz:

Frequency	Receiver		Rx Antenna Factor	Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
	Reading	Detector						
MHz	dBμV	PK/QP/AV	dB(1/m)	dB	dB	dBμV/m	dBμV/m	dB
13.56	48.4	QP	32.08	0.35	21.44	59.39	124.00	64.61
13.553	37.1	QP	32.08	0.35	21.44	48.09	90.50	42.41
13.567	37.9	QP	32.08	0.35	21.44	48.89	90.50	41.61
13.389	33.4	QP	32.07	0.35	21.43	44.39	80.50	36.11
13.904	32.8	QP	32.10	0.35	21.44	43.81	80.50	36.69
15.996	24.9	QP	32.00	0.36	21.44	35.82	69.54	33.72
3.668	28.5	QP	37.13	0.18	21.47	44.34	69.54	25.20

2) 30 MHz ~1 GHz:

Frequency	Receiver		Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
	Reading	Detector	Polar	Factor					
MHz	dBμV	PK/QP/AV	H/V	dB(1/m)	dB	dB	dBμV/m	dBμV/m	dB
74.86	25.6	QP	H	8.47	1.07	21.41	13.73	40.00	26.27
103.72	26.1	QP	H	11.51	1.26	21.40	17.47	43.50	26.03
161.92	27.8	QP	H	12.66	1.56	21.44	20.58	43.50	22.92
170.40	27.1	QP	H	11.87	1.57	21.44	19.10	43.50	24.40
256.70	24.7	QP	H	12.35	1.92	21.49	17.48	46.00	28.52
309.36	23.9	QP	H	14.32	2.19	21.54	18.87	46.00	27.13
338.46	24.3	QP	H	14.80	2.19	21.62	19.67	46.00	26.33
90.50	26.8	QP	V	7.96	1.20	21.40	14.56	43.50	28.94
113.42	23.5	QP	V	13.40	1.29	21.41	16.78	43.50	26.72
161.90	25.1	QP	V	12.66	1.56	21.44	17.88	43.50	25.62
231.96	24.4	QP	V	11.99	1.83	21.48	16.74	46.00	29.26
279.52	24.8	QP	V	13.77	2.02	21.51	19.08	46.00	26.92
303.07	25.4	QP	V	14.14	2.13	21.53	20.14	46.00	25.86
411.96	25.7	QP	V	16.51	2.46	21.80	22.87	46.00	23.13

FCC§15.225(e) - FREQUENCY STABILITY**Applicable Standard**

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was using one new battery with full charge and loop antenna was connected to a Spectrum Analyzer. The EUT was placed inside the temperature chamber.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Spectrum Analyzer.

Frequency Stability vs. Voltage: The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the end point. The output frequency was recorded for each voltage.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Dongzhixu	High Temperature Test Chamber	DP1000	201105083-4	2015-09-10	2016-09-09
The Electro-Mechanics Company	Passive Loop Antenna	6512	9706-1206	2014-11-30	2017-11-29
N/A	Coaxial Cable	1.5m	N/A	2015-05-06	2016-05-06

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	16.5 °C
Relative Humidity:	32 %
ATM Pressure:	102.8 kPa

* The testing was performed by Lion Xiao on 2016-01-25.

Test Mode: Transmitting

Test Result: Pass

$f_0 = 13.56 \text{ MHz}$				
Temperature	Voltage	Measured frequency	Frequency Error	Limit

FCC §15.215(c) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Per FCC §15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through § 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
The Electro-Mechanics Company	Passive Loop Antenna	6512	9706-1206	2014-11-30	2017-11-29
N/A	Coaxial Cable	14m	N/A	2015-05-06	2016-05-06

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data Environmental Conditions

Temperature:	16.5 °C
Relative Humidity:	32 %
ATM Pressure:	102.8 kPa

* The testing was performed by Lion Xiao on 2016-01-25.

Test Mode: Transmitting

20 dB Emission Bandwidth



Date: 25.JAN.2016 20:08:30

*****END OF REPORT*****