



中国认可  
国际互认  
检测  
TESTING  
CNAS L7649



## RADIO TEST REPORT

Report No: STS2107201H02

Issued for

GODOX PHOTO EQUIPMENT CO.LTD

1st to 4th Floor, Building 2/1st to 4th Floor, Building 4,  
Yaochuan Industrial Zone, Tangwei Community, Fuhai Street,  
Baoan District, Shenzhen 518103, China

|                       |                      |
|-----------------------|----------------------|
| <b>Product Name:</b>  | Waterproof LED Light |
| <b>Brand Name:</b>    | Godox                |
| <b>Model Name:</b>    | WL8P                 |
| <b>Series Model:</b>  | N/A                  |
| <b>FCC ID:</b>        | 2ABYN039             |
| <b>Test Standard:</b> | FCC 47CFR §2.1093    |

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.  
A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ,  
Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China  
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail: sts@stsapp.com





## Test Report Certification

**Applicant's Name** .....: GODOX PHOTO EQUIPMENT CO.LTD  
**Address**.....: 1st to 4th Floor, Building 2/1st to 4th Floor, Building 4, Yaochuan Industrial Zone, Tangwei Community, Fuhai Street, Baoan District, Shenzhen 518103, China  
**Manufacturer's Name**.....: GODOX Photo Equipment Co.,Ltd.  
**Address**.....: 4th Floor of Building 1, 1st to 4th Floor of Building 2, 4th Floor of Building 3, 1st to 4th Floor of Building 4, Yaochuan Industrial Zone, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen 518103, China

### Product Description

**Product Name** .....: Waterproof LED Light  
**Brand Name** .....: Godox  
**Model Name** .....: WL8P  
**Series Model**.....: N/A

**Standards** .....: FCC 47CFR §2.1093

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

### Date of Test .....

**Date of receipt of test item**..... 27 July 2021  
**Date (s) of performance of tests** ..... 27 July 2021 ~ 14 Sept. 2021  
**Date of Issue** ..... 14 Sept. 2021  
**Test Result**..... **Pass**

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sean she)

Authorized Signatory :

(Vita Li)





## TABLE OF CONTENTS

|                                         |          |
|-----------------------------------------|----------|
| <b>1. GENERAL INFORMATION</b>           | <b>5</b> |
| 1.1 GENERAL DESCRIPTION OF THE EUT      | 5        |
| 1.2 TEST FACTORY                        | 5        |
| <b>2. FCC 47CFR §2.1093 REQUIREMENT</b> | <b>6</b> |
| 2.1 TEST STANDARDS                      | 6        |
| 2.2 LIMIT                               | 6        |
| 2.3 TEST RESULT                         | 8        |



**Revision History**

| Rev. | Issue Date    | Report No.    | Effect Page | Contents      |
|------|---------------|---------------|-------------|---------------|
| 00   | 14 Sept. 2021 | STS2107201H02 | ALL         | Initial Issue |
|      |               |               |             |               |





## 1. GENERAL INFORMATION

### 1.1 GENERAL DESCRIPTION OF THE EUT

|                         |                                                                         |               |
|-------------------------|-------------------------------------------------------------------------|---------------|
| Product Name            | Waterproof LED Light                                                    |               |
| Brand Name              | Godox                                                                   |               |
| Model Name              | WL8P                                                                    |               |
| Series Model            | N/A                                                                     |               |
| Model Difference        | N/A                                                                     |               |
| Product Description     | The EUT is Waterproof LED Light                                         |               |
|                         | Operation Frequency:                                                    | 2402~2480 MHz |
|                         | Modulation Type:                                                        | GFSK          |
|                         | Antenna gain:                                                           | 0dBi          |
|                         | Antenna Designation:                                                    | PCB           |
| Rating                  | Input: Charge By Type-C USB cable DC 5V,2A                              |               |
| Battery                 | Rated Voltage: 3.7V<br>Charge Limit Voltage: 4.28V<br>Capacity: 2900mAh |               |
| Hardware version number | 20210503S10                                                             |               |
| Software version number | V1.0                                                                    |               |

### 1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



## 2. FCC 47CFR §2.1093 REQUIREMENT

### 2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in KDB 447498 D01 General RF Exposure Guidance v06 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

### 2.2 LIMIT

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

| MHz  | 5   | 10  | 15  | 20  | 25  | mm                                      |
|------|-----|-----|-----|-----|-----|-----------------------------------------|
| 150  | 39  | 77  | 116 | 155 | 194 | SAR Test<br>Exclusion<br>Threshold (mW) |
| 300  | 27  | 55  | 82  | 110 | 137 |                                         |
| 450  | 22  | 45  | 67  | 89  | 112 |                                         |
| 835  | 16  | 33  | 49  | 66  | 82  |                                         |
| 900  | 16  | 32  | 47  | 63  | 79  |                                         |
| 1500 | 12  | 24  | 37  | 49  | 61  |                                         |
| 1900 | 11  | 22  | 33  | 44  | 54  |                                         |
| 2450 | 10  | 19  | 29  | 38  | 48  |                                         |
| 3600 | 8   | 16  | 24  | 32  | 40  |                                         |
| 5200 | 7   | 13  | 20  | 26  | 33  |                                         |
| 5400 | 6   | 13  | 19  | 26  | 32  |                                         |
| 5800 | 6   | 12  | 19  | 25  | 31  |                                         |
| MHz  | 30  | 35  | 40  | 45  | 50  | mm                                      |
| 150  | 232 | 271 | 310 | 349 | 387 | SAR Test<br>Exclusion<br>Threshold (mW) |
| 300  | 164 | 192 | 219 | 246 | 274 |                                         |
| 450  | 134 | 157 | 179 | 201 | 224 |                                         |
| 835  | 98  | 115 | 131 | 148 | 164 |                                         |
| 900  | 95  | 111 | 126 | 142 | 158 |                                         |
| 1500 | 73  | 86  | 98  | 110 | 122 |                                         |
| 1900 | 65  | 76  | 87  | 98  | 109 |                                         |
| 2450 | 57  | 67  | 77  | 86  | 96  |                                         |
| 3600 | 47  | 55  | 63  | 71  | 79  |                                         |
| 5200 | 39  | 46  | 53  | 59  | 66  |                                         |
| 5400 | 39  | 45  | 52  | 58  | 65  |                                         |
| 5800 | 37  | 44  | 50  | 56  | 62  |                                         |



The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where } f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz.}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.





## 2.3 TEST RESULT

Maximum measured transmitter power.

BLE The Worst Case

| Mode | frequency | Maximum AV Output Power | Tune up tolerance | Max Tune up |
|------|-----------|-------------------------|-------------------|-------------|
|      | GHz       | dBm                     | dBm               | dBm         |
| GFSK | 2402      | -0.86                   | -1±1              | 0           |

Remark: The worst case gain of the antenna is 0dBi.

0dBi logarithmic terms convert to numeric result is nearly 1

Maximum Tune up Power<sub>(2402)</sub>= 1mw

$[(\text{GFSK power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 1/5 \cdot \sqrt{2402} = 0.309 \leq 3.0$

Threshold at which no SAR required is  $0.309 \leq 3.0$  for 1-g SAR, Separation distance  $\leq 5\text{mm}$ .

※※※※※END OF THE REPORT※※※※※