

TEST REPORT

Product : Pulse Oximeter
Trade mark : N/A
Model/Type reference : PO6, PO6A
Serial Number : N/A
Report Number : EED32M00324201
FCC ID : 2ADXX-4708
Date of Issue : Nov. 09, 2020
Test Standards : 47 CFR Part 15 Subpart C
Test result : PASS

Prepared for:

Shenzhen Viatom Technology Co., Ltd.
4E, 3#, Tingwei Industrial Park, Honglang North 2nd Road,
Baoan District, Shenzhen, China.

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Sunlight Sun

Sunlight Sun

Reviewed by:

Ware Xin

Ware Xin

Approved by:

Aaron Ma

Aaron Ma

Date:

Nov. 09, 2020



Check No.: 3970389710

2 Version

Version No.	Date	Description
00	Nov. 09, 2020	Original

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013	PASS
Conducted Peak Output Power	47 CFR Part 15 Subpart C Section 15.247 (b)(3)	ANSI C63.10-2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15 Subpart C Section 15.247 (a)(2)	ANSI C63.10-2013	PASS
Power Spectral Density	47 CFR Part 15 Subpart C Section 15.247 (e)	ANSI C63.10-2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
Radiated Spurious Emissions	47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS

Remark:

Test according to ANSI C63.4-2014 & ANSI C63.10-2013.

Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

Model No.: PO6, PO6A

Only the model PO6 was tested, Their electrical circuit design, layout, components used and internal wiring are identical only the color of silicon finger-cot appearance is different.


4 Content

1 COVER PAGE	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENT	4
5 TEST REQUIREMENT	5
5.1 TEST SETUP	5
5.1.1 For Conducted test setup	5
5.1.2 For Radiated Emissions test setup	5
5.1.3 For Conducted Emissions test setup	6
5.2 TEST ENVIRONMENT	6
5.3 TEST CONDITION	6
6 GENERAL INFORMATION	7
6.1 CLIENT INFORMATION	7
6.2 GENERAL DESCRIPTION OF EUT	7
6.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	7
6.4 DESCRIPTION OF SUPPORT UNITS	8
6.5 TEST LOCATION	8
6.6 DEVIATION FROM STANDARDS	9
6.7 ABNORMALITIES FROM STANDARD CONDITIONS	9
6.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	9
6.9 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, $k=2$)	9
7 EQUIPMENT LIST	10
8 RADIO TECHNICAL REQUIREMENTS SPECIFICATION	11
Appendix A): 6dB Occupied Bandwidth	13
Appendix B): Conducted Peak Output Power	17
Appendix C): Band-edge for RF Conducted Emissions	19
Appendix D): RF Conducted Spurious Emissions	20
Appendix E): Power Spectral Density	23
Appendix F): Antenna Requirement	25
Appendix G): AC Power Line Conducted Emission	26
Appendix H): Restricted bands around fundamental frequency (Radiated)	29
Appendix I) Radiated Spurious Emissions	38
PHOTOGRAPHS OF TEST SETUP	42
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	44

5 Test Requirement

5.1 Test setup

5.1.1 For Conducted test setup



5.1.2 For Radiated Emissions test setup

Radiated Emissions setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1GHz

5.1.3 For Conducted Emissions test setup

Conducted Emissions setup



5.2 Test Environment

Operating Environment:	
Temperature:	23 °C
Humidity:	51 % RH
Atmospheric Pressure:	1010mbar

5.3 Test Condition

Test channel:

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
GFSK	2402MHz ~2480 MHz	Channel 0	Channel 19	Channel 39
		2402MHz	2440MHz	2480MHz
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.			

6 General Information

6.1 Client Information

Applicant:	Shenzhen Viatom Technology Co., Ltd.
Address of Applicant:	4E, 3#, Tingwei Industrial Park, Honglang North 2nd Road, Baoan District, Shenzhen, China.
Manufacturer:	Shenzhen Viatom Technology Co., Ltd.
Address of Manufacturer:	4E, 3#, Tingwei Industrial Park, Honglang North 2nd Road, Baoan District, Shenzhen, China.
Factory:	Shenzhen Viatom Technology Co., Ltd.
Address of Factory:	4E, 3#, Tingwei Industrial Park, Honglang North 2nd Road, Baoan District, Shenzhen, China.

6.2 General Description of EUT

Product Name:	Pulse Oximeter
Model No.(EUT):	PO6, PO6A
Test Model No.:	PO6
Trade mark:	N/A
EUT Supports Radios application:	2402MHz to 2480MHz
Power Supply:	DC 5V
Sample Received Date:	Oct. 22, 2020
Sample tested Date:	Oct. 22, 2020 to Oct. 30, 2020

6.3 Product Specification subjective to this standard

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	BLE
Modulation Technique:	DSSS
Modulation Type:	GFSK
Number of Channel:	40
Test Power Grade:	Default
Test Software of EUT:	DTM Tester
Antenna Type and Gain:	Chip antenna; 3.45dBi
Test Voltage:	DC 5V

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

6.4 Description of Support Units

The EUT has been tested with associated equipment below.

Associated equipment name		Manufacture	model	S/N serial number	Supplied by	Certification
AE	Notebook	DELL	DELL 3490	D245DX2	DELL	CE&FCC

6.5 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

6.6 Deviation from Standards

None.

6.7 Abnormalities from Standard Conditions

None.

6.8 Other Information Requested by the Customer

None.

6.9 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-18GHz)
3	Radiated Spurious emission test	4.3dB (30MHz-1GHz)
		4.5dB (1GHz-12.75GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

7 Equipment List

3M Semi/full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	05-24-2019	05-23-2022
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-618	05-16-2020	05-15-2021
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04-25-2018	04-24-2021
Receiver	R&S	ESCI7	100938-003	10-21-2019 10-16-2020	10-20-2020 10-15-2021
Multi device Controller	maturo	NCD/070/10711 112	---	---	---
Temperature/ Humidity Indicator	Shanghai qixiang	HM10	1804298	06-29-2020	06-28-2021
Cable line	Fulai(7M)	SF106	5219/6A	---	---
Cable line	Fulai(6M)	SF106	5220/6A	---	---
Cable line	Fulai(3M)	SF106	5216/6A	---	---
Cable line	Fulai(3M)	SF106	5217/6A	---	---

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Receiver	R&S	ESCI	100435	04-28-2020	04-27-2021
Temperature/ Humidity Indicator	Defu	TH128	/	---	---
LISN	R&S	ENV216	100098	03-05-2020	03-04-2021
Barometer	changchun	DYM3	1188	---	---

8 Radio Technical Requirements Specification


Reference documents for testing:

No.	Identity	Document Title
1	FCC Part15C	Subpart C-Intentional Radiators
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Test Results List:

Test Requirement	Test method	Test item	Verdict	Note
Part15C Section 15.247 (a)(2)	ANSI C63.10	6dB Occupied Bandwidth	PASS	Appendix A)
Part15C Section 15.247 (b)(3)	ANSI C63.10	Conducted Peak Output Power	PASS	Appendix B)
Part15C Section 15.247(d)	ANSI C63.10	Band-edge for RF Conducted Emissions	PASS	Appendix C)
Part15C Section 15.247(d)	ANSI C63.10	RF Conducted Spurious Emissions	PASS	Appendix D)
Part15C Section 15.247 (e)	ANSI C63.10	Power Spectral Density	PASS	Appendix E)
Part15C Section 15.203/15.247 (c)	ANSI C63.10	Antenna Requirement	PASS	Appendix F)
Part15C Section 15.207	ANSI C63.10	AC Power Line Conducted Emission	PASS	Appendix G)
Part15C Section 15.205/15.209	ANSI C63.10	Restricted bands around fundamental frequency (Radiated Emission)	PASS	Appendix H)
Part15C Section 15.205/15.209	ANSI C63.10	Radiated Spurious Emissions	PASS	Appendix I)

Duty cycle





Appendix A): 6dB Occupied Bandwidth

Test Result

Mode	Channel	6dB Bandwidth [MHz]	Verdict
BLE	LCH	0.6829	PASS
BLE	MCH	0.6870	PASS
BLE	HCH	0.6867	PASS

Test Graphs







OBD99%

Mode	Channel	99% OBW[MHz]	Verdict
BLE	LCH	1.0706	PASS
BLE	MCH	1.0728	PASS
BLE	HCH	1.0729	PASS

Test Graphs







Appendix B): Conducted Peak Output Power

Test Result

Mode	Channel	Conduct Peak Power[dBm]	Verdict
BLE	LCH	-8.062	PASS
BLE	MCH	-7.546	PASS
BLE	HCH	-7.582	PASS

Test Graphs






Appendix C): Band-edge for RF Conducted Emissions

Result Table

Mode	Channel	Carrier Power[dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
BLE	LCH	-8.095	-60.983	-28.1	PASS
BLE	HCH	-7.582	-57.485	-27.58	PASS

Test Graphs





Appendix D): RF Conducted Spurious Emissions


Result Table

Mode	Channel	Pref [dBm]	Puw[dBm]	Verdict
BLE	LCH	-8.28	<Limit	PASS
BLE	MCH	-7.733	<Limit	PASS
BLE	HCH	-7.781	<Limit	PASS

Test Graphs








Appendix E): Power Spectral Density

Result Table

Mode	Channel	PSD [dBm]	Verdict
BLE	LCH	-25.523	PASS
BLE	MCH	-25.206	PASS
BLE	HCH	-25.261	PASS

Test Graphs





Appendix F): Antenna Requirement


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3.45dBi.

Appendix G): AC Power Line Conducted Emission

Test Procedure:	Test frequency range :150KHz-30MHz 1)The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3)The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.															
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBμV)</th></tr> <tr> <th>Quasi-peak</th><th>Average</th></tr> </thead> <tbody> <tr> <td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr> <tr> <td>0.5-5</td><td>56</td><td>46</td></tr> <tr> <td>5-30</td><td>60</td><td>50</td></tr> </tbody> </table> * The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz. NOTE : The lower limit is applicable at the transition frequency		Frequency range (MHz)	Limit (dB μ V)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dB μ V)															
	Quasi-peak	Average														
0.15-0.5	66 to 56*	56 to 46*														
0.5-5	56	46														
5-30	60	50														


Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


Data

Live line:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1680	37.60	9.87	47.47	65.06	-17.59	peak	
2		0.1770	19.56	9.87	29.43	54.63	-25.20	AVG	
3		0.2400	34.54	9.95	44.49	62.10	-17.61	peak	
4		0.2445	17.92	9.96	27.88	51.94	-24.06	AVG	
5		0.3209	14.27	10.05	24.32	49.68	-25.36	AVG	
6		0.3255	31.15	10.04	41.19	59.57	-18.38	peak	
7		0.3930	27.33	9.98	37.31	58.00	-20.69	peak	
8		0.4110	10.91	9.97	20.88	47.63	-26.75	AVG	
9	*	0.8025	19.99	9.85	29.84	46.00	-16.16	AVG	
10		0.8070	27.07	9.85	36.92	56.00	-19.08	peak	
11		1.4325	9.85	9.81	19.66	46.00	-26.34	AVG	
12		1.5405	18.09	9.81	27.90	56.00	-28.10	peak	

Neutral line:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin		
		MHz	dBuV	Factor	ment	dBuV	dB	Detector	Comment
1		0.1635	37.15	9.87	47.02	65.28	-18.26	peak	
2		0.1635	20.81	9.87	30.68	55.28	-24.60	AVG	
3		0.2445	34.45	9.96	44.41	61.94	-17.53	peak	
4		0.2445	17.09	9.96	27.05	51.94	-24.89	AVG	
5		0.3165	30.97	10.05	41.02	59.80	-18.78	peak	
6		0.3165	11.29	10.05	21.34	49.80	-28.46	AVG	
7		0.5730	25.32	10.04	35.36	56.00	-20.64	peak	
8		0.5820	10.14	10.05	20.19	46.00	-25.81	AVG	
9	*	0.8025	29.19	9.85	39.04	56.00	-16.96	peak	
10		0.8025	16.34	9.85	26.19	46.00	-19.81	AVG	
11		1.2795	17.77	9.82	27.59	56.00	-28.41	peak	
12		1.4595	7.37	9.81	17.18	46.00	-28.82	AVG	

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.


Appendix H): Restricted bands around fundamental frequency (Radiated)

Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Test Procedure:	Below 1GHz test procedure as below: Test method Refer as KDB 558074 D01 v04, Section 12.1 - The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel Above 1GHz test procedure as below: - Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter). . Test the EUT in the lowest channel , the Highest channel - The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case. - Repeat above procedures until all frequencies measured was complete.				
Limit:	Frequency	Limit (dBμV/m @3m)	Remark		
	30MHz-88MHz	40.0	Quasi-peak Value		
	88MHz-216MHz	43.5	Quasi-peak Value		
	216MHz-960MHz	46.0	Quasi-peak Value		
	960MHz-1GHz	54.0	Quasi-peak Value		
	Above 1GHz	54.0	Average Value		
		74.0	Peak Value		

Test plot as follows:

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	PK		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	47.80	50.30	74.00	23.70	Pass	Horizontal
2	2402.1308	32.26	13.31	-43.12	84.10	86.55	74.00	-12.55	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	PK		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	48.18	50.68	74.00	23.32	Pass	Vertical
2	2401.7254	32.26	13.31	-43.12	74.40	76.85	74.00	-2.85	Pass	Vertical

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	AV		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	36.05	38.55	54.00	15.45	Pass	Horizontal
2	2401.9471	32.26	13.31	-43.12	43.15	45.60	54.00	8.40	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	AV		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	36.08	38.58	54.00	15.42	Pass	Vertical
2	2401.9408	32.26	13.31	-43.12	42.60	45.05	54.00	8.95	Pass	Vertical

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	PK		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2479.7872	32.37	13.39	-43.10	74.78	77.44	74.00	-3.44	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	48.33	50.98	74.00	23.02	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	PK		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2479.6596	32.37	13.39	-43.10	69.19	71.85	74.00	2.15	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	49.09	51.74	74.00	22.26	Pass	Vertical

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	AV		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2479.9149	32.37	13.39	-43.10	42.76	45.42	54.00	8.58	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	36.12	38.77	54.00	15.23	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	AV		

Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2479.8723	32.37	13.39	-43.10	41.48	44.14	54.00	9.86	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	36.11	38.76	54.00	15.24	Pass	Vertical

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

Appendix I) Radiated Spurious Emissions

Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Test Procedure:					
Below 1GHz test procedure as below:					
Test method Refer as KDB 558074 D01 v04, Section 12.1					
a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.					
b. The EUT was set 3 meters away from the interference-receiving antenna, whichwas mounted on the top of a variable-height antenna tower.					
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.					
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading.					
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.					
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Above 1GHz test procedure as below:					
g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).					
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel					
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.					
j. Repeat above procedures until all frequencies measured was complete.					
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBµV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Radiated Spurious Emissions test Data:
Radiated Emission below 1GHz

Mode:			BLE GFSK Transmitting					Channel:		2440	
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	36.5967	11.21	0.67	-31.38	43.20	23.70	40.00	16.30	Pass	H	PK
2	89.5640	9.30	1.10	-32.09	56.04	34.35	43.50	9.15	Pass	H	PK
3	252.5403	12.25	1.89	-31.89	49.34	31.59	46.00	14.41	Pass	H	PK
4	383.4063	15.03	2.33	-31.86	40.09	25.59	46.00	20.41	Pass	H	PK
5	600.0290	19.00	2.96	-31.50	40.39	30.85	46.00	15.15	Pass	H	PK
6	844.9785	21.44	3.50	-31.82	38.10	31.22	46.00	14.78	Pass	H	PK
7	36.5967	11.21	0.67	-31.38	43.76	24.26	40.00	15.74	Pass	V	PK
8	95.9666	10.35	1.13	-31.97	53.50	33.01	43.50	10.49	Pass	V	PK
9	195.0135	10.43	1.64	-31.94	45.64	25.77	43.50	17.73	Pass	V	PK
10	411.4421	15.58	2.42	-31.83	38.45	24.62	46.00	21.38	Pass	V	PK
11	600.0290	19.00	2.96	-31.50	41.22	31.68	46.00	14.32	Pass	V	PK
12	875.0515	21.80	3.55	-31.70	36.41	30.06	46.00	15.94	Pass	V	PK

Transmitter Emission above 1GHz

Mode:			BLE GFSK Transmitting					Channel:		2402	
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1993.499	31.66	3.46	-43.18	52.99	44.93	74.00	29.07	Pass	H	PK
2	3181.012	33.27	4.62	-43.10	50.85	45.64	74.00	28.36	Pass	H	PK
3	4804.000	34.50	4.55	-42.80	48.91	45.16	74.00	28.84	Pass	H	PK
4	7206.280	36.31	5.81	-42.16	54.34	54.30	74.00	19.70	Pass	H	PK
5	9608.000	37.64	6.63	-42.10	46.67	48.84	74.00	25.16	Pass	H	PK
6	12010.00	39.31	7.60	-41.90	46.35	51.36	74.00	22.64	Pass	H	PK
7	7205.840	36.31	5.82	-42.16	36.01	35.98	54.00	18.02	Pass	H	AV
8	1990.699	31.64	3.46	-43.18	56.65	48.57	74.00	25.43	Pass	V	PK
9	3794.052	33.64	4.37	-43.05	49.78	44.74	74.00	29.26	Pass	V	PK
10	4804.000	34.50	4.55	-42.80	46.53	42.78	74.00	31.22	Pass	V	PK
11	7205.280	36.31	5.82	-42.17	52.14	52.10	74.00	21.90	Pass	V	PK
12	9608.000	37.64	6.63	-42.10	46.61	48.78	74.00	25.22	Pass	V	PK
13	12010.00	39.31	7.60	-41.90	46.66	51.67	74.00	22.33	Pass	V	PK

Mode:			BLE GFSK Transmitting					Channel:		2440	
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1807.880	30.43	3.33	-42.73	51.54	42.57	74.00	31.43	Pass	H	PK
2	3189.012	33.28	4.63	-43.10	50.12	44.93	74.00	29.07	Pass	H	PK
3	4880.000	34.50	4.80	-42.80	47.22	43.72	74.00	30.28	Pass	H	PK
4	7320.288	36.42	5.85	-42.14	55.69	55.82	74.00	18.18	Pass	H	PK
5	9760.000	37.70	6.73	-42.10	48.07	50.40	74.00	23.60	Pass	H	PK
6	12200.00	39.42	7.67	-41.90	48.67	53.86	74.00	20.14	Pass	H	PK
7	7319.823	36.42	5.85	-42.14	36.84	36.97	54.00	17.03	Pass	V	AV
8	1798.879	30.37	3.32	-42.71	56.05	47.03	74.00	26.97	Pass	V	PK
9	3055.003	33.22	4.82	-43.10	50.90	45.84	74.00	28.16	Pass	V	PK
10	4880.000	34.50	4.80	-42.80	47.02	43.52	74.00	30.48	Pass	V	PK
11	7320.000	36.42	5.85	-42.14	52.03	52.16	74.00	21.84	Pass	V	PK
12	9760.000	37.70	6.73	-42.10	47.32	49.65	74.00	24.35	Pass	V	PK
13	12200.00	39.42	7.67	-41.90	45.75	50.94	74.00	23.06	Pass	V	PK

Mode:			BLE GFSK Transmitting					Channel:		2480	
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1470.847	28.37	2.97	-42.98	51.51	39.87	74.00	34.13	Pass	H	PK
2	1996.499	31.68	3.47	-43.20	52.23	44.18	74.00	29.82	Pass	H	PK
3	4960.000	34.50	4.82	-42.80	49.25	45.77	74.00	28.23	Pass	H	PK
4	7440.296	36.54	5.85	-42.11	53.45	53.73	74.00	20.27	Pass	H	PK
5	9920.000	37.77	6.79	-42.10	46.12	48.58	74.00	25.42	Pass	H	PK
6	12400.00	39.54	7.86	-41.90	48.14	53.64	74.00	20.36	Pass	H	PK
7	1800.480	30.38	3.32	-42.71	53.86	44.85	74.00	29.15	Pass	V	PK
8	3842.056	33.67	4.36	-43.03	50.48	45.48	74.00	28.52	Pass	V	PK
9	4960.000	34.50	4.82	-42.80	49.53	46.05	74.00	27.95	Pass	V	PK
10	7440.296	36.54	5.85	-42.11	54.53	54.81	74.00	19.19	Pass	V	PK
11	9920.000	37.77	6.79	-42.10	45.69	48.15	74.00	25.85	Pass	V	PK
12	12400.00	39.54	7.86	-41.90	47.14	52.64	74.00	21.36	Pass	V	PK
13	7439.830	36.54	5.85	-42.11	36.70	36.98	54.00	17.02	Pass	V	AV

Transmitter Emission above 18GHz

Mode:			BLE GFSK Transmitting					Channel:		2440	
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18311.93	37.74	0.00	-64.02	70.25	43.97	74.00	30.03	Pass	H	PK
2	19473.69	38.96	0.00	-62.90	68.90	44.96	74.00	29.04	Pass	H	PK
3	21260.45	38.54	0.00	-63.24	68.48	43.78	74.00	30.22	Pass	H	PK
4	22488.29	38.57	0.00	-62.95	69.97	45.59	74.00	28.41	Pass	H	PK
5	23763.19	39.86	0.00	-60.97	66.34	45.23	74.00	28.77	Pass	H	PK
6	24589.50	40.49	0.00	-60.34	64.77	44.92	74.00	29.08	Pass	H	PK
7	18627.50	38.30	0.00	-63.83	70.14	44.61	74.00	29.39	Pass	V	PK
8	19902.67	38.97	0.00	-62.30	68.42	45.09	74.00	28.91	Pass	V	PK
9	20995.83	38.62	0.00	-63.39	68.94	44.17	74.00	29.83	Pass	V	PK
10	22174.68	38.40	0.00	-63.15	69.18	44.43	74.00	29.57	Pass	V	PK
11	23595.18	39.63	0.00	-61.51	66.97	45.09	74.00	28.91	Pass	V	PK
12	24817.15	40.61	0.00	-60.41	65.21	45.41	74.00	28.59	Pass	V	PK

Note:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.