

RF EXPOSURE EVALUATION

FCC ID : 2AFWN-SLG-EN101U
IC : 22800-SLGEN101U

Standard Requirement

The following FCC Rule Parts and procedures are applicable :

Part 1.1310 Radiofrequency radiation exposure limits

Part 2.1091 Radiofrequency radiation exposure evaluation : Mobile device

KDB447498 D01 v06 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

Table 1 below sets forth limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			<u>1.0</u>	30

f = frequency in MHz * = Plane-wave equivalent power density

RSS-102(Issue5) Exposure Limits

Table : RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Frequency range (MHz)	Electric field strength (V/m rms)	Magnetic field strength (A/m rms)	Power density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73 / f	-	6**
1.1-10	87 / f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07 / f ^{0.25}	0.1540 / f ^{0.25}	8.944 / f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	<u>0.02619 f^{0.6834}</u>	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000 / f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁰⁵ f	616000 / f ^{1.2}

f is frequency in MHz,

*:Based on nerve stimulation(NS), **:Based on specific absorption rate(SAR)



CTK Co., Ltd.
The First Leader of Global Regulatory Compliance

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

MPE calculation

$$S = \text{EIRP} / (4\pi R^2)$$

Where S : Power density
EIRP : $P \times G$
P : Maximum transmitter power
G : Antenna gain
R : distance to the centre of radiation of the antenna

Note

P : 12.61 dBm (18.239 mW)(0.018 239 W)
G : 3.2 dBi x(2.089)
R : 20.00 cm (0.20 m)

FCC MPE : 1 mW/cm^2
RSS-102 : $0.02619 f^{0.6834} \Rightarrow 5.35 \text{ W/m}^2$

Test Data(Maximum RF Power)

Frequency	Measurement data	Limit	Result
2 402 MHz	0.007 585 mW/cm ²	1.00 mW/cm ²	Complies
	0.075 849 W/m ²	5.35 W/m ²	Complies

Conclusion

This confirms compliance to the required Radio frequency radiation exposure limit.