



## **TEST REPORT**

Report No. : AG025001-001 Date : 2006 October 12

Application No. : LG219629(7)

Client : Mattel Asia Pacific Sourcing Limited  
13/F., South Tower, World Finance Centre,  
Harbour City, Tsim Sha Tsui,  
Kowloon, Hong Kong

Sample Description : One(1) submitted sample(s) stated to be RC Bloo  
of Model No. K3841  
Radio Frequency : 27.145 MHz Transmitter  
Rating : 2 x 1.5V AA size batteries  
No. of submitted sample : Three (3) piece(s) \*\*\*

Date Received : 2006 September 11

Test Period : 2006 September 11 – 2006 September 22

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-05 Edition)  
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15  
Subpart C.

*For and on behalf of*  
CMA Industrial Development Foundation Limited

Authorized Signature : \_\_\_\_\_

Danny Chui  
Deputy Manager - EL. Division

FCC ID: PIYK3841-06A2T

Page 1 of 11



## **TEST REPORT**

Report No. : AG025001-001

Date : 2006 October 12

### **Table of Contents**

1	General Information .....	3
1.1	General Description .....	3
1.2	Location of the test site .....	4
1.3	List of measuring equipment.....	5
2	Description of the radiated emission test .....	6
2.1	Test Procedure.....	6
2.2	Test Result.....	6
2.3	Radiated Emission Measurement Data .....	7
3	Description of the Line-conducted Test.....	8
3.1	Test Procedure.....	8
3.2	Test Result.....	8
3.3	Graph and Table of Conducted Emission Measurement Data .....	8
4	Photograph .....	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission .....	9
4.2	Photographs of the External and Internal Configurations of the EUT.....	9
5	Supplementary document.....	10
5.1	Bandwidth .....	10
5.2	Duty cycle .....	10
5.3	Transmission time .....	10
6	Appendices.....	11



## **TEST REPORT**

Report No. : AG025001-001

Date : 2006 October 12

### **1 General Information**

#### **1.1 General Description**

The equipment under test (EUT) is a transmitter for RC Bloo. It operates at 27.145MHz which is controlled by a crystal. The EUT is powered by 2 x 1.5V AA size batteries. There are five buttons in the EUT. When the forward, turn right, turn left, self-rotate and sound button is pressed once, it will transmit different radio control signal to the receiver.

The brief circuit description is listed as follows:

- U1 and associated circuit act as encoder and RF amplifier
- Y1 and associated circuit act as an oscillator for U1



**CMA Testing  
and Certification  
Laboratories**  
廠商會檢定中心

## **TEST REPORT**

Report No. : AG025001-001

Date : 2006 October 12

### **1.2 Location of the test site**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.



## **TEST REPORT**

Report No. : AG025001-001

Date : 2006 October 12

### **1.3 List of measuring equipment**

Equipment	Manufacturer	Model No.	Serial No.
EMI Test Receiver	R&S	ESCS30	100001
Broadband Antenna	Schaffner	CBL6112B	2692
Loop Antenna	EMCO	6502	00056620
Spectrum Analyzer	Rohde & Schwarz	FSP30	100628



## **TEST REPORT**

Report No. : AG025001-001

Date : 2006 October 12

### **2 Description of the radiated emission test**

#### **2.1 Test Procedure**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

#### **2.2 Test Result**

All other measurements are well below the limit. Thus, those highest emissions were presented in next page.

Peak Detector data was measured unless otherwise stated.

The harmonic emissions meeting the requirement of section 15.209 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

It was found that the EUT meet the FCC requirement.



## **TEST REPORT**

Report No. : AG025001-001

Date : 2006 October 12

### **2.3 Radiated Emission Measurement Data**

#### **Radiated emission**

#### **pursuant to**

#### **the requirement of FCC Part 15 subpart C**

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB $\mu$ V/m)	Antenna and Cable factor (dB)	Average Factor (dB)	Field Strength (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
27.145	V	69.1	9.0	-5.7	72.4	80.0	-7.6
54.286	V	15.0	8.1	-	23.1	40.0	-16.9
81.428	H	13.6	7.2	-	20.8	40.0	-19.2
*108.577	H	14.3	11.0	-	25.3	43.5	-18.2
*135.722	V	12.7	12.4	-	25.1	43.5	-18.4
*162.880	H	13.5	10.4	-	23.9	43.5	-19.6
190.010	V	13.1	9.2	-	22.3	43.5	-21.2
217.160	H	14.1	9.7	-	23.8	46.0	-22.2
*244.306	H	22.6	9.7	-	32.3	46.0	-13.7
*271.440	H	17.0	13.9	-	30.9	46.0	-15.1



## **TEST REPORT**

Report No. : AG025001-001

Date : 2006 October 12

### **3 Description of the Line-conducted Test**

#### **3.1 Test Procedure**

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

#### **3.2 Test Result**

No measurement is required as the EUT is a battery-operated product.

#### **3.3 Graph and Table of Conducted Emission Measurement Data**

Not Applicable





## **TEST REPORT**

Report No. : AG025001-001

Date : 2006 October 12

### **4 Photograph**

#### **4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission**

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

#### **4.2 Photographs of the External and Internal Configurations of the EUT**

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



## **TEST REPORT**

Report No. : AG025001-001

Date : 2006 October 12

### **5 Supplementary document**

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

<b>Document</b>	<b>Filename</b>
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

#### **5.1 Bandwidth**

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.209 requirement at 26.9599 and 27.2801 MHz.

#### **5.2 Duty cycle**

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 32.12ms

Effective period of the cycle = (0.970ms x 8) + (0.490ms x 18)  
= 16.58ms

Duty Cycle = 16.58 / 32.12  
= 0.52

Therefore, the average factor is found by  $20 \log_{10} 0.52 = -5.7\text{dB}$

#### **5.3 Transmission time**

N/A



## **TEST REPORT**

Report No. : AG025001-001

Date : 2006 October 12

### **6 Appendices**

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of External Configurations	1	page
A3.	Photos of Internal Configurations	1	page
A4.	ID Label/Location	1	page
A5.	Bandwidth Plot	1	page
A6.	Average Factor	2	pages
A7.	Block Diagram	1	page
A8.	Schematics Diagram	1	page
A9.	User Manual	1	page
A10.	Operation Description	1	page

\*\*\*\*\* End of Report \*\*\*\*\*