

# ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

**Test Report No.** : OT-188-RWD-010  
**AGR No.** : A185A-337  
**Applicant** : C&A Marketing Inc.  
**Address** : 114 Tived Lane East, Edison, New Jersey, 08837, United States  
**Manufacturer** : DSGLOBAL CO.,LTD  
**Address** : 107, Gasan digital 2-ro, Geumcheon-gu, Seoul, Korea  
**Type of Equipment** : Polaroid mint mobile printer  
**FCC ID.** : 2AD2WPOLMP02  
**Model Name** : POLMP02  
**Serial number** : N/A  
**Total page of Report:** 8 pages (including this page)  
**Date of Incoming** : June 02, 2018  
**Date of issue** : August 09, 2018

## SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247*


This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:

  
 Ki-Hong, Nam / Chief Engineer  
 ONETECH Corp.

Approved by:

  
 Keun-Young, Choi / Vice President  
 ONETECH Corp.

## CONTENTS

### PAGE

<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION.....</b>	<b>5</b>
<b>2.1 PRODUCT DESCRIPTION.....</b>	<b>5</b>
<b>2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....</b>	<b>5</b>
<b>3. EUT MODIFICATIONS.....</b>	<b>5</b>
<b>4. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>6</b>
<b>4.1 RF EXPOSURE CALCULATION .....</b>	<b>6</b>
<b>4.2 EUT DESCRIPTION.....</b>	<b>7</b>
<b>4.3 TEST RESULT .....</b>	<b>8</b>

**Revision History**

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-188-RWD-010	2018.08.09	Initial Release	All

## 1. VERIFICATION OF COMPLIANCE

Applicant : C&A Marketing Inc.  
Address : 114 Tived Lane East, Edison, New Jersey, 08837, United States  
Contact Person : Chaim, Piekarski / Chief Executive Officer  
Telephone No. : +8482442000  
FCC ID : 2AD2WPOLMP02  
Model Name : POLMP02  
Serial Number : N/A  
Date : August 09, 2018

EQUIPMENT CLASS	DSS – PART 15 SPREAD SPECTRUM TRANSMITTER
E.U.T. DESCRIPTION	Polaroid mint mobile printer
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

## 2. GENERAL INFORMATION

### 2.1 Product Description

The C&A Marketing Inc., Model POLMP02 (referred to as the EUT in this report) is a Polaroid mint mobile printer. Product specification information described herein was obtained from product data sheet or user's manual.

Device Type	Polaroid mint mobile printer	
Operating Frequency	2 402 MHz ~ 2 480 MHz	
RF Output Power	1 Mbps	8.85 dBm
	2 Mbps	7.03 dBm
	3 Mbps	7.61 dBm
Number of Channel	79 Channel	
Modulation Type	1 Mbps	GFSK
	2 Mbps	$\pi/4$ -QPSK
	3 Mbps	8-DPSK
Antenna Type	Chip Antenna	
Antenna Gain	1.80 dBi	
List of each Osc. or crystal Freq.(Freq. $\geq$ 1 MHz)	26 MHz	

### 2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

## 3. EUT MODIFICATIONS

-. None

## 4. MAXIMUM PERMISSIBLE EXPOSURE

### 4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are  $f/1500 \text{ mW/cm}^2$  for the frequency range between 300 MHz and 1 500 MHz and  $1.0 \text{ mW/cm}^2$  for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a  $1 \text{ mW/cm}^2$  exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

$S$  = Power density in  $\text{mW/cm}^2$ ,  $Z$  = Impedance of free space,  $377 \Omega$

$E$  = Electric field strength in  $\text{V/m}$ ,  $G$  = Numeric antenna gain, and  $d$  = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of  $\text{mW}$  and  $\text{cm}$ , using  $P (\text{mW}) = P (\text{W}) / 1000$ ,  $d (\text{cm}) = 0.01 * d (\text{m})$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

$d$  = distance in  $\text{cm}$ ,  $P$  = Power in  $\text{mW}$ ,  $G$  = Numeric antenna gain, and  $S$  = Power density in  $\text{mW/cm}^2$

## 4.2 EUT Description

Kind of EUT	Polaroid mint mobile printer
Operating Frequency Band	<input type="checkbox"/> Wireless Microphone: 494.000 MHz ~ 501.000 MHz and 498.200 MHz ~ 505.200 MHz <input type="checkbox"/> WLAN: 2 412 MHz ~ 2 462 MHz <input type="checkbox"/> WLAN: 5 180 MHz ~ 5 320 MHz / 5 500 MHz ~ 5 700 MHz <input type="checkbox"/> WLAN: 5 745 MHz ~ 5 825 MHz <input checked="" type="checkbox"/> Bluetooth: 2 402 MHz ~ 2 480 MHz <input type="checkbox"/> Zigbee: 2 405 MHz ~ 2 480 MHz
Device Category	<input checked="" type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input type="checkbox"/> Others
Max. Output Power	1 Mbps: 8.85 dBm 2 Mbps: 7.03 dBm 3 Mbps: 7.61 dBm
Used Antenna	Chip Antenna
Used Antenna Gain	1.80 dBi
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

### 4.3 Test Result

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
		(dBm)	(dBm)	(mW)	Log	Linear			
2 405 ~ 2 480	1 Mbps	8.0 ± 1.0	9.0	7.94	1.80	1.51	0.98	0.002 4	1.00
	2 Mbps	6.5 ± 1.0	7.5	5.62			0.82	0.001 7	
	3 Mbps	7.0 ± 1.0	8.0	6.31			0.87	0.001 9	

According to above table, for 2 405 MHz ~ 2 480 MHz Band, safe distance,

$$D = 0.282 * \sqrt{(7.94 * 1.51)} / 1.00 = 0.98 \text{ cm}$$

For getting power density at 20 cm separation in above table, following formula was used.


$$S = P * G / (4\pi * R^2) = 7.94 * 1.51 / (4 * 3.14 * 20^2) = 0.002 4$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

  
 Tested by: Tae-Ho, Kim / Senior Manager