

# TEST REPORT No. I19Z60845-WMD02

for

# amsung Electronics Co Ltd

# MULTI-BAND GSM/WCDMA/LTE PHONE WITH BLUETOOTH, WLAN

Model Name: SM-T295C

FCC ID: ZCASMT295C

with

Hardware Version: REV0.4

Software Version: T295CZCU0ASEA

Issued Date: 2019-07-25



#### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

#### **Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl\_terminals@caict.ac.cn, website: www.caict.ac.cn



# **REPORT HISTORY**

Report Number	Revision	Description	Issue Date
I19Z60845-WMD02	Rev.0	1 <sup>st</sup> edition	2019-07-17
I19Z60845-WMD02	Rev.1	2 <sup>nd</sup> edition	2019-07-25
		Removed all the	
		results for WCDMA IV	



# **CONTENTS**

1.	TEST LABORATORY	4
1.1.	INTRODUCTION & ACCREDITATION	4
1.2.	TESTING LOCATION	4
1.3.	TESTING ENVIRONMENT	4
1.4.		
1.5.	SIGNATURE	5
2.	CLIENT INFORMATION	
2.1.		
2.2.		
3.	EQUIPMENT UNDERTEST (EUT) AND ANCILLARY EQUIPMENT (AE)	
3.1.		
3.2.	INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	7
3.3.	INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	7
3.4.	NORMAL ACCESSORY SETTING	8
3.5.	GENERAL DESCRIPTION	8
4.	REFERENCE DOCUMENTS	9
4.1.	REFERENCE DOCUMENTS FOR TESTING	9
5.	LABORATORY ENVIRONMENT	
6.	SUMMARY OF TEST RESULTS	
6.1.		
6.2.		
7.	TEST EQUIPMENTS UTILIZED	
ANI	NEX A: MEASUREMENT RESULTS	14
	.1 OUTPUT POWER	
	.2 EMISSION LIMIT	
	3 FREQUENCY STABILITY	
	.4 OCCUPIED BANDWIDTH	
	5 EMISSION BANDWIDTH	
	.7 CONDUCTED SPURIOUS EMISSION	
	8 PEAK-TO-AVERAGE POWER RATIO	44
A TATE	NEV D. ACCDEDITATION CERTIFICATE	15



# 1. Test Laboratory

# 1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

#### 1.2. Testing Location

Location 1: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,

P. R. China 100191

Location 2: CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,

Haidian District, Beijing, P. R. China 100191

Location 3:CTTL (BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology

Development Area, Beijing, P. R. China 100176

# 1.3. Testing Environment

Normal Temperature:  $15-35^{\circ}$ C Relative Humidity: 20-75%

#### 1.4. Project data

Testing Start Date: 2019-04-15 Testing End Date: 2019-07-16



# 1.5. Signature



Dong Yuan (Prepared this test report)



Zhou Yu (Reviewed this test report)

赵瑟麟

Zhao Hui Lin
Deputy Director of the laboratory
(Approved this test report)



# 2. Client Information

# 2.1. Applicant Information

Company Name: Samsung Electronics Co Ltd

Address / Post: 19 Chapin Rd., Building D Pine Brook, NJ 07058

Contact: Jenni Chun

Email: NA
Telephone: NA
Fax: NA

# 2.2. Manufacturer Information

Company Name: Jiaxing Yongrui Electron Technology Co., Ltd.

NO.777 Yazhong Road, Daqiao Town, Nanhu District, Jiaxing

City ,Zhejiang

Contact: NA
Email: NA
Telephone: NA
Fax: NA

Address /Post:



# 3. Equipment UnderTest (EUT) and Ancillary Equipment (AE)

# 3.1. About EUT

Description MULTI-BAND GSM/WCDMA/LTE PHONE WITH BLUETOOTH,

**WLAN** 

Model Name SM-T295C FCC ID ZCASMT295C Antenna Embedded

Output power 24.28dBm maximum EIRP measured for WCDMA Band II

Extreme vol. Limits 3.6VDC to 4.2VDC (nominal: 3.8VDC)

Extreme temp. Tolerance -10°C to +55°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

#### 3.2. Internal Identification of EUT used during the test

 EUT ID\*
 IMEI
 HW Version
 SW Version
 Date of receipt

 UT05a
 356221100013137
 REV0.4
 T295CZCU0ASEA
 2019-05-16

# 3.3. Internal Identification of AE used during the test

AE ID\* Description
AE1 Battery
AE2 Battery

AE1

Model SWD-WT-N8

Manufacturer Sunwoda Electronic Co., Ltd .

Capacitance 4980mAh

AE2

Model SCUD-WT-N8

Manufacturer SCUD(Fujian) Electronic Co., Ltd.

Capacitance 4980mAh

<sup>\*</sup>EUT ID: is used to identify the test sample in the lab internally.

<sup>\*</sup>AE ID: is used to identify the test sample in the lab internally.



# 3.4. Normal Accessory setting

Fully charged battery was used during the test.

# 3.5. General Description

The Equipment Under Test (EUT) is a model of MULTI-BAND GSM/WCDMA/LTE PHONE WITH BLUETOOTH, WLAN with embedded antenna. Manual and specifications of the EUT were provided to fulfil the test.



# 4. Reference Documents

# 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-18
		Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-18
		Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment	2016
	Measurement and Performance Standards	
ANSI/TIA-102.CAAA	DIGITAL C4FMCQPSK TRANSCEIVER MEASUREMENT	2016
-E	METHODS	
ANSI C63.26	American National Standard for Compliance Testing of	2015
	Transmitters Used in Licensed Radio Services	
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF	v03r01
	LICENSED DIGITAL TRANSMITTERS	



# 5. LABORATORY ENVIRONMENT

Control room / conducted chamber did not exceed following limits along the EMC testing:

	· · · · · · · · · · · · · · · · · · ·
Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber 2** (8.6 meters × 6.1 meters × 3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	<1 Ω
Site voltage standing-wave ratio (S <sub>VSWR</sub> )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

**Semi-anechoic chamber 2 / Fully-anechoic chamber 3** (10 meters × 6.7 meters × 6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	<±3.5 dB, 3 m distance
Site voltage standing-wave ratio (S <sub>VSWR</sub> )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz



# 6. SUMMARY OF 错误!未找到引用源。

# 6.1. Summary of test results

# WCDMA Band II

Items	Test Name	Test Name Clause in FCC rules	
1	Output Power	24.232	BR
2	Emission Limit	2.1051/24.238	BR
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	24.238	BR
6	Band Edge Compliance	24.238	BR
7	Conducted Spurious Emission	24.238	BR
8	Peak-to-Average Power Ratio	24.232	BR

#### **WCDMA Band V**

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	22.913	Р
2	Emission Limit	2.1051/22.917	Р
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	22.917	BR
6	Band Edge Compliance	22.917	BR
7	Conducted Spurious Emission	22.917	BR

#### Terms used in Verdict column

Р	Pass, The EUT complies with the essential requirements in the standard.		
NP	Not Perform, The test was not performed by CTTL		
NA	Not Applicable, The test was not applicable		
BR	Re-use test data from basic model report.		
F	Fail, The EUT does not comply with the essential requirements in the		
	standard		



#### 6.2. Explanation of re-use of test data

The Equipment Under Test (EUT) model SM-T295C (FCC ID: ZCASMT295C) is a variant product of SM-T295 (FCC ID: ZCASMT295), according to the declaration of changes provided by the applicant and FCC KDB publication 484596 D01, spot check measurements were performed on this device, all the test results are derived from test report No.I19Z60464-WMD02. Please refer Annex A for detail spot check verification data and reference data.the spot check test results are consistent with basic model.

For detail differences between two models please refer the Declaration of Changes document.



# 7. Test Equipments Utilized

NO.	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	EMI Antenna	VULB9163	9163-235	Schwarzbeck	2019-11-20	1 year
2	EMI Antenna	3117	00058889	ETS-Lindgren	2020-01-12	1 year
3	EMI Antenna	3117	00119024	ETS-Lindgren	2020-02-25	1 year
4	Universal Radio Communication Tester	CMU200	108646	R&S	2020-01-03	1 year
5	Spectrum Analyzer	FSU26	200030	R&S	2020-06-03	1 year
6	EMI Antenna	9117	177	Schwarzbeck	2019-08-22	1 year
7	Signal Generator	SMF100A	101295	R&S	2019-11-27	1 year
8	Climate chamber	SH-242	93008556	ESPEC	2019-12-21	2 year
9	Test Receiver	E4440A	MY48250642	Agilent	2020-03-18	1 year
10	Universal Radio Communication Tester	CMW500	143008	R&S	2019-11-26	1 year
11	Power Amplifier	5S1G4	0341863	AR	/	



# **ANNEX A: MEASUREMENT RESULTS**

# A.1 OUTPUT POWER

#### A.1.1 Summary

During the process of testing, the EUT was controlled via communication tester to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### A.1.2 Conducted

#### A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II;826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V.

#### **WCDMA Band II**

#### Measurement result-QPSK

	CH	Frequency(MHz)	output power(dBm)
WCDMA	9262	1852.4	23.39
(Band II)	9400	1880.0	23.41
	9538	1907.6	23.44

#### **WCDMA Band V**

#### Measurement result-QPSK

	СН	Frequency(MHz)	output power(dBm)
WCDMA	4132	826.4	23.50
(Band V)	4183	836.6	23.60
	4233	846.6	23.48



#### A.1.3 Radiated

#### A.1.3.1 Description


This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360°and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with RMS detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere



with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. An amplifier should be connected to the Signal Source output port. And the cable should be connecting between the Amplifier and the Substitution Antenna.

The cable loss  $(P_{cl})$ , the Substitution Antenna Gain  $(G_a)$  and the Amplifier Gain  $(P_{Ag})$  should be recorded after test.

The measurement results are obtained as described below:

Power (EIRP)=P<sub>Mea</sub>-P<sub>Ag</sub>-P<sub>cl</sub> -G<sub>a</sub>

- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.



# **Spot check Measurement Results:**

#### **WCDMA Band V-ERP**

#### Limits

	Burst Peak ERP (dBm)
WCDMA Band V	≤38.45dBm

#### **Measurement result-QPSK**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.40	-20.52	2.25	45.76	0.93	2.15	21.77	38.45	16.68	Н
836.60	-20.10	2.26	45.66	0.82	2.15	21.97	38.45	16.48	Н
846.60	-20.49	2.26	45.56	0.81	2.15	21.47	38.45	16.98	Н

ANALYZER SETTINGS: RBW = VBW = 5MHz

Frequency: 826.40MHz

 $Peak \; ERP(dBm) = P_{Mea}(-20.10dBm) - P_{cl}(2.26dB) - P_{Ag}(-45.66dB) - G_a \; (-0.82dB) - 2.15dB = 21.97dBm$ 



# Reference Measurement Results from basic model:

#### **WCDMA Band II-EIRP**

#### Limits

	Burst Peak EIRP (dBm)
WCDMA Band II	≤33dBm (2W)

#### **Measurement result-QPSK**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.40	-22.50	2.84	43.75	4.87	23.28	33.00	9.72	Н
1880.00	-21.94	2.85	43.75	4.82	23.78	33.00	9.22	Н
1907.60	-21.38	2.88	43.77	4.77	24.28	33.00	8.72	Н

ANALYZER SETTINGS: RBW = VBW = 5MHz

Frequency: 1907.60MHz

Peak EIRP(dBm)= $P_{Mea}(-21.38)-P_{cl}(2.88dB)-P_{Ag}(-43.77dB)-G_a(-4.77dB)=24.28dBm$ 

#### **WCDMA Band V-ERP**

#### Limits

	Burst Peak ERP (dBm)
WCDMA Band V	≤38.45dBm

#### Measurement result-QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.40	-21.02	2.25	45.76	0.93	2.15	21.27	38.45	17.18	Н
836.60	-21.21	2.26	45.66	0.82	2.15	20.86	38.45	17.59	Н
846.60	-21.81	2.26	45.56	0.81	2.15	20.15	38.45	18.30	Н

ANALYZER SETTINGS: RBW = VBW = 5MHz

Frequency: 826.40MHz

 $Peak \; ERP(dBm) = P_{Mea}(-21.02dBm) - P_{cl}(2.25dB) - P_{Ag}(-45.76dB) - G_a \; (-0.93dB) - 2.15dB = 21.27dBm$ 

Note: Expanded measurement uncertainty is U = 2.84 dB, k = 2.



#### A.2 EMISSION LIMIT

#### A.2.1 Measurement Method

The measurements procedures in TIA-603E-2016 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238, Part 22.917. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II and WCDMA Band V.

#### The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{\text{Mea}}$ ) is applied to the input of the



substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach thepreviously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P<sub>pl</sub>) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G<sub>a</sub>) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (Ppl) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

Power (EIRP)=P<sub>Mea</sub>-P<sub>pl</sub>-G<sub>a</sub>

- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.

#### A.2.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

#### A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of WCDMA Band II (1852.4 MHz, 1880.0MHz and 1907.6MHz) and WCDMA Band V(826.4MHz, 836.6MHz and 846.6MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II and WCDMA Band V into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.



#### A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result	
	Low	30MHz-10GHz	Pass	
WCDMA Band V	Middle	30MHz-10GHz	Pass	
	High	30MHz-10GHz	Pass	
	Low	30MHz-20GHz	Pass	
WCDMA Band II	Middle	30MHz-20GHz	Pass	
	High	30MHz-20GHz	Pass	

#### A.2.5 Sweep Table

A.Z.5 Sweep Table				
Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
WCDMA Band V	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
WCDMA Band II	5~8	1 MHz	3 MHz	3
WCDIVIA Bariu II	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2



# **Spot check Measurement Results:**

# WCDMA BAND V Mode Channel 4132/826.4MHz

Fraguency/MHz)	D. (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization	
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	Bi) (dB) ERP(d		(dBm)	Margin(dB)	FUIAITZALIUIT	
1654.01	-54.19	3.57	5.22	2.15	-54.69	-13.00	41.69	Н	
2479.00	-53.51	4.60	6.04	2.15	-54.22	-13.00	41.22	V	
3303.02	-54.63	5.29	7.73	2.15	-54.34	-13.00	41.34	Н	
4102.02	-55.50	6.04	9.00	2.15	-54.69	-13.00	41.69	Н	
4927.01	-55.63	6.73	9.83	2.15	-54.68	-13.00	41.68	V	
5765.01	-54.84	7.24	10.55	2.15	-53.68	-13.00	40.68	Н	

#### WCDMA BAND V Mode Channel 4183/836.6MHz

Frequency(MHz)	Frequency(MHz) P <sub>Mea</sub> (dBm)	Path	Antenna	Correction	Peak	Limit	Margin(dB)	Polarization
1 requericy(wir iz)	r Mea(ubiii)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	ivialyili(ub)	1 Glarization
1675.01	-53.67	3.58	5.18	2.15	-54.22	-13.00	41.22	Н
2501.00	-53.47	4.63	6.10	2.15	-54.15	-13.00	41.15	Н
3336.02	-54.55	5.31	7.81	2.15	-54.20	-13.00	41.20	Н
4176.02	-55.11	6.15	9.08	2.15	-54.33	-13.00	41.33	V
5005.01	-56.14	6.59	9.91	2.15	-54.97	-13.00	41.97	Н
5851.01	-53.63	7.24	10.53	2.15	-52.49	-13.00	39.49	V

#### WCDMA BAND V Mode Channel 4233/846.6MHz

Fragues (MUz)	onov(MHz) D. (dPm)		Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polatization
1692.01	-55.43	3.59	5.15	2.15	-56.02	-13.00	43.02	Н
2546.00	-52.51	4.66	6.18	2.15	-53.14	-13.00	40.14	Н
3404.02	-54.65	5.37	7.97	2.15	-54.20	-13.00	41.20	V
4256.02	-56.17	6.23	9.16	2.15	-55.39	-13.00	42.39	Н
5105.01	-55.56	6.79	10.05	2.15	-54.45	-13.00	41.45	V
5940.01	-52.74	7.47	10.51	2.15	-51.85	-13.00	38.85	V



# Reference Measurement Results from basic model: WCDMA BAND II Mode Channel 9262/1852.4MHz

Fragues av (MHz)	ency(MHz) P., (dRm)		Antenna	Peak	Limit(dBm)	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (ubiii)	P <sub>Mea</sub> (dBm) Loss(dB) Gain(dBi) EIRP(dBm) Lim		Limit(ubin)	Margin(dB)	Polarization	
7406.01	-54.96	8.13	12.09	-51.00	-13.00	38.00	V
9241.01	-54.03	9.02	13.24	-49.81	-13.00	36.81	V
11131.01	-51.89	9.70	13.17	-48.42	-13.00	35.42	V
12977.01	-49.19	10.48	13.49	-46.18	-13.00	33.18	Н
14817.00	-45.79	11.14	14.15	-42.78	-13.00	29.78	V
16692.00	-42.95	11.75	13.68	-41.02	-13.00	28.02	V

#### WCDMA BAND II Mode Channel 9400/1880MHz

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path	Antenna	Peak	Limit(dBm)	Margin(dB)	Polarization
1 requeries (Will 12)	i Mea(GDIII)	Loss(dB)	Gain(dBi)	EIRP(dBm)	Limit(abin)	Margin(ab)	1 Glanzation
7515.01	-55.08	8.33	12.21	-51.20	-13.00	38.20	Н
9379.01	-54.81	9.06	13.33	-50.54	-13.00	37.54	V
11261.01	-51.86	9.76	13.15	-48.47	-13.00	35.47	Н
13171.01	-48.68	10.62	13.74	-45.56	-13.00	32.56	V
15024.00	-45.70	11.25	13.99	-42.96	-13.00	29.96	V
16943.00	-42.30	12.16	13.78	-40.68	-13.00	27.68	Н

#### WCDMA BAND II Mode Channel 9538/1907.6MHz

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path	Antenna	Peak	Limit(dBm)	Margin(dB)	Polarization
1 requericy(ivii iz)	F Mea(UDIII)	Loss(dB)	Gain(dBi)	EIRP(dBm)	Lillit(dBill)	iviargiri(ub)	Folalization
7645.01	-54.75	8.18	12.32	-50.61	-13.00	37.61	Н
9545.01	-54.00	9.38	13.35	-50.03	-13.00	37.03	H
11455.01	-51.23	9.93	13.11	-48.05	-13.00	35.05	V
13364.01	-48.33	10.57	14.01	-44.89	-13.00	31.89	Н
15275.00	-45.76	11.31	13.83	-43.24	-13.00	30.24	V
17195.00	-42.85	12.37	14.23	-40.99	-13.00	27.99	Н



#### WCDMA BAND V Mode Channel 4132/826.4MHz

Fraguency/MHz)	D. (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1654.01	-52.79	3.57	5.22	2.15	-53.29	-13.00	40.29	Н
2463.00	-52.92	4.59	5.99	2.15	-53.67	-13.00	40.67	<b>V</b>
3302.02	-54.78	5.29	7.72	2.15	-54.50	-13.00	41.50	Н
4118.02	-55.15	6.04	9.02	2.15	-54.32	-13.00	41.32	V
4934.01	-55.03	6.72	9.83	2.15	-54.07	-13.00	41.07	V
5762.01	-52.79	7.25	10.55	2.15	-51.64	-13.00	38.64	Н

#### WCDMA BAND V Mode Channel 4183/836.6MHz

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path	Antenna	Correction	Peak	Limit	Margin(dB)	Polarization
1 requericy(Wir IZ)	i Mea(dDiii)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	iviargiri(db)	1 Glanzation
1675.01	-52.08	3.58	5.18	2.15	-52.63	-13.00	39.63	Н
2515.00	-53.40	4.64	6.13	2.15	-54.06	-13.00	41.06	Н
3342.02	-54.34	5.31	7.82	2.15	-53.98	-13.00	40.98	Н
4188.02	-54.79	6.18	9.09	2.15	-54.03	-13.00	41.03	Н
5021.01	-54.94	6.57	9.93	2.15	-53.73	-13.00	40.73	V
5839.01	-53.72	7.20	10.53	2.15	-52.54	-13.00	39.54	V

#### WCDMA BAND V Mode Channel 4233/846.6MHz

- WODIN	WODINA BAND V Mode Ondrine: 4200/040.00012							
Fragues av (MHz)	D. (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1691.01	-53.06	3.59	5.16	2.15	-53.64	-13.00	40.64	Н
2545.00	-52.59	4.66	6.18	2.15	-53.22	-13.00	40.22	Н
3381.02	-55.08	5.35	7.91	2.15	-54.67	-13.00	41.67	V
4244.02	-54.71	6.25	9.14	2.15	-53.97	-13.00	40.97	Н
5087.01	-54.67	6.74	10.02	2.15	-53.54	-13.00	40.54	Н
5933.01	-52.04	7.47	10.51	2.15	-51.15	-13.00	38.15	Н

Note: Expanded measurement uncertainty is U = 5.16 dB, k = 2.



#### A.3 FREQUENCY STABILITY

#### A.3.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the EUT to overnight soak at -10℃.
- 3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of WCDMA Band II and WCDMA Band V, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10°C increments from -10°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6. Subject the EUT to overnight soak at  $+50^{\circ}$ C.
- 7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10°C increments from -10°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.6VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.



# A.3.2 Measurement results WCDMA Band II

# Frequency Error vs Voltage-QPSK

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.6	-4.04	0.0021
3.8	3.68	0.0020
4.2	-4.78	0.0025

# Frequency Error vs Temperature-QPSK

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	-3.19	0.0017
0	-3.22	0.0017
10	2.91	0.0015
20	-1.80	0.0010
30	-3.13	0.0017
40	-2.17	0.0012
50	2.64	0.0014

#### **WCDMA Band V**

# Frequency Error vs Voltage-QPSK

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.6	-3.14	0.0038
3.8	3.16	0.0038
4.2	2.41	0.0029

# Frequency Error vs Temperature-QPSK

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	2.24	0.0027
0	-2.82	0.0034
10	1.74	0.0021
20	1.72	0.0021
30	-2.56	0.0031
40	-1.80	0.0022
50	-2.30	0.0027



#### A.4 OCCUPIED BANDWIDTH

#### A.4.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from KDB 971168 4.2:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least 10log (OBW / RBW) below the reference level.
- d) Set the detection mode to peak, and the trace mode to max hold.
- e) Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.




# WCDMA Band II (99% BW)-QPSK

Frequency(MHz)	Occupied Bandwidth (99% BW)( KHz)
1852.4	4150.64
1880.0	4134.62
1907.6	4134.62

#### WCDMA Band II


# Channel 9262-Occupied Bandwidth (99% BW)



Date: 18.APR.2019 10:11:35




# Channel 9400-Occupied Bandwidth (99% BW)



Date: 18.APR.2019 10:12:47

# Channel 9538-Occupied Bandwidth (99% BW)



Date: 18.APR.2019 10:13:58




# WCDMA Band V(99% BW)-QPSK

Frequency(MHz)	Occupied Bandwidth (99% BW)( KHz)
826.4	4134.62
836.6	4134.62
846.6	4134.62

#### **WCDMA Band V**


# Channel 4132-Occupied Bandwidth (99% BW)



Date: 18.APR.2019 09:47:57




# Channel 4183-Occupied Bandwidth (99% BW)



Date: 18.APR.2019 09:49:09

# Channel 4233-Occupied Bandwidth (99% BW)



Date: 18.APR.2019 09:50:20



# A.5 EMISSION BANDWIDTH


#### A.5.1Emission Bandwidth Results

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

#### **WCDMA Band II-QPSK**

Frequency(MHz)	Emission Bandwidth ( KHz)
1852.4	4711.54
1880.0	4711.54
1907.6	4711.54


# WCDMA Band II Channel 9262-Emission Bandwidth



Date: 18.APR.2019 10:15:59




#### **Channel 9400-Emission Bandwidth**



Date: 18.APR.2019 10:17:11

#### **Channel 9538-Emission Bandwidth**



Date: 18.APR.2019 10:18:23




# WCDMA Band V-QPSK

Frequency(MHz)	Emission Bandwidth (KHz)
826.40	4727.56
836.60	4695.51
846.60	4695.51

#### **WCDMA Band V**


#### **Channel 4132-Emission Bandwidth**



Date: 18.APR.2019 09:52:21




#### **Channel 4183-Emission Bandwidth**



Date: 18.APR.2019 09:53:33

# **Channel 4233-Emission Bandwidth**



Date: 18.APR.2019 09:54:45




# A.6 BAND EDGE COMPLIANCE

#### A.6.1 Measurement limit

On any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log (P) dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm. According to KDB 971168 6.0, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.




# A.6.2 Measurement result WCDMA Band II-QPSK LOW BAND EDGE BLOCK-A (WCDMA Band ${\rm II}$ )-Channel 9262



Date: 18.APR.2019 10:19:32


# HIGH BAND EDGE BLOCK-C (WCDMA Band II) -Channel 9538



Date: 18.APR.2019 10:19:52




# WCDMA Band V-QPSK LOW BAND EDGE BLOCK-A (WCDMA Band $\,\mathrm{V}$ )-Channel 4132



Date: 18.APR.2019 09:55:54

# HIGH BAND EDGE BLOCK-C (WCDMA Band $\,\mathrm{V}\,$ ) –Channel 4233



Date: 18.APR.2019 09:56:13



#### A.7 CONDUCTED SPURIOUS EMISSION

#### A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
- 2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
- According to KDB 971168 6.0, the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz)

#### **WCDMA Band** II Transmitter

Channel	Frequency (MHz)	
9262	1852.40	
9400	1880.00	
9538	1907.60	

#### **WCDMA Band V Transmitter**

Channel	Frequency (MHz)	
4132	826.40	
4183	836.60	
4233	846.60	

#### A. 7.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.




#### A.7.3 Measurement result

#### **WCDMA Band II**

Channel 9262: 30MHz - 19.15GHz


Spurious emission limit -13dBm.



Date: 18.APR.2019 10:20:57

# Channel 9400: 30MHz - 19.15GHz

Spurious emission limit -13dBm.




Date: 18.APR.2019 10:21:13



# Channel 9538: 30MHz -19.15GHz

Spurious emission limit –13dBm.




Date: 18.APR.2019 10:21:29



#### **WCDMA Band V**

#### Channel 4132: 30MHz -8.49GHz


Spurious emission limit -13dBm.



Date: 18.APR.2019 09:57:19

#### Channel 4183: 30MHz -8.49GHz

Spurious emission limit -13dBm.




Date: 18.APR.2019 09:57:34



# Channel 4233: 30MHz -8.49GHz

Spurious emission limit -13dBm.



Date: 18.APR.2019 09:57:50



#### A.8 PEAK-TO-AVERAGE POWER RATIO

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

#### According to KDB 971168:

- a)Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e)Record the maximum PAPR level associated with a probability of 0.1%

#### A.8.1 Measurement limit

not exceed 13 dB

# A.8.2 Measurement results WCDMA Band II-QPSK Measurement result

CH	Frequency(MHz)	PAPR(dB)
9400	1880.0	3.88



# **ANNEX B: Accreditation Certificate**

United States Department of Commerce National Institute of Standards and Technology



#### Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 600118-0

#### Telecommunication Technology Labs, CAICT

Beijing China

is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:

#### **Electromagnetic Compatibility & Telecommunications**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).

2018-09-28 through 2019-09-30

Effective Dates



For the National Voluntary Laboratory Accreditation Program

\*\*\*END OF REPORT\*\*\*