



MPE ESTIMATION

FCC ID: 2AQ3F-CGF1W

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

2.4G WIFI/BT

Mode	Frequency (MHz)	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
2.4g WiFi	2412	13.93	13±1(14)	25.12	0	1.0000	0.004997
BLE	2480	0.133	0±1(1)	1.26	0	1.0000	0.000251

$$Pd = \frac{P_{out} * G}{4\pi r^2};$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK2010092864-1E/2E, antenna gain=0dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.004997 mW/cm² which is < 1.0mW/cm², RF Exposure testing is not required.

-----The End-----