



**RADIO TEST REPORT**

Report No: STS2107185H01

Issued for

BLU Products, Inc.

10814 NW 33rd St # 100 Doral, FL 33172, USA

<b>Product Name:</b>	Speaker
<b>Brand Name:</b>	BOLD
<b>Model Name:</b>	BOLD ARIA Z
<b>Series Model:</b>	N/A
<b>FCC ID:</b>	YHLBLUARIAZ
<b>Test Standard:</b>	FCC 47CFR §2.1091

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.





### Test Report Certification

**Applicant's Name**..... : BLU Products, Inc.  
 Address ..... : 10814 NW 33rd St # 100 Doral, FL 33172, USA  
**Manufacturer's Name** ..... : BLU Products, Inc.  
 Address ..... : 10814 NW 33rd St # 100 Doral, FL 33172, USA

#### Product Description

Product Name..... : Speaker  
 Brand Name ..... : BOLD  
 Model Name ..... : BOLD ARIA Z  
 Series Model..... : N/A

**Standards**..... : FCC 47CFR §2.1091

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

**Date of Test**..... :  
 Date of receipt of test item ..... : 26 July 2021  
 Date (s) of performance of tests..... : 26 July 2021~ 06 Aug. 2021  
 Date of Issue..... : 06 Aug. 2021  
 Test Result..... : **Pass**

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sean she)



Authorized Signatory :

(Vita Li)



## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION</b>	<b>5</b>
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	5
<b>2. FCC 47CFR §2.1091 REQUIREMENT</b>	<b>6</b>
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 EUT OPERATION CONDITION	6
2.4 CLASSIFICATION	6
2.5 TEST RESULT	7





**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	06 Aug. 2021	STS2107185H01	ALL	Initial Issue





## 1. GENERAL INFORMATION

### 1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Speaker	
Brand Name	BOLD	
Model Name	BOLD ARIA Z	
Series Model	N/A	
Model Difference	N/A	
Product Description	The EUT is Speaker	
	Operation Frequency:	2402–2480 MHz
	Modulation Type:	BT: GFSK(1Mbps), $\pi/4$ -DQPSK(2Mbps), 8DPSK(3Mbps) BLE: GFSK
	Antenna gain:	2 dBi
	Antenna Designation:	PCB Antenna
Rating	Input: 5V, 500mA	
Battery	Rated Voltage:3.7V Charge Limit Voltage:4.2V Capacity:400mAh	
Hardware version number	V3	
Software version number	V3	

### 1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



## 2. FCC 47CFR §2.1091 REQUIREMENT

### 2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

### 2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

F= Frequency in MHz

Friss Formula

Friss Transmission Formula:  $Pd = (Pout * G) / (4*pi*r^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

### 2.3 EUT OPERATION CONDITION

EUT was enabled to transmit and receive at lowest, middle and highest channels.

### 2.4 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.



## 2.5 TEST RESULT

## Turn up

Mode	Detector	Turn up Power
GFSK	AV	4±1dBm
DSSS	AV	-3±1dBm

## ANT Gain (G)

2402-2483.5MHz: 2dBi (gain of antenna in linear scale=1.585)

Protocol	Max Turn up Power (dBm)	Max Turn up Power (mW)	ANT Gain(gain of antenna in linear scale)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/c m <sup>2</sup> )	Result
GFSK	5	3.162	1.585	0.001	1	Pass
DSSS	-2	0.631	1.585	0.0002	1	Pass

※※※※※END OF THE REPORT※※※※※