## **Operation Description**

## SOFTWARE SECURITY REQUIREMENTS FOR U-NII DEVICES

## FCC ID: 2AG7C-6131E-U

Pursuant to KDB 594280, the overall security measures and systems that ensure that:

- 1. only properly authenticated software is loaded and operating the device; and
- 2. the device is not easily modified to operate with RF parameters outside of the authorization.

are described.

The following questions are addressed the description of the software in the operational description for the device and clearly how the device meets the security requirements.

		SOFTWARE SECURITY	DESCRIPTION
General Description	1.	Describe how any software/firmware updates for elements than can affect the device's RF parameters will be obtained, downloaded, validated and installed. For software that is accessed through manufacturer's website or device's management system, describe the different levels of security as appropriate.	Software/firmware will be obtained by the factory, downloaded and validated from the ODM website, and installed by the end user.  Software is accessed through Web UI when computer is connected.
	2.	Describe the RF parameters that are modified by any software/firmware without any hardware changes. Are these parameters in some way limited such that any other software/firmware changes will not allow the device to exceed the authorized RF characteristics?	The RF parameters cannot be modified by software.  All these parameters will not exceed the authorized parameters. The firmware has been complied as binary file. It couldn't change the setting RF parameter through this binary file. It is read-only without change.
	3.	Describe in detail the authentication protocols that are in place to ensure that the source of the RF-related software/firmware is valid. Describe in detail how the RF-related software is protected against modification.	No any authentication protocol is used. The RF Parameters is put in read-only partition of EUT's flash and are only installed in the factory. RF parameters including frequency of operation, power setting, modulation type, antenna types or country code setting will be locked in this partition.
	4.	Describe in detail any encryption methods used to support the use of legitimate RF-related software/firmware.	No encryption methods used. The firmware is programmed at the factory and cannot be modified by third parties.
	5.	For a device that can be configured as a master and client (with active or passive scanning), explain how the device ensures compliance for each mode? In	This is a client module only without radar detection.

particular if the device acts as master in some band of operation and client in another; how is compliance ensured in each band of operation? **Third-Party** Explain if any third parties have the capability No any third parties have the capability to Access to operate a U.S.-sold device on any other operate a US sold device on any other Control regulatory domain, frequencies, or in any regulatory domain, frequencies, or in any manner that may allow the device to operate in manner that may allow the device to violation of the device's authorization if operate in violation of the device's activated in the U.S. authorization if activated in the U.S. 2. Describe, if the device permits third-party The RF Parameters is put in read-only software or firmware installation, what partition of EUT's flash and are only mechanisms are provided by the manufacturer installed in the factory. RF parameters to permit integration of such functions while including frequency of operation, power ensuring that the RF parameters of the device setting, modulation type, antenna types or cannot be operated outside its authorization for country code setting will be locked in this operation in the U.S. In the description include partition. what controls and/or agreements are in place with providers of third-party functionality to ensure the devices' underlying RF parameters are unchanged and how the manufacturer verifies the functionality. For Certified Transmitter modular devices, There are no RF parameters that can be describe how the module grantee ensures that modified. All RF parameters are host manufacturers fully comply with these programmed in OTP memory at the factory software security requirements for U-NII and cannot be modified or overridden by devices. If the module is controlled through third parties. The module is not controlled

## SOFTWARE CONFIGURATION DESCRIPTION GUIDE

driver software loaded in the host, describe

how the drivers are controlled and managed

parameters are not modified outside the grant

such that the modular transmitter RF

of authorization.

For devices which have "User Interfaces" (UI) to configure the device in a manner that may impact the operational RF parameters, the following questions shall be answered by the applicant and the information included in the operational description. The description must address if the device supports any of the country code configurations or peer-peer mode communications discussed in KDB 594280 Publication D01.

by driver software on the host and cannot

override critical RF parameters stored in

module OTP memory.

	SOFTWARE CONFIGURATION DES	CRIPTION
USER CONFIGURATION GUIDE	Describe the user configurations permitted through the UI. If different levels of access are permitted for professional installers, system integrators or end-users, describe the differences.	Authorized channel, bandwidth, and modulation can be configured through the UI.  There are no different levels of access.
	a. What parameters are viewable and configurable by different parties?	Authorized channel, bandwidth, and modulation.

	1
<ul> <li>b. What parameters are accessible or modifiable by the professional installer or system integrators?</li> </ul>	This is not professional install device.
(1) Are the parameters in some way limited, so that the installers will not enter parameters that exceed those authorized?	This is not professional install device.
(2) What controls exist that the user cannot operate the device outside its authorization in the U.S.?	The RF Parameters is put in read-only partition of EUT's flash and are only installed in the factory. RF parameters including frequency of operation, power setting, modulation type, antenna types or country code setting will be locked in this partition.
c. What parameters are accessible or modifiable by the end-user?	Authorized channel, bandwidth, and modulation.
(1) Are the parameters in some way limited, so that the user or installers will not enter parameters that exceed those authorized?	This is not professional install device.
(2) What controls exist so that the user cannot operate the device outside its authorization in the U.S.?	The RF Parameters is put in read-only partition of EUT's flash and are only installed in the factory. RF parameters including frequency of operation, power setting, modulation type, antenna types or country code setting will be locked in this partition.
d. Is the country code factory set? Can it be changed in the UI?	Yes, the country code is set by factory. It cannot be changed in the UI.
(1) If it can be changed, what controls exist to ensure that the device can only operate within its authorization in the U.S.?	The country code cannot be changed in the UI.
e. What are the default parameters when the device is restarted?	Factory setting.
<ol> <li>Can the radio be configured in bridge or mesh mode? If yes, an attestation may be required. Further information is available in KDB Publication 905462 D02.</li> </ol>	No, this device cannot be configured in both bridge and mesh mode.
3. For a device that can be configured as a master and client (with active or passive scanning), if this is user configurable, describe what controls exist, within the UI, to ensure compliance for each mode. If the device acts as a master in some bands and client in others, how is this configured to ensure compliance?	This device cannot be configured as a master and client.
For a device that can be configured as different types of access points, such as point-to-point or point-to-multipoint, and use	This device cannot be configured as different types of access points.
	modifiable by the professional installer or system integrators?  (1) Are the parameters in some way limited, so that the installers will not enter parameters that exceed those authorized?  (2) What controls exist that the user cannot operate the device outside its authorization in the U.S.?  c. What parameters are accessible or modifiable by the end-user?  (1) Are the parameters in some way limited, so that the user or installers will not enter parameters that exceed those authorized?  (2) What controls exist so that the user cannot operate the device outside its authorization in the U.S.?  d. Is the country code factory set? Can it be changed in the UI?  (1) If it can be changed, what controls exist to ensure that the device can only operate within its authorization in the U.S.?  e. What are the default parameters when the device is restarted?  2. Can the radio be configured in bridge or mesh mode? If yes, an attestation may be required. Further information is available in KDB Publication 905462 D02.  3. For a device that can be configured as a master and client (with active or passive scanning), if this is user configurable, describe what controls exist, within the UI, to ensure compliance for each mode. If the device acts as a master in some bands and client in others, how is this configured to ensure compliance?  4. For a device that can be configured as different types of access points, such as

different types of antennas, describe what controls exist to ensure compliance with	
applicable limits and the proper antenna is used for each mode of operation. (See Section 15.407(a))	